

CSE 142 Sample Midterm Exam #2 Key

1. Expressions

<u>Expression</u>	<u>Value</u>
8 + 5 * 3 / 2	15
1.5 * 4 * 7 / 8 + 3.4	8.65
73 % 10 - 6 % 10 + 28 % 3	-2
4 + 1 + 9 + "." + (-3 + 10) + 11 / 3	"14.73"
3 / 14 / 7 / (1.0 * 2) + 10 / 6	1.0
10 > 11 == 4 / 3 > 1	true

2. Parameter Mystery

happy and pumpkin were orange
orange and happy were pumpkin
orange and sleepy were y
pumpkin and x were green
green and pumpkin were vampire

3. While Loop Simulation

<u>Method Call</u>	<u>Value Returned</u>
mystery(2, 9)	0
mystery(5, 1)	6
mystery(38, 5)	119
mystery(5, 5)	0
mystery(40, 10)	57

4. Assertions

	next < 0	y > z	y == 0
Point A	SOMETIMES	NEVER	ALWAYS
Point B	NEVER	SOMETIMES	SOMETIMES
Point C	NEVER	ALWAYS	NEVER
Point D	SOMETIMES	SOMETIMES	NEVER
Point E	ALWAYS	SOMETIMES	SOMETIMES

5. Programming (one solution shown)

```
public static void printMultiples(int n, int times) {
    System.out.print("The first " + times + " multiples of " + n + " are " + n);
    for (int i = 2; i <= times; i++) {
        System.out.print(", " + i * n);
    }
    System.out.println();
}
```

6. Programming (four solutions shown)

```
public static boolean monthApart(int m1, int d1, int m2, int d2) {  
    if (m1 == m2) {  
        return false;  
    } else if (m1 <= m2 - 2) {  
        return true;  
    } else if (m1 >= m2 + 2) {  
        return true;  
    } else if (m1 == m2 - 1) {  
        if (d1 <= d2) {  
            return true;  
        } else {  
            return false;  
        }  
    } else if (m1 == m2 + 1) {  
        if (d1 >= d2) {  
            return true;  
        } else {  
            return false;  
        }  
    } else {  
        return false;  
    }  
}  
  
public static boolean monthApart(int m1, int d1, int m2, int d2) {  
    if (m1 < m2 - 1 || m1 > m2 + 1) {  
        return true;  
    } else if (m1 == m2 - 1 && d1 <= d2) {  
        return true;  
    } else if (m1 == m2 + 1 && d1 >= d2) {  
        return true;  
    } else {  
        return false;  
    }  
}  
  
public static boolean monthApart(int m1, int d1, int m2, int d2) {  
    return (m2 - m1 > 1) || (m1 - m2 > 1) ||  
           (m2 - m1 == 1 && d1 <= d2) ||  
           (m1 - m2 == 1 && d1 >= d2);  
}  
  
public static boolean monthApart(int m1, int d1, int m2, int d2) {  
    return Math.abs((m1 * 31 + d1) - (m2 * 31 + d2)) >= 31;  
}
```

7. Programming (one solution shown)

```
public static void threeHeads() {  
    Random r = new Random();  
    int numHeads = 0;  
  
    while (numHeads < 3) {  
        int flip = r.nextInt(2); // flip coin  
        if (flip == 0) { // heads  
            numHeads++;  
            System.out.print("H ");  
        } else {  
            numHeads = 0;  
            System.out.print("T ");  
        }  
    }  
    System.out.println();  
    System.out.println("Three heads in a row!");  
}
```