

CSE 341: Programming Languages

Dan Grossman

Spring 2004

Lecture 13— Scheme Intro, Several Binding Forms

Scheme

- Like ML, functional focus with imperative features
 - anonymous functions, function closures, etc.
 - but every binding is mutable
- A really minimalist syntax/semantics
 - In the LISP tradition
 - Current standard is 50 pages
- Dynamically typed
 - Less “compile-time” checking
 - Accepts more perfectly reasonable programs
- Some “advanced” features for decades
 - Programs as data, hygienic macros, continuations

Which Scheme?

Scheme has a few dialects and many extensions.

We will use “textual MzScheme” for the language and DrScheme as a convenient environment.

Most of what we do will be “pure Scheme”.

Exceptions are multiline comments, `define-struct`, and perhaps a brief foray into the MzScheme module system.

Scheme syntax

Syntactically, a Scheme term is either an *atom* (identifier, number, symbol, string, ...) or a sequence of terms ($t_1 \dots t_n$).

Note: Scheme used to get (still gets?) “paren bashed”, which is hilarious in an XML world.

Semantically, identifiers are resolved in an environment and other atoms are values.

The semantics of a sequence depends on t_1 :

- certain character sequences are “special forms”
- otherwise a sequence is a function application (semantics same as ML)

Some special forms

- `define`
- `lambda`
- `if`, `cond`, `and`, `or`
- `let`, `let*`, `letrec`

Some predefined values

- `#t`, `#f`
- `()`, `cons`, `car`, `cdr`, `null?`, `list`
- a “numeric tower” with math operations (e.g., `+`) defined on all of them
- tons more (strings vs. symbols discussed later)

Note: Prefix and variable-arity help make lots of things functions.

Local bindings

There are 3 forms of local bindings with different semantics:

- `let`
- `let*`
- `letrec`

Also, in function bodies, a sequence of definitions is equivalent to `letrec`.

But at top-level redefinitions is assignment!

This makes it ghastly hard to encapsulate code, but in practice:

- people assume non-malicious clients
- implementations provide access to “real primitives”

For your homework, assume top-level definitions are immutable.