

CSE 341 Section

Preparing for MUPL!
Justin Harjanto

Today's Agenda

- Building a MUPL Interpreter
 - Assume Correct Syntax
 - Check for Correct Semantics
 - Evaluating the AST
- MUPL “Macros”
- Eval, Quote, and Quasiquote

2

Building a MUPL Interpreter

- Skipping the parsing phase ← Do Not Implement
- Interpreter written in Racket
 - Racket is the “Metalanguage”
- MUPL code represented as an AST
 - AST nodes represented as Racket structs
- Can assume AST has valid syntax
- Can **NOT** assume AST has valid semantics

3

Correct Syntax Examples

Given this syntax:

```
(struct int (num) #:transparent)
(struct add (e1 e2) #:transparent)
(struct ifnz (e1 e2 e3) #:transparent)
```

We can need to evaluate these MUPL programs:

```
(int 34)
(add (int 34) (int 30))
(ifnz (add (int 5) (int 7)) (int 12) (int 1))
```

4

Incorrect Syntax Examples

Given this syntax:

```
(struct int (num) #:transparent)
(struct add (e1 e2) #:transparent)
(struct ifnz (e1 e2 e3) #:transparent)
```

We can assume we won't see MUPL programs like:

```
(int "dan then dog")
(int (ifnz (int 0) (int 5) (int 7)))
(add (int 8) #t)
(add 5 4)
```

Illegal input ASTs may crash the interpreter - [this is OK](#)

Check for Correct Semantics

What if the program is a legal AST, but evaluation of it tries to use the wrong kind of value?

- For example, “add an integer and a function”
- You should detect this and give an error message that is not in terms of the interpreter implementation
- We need to check that the type of a recursive result is what we expect
 - No need to check if any type is acceptable

6

Evaluating the AST

- `eval-exp` should return a MUPL value
- MUPL values all evaluate to themselves
- Otherwise we haven't interpreted far enough

```
(int 7) ; evaluates to (int 7)
(add (int 3) (int 4)) ; evaluates to (int 7)
```

7

Macros Review

- Extend language syntax (allow new constructs)
- Written in terms of existing syntax
- Expanded before language is actually interpreted or compiled

8

MUPL “Macros”

- Interpreting MUPL using Racket as the metalanguage
- MUPL is represented as Racket structs
- In Racket, these are just data types
- Why not write a Racket function that returns MUPL ASTs?

9

MUPL “Macros”

If our MUPL Macro is a Racket function

```
(define (++ exp) (add (int 1) exp))
```

Then the MUPL code

```
(++ (int 7))
```

Expands to

```
(add (int 1) (int 7))
```

10

quote

- Syntactically, Racket statements can be thought of as lists of tokens
- `(+ 3 4)` is a “plus sign”, a “3”, and a “4”
- `quote`-ing a parenthesized expression produces a list of tokens

11

quote Examples

```
(+ 3 4) ; 7
(quote (+ 3 4)) ; '(+ 3 4)
(quote (+ 3 #t)) ; '(+ 3 #t)
(+ 3 #t) ; Error
```

- You may also see the single quote `'` character used as syntactic sugar

12

quasiquote

- Inserts evaluated tokens into a quote
- Convenient for generating dynamic token lists
- Use `unquote` to escape a `quasiquote` back to evaluated Racket code
- A `quasiquote` and `quote` are equivalent unless we use an `unquote` operation

13

quasiquote Examples

```
(quasiquote (+ 3 (unquote(+ 2 2)))) ; '(+ 3 4)
(quasiquote
 (string-append
  "I love CSE"
  (number->string
   (unquote (+ 3 338)))))
; '(string-append "I love CSE" (number->string 341))
```

- You may also see the backtick ``` character used as syntactic sugar for `quasiquote`
- The comma character `,` is used as syntactic sugar for `unquote`

Self Interpretation

- Many languages provide an `eval` function or something similar
- Performs interpretation or compilation at runtime
 - Needs full language implementation during runtime
- It's useful, but there's usually a better way
- Makes analysis, debugging difficult

15

eval

- Racket's `eval` operates on lists of tokens
- Like those generated from `quote` and `quasiquote`
- Treat the input data as a program and evaluate it

16

eval examples

```
(define quoted (quote (+ 3 4)))
(eval quoted) ; 7
(define bad-quoted (quote (+ 3 #t)))
(eval bad-quoted) ; Error
(define qqquoted (quasiquote (+ 3 (unquote(+ 2 2)))))
(eval qqquoted) ; 7
(define big-qqquoted
 (quasiquote
  (string-append
   "I love CSE"
   (number->string
    (unquote (+ 3 338)))))
(eval big-qqquoted) ; "I love CSE341"
```

17

RackUnit

- Unit testing is built into the standard library
 - <http://docs.racket-lang.org/rackunit/>
- Built in test functions to make testing your code easier
 - Test for equality, `check-eq?`
 - Test for True, `check-true`
 - Test for raised exception, `check-exn`
 - and many more

18