

# **Log-Structured File Systems**

Hank Levy

# Basic Problem

- **Most file systems now have large memory caches (buffers) to hold recently-accessed blocks**
- **Most reads are thus satisfied from the buffer cache**
- **From the point of view of the disk, most traffic is write traffic**
- **So to speed up disk I/O, we need to make writes go faster**
- **But disk performance is limited ultimately by disk head movement**
- **With current file systems, adding a block takes several writes (to the file and to the metadata), requiring several disk seeks**



# LFS: Basic Idea

- An alternative is to use the disk as a *log*
- A log is a data structure that is written only at the head
- If the disk were managed as a log, there would be effectively no head seeks
- The “file” is always added to sequentially
- New data and metadata (inodes, directories) are accumulated in the buffer cache, then written all at once in large blocks (e.g., segments of .5M or 1M)
- This would greatly increase disk thruput
- How does this really work? How do we read? What does the disk structure look like? etc.?

# LFS Data Structures

- **inodes:** as in Unix, inodes contain physical block pointers for files
- **inode map:** a table indicating where each inode is on the disk
  - inode map blocks are written as part of the segment; a table in a fixed checkpoint region on disk points to those blocks
- **segment summary:** info on every block in a segment
- **segment usage table:** info on the amount of “live” data in a block

# LFS vs. UFS



Blocks written to  
create two 1-block  
files: dir1/file1 and  
dir2/file2, in UFS and  
LFS

# **LFS: read and write**

- **Every write causes new blocks to be added to the current segment buffer in memory; when that segment is full, it is written to the disk**
- **Reads are no different than in Unix File System, once we find the inode for a file (in LFS, using the inode map, which is cached in memory)**
- **Over time, segments in the log become fragmented as we replace old blocks of files with new block**
- **Problem: in steady state, we need to have contiguous free space in which to write**

# Cleaning

- The major problem for a LFS is *cleaning*, i.e., producing contiguous free space on disk
- A cleaner process “cleans” old segments, i.e., takes several non-full segments and compacts them, creating one full segment, plus free space
- The cleaner chooses segments on disk based on:
  - utilization: how much is to be gained by cleaning them
  - age: how likely is the segment to change soon anyway
- Cleaner cleans “cold” segments at 75% utilization and “hot” segments at 15% utilization (because it’s worth waiting on “hot” segments for blocks to be rewritten by current activity)

# **LFS Summary**

- **Basic idea is to handle reads through caching and writes by appending large segments to a log**
- **Greatly increases disk performance on writes, file creates, deletes, ....**
- **Reads that are not handled by buffer cache are same performance as normal file system**
- **Requires cleaning demon to produce clean space, which takes additional cpu time**