

Oct 19, 15 6:43

IMPSemantics.v

Page 1/5

```
(*** * IMP Semantics *)

Require Import ZArith.
Require Import String.

Open Scope string_scope.
Open Scope Z_scope.

Require Import IMPSyntax.

Definition heap : Type :=
  string -> Z.

Definition empty : heap :=
  fun v => 0.

Definition exec_op (op: binop) (i1 i2: Z) : Z :=
  match op with
  | Add => i1 + i2
  | Sub => i1 - i2
  | Mul => i1 * i2
  | Div => i1 / i2
  | Mod => i1 mod i2
  | Lt => if Z_lt_dec i1 i2 then 1 else 0
  | Lte => if Z_le_dec i1 i2 then 1 else 0
  | Conj => if Z_eq_dec i1 0 then 0 else
    if Z_eq_dec i2 0 then 0 else 1
  | Disj => if Z_eq_dec i1 0 then
    if Z_eq_dec i2 0 then 0 else 1
    else 1
  end.

Inductive eval : heap -> expr -> Z -> Prop :=
| eval_int:
  forall h i,
  eval h (Int i) i
| eval_var:
  forall h v,
  eval h (Var v) (h v)
| eval_binop:
  forall h op e1 e2 i1 i2 i3,
  eval h e1 i1 ->
  eval h e2 i2 ->
  exec_op op i1 i2 = i3 ->
  eval h (BinOp op e1 e2) i3.

Fixpoint interp_expr (h: heap) (e: expr) : Z :=
  match e with
  | Int i => i
  | Var v => h v
  | BinOp op e1 e2 =>
    exec_op op (interp_expr h e1) (interp_expr h e2)
  end.

Lemma interp_expr_eval:
  forall h e i,
  interp_expr h e = i ->
  eval h e i.
Proof.
  intros h e.
  induction e; simpl in *; intros.
  - subst; constructor.
  - subst; constructor.
  - apply eval_binop with (i1 := interp_expr h e1)
    (i2 := interp_expr h e2).
    + apply IHel. auto.
    + apply IHHe2. auto.
    + assumption.
Qed.
```

Oct 19, 15 6:43

IMPSemantics.v

Page 2/5

```
Lemma eval_interp_expr:
  forall h e i,
  eval h e i ->
  interp_expr h e = i.
Proof.
  intros h e.
  induction e; simpl in *; intros.
  - inversion H; subst; auto.
  - inversion H; subst; reflexivity.
  - inversion H; subst.
    rewrite (IHel il H4).
    rewrite (IHHe2 i2 H6).
    reflexivity.
Qed.

Lemma eval_interp:
  forall h e,
  eval h e (interp_expr h e).
Proof.
  intros. induction e; simpl.
  - constructor.
  - constructor.
  - econstructor.
    + eassumption.
    + eassumption.
    + reflexivity.
Qed.

Lemma eval_det:
  forall h e i1 i2,
  eval h e i1 ->
  eval h e i2 ->
  i1 = i2.
Proof.
  intros.
  apply eval_interp_expr in H.
  apply eval_interp_expr in H0.
  subst. reflexivity.
Qed.

Definition update (h: heap) (v: string) (i: Z) : heap :=
  fun v' =>
    if string_dec v' v then
      i
    else
      h v'.

Inductive step : heap -> stmt -> heap -> stmt -> Prop :=
| step_assign:
  forall h v e i,
  eval h e i ->
  step h (Assign v e) (update h v i) Nop
| step_seq_nop:
  forall h s,
  step h (Seq Nop s) h s
| step_seq:
  forall h s1 s2 s1' h',
  step h s1 h' s1' ->
  step h (Seq s1 s2) h' (Seq s1' s2)
| step_cond_true:
  forall h e s i,
  eval h e i ->
  i <> 0 ->
  step h (Cond e s) h s
| step_cond_false:
  forall h e s i,
  eval h e i ->
  i = 0 ->
```

Oct 19, 15 6:43

IMPSemantics.v

Page 3/5

```

step h (Cond e s) h Nop
| step_while_true:
  forall h e s i,
  eval h e i ->
  i <> 0 ->
  step h (While e s) h (Seq s (While e s))
| step_while_false:
  forall h e s i,
  eval h e i ->
  i = 0 ->
  step h (While e s) h Nop.

(***
/ step_while:
forall h e s,
  step h (While e s) h (Cond e (Seq s (While e s)))
*)

Definition isNop (s: stmt) : bool :=
match s with
| Nop => true
| _ => false
end.

Lemma isNop_ok:
forall s,
isNop s = true <-> s = Nop.
Proof.
destruct s; simpl; split; intros;
auto; discriminate.
Qed.

Fixpoint interp_step (h: heap) (s: stmt) : option (heap * stmt) :=
match s with
| Nop => None
| Assign v e =>
  Some (update h v (interp_expr h e), Nop)
| Seq s1 s2 =>
  if isNop s1 then
    Some (h, s2)
  else
    match interp_step h s1 with
    | Some (h', s1') => Some (h', Seq s1' s2)
    | None => None
  end
| Cond e s =>
  if Z_eq_dec (interp_expr h e) 0 then
    Some (h, Nop)
  else
    Some (h, s)
| While e s =>
  if Z_eq_dec (interp_expr h e) 0 then
    Some (h, Nop)
  else
    Some (h, Seq s (While e s))
end.

Lemma interp_step_step:
forall h s h' s',
interp_step h s = Some (h', s') ->
step h s h' s'.
Proof.
intros h s. revert h.
induction s; simpl; intros.
- discriminate.
- inversion H. subst.
  constructor. apply interp_expr_eval; auto.
- destruct (isNop s1) eqn:?.
  + rewrite isNop_ok in Heqb. subst.

```

Oct 19, 15 6:43

IMPSemantics.v

Page 4/5

```

inversion H. subst. constructor.
+ destruct (interp_step h s1) as [[newHeap newStmt]] eqn:?.
  * inversion H. subst.
    apply IHs1 in Heqb.
    constructor. assumption.
  * discriminate.
- destruct (Z.eq_dec (interp_expr h e) 0) eqn:?.
  + inversion H. subst.
    clear Heqb0. apply interp_expr_eval in e0. econstructor.
    eassumption. auto.
  + inversion H; subst.
    eapply step_cond_true; eauto.
    apply interp_expr_eval; auto.
- destruct (Z.eq_dec (interp_expr h e) 0) eqn:?.
  + inversion H; subst.
    eapply step_while_false; eauto.
    apply interp_expr_eval; auto.
  + inversion H; subst.
    eapply step_while_true; eauto.
    apply interp_expr_eval; auto.
Qed.

Lemma step_interp_step:
forall h s h' s',
step h s h' s' ->
interp_step h s = Some (h', s').
Proof.
intros. induction H; simpl; auto.
- apply eval_interp_expr in H.
  subst; auto.
- destruct (isNop s1) eqn:?.
  + apply isNop_ok in Heqb. subst.
    inversion H. (** nop can't step *)
    + rewrite IHstep. auto.
- apply eval_interp_expr in H. subst.
  destruct (Z.eq_dec (interp_expr h e) 0); auto.
  exfalso. unfold not in H0. apply H0. assumption.
- apply eval_interp_expr in H. subst.
  destruct (Z.eq_dec (interp_expr h e) 0); auto.
  unfold not in n. apply n in H0.
  exfalso. assumption.
- apply eval_interp_expr in H. subst.
  destruct (Z.eq_dec (interp_expr h e) 0); auto.
  unfold not in H0. apply H0 in e0.
  inversion e0.
- apply eval_interp_expr in H. subst.
  destruct (Z.eq_dec (interp_expr h e) 0); auto.
  omega.
Qed.

Inductive step_n : heap -> stmt -> nat -> heap -> stmt -> Prop :=
| sn_refl:
  forall h s,
  step_n h s 0 h s
| sn_step:
  forall h1 s1 n h2 s2 h3 s3,
  step h1 s1 h2 s2 ->
  step_n h2 s2 n h3 s3 ->
  step_n h1 s1 (S n) h3 s3.

Fixpoint run (fuel: nat) (h: heap) (s: stmt) : (heap * stmt) :=
match fuel with
| 0 => (h, s)
| S n =>
  match interp_step h s with
  | Some (h', s') => run n h' s'
  | None => (h, s)
end
end.
```

Oct 19, 15 6:43

IMPSemantics.v

Page 5/5

```
Lemma run_stepn:  
forall fuel h s h' s',  
run fuel h s = (h', s') ->  
exists n, step_n h s n h' s'.
```

Proof.

```
induction fuel; simpl; intros.  
- inversion H; subst.  
  exists O. constructor.  
- destruct (interp_step h s) as [[foo bar]] eqn:?.  
+ apply IHfuel in H.  
  apply interp_step_step in Heqo.  
  destruct H. exists (S x).  
  econstructor; eauto.  
+ inversion H; subst.  
  exists O. constructor; auto.
```

Qed.

```
Lemma stepn_run:  
forall h s n h' s',  
step_n h s n h' s' ->  
run n h s = (h', s').
```

Proof.

```
intros. induction H; simpl; auto.  
destruct (interp_step h1 s1) as [[h' s']] eqn:?.  
+ apply step_interp_step in H.  
  (** step is deterministic *)  
  rewrite H in Heqo. inversion Heqo; subst.  
  assumption.  
+ apply step_interp_step in H.  
  rewrite H in Heqo. discriminate.
```

Qed.