

4. Miscellaneous Project Issues

CSEP 545 Transaction Processing
for E-Commerce
Philip A. Bernstein

Copyright ©2007 Philip A. Bernstein

Lock Conversions

- This is step 3 of the course project
- Lock conversion - upgrading an r-lock to a w-lock
 - e.g., $T_i = \text{read}(x) \dots \text{write}(x)$
- The main purpose of step 3 is to ensure you understand the lock manager code we supply.
- Deadlocks are an issue
 - if two txns convert a lock concurrently, they'll deadlock
(both get an r-lock on x before either gets a w-lock)
 - To avoid the deadlock, a caller can get a w-lock first and down-grade to an r-lock if it doesn't need to write.

Lecture Dependencies

- Step 5 involves implementing a workflow controller.
It depends on
 - Transaction bracketing
 - Partitioning work between WC and transaction servers
(= RM in the project)
 - Propagating transaction context in RM calls
 - Parameter-based routing (e.g. choose an RM based on flight number)
 - I'll cover this on April 26. See Chapters 2 & 3 of text.
- Steps 6 – 10 involve two-phase commit.
 - I'll cover it by April 30. See also Chapter 8.

Process Structure

- For architectural reasons, RM and WC should be processes.
- Ordinarily, there's a TM per network node.
 - To simulate this, a TM should be a process