

LEC 05

ArrayList Applications

Questions during Class?

Raise hand or send here

sli.do #cse122



BEFORE WE START

*Talk to your neighbors:
Any weekend plans?*

Music: [122 25au Lecture Tunes ?](#)

Instructor: Elba Garza

TAs: Sreshta	Merav	Shivani	Yang
William	Nicole	Naomi	Cady
Arjun	Vrinda	Hanna	Diya
Dani	Shreya	David	Katharine
Rohan	Wesley	Sushma	
Andrew	Isis	Rio	
Saachi	Colin	Nicolae	
Ava	Medha	Ivory	

Lecture Outline

- **Announcements** 
- Warm Up
- ArrayList Extended Application

Announcements

- C0 grades and R0 out yesterday
 - Now that you have your first set of grades, review the [Course Grades](#) section of the syllabus to understand how they factor into your grade at the end of the quarter!
 - See [Resubmission page](#) and [Ed post](#) for R0 logistics
- Creative Assignment 1 (C1) out later today!
 - Focused on ArrayLists
 - Due next Thursday, Oct 16th by 11:59pm PT
- First quiz in section on Tuesday Oct 14th
 - Practice Quiz 0 released!
- Reminder: Section participation in 11+ sections → Extra resub!
 - No need to do anything; TAs will track on Gradescope

Lecture Outline

- Announcements
- Warm Up 
- ArrayList Extended Application

Edge Cases! (And Testing)

When writing a method, especially one that takes input of some kind (e.g., parameters, user input, a Scanner with input) it's good to think carefully about what assumptions you can make (or cannot make) about this input.

Edge case: A scenario that is uncommon but possible, especially at the “edge” of a parameter's valid range.

- ? What happens if the user passes a negative number to `moveDown`?
- ? What happens if the user passes a number larger than the length of the list to `moveDown`?

More [testing tips](#) on the course website's Resources page!

ArrayList Methods

Method	Description
<code>add(type <i>element</i>)</code>	Adds <i>element</i> to the <i>end</i> of the ArrayList
<code>add(int <i>index</i>, type <i>element</i>)</code>	Adds <i>element</i> to the specified <i>index</i> in the ArrayList
<code>size()</code>	Returns the number of elements in the ArrayList
<code>contains(type <i>element</i>)</code>	Returns true if <i>element</i> is contained in the ArrayList, false otherwise
<code>get(int <i>index</i>)</code>	Returns the element at <i>index</i> in the ArrayList
<code>remove(int <i>index</i>)</code>	Removes the element at <i>index</i> from the ArrayList and returns the removed element.
<code>indexOf(type <i>element</i>)</code>	Returns the index of <i>element</i> in the ArrayList; returns -1 if the <i>element</i> doesn't exist in the ArrayList
<code>set(int <i>index</i>, type <i>element</i>)</code>	Sets the element at <i>index</i> to the given <i>element</i> and returns the old value

addAll

Write a method called `addAll` that accepts two `ArrayLists` of `Characters`, `list1` and `list2`, and an integer `location` as parameters and inserts all of the elements from `list2` into `list1` at the specified `location`.

Lecture Outline

- Announcements
- Warm Up
- **ArrayList Extended Application** 

Bakery Favorites

We will write a program called `BakeryFavorites.java` that manages a list of favorite bakeries for a user (using an `ArrayList`) and allows the user to perform various different operations on their stored list of favorite bakeries.

Key skills used:

- User Interaction (UI) loop
- Iterative development strategies
- Functional decomposition
- Practice with `ArrayList` methods!

Bakery Favorites: Operations

- Load a list of favorites in from a file provided by the user.
- Compare the stored list of favorites to another list of favorites provided by the user in another file.
- Report the top n favorites according to the list, where the user can specify n .
- Move a specific favorite down in the list.
- Add a list of favorites in a user-provided file to the stored list of favorites at a specified location.
- Save the current list of favorites to a file provided by the user.

Bakery Favorites: Development Strategy

- Set up the main scaffold code
- Menu loop
- Develop each operation, one at a time

You'll see a similar development strategy in Creative Project 1's specification — we recommend you follow it!

Bakery Favorites: Operations

- Load a list of favorites in from a file provided by the user.
- Compare the stored list of favorites to the list of favorites provided by the user in another file.
- Report the top n favorites that the user can spend the most money on.
- Move the top n favorites to the front of the list.
- Add a new favorite from a user-provided file to the stored list of favorites at the specified location.
- Save the current list of favorites to a file provided by the user.

ALREADY DONE!

See In-Class 4