

CSE 143

Class Constructors

[Chapter 3, pp. 127-131]

06/26/01 F-1

Initialization: Review

- Variables **must** be initialized before 1st use

```
int sum;
for (int i = 0; i < 10; i++)
    sum = sum + i;           //whoops!
```

- Simple types can be initialized at declaration

```
int x = 23;
string InstructorName = "I. M. Boring";
```

- Input might do it

```
int num;
cin >> num;
```

06/26/01 F-2

Initialization: Other Cases

- Parameter: maybe

```
int angle;
modifyTriangle (angle);
//is this or is it not initializing "angle"?
```

- If a variable is not initialized somehow, it is an error.

- What kind of error?

- C++ variables are **not, not, not** initialized automatically!

- But some C++ implementations do (trying to be "helpful")

- ✦ C++ language != a particular C++ system.

- Useful advice: *Always test your program using different compilers/configurations (release vs debug mode in MSVC, for example)*

06/26/01 F-3

Initialization of Instances

- When declaring an instance of a class, its data members are all uninitialized

- no surprise, consistent with C philosophy

```
BankAccount a1; // what is "owner"? "balance"?
a1.deposit(20.0);
cout << a1.amount(); //what's the result?
```

- Need a way to "construct" and initialize new objects

06/26/01 F-4

One Solution: Programmer-defined init function

```
class BankAccount {
public:
    void init(string name, double initBalance);
    ...
};
```

```
BankAccount anAccount;
anAccount.init("Bob", 200.0);
```

- Drawback: What if the client doesn't call `init`?

06/26/01 F-5

Constructors

- In C++, a **constructor** is a special function (method) *automatically* called when a class instance is created (declared)

- Three Weirdnesses:

- Constructor's name is class name
- No explicit return type, not even `void...`
- Invocation is automatic: can't disable; can't call explicitly

06/26/01 F-6

A Better Bank Account

in BankAccount.h:

```
class BankAccount {  
...  
public:  
    BankAccount();  
    void deposit(double amount);  
    ...  
};
```

in BankAccount.cpp:

```
BankAccount::BankAccount() {  
    balance = 0.0;  
    owner = "";  
}
```

06/26/01 F-7

Called Automatically

- With the constructor defined, what's wrong with the example now? (trick question!)

```
BankAccount a1;  
a1.deposit(20.0);  
cout << a1.amount(); //what's the result?
```

Answer: Nothing! the constructor was called automatically and initialized the private variable balance.

06/26/01 F-8

Constructors w/ Arguments

Q: What's still wrong with the improved bank account class?

A: "" was a silly way to initialize the 'owner' field.

- Solution: We can declare constructors that have parameters
- allows us to pass in meaningful values for initialization.

```
class BankAccount {  
public:  
    BankAccount(string name);  
    ...  
};
```

06/26/01 F-9

Multiple Constructors

- May be several reasonable ways to initialize a class instance
- Solution: multiple constructors
 - All have same name (name of class)
 - Distinguished by number and types of arguments
- We say the constructor is "overloaded."
 - You can do this with any function or methods in C++. More later!
 - It's one case of "polymorphism," one of the chief characteristics of object-oriented programming

06/26/01 F-10

An Even Better Bank Account

- Specification

```
class BankAccount {  
public:  
    BankAccount();  
    BankAccount(string name);  
    BankAccount(string name, double b);  
    ...  
};
```

06/26/01 F-11

An Even Better Bank Account

- Implementation

```
BankAccount::BankAccount() {  
    balance = 0.0;  
    owner = "";  
}  
BankAccount::BankAccount(string name) {  
    balance = 0.0;  
    owner = name;  
}  
BankAccount::BankAccount(string name, double b) {  
    balance = b;  
    owner = name;  
}
```

06/26/01 F-12

Invoking a Constructor

- A constructor is never invoked using the dot notation
- A constructor is invoked (automatically) whenever a class instance is created:

```
// implicit invocation of BankAccount ()
BankAccount a1;

// implicit invocation of BankAccount (string)
BankAccount a2("Bob");

// explicit invocation of BankAccount (string)
BankAccount a3 = BankAccount("Bob");
//This is NOT an assignment statement!
```

06/26/01 F-13

"Default" Constructors

- A constructor with 0 arguments is called a *default constructor*.
 - It is invoked in the variable declaration without () -- another weirdness
- If no explicit constructors are given, a default is supplied by compiler
 - Takes no arguments, does nothing
 - Not guaranteed to perform **any** initialization
 - Invisible

06/26/01 F-14

Default Constructor Pitfall

- If a class has one or more "non-default" constructors:
 - then NO compiler-generator default constructor will be supplied
- Can cause subtle errors
- Wise advice: *always define your own default constructor*

06/26/01 F-15

Constructors and Arrays

- `BankAccount AccountList [10000];`
- How many objects are being created?
- Is a constructor called? How many times? Which constructor?
- **Answer:** in an array of class instances, the default constructor is called for each array element
 - If there is one
- What if you want to invoke one of the other constructors, e.g., `BankAccount(string name, double b);`
 - Answer: Sorry, no way.

06/26/01 F-16

Puzzler

- *How many times is a constructor called in this code?*

```
BankAccount anAccount ("Dilbert"), anotherAccount;
BankAccount otherAccounts [100];

}
```

06/26/01 F-17

Constructors: Review

- A constructor cannot return a value
 - so it must be declared without a return type
- A class may provide multiple constructors
 - Compiler will choose appropriate one, depending on context.

- Syntax for invoking a constructor

```
BankAccount a1;           //NOT BankAccount a1( );
BankAccount a2("Bob", 10.0);
BankAccount a3 = BankAccount("Susan");
```

But not this:

```
BankAccount a3;
a3 = BankAccount("Susan");
```

06/26/01 F-18

Exercise

- Design a TranscriptItem class
 - Year
 - Quarter
 - Course name
 - Grade - prof could enter number (4.0) or letter (A)

- Specify 2 overloaded **constructors** (same number of arguments but different types)

```
ti.SetGrade(2.0); // example of overloaded method
ti.SetGrade('C');
```

06/26/01 F-19

Transcript Item

```
enum QuarterType{WINTER, SPRING, SUMMER, AUTUMN};

class TranscriptItem {
public:
    TranscriptItem(int, QuarterType, string, double);
    TranscriptItem(int, QuarterType, string, char);
private:
    int year;
    QuarterType quarter;
    string courseName;
    double grade;        // A=4.0, B=3.0, C=2.0, D=1.0
};
```

06/26/01 F-20

Exercise II

- Design a Transcript class
 - How is the data represented?
 - What are the public methods?
 - Are there any private methods?

06/26/01 F-21