

CSE 143

Lecture 1


Arrays (review)

slides created by Marty Stepp

<http://www.cs.washington.edu/143/>

Arrays (7.1)

- **array**: An object that stores many values of the same type.
 - **element**: One value in an array.
 - **index**: A 0-based integer to access an element from an array.



Array declaration

```
type[ ] name = new type[length];
```

- Example:

```
int[ ] numbers = new int[10];
```

- All elements' values are initially 0.

<i>index</i>	0	1	2	3	4	5	6	7	8	9
<i>value</i>	0	0	0	0	0	0	0	0	0	0

Accessing elements

```
name [ index ]           // access  
name [ index ] = value ; // modify
```

- Example:

```
numbers[ 0 ] = 27;  
numbers[ 3 ] = -6;
```

```
System.out.println( numbers[ 0 ] );  
if ( numbers[ 3 ] < 0 ) {  
    System.out.println( "value 3 is negative" );  
}
```

<i>index</i>	0	1	2	3	4	5	6	7	8	9
<i>value</i>	27	0	0	-6	0	0	0	0	0	0

Out-of-bounds

- Legal indexes: between **0** and the **array's length - 1**.
 - Reading or writing any index outside this range will throw an `ArrayIndexOutOfBoundsException`.

- Example:

```
int[] data = new int[10];
System.out.println(data[0]);           // okay
System.out.println(data[9]);           // okay
System.out.println(data[-1]);          // exception
System.out.println(data[10]);          // exception
```

<i>index</i>	0	1	2	3	4	5	6	7	8	9
<i>value</i>	0	0	0	0	0	0	0	0	0	0

The length field

name.length

- An array's `length` field stores its number of elements.

```
for (int i = 0; i < numbers.length; i++) {  
    System.out.print(numbers[i] + " ");  
}  
// output: 0 2 4 6 8 10 12 14
```

- It does not use parentheses like a `String's .length()`.

Quick initialization

```
type[ ] name = {value, value, ... value};
```

- Example:

```
int[ ] numbers = {12, 49, -2, 26, 5, 17, -6};
```

<i>index</i>	0	1	2	3	4	5	6
<i>value</i>	12	49	-2	26	5	17	-6

- Useful when you know what the array's elements will be.
- The compiler figures out the size by counting the values.

The Arrays class

- Class `Arrays` in package `java.util` has useful static methods for manipulating arrays:

Method name	Description
<code>binarySearch(array, value)</code>	returns the index of the given value in a sorted array (< 0 if not found)
<code>copy(array)</code>	returns a new array with same elements
<code>equals(array1, array2)</code>	returns <code>true</code> if the two arrays contain the same elements in the same order
<code>fill(array, value)</code>	sets every element in the array to have the given value
<code>sort(array)</code>	arranges the elements in the array into ascending order
<code>toString(array)</code>	returns a string representing the array, such as "[10, 30, 17]"

Array as parameter

```
public static type methodName(type[ ] name) {
```

- Example:

```
public static double average(int[ ] numbers) {  
    ...  
}
```

- Call:

methodName(arrayName) ;

- Example:

```
int[ ] scores = {13, 17, 12, 15, 11};  
double avg = average(scores);
```

Array as return

```
public static type[ ] methodName(parameters) {
```

- Example:

```
public static int[ ] countDigits(int n) {  
    int[ ] counts = new int[10];  
    ...  
    return counts;  
}
```

- Call:

```
type[ ] name = methodName(parameters);
```

- Example:

```
int[ ] tally = countDigits(229231007);  
System.out.println(Arrays.toString(tally));
```

Exercise

- Write a method named `stutter` that accepts an array of integers as a parameter and returns a new array, twice as long as the original, with two copies of each original element.

- If the method were called in the following way:

```
int[ ] a = { 4, 7, -2, 15, 6 } ;  
int[ ] a2 = stutter(a) ;  
System.out.println(Arrays.toString(a2)) ;
```

- The output produced would be:

```
[ 4, 4, 7, 7, -2, -2, 15, 15, 6, 6 ]
```

Exercise solutions

```
public static int[] stutter(int[] a) {  
    int[] result = new int[a.length * 2];  
    for (int i = 0; i < a.length; i++) {  
        result[2 * i] = a[i];  
        result[2 * i + 1] = a[i];  
    }  
    return result;  
}  
  
public static int[] stutter(int[] a) {  
    int[] result = new int[a.length * 2];  
    for (int i = 0; i < result.length; i++) {  
        result[i] = a[i / 2];  
    }  
    return result;  
}
```

Testing code

- Q: How can we tell if our stutter method works properly?
 - A: We must test it.
- Q: How do we test code?
 - A: Call the method several times and print/examine the results.
- Q: Can we test all possible usages of this method?
Q: Can we prove that the stutter code has no bugs?
 - A: No; exhaustive testing is impractical/impossible for most code.
 - A: No; testing finds bugs but cannot prove the absence of bugs.

How to test code

- **test case:** Running a piece of code once on a given input.
- Q: Which cases should we choose to test?
 - *equivalence classes of input*: Think about kinds of inputs:
 - positive vs. negative numbers vs. 0; null (maybe)
 - unique values vs. duplicates (consecutive and non-consecutive)
 - an empty array; a 1-element array; a many-element array
- Q: What are some properties to look for in testing code?
 - *boundaries*: Hits cases close to a relevant boundary, e.g. the maximum allowed value, the first/last element in an array, etc.
 - *code coverage*: Hits all paths through code (if/elses, etc.)
 - *preconditions*: What does the method assume? Does the code ever violate those assumptions?

Exercise

- Write a short piece of code that tests the `stutter` method.
 - Decide on a group of test input cases.
 - For each test case:
 - Print the array's contents before and after stuttering.
 - Print whether the test was successful or failed.

Exercise solution 1

```
public static void main(String[] args) {  
    int[] a1 = {1, 2, 4, 5, 6};  
    int[] a2 = stutter(a1);  
    System.out.println(Arrays.toString(a2));  
    ...  
}
```

- Pros:
 - simple, short
- Cons:
 - must manually check output to see if it is correct
 - must copy/paste to create each test case (redundant)

Exercise solution 2

```
public static void main(String[] args) {  
    test(new int[] {1, 2, 4, 5, 6, 8},  
         new int[] {1, 1, 2, 2, 4, 4, 5, 5, 6, 6, 8, 8});  
    test(new int[] {0, 0, 7, 9},  
         new int[] {0, 0, 0, 0, 7, 7, 9, 9});  
    test(new int[] {-50, 95, -9876},  
         new int[] {-50, -50, 95, 95, -9876, -9876});  
    test(new int[] {42}, new int[] {42, 42});  
    test(new int[] {}, new int[] {});  
}  
  
public static void test(int[] a, int[] expected) {  
    int[] a2 = stutter(a);  
    System.out.print(Arrays.toString(a) + " -> " +  
                    Arrays.toString(a2) + " : ");  
    if (Arrays.equals(a2, expected)) {  
        System.out.println("Pass");  
    } else {  
        System.out.println("FAIL!!!!");  
    }  
}
```