

^ ^ CSE 143 MIDTERM EXAM CHEAT SHEET ^ ^

Constructing Various Collections

```
List<Integer> list = new ArrayList<Integer>();
Queue<Double> queue = new LinkedList<Double>();
Stack<String> stack = new Stack<String>();
Set<String> words = new HashSet<String>();
Map<String, Integer> counts = new TreeMap<String, Integer>();
```

Methods Found in ALL collections (Lists, Stacks, Queues, Sets, Maps)

<code>equals(collection)</code>	returns true if the given other collection contains the same elements
<code>isEmpty()</code>	returns true if the collection has no elements
<code>size()</code>	returns the number of elements in the collection
<code>toString()</code>	returns a string representation such as "[10, -2, 43]"

Methods Found in both Lists and Sets (ArrayList, LinkedList, HashSet, TreeSet)

<code>add(value)</code>	adds value to collection (appends at end of list)
<code>addAll(collection)</code>	adds all the values in the given collection to this one
<code>contains(value)</code>	returns true if the given value is found somewhere in this collection
<code>iterator()</code>	returns an Iterator object to traverse the collection's elements
<code>clear()</code>	removes all elements of the collection
<code>remove(value)</code>	finds and removes the given value from this collection
<code>removeAll(collection)</code>	removes any elements found in the given collection from this one
<code>retainAll(collection)</code>	removes any elements <i>not</i> found in the given collection from this one

List<E> Methods (10.1)

<code>add(index, value)</code>	inserts given value at given index, shifting subsequent values right
<code>indexOf(value)</code>	returns first index where given value is found in list (-1 if not found)
<code>get(index)</code>	returns the value at given index
<code>lastIndexOf(value)</code>	returns last index where given value is found in list (-1 if not found)
<code>remove(index)</code>	removes/returns value at given index, shifting subsequent values left
<code>set(index, value)</code>	replaces value at given index with given value
<code>subList(from, to)</code>	returns sub-portions at indexes from (inclusive) and to (exclusive)

Stack<E> Methods

<code>pop()</code>	removes the top value from the stack and returns it; peek/pop throw an EmptyStackException if the stack is empty
<code>push(value)</code>	places the given value on top of the stack

Queue<E> Methods

<code>add(value)</code>	places the given value at the back of the queue
<code>remove()</code>	removes the value from the front of the queue and returns it; throws a NoSuchElementException if the queue is empty

^_ ^ CSE 143 MIDTERM EXAM CHEAT SHEET ^_ ^

Map<K, V> Methods (11.3)

<code>containsKey(key)</code>	true if the map contains a mapping for the given key
<code>get(key)</code>	the value mapped to the given key (<code>null</code> if none)
<code>keySet()</code>	returns a <code>Set</code> of all keys in the map
<code>put(key, value)</code>	adds a mapping from the given key to the given value
<code>putAll(map)</code>	adds all key/value pairs from the given map to this map
<code>remove(key)</code>	removes any existing mapping for the given key
<code>toString()</code>	returns a string such as " <code>{a=90, d=60, c=70}</code> "
<code>values()</code>	returns a <code>Collection</code> of all values in the map

String Methods (3.3, 4.4)

<code>charAt(i)</code>	the character in this String at a given index
<code>contains(str)</code>	true if this String contains the other's characters inside it
<code>endsWith(str)</code>	true if this String ends with the other's characters
<code>equals(str)</code>	true if this String is the same as <code>str</code>
<code>equalsIgnoreCase(str)</code>	true if this String is the same as <code>str</code> , ignoring capitalization
<code>indexOf(str)</code>	first index in this String where given String begins (-1 if not found)
<code>lastIndexOf(str)</code>	last index in this String where given String begins (-1 if not found)
<code>length()</code>	number of characters in this String
<code>isEmpty()</code>	true if this String is the empty string
<code>startsWith(str)</code>	true if this String begins with the other's characters
<code>substring(i, j)</code>	characters in this String from index <code>i</code> (inclusive) to <code>j</code> (exclusive)
<code>toLowerCase(), toUpperCase()</code>	a new String with all lowercase or uppercase letters

Math Methods (3.2)

<code>abs(x)</code>	returns the absolute value of <code>x</code>
<code>max(x, y)</code>	returns the larger of <code>x</code> and <code>y</code>
<code>min(x, y)</code>	returns the smaller of <code>x</code> and <code>y</code>
<code>pow(x, y)</code>	returns the value of <code>x</code> to the <code>y</code> power
<code>random()</code>	returns a random number between <code>0.0</code> and <code>1.0</code>
<code>round(x)</code>	returns <code>x</code> rounded to the nearest integer