

## CSE 142 Sample Midterm Exam #4 Key

Also check out Practice-It to test solving these problems or to type in your own solution to see if it works!

### 1. Expressions

<u>Expression</u>	<u>Value</u>
<code>5 * 2 * 4 - 3 * 3</code>	31
<code>29 / 4 / 2.0 + 18 / 5 + 1.5</code>	8.0
<code>30 % (4 + 3) + 16 % 20</code>	18
<code>!(23 + 2 * 2 &lt;= 27) &amp;&amp; 5 % 2 == 1</code>	false
<code>1 + 1 + "(8 - 2)" + (8 - 2) + 1 + 1</code>	"2(8 - 2)611"

### 2. Parameter Mystery

`10` is roughly `4` plus `3`  
`5` is roughly `10` plus `3`  
`17` is roughly `2` plus `6`  
`3` is roughly `17` plus `40`  
`3` is roughly `7` plus `4`

### 3. If/Else Simulation

<u>Method Call</u>	<u>Output</u>
<code>mystery(4);</code>	4 7
<code>mystery(30);</code>	30 16
<code>mystery(-6);</code>	-6 -13
<code>mystery(18);</code>	18 10
<code>mystery(15);</code>	15 8

### 4. While Loop Simulation

<u>Method Call</u>	<u>Output</u>
<code>mystery(-2, -6);</code>	0
<code>mystery(2, 3);</code>	0 1 1
<code>mystery(4, 8);</code>	0 3 5 6
<code>mystery(5, 40);</code>	0 4 7 9 10 10
<code>mystery(10, 31);</code>	0 9 17 24 30

### 5. Assertions

	<code>a != 0</code>	<code>c % 2 == 0</code>	<code>b &gt; 0</code>
<b>Point A</b>	SOMETIMES	ALWAYS	NEVER
<b>Point B</b>	ALWAYS	SOMETIMES	SOMETIMES
<b>Point C</b>	ALWAYS	NEVER	NEVER
<b>Point D</b>	SOMETIMES	SOMETIMES	SOMETIMES
<b>Point E</b>	NEVER	SOMETIMES	SOMETIMES

## 6. Programming (two solutions shown)

```
public static String graduation(double gpa, int credits, int honorsCredits) {  
    if (credits >= 180 && gpa >= 2.0) {  
        if (honorsCredits >= 15 && gpa >= 3.8) {  
            return "summa cum laude";  
        } else if ((honorsCredits >= 15 && gpa >= 3.6) || gpa >= 3.8) {  
            return "magna cum laude";  
        } else if (gpa >= 3.6) {  
            return "cum laude";  
        } else {  
            return "graduating";  
        }  
    } else {  
        return "not graduating";  
    }  
}  
  
public static String graduation(double gpa, int credits, int honorsCredits) {  
    if (credits < 180 || gpa < 2.0) {  
        return "not graduating";  
    } else if (honorsCredits >= 15 && gpa >= 3.8) {  
        return "summa cum laude";  
    } else if (honorsCredits >= 15 && gpa >= 3.6 || gpa >= 3.8) {  
        return "magna cum laude";  
    } else if (gpa >= 3.6) {  
        return "cum laude";  
    } else {  
        return "graduating";  
    }  
}
```

## 7. Programming (three solutions shown)

```
public static void cheerleader(int lines, int cheers) {  
    for (int line = 0; line < lines; line++) {  
        for (int space = 1; space <= line * 3; space++) {  
            System.out.print(" ");  
        }  
  
        System.out.print("Go");  
        for (int cheer = 2; cheer <= cheers; cheer++) {  
            System.out.print(" Team Go");  
        }  
        System.out.println();  
    }  
}  
  
public static void cheerleader(int lines, int cheers) {  
    String indent = " ";  
    for (int line = 1; line <= lines; line++) {  
        System.out.print(indent);  
        for (int cheer = 1; cheer <= cheers - 1; cheer++) {  
            System.out.print("Go Team ");  
        }  
        System.out.println("Go");  
        indent += "    ";  
    }  
}  
  
public static void cheerleader(int lines, int cheers) {  
    for (int line = 1; line <= lines; line++) {  
        for (int space = 1; space <= line - 1; space++) {  
            System.out.print("    ");  
        }  
        for (int cheer = 1; cheer <= cheers - 1; cheer++) {  
            System.out.print("Go Team ");  
        }  
        System.out.println("Go");  
    }  
}
```

## 8. Programming (three solutions shown)

```
public static void randomRects() {
    Random r = new Random();
    int last = 100; // can also be 0
    int count = 0;

    while (count < 4) {
        int w = r.nextInt(10) + 1;
        int h = r.nextInt(10) + 1;

        System.out.println("w: " + w + ", h: " + h + ", area: " + w * h);

        if (last < w * h) {
            count++;
        } else {
            count = 1; // need to count first rect in sequence
        }
        last = w * h;
    }
    System.out.println("Four rectangles of increasing area.");
}

public static void randomRects() {
    Random r = new Random();
    int a1 = 0, a2 = 0, a3 = 0, a4 = 0;
    while (a1 == 0 || a1 >= a2 || a2 >= a3 || a3 >= a4) {
        int w = r.nextInt(10) + 1;
        int h = r.nextInt(10) + 1;
        a1 = a2;
        a2 = a3;
        a3 = a4;
        a4 = w * h;
        System.out.println("w: " + w + ", h: " + h + ", area: " + a4);
    }
    System.out.println("Four rectangles of increasing area.");
}

public static void randomRects() {
    Random r = new Random();
    int area = 0;
    int last = 0;
    int count = 0;
    while (count != 4) {
        int w = r.nextInt(10) + 1;
        int h = r.nextInt(10) + 1;
        area = w * h;
        if (area <= last) {
            count = 1;
        } else {
            count++;
        }
        System.out.println("w: " + w + ", h: " + h + ", area: " + area);
        last = area;
    }
    System.out.println("Four rectangles of increasing area.");
}
```