

CSE 303: Concepts and Tools for Software Development

Dan Grossman

Spring 2005

Lecture 2— Processes, Users, Shell Special Characters, Emacs

Where are we

It's like we started over using the computer from scratch.

And all we can do is run dinky programs at the command-line.

But we are learning a *model* (the system is files, processes, and users) and a powerful way to *control* it (the shell).

If we get the model right, hopefully we can learn lots of details quickly.

Today:

- The rest of the model briefly: Processes and Users
- More programs (`ps`, `chmod`, `kill`, ...)
- Special shell characters (`*`, `~`, ...)
- Text editing (particularly `emacs`)

Users

- There is one file-system, one operating system, (often) one CPU, and multiple users.
- `whoami`
- `ls -l` and `chmod` (permissions), `quota` (limits)
- `/etc/passwd` guides the *login* program:
 - Correct username and password
 - Home directory
 - Which shell to open (pass it the home directory)
 - The shell then takes over, with *startup scripts* (e.g., `.cshrc`).
(`ls -a`)
- one “superuser” a.k.a. *root*. (Change passwords, halt machine, ...)

Processes

- A running program is called a *process*. An *application* (e.g., emacs), may be running as 0, 1, or 57 processes at any time.
- The shell runs a program by “launching a process” waiting for it to finish, and giving you your prompt back.
 - What you want for `ls`, but not for `emacs`.
 - `&`, `jobs`, `fg`, `bg`, `kill`
 - `ps`, `top`
- A running shell is just a process that kills itself when interpreting the `exit` command.
- (Apologies for aggressive vocabulary, but we’re stuck with it for now.)

That's most of a running system

- File-system, users, processes
- The operating system manages these
- Processes can do I/O, change files, launch other processes.
- Other things: Input/Output devices (monitor, keyboard, network)
- GUIs don't change any of this, but they do hide it a bit.

Now: Back to the shell...

Complicating the shell

So far, our view of the shell is the barest minimum:

- *builtins* affect subsequent interpretations. New: `source`, `alias`
- Otherwise, the first “word” is a program run with the other “words” passed as arguments.
 - Programs interpret arguments arbitrarily, but conventions exist.

But you want (and `tcsh` has) so much more:

- Filename metacharacters
- Pipes and Redirections (redirecting I/O from and to files)
- Command-line editing and history access
- Shell and environment variables
- Programming Constructs (`ifs`, loops, arrays, expressions, ...)

All together, a very powerful feature set, but awfully unelegant.

Filename metacharacters

Much happens to a command-line to turn it into a “call program with arguments” (or “invoke builtin”).

Certain characters can *expand* into (potentially) multiple filenames:

- `~foo` – home directory of user `foo`
- `~` – current user’s home directory (same as `~$user` or `‘whoami’`).
- `*` (by itself) – all files in current directory
- `*` – *match* 0 or more filename characters
- `?` – *match* 1 filename character
- `[abc]`, `[a-E]`, `[^a]`, ... more matching

Remember, this happens *before* deciding what to pass to a program.

Filename metacharacters: why

- Manually, you use them all the time to *save typing*.
- In scripts, you use them for *flexibility*. Example: You do not know what files will be in a directory, but you can still do: `cat *` (though a better script would skip directories).

But what if it's not what you want? Use quoting ("`*`") or escaping (`*`).

The rules on what needs escaping where are *very* arcane.

Where are we

Features of the `tcsh` “language”:

1. builtins
 2. program execution
 3. filename expansion
-
4. command-line editing and history
 5. shell and environment variables
 6. programming constructs

But file editing is too useful to put off... so a detour to `emacs` (which shares some editing commands with `tcsh`)

What is emacs?

A programmable, extensible text editor, with lots of goodies for programmers.

Not a full-blown IDE.

Much “heavier weight” than vi.

Top-6 commands:

- C-g
- C-x C-f
- C-x C-s, C-x C-w
- C-x C-c
- C-x b
- C-k, C-w, C-y, ...

Customizable with elisp (starting with your .emacs).

Putting it all together: Java

Java is a programming language; you can write and run programs in various environments.

The `javac` and `java` programs “compile” and “run” Java programs and `emacs` has a decent Java mode.

So we can write Java files in `emacs`, and use the shell to run the program and pass arguments.

(The Java program takes the class whose main should be run as its first argument and gives it the remaining arguments.)

History

- The `history` builtin
- The `!` special character
 - `!!`, `!n`, `!abc`, ...
 - Can add, substitute, etc.

This is really for fast manual use; not so useful in scripts.

Command-line editing

Note: getting backspace to work in Reflection-X

Lots of control-characters for moving around and editing the command-line.

They make no sense in scripts.

Gotcha: C-q is a strange one (stops displaying output until C-s, but input does get executed).

Good news: many of the control characters have the same meaning in emacs (and tcsh has a vi “mode” too).

Summary

As promised, we are flying through this stuff!

- Your computing environment has files, processes, users, a shell, and programs (including emacs).
- Lots of small programs for files, permissions, manuals, etc.
- The shell has strange rules for interpreting command-lines. So far:
 - Filename expansion
 - History expansion
- The shell has lots of ways to customize/automate. So far:
 - `alias`
 - `source`
 - run `.cshrc` when shell starts.

Next: I/O Redirection, Shell Programming