

CSE 303: Concepts and Tools for Software Development

Dan Grossman
Winter 2006
Lecture 11— C: casts, lists

Where are We

We have learned most of the important stuff with C, so now we will move more toward idioms and larger programs.

- Today: casts, linked lists
- Wednesday: The C pre-processor (stuff starting with #) and `printf` (by Ben)
- Friday: Post-overview, function pointers
- Monday: Societal Implications (TBD)
- Wednesday: MIDTERM (through next Friday, not counting “lecture” 10)
 - Will post a bit of information
 - Closed-book, but one side of 8.5x11 sheet of paper

Later: 30–50 minutes on C++

The C types

There are an infinite number of types in C, but only a few ways to make them:

- `char`, `int`, `double`, etc. (many more such as `unsigned int`)
- `void` (a type no expression can have)
- `struct T` where there is already a declaration for that struct type.
- Array types (basically only for stack arrays and struct fields, every use is automatically converted to a pointer type)
- `t*` where `t` is a type
- `union T`, `enum E` (later, maybe)
- function-pointer types (later)
- *typedefs* (just expand to their definition)

Casts, part 1

Syntax: `(t)e` where `t` is a type and `e` is an expression (same as Java).

Semantics: It depends.

- If `e` is a numeric type and `t` is a numeric type, this is a *conversion*.
 - To *wider* type, get same value
 - To *narrower* type, may not (will get *mod*)
 - From floating-point to integral, will *round*
 - From integral to floating-point, may round (but `int` to `double` won't round on most machines)

Note: Java is the same without the “most machines” part.

Note: There are also lots of *implicit* conversions such as in function calls.

Bottom line: Conversions involve “real” operations; `(double)3` is a very different bit pattern than `(int)3`.

Casts, part 2

- If `e` has type `t1*`, then `(t2*)e` is a (pointer) cast.
 - You still have the same pointer (index into the address space).
 - Nothing “happens” at run-time.
 - You are just “getting around” the type system, making it easy to potentially set the computer on fire.
 - Old example: `malloc` has return type `void*`.

```
void evil(int **p, int x) {
    int * q = (int*)p;
    *q = x;
}

void f(int **p) {
    evil(p,345);
    **p = 17; // writes 17 to address 345 (crash)
}
```

Note: The C standard is more picky than I will suggest, but few people know that and little code obeys the official rules.

Pointer casts continued

Questions worth answering:

- How does this compare to Java's casts?
 - Unsafe, unchecked
 - Otherwise more similar than it seems
- When *should* you use pointer casts in C?
 - For “generic” libraries (`malloc`, linked lists, etc.)
 - For “subtyping” (later)
- What about other casts?
 - Casts to/from struct types are compile-time errors.

Java casts

Java casts (e.g., `(Foo)e` explained) to C programmers:

- `e` evaluates to a pointer to an object.
- Objects have “secret fields” at *run-time* indicating their class.
- If the object’s secret field is `Foo` or a (transitive) subclass of `Foo` “succeed”. Else raise an exception.
- If `e`’s (*compile-time*) type is a (transitive) subtype of `Foo`, then the compiler can “omit the check”. (Called an upcast.)
- If `e`’s (*compile-time*) type is neither a (transitive) subtype nor supertype of `Foo`, it is a compile-time error. (The cast could never succeed.)

Linked lists

Linked lists are a very common data structure.

Building them in C:

- Gives practice with pointers, structs, malloc, etc.
- Leads to using casts for “generic” types.
- Shows memory management problems if lists “share tails”.
- Shows the trade-offs between lists and arrays.

See the code! Understand the code!