CSE 321: Discrete Structures
Assignment #3
April 12, 2000
due: Wednesday, April 19

1. Section 2.3, exercise 4. Give a careful proof.

2. Section 2.3, exercise 12. Justify your answer. The function $n!$ is defined on page 85. (Hint: Think about the unique factorization of 100! into primes. What about this factorization determines the number of zeros at the end of the decimal representation of 100! ?)

3. Using only your brain, pencil, and paper (e.g., no calculator), compute $23^{25} \bmod 31$. Show your intermediate steps (as proof that you used your brain instead of a calculator). (Hint: If you use the method I demonstrated in lecture, you should never need to compute any product greater than $15 \cdot 15$.)

4. Section 2.3, exercise 38. Give a careful proof.

5. Use Euclid's algorithm to compute the following, showing the values of x and y for each iteration of the algorithm.

   (a) $\gcd(1020, 1173)$

   (b) $\gcd(1019, 1173)$

6. Suppose that you want to compute $\gcd(a, b)$, where a and b each have n digits. The naive algorithm that first finds the prime factorization of a and b uses approximately $10^{n/2}$ integer divisions to do so, by trying all possible divisors up to $\sqrt{a}$ and $\sqrt{b}$, respectively. In contrast, Euclid's algorithm uses approximately $5n$ divisions. Suppose you were running these two algorithms on a computer that could do 10^9 divisions per second. Put your answers to the following questions into a single 3×2 table:

   - What is the greatest number n of digits that you could handle by each of the two methods in 10^{-6} seconds of computer time?
   - What is the greatest number n of digits that you could handle by each of the two methods in 10^{-3} seconds of computer time?
   - What is the greatest number n of digits that you could handle by each of the two methods in 1 second of computer time?