CSE 326
Lecture 12

Spring Quarter 1997

B - Trees

- B-trees are multiway trees which are not binary



- B-tree nodes contain search keys only, actual data is stored at the leaves.
- B-tree developed for database applications where minimizing the number of disk accesses is important. B-tree nodes are large enough to balance the disk access time with the internal search time within a B-tree node.

Properties of B-Trees of Order m

- The root is either a leaf or has between 2 and m children
- All non-leaf node (except the root) have between | m/2 | and m children.
- All leaves are at the same depth and contain between | m/2 | and m - 1 keys.
- A node will have keys $k_1, k_2, k_3, ..., k_i$ where | m/2 | < i < m



Example



Find in a B-Tree

- If m is large then binary search within a B-tree node.



- If m is small then linear search is fine.



Insertion in a B-tree

- Begin by inserting in the proper leaf.
- If the leaf ends up with m items, it has overflowed.
- An overflowed leaf node is split into two nodes with | m/ 2 | in one and | m/2 | in the other. A new child is added to the parent.
- An overflowed internal node with m+1 children is split into two nodes, one with | (m+1)/2 | children and the other with | (m+1)/2 | children. A new child is added to the parent.
- If overflow propagates to the root, then the node is split into two and a new root with two children is formed.

Insertion with Overflow - Leaf Case

B-tree of order 4



Splitting a node



Insertion with Overflow - Internal Node Case

B-tree of order 4



Splitting a node



Example of Insertion

- Insert 1,2,3,4 5,6 7,8, ... into a B-tree of order 4

B-Tree Deletion

- In deletion a leaf may underflow, that is, have < | m/2 | items.

  1. Borrow from a sibling.

  2. If borrowing is impossible then give all to siblings evenly and physically delete the node. Deletion may propagate to the parent.

Borrowing



Elimination without Propagation



Deletion with Propagation



Summary of B-Trees

- B-trees of order 3 are often called 2-3 trees and B-trees of order 4 are often called 2-3-4 trees.
- B-trees are used when accessing a new node can be costly, like in large data bases. The root and next level are often kept in main memory.
- B-tree insertion causes splitting which may propagate.
- B-tree deletion causes borrowing (good) or physical deletion which may propagate. Propagation is quite rare if the order of the tree is large.
- In standard B-trees there can be thrashing with repeated insertions followed by deletions. This can be overcomed with B* trees.
- If order of the tree is large like 64 or 128, then only a few levels are need to store very large data sets. For example, if m = 128 then a B-tree of height 4 will store at least 30 million items.

Summary of Search Trees

- Plain vanilla binary search trees

  Good on average - simple to understand and use.
- AVL trees - height balanced trees

  Good in worst case - more complicated.
- Splay trees

  Good amortized cost and good locality properties - slightly more complicated than AVL.
- B-trees

  Good in worst case when node access is expensive - most complicated of the algorithms.

Summary of Dictionary Data Structures

	Find	Insert	Delete	Find-min	List-all	n Finds
Sorted Array	log n	n	n	1	n	n log n
Ordered List	n	n	n	1	n	n^2
Binary Search Tree	n	n	n	n	n	n^2
AVL Tree	log n	log n	log n	log n	n	n log n
Splay Tree[1]	n	n	n	n	n	n log n
B-tree[2]	log n	log n	log n	log n	n	n log n

1. Splay Tree efficiently supports the additional operations of split and merge.

2. B-tree is suitable for out of memory applications while other data structures are for in memory applications.