CSE 326
Lecture 18

Spring Quarter 1997

Mergeable Priority Queue

- Mergeable priority queues allow for the efficient implementation of the operation Merge(H_1,H_2) which merges two priority queues into a single priority queue.
- Normally, Merge(H_1,H_2) returns a new priority queue destroying H_1 and H_2 in the process.
- Applications

  1. Specific algorithms like one for minimum spanning tree and another for the optimal binary search tree.

  2. Managing work queues in a distributed system.

Leftist Trees

- A leftist tree is a binary tree with two properties.

  1. Heap property - key at a node is less than or equal to the keys of its children.

  2. Leftist property - For each node the null path length of the left subtree is greater than or equal to the null path length of the right subtree.
- Null path length - The null path length of a node (subtree) is the shortest path to a node without two children. A null has null path length = -1.

not a leftist tree



leftist tree



The Right Path of a Leftist Tree is Short

- In a leftist tree if the right path has length at least r then the leftist tree has at least $2^r - 1$ nodes.
- Proof is by induction on r.

  Basis: r = 1. The tree must have at least 1 node, the root, and $2^1 - 1 = 1$.

  Inductive Step: Assume the statement is true for all r' < r and r > 1. The right subtree has a right path of at least r-1 nodes, so by the induction hypothesis, it has at least $2^{r-1} - 1$ nodes. The left subtree must also have a right path of length at least r - 1. By the inductive hypothesis it has at least $2^{r-1} - 1$ nodes. Thus the total number of nodes is at least

  $$2^{r-1} - 1 + 2^{r-1} - 1 + 1 = 2^r - 1.$$
- Thus a leftist tree with n nodes must have a right path of length $\leq \log n$.

Data Structure for Leftist Trees

- Assume that a node of a leftist tree contains the following



- The basic operation is the merging of two leftist trees. O(log n)
- Insert by merging a single node with a leftist tree. O(log n)
- Delete_min by merging the left and right subtrees of the root. O(log n)

Merging Two Leftist Trees

- Merge(T_1,T_2) returns a new leftist tree assuming T_1 and T_2 are two distinct leftist trees. Without loss of generality we can assume root of T_1 has the smaller of the two roots.



Merge Continued



Example



Example Continued



Example Continued



Example Continued



Example Continued



Iterative Leftist Tree Merging

- Two passes to merge T_1 and T_2.

  Downward pass: merge the right paths of T_1 and T_2 forming a new tree T.

  Upward pass: Return along the right path of T computing the null path lengths and interchanging the left and right subtrees to maintain the leftist property.

Iterative Leftist Tree



Upwards Pass



Insertion in leftist trees

- Insert 12



Delete_min



Skew Heaps

- Self adjusting version of leftist heaps (priority queues)
- Amortized time to merge, insertion, and delete_min is O(log n)
- Worst case time is O(n) for these operations.
- Merging

  Always switch children on merging except for the final step.
- Top down method - one pass

Skew Heap



Skew Heap Code

- merge(S, T) {

  local pointer temp;

  case
  S=null: return(T);
  T=null: return(S);
  S.key < T.key: {
  temp := S.left;
  S.left := merge(S.right,T);
  S.right := temp;
  return(S) }
  T.key ≤ S.key: {
  temp := T.left;
  T.left := merge(T.right,S);
  T.right := temp;
  return(T) }
  endcase }

Skew Heap Example



Example Continued



Example Continued



Example Continued