
CSE 331

Software Design & Implementation

Hal Perkins
Winter 2022
Subtypes and Subclasses

Administrivia (1)

- HW5 part 2 due tomorrow night (plus late day if available)
 - Don't get overly ambitious – no generics for now, etc.
 - Remember main Graph ADT should not assume that node/edge labels will always be comparable
 - Client code should compare/sort as needed
 - Don't overuse strings - store data as data, not printable strings, unless it really is a string
 - Remember to disable expensive checkRep()s in commit that has the final hw5 part 2 tag on it
 - And *get the tag right* ! It's in the hw5-2 assignment
 - Don't blindly import libraries that IntelliJ "suggests"
- Reminder: **DO NOT** submit work found on the web or written by anyone else as your own work. It's not, and it's a problem. (We have some of this on hw5-1 already)
 - If you need help please reach out to course staff


Administrivia (2)

- Midterm exam: thanks everyone for helping things go so smoothly. We'll try to get it graded fairly soon, but probably won't be done until next week.
- Sections tomorrow: hw6 (data files, graph search, etc.)
 - Starter code will be pushed to repos later tonight

What is subtyping?

Sometimes “*every B is an A*”

- Example: In a library database:
 - Every book is a library holding
 - Every CD is a library holding



Subtyping expresses this

- “*B is a subtype of A*” means:
“every object that satisfies the rules for a B also satisfies the rules for an A”

Goal: code written using A's specification operates correctly even if given a B

- Plus: clarify design, share tests, (sometimes) share code

Subtypes are substitutable

Subtypes are **substitutable** for supertypes

- Instances of subtype won't surprise client by failing to satisfy the supertype's specification
- Instances of subtype won't surprise client by having more expectations than the supertype's specification
- i.e., a client that expects a Shape will work fine if given a Circle

We say that B is a **true subtype** of A if B has a stronger specification than A

- This is **not** the same as a **Java subtype** (B extends A)
- Java subtypes that are not true subtypes are **confusing** and **dangerous**
 - But unfortunately fairly common poor-design ☹️

Subtyping vs. subclassing

Substitution (**subtype**) — a **specification** notion

- B is a subtype of A iff an object of B can masquerade as an object of A in any context
- Any fact about an A object is true about a B object
- Similar to satisfiability (behavior of a B is a subset of A's spec)

Inheritance (**subclass**) — an **implementation** notion

- Factor out repeated code
- To create a new class, write only the differences

Java purposely merges these notions for classes:

- Every subclass is a Java subtype
 - But not necessarily a true subtype
 - (Java compiler can't check or guarantee that B is a true subtype of A)

Inheritance makes adding functionality easy

Suppose we run a web store with a class for *products*...

```
class Product {
    private String title;
    private String description;
    private int price; // in cents
    public int getPrice() {
        return price;
    }
    public int getTax() {
        return (int)(getPrice() * 0.096);
    }
    ...
}
```

... and we need a class for *products that are on sale*

We know: don't copy code!

We would never dream of cutting and pasting like this:

```
class SaleProduct {
    private String title;
    private String description;
    private int price; // in cents
    private float factor;
    public int getPrice() {
        return (int) (price*factor);
    }
    public int getTax() {
        return (int) (getPrice() * 0.096);
    }
    ...
}
```


Inheritance makes small extensions small

Much better:

```
class SaleProduct extends Product {  
    private float factor;  
    @Override  
    public int getPrice() {  
        return (int) (super.getPrice() * factor);  
    }  
}
```

Benefits of subclassing & inheritance

- Don't repeat unchanged fields and methods
 - In implementation
 - Simpler maintenance: fix bugs once
 - In specification
 - Clients who understand the superclass specification need only study novel parts of the subclass
 - Modularity: can ignore private fields and methods of superclass (if properly defined)
 - Differences not buried under mass of similarities
- Ability to substitute new implementations
 - No client code changes required to use new subclasses

Subclassing can be misused

- Poor planning can lead to a muddled *class hierarchy*
 - Relationships might not match untutored intuition
- Poor design can produce subclasses that depend on many implementation details of superclasses
- Changes in superclasses can break subclasses if they are tightly coupled
 - “fragile base class problem”
- **Subtyping and implementation inheritance are orthogonal!**
 - Subclassing gives you both
 - Sometimes you want just one
 - *Interfaces*: subtyping without inheritance
 - *Composition*: use implementation without subtyping
 - Can seem less convenient, but often better long-term

Is every square a rectangle?

```
interface Rectangle {
    // effects: fits shape to given size:
    //           thispost.width = w, thispost.height = h
    void setSize(int w, int h);
}
interface Square extends Rectangle {...}
```


Which is the best option for Square's `setSize` specification?

1. `// requires: w = h`
`// effects: fits shape to given size`
`void setSize(int w, int h);`
2. `// effects: sets all edges to given size`
`void setSize(int edgeLength);`
3. `// effects: sets this.width and this.height to w`
`void setSize(int w, int h);`
4. `// effects: fits shape to given size`
`// throws BadSizeException if w != h`
`void setSize(int w, int h) throws BadSizeException;`

Square, Rectangle Unrelated (Java)


Square is not a (true subtype of) **Rectangle**:

- **Rectangles** are expected to have a width and height that can be mutated independently
- **Squares** violate that expectation, could surprise client



Rectangle is not a (true subtype of) **Square**:

- **Squares** are expected to have equal widths and heights
- **Rectangles** violate that expectation, could surprise client




Inheritance is not always intuitive

- Benefit: it forces clear thinking and prevents errors

Solutions:

- Make them unrelated (or siblings)
- Make them immutable (!)
 - Recovers elementary-school intuition



Inappropriate subtyping in the JDK

```
class Hashtable<K,V> {  
    public void put(K key, V value) {...}  
    public V get(K key) {...}  
}
```

```
// Keys and values are strings.
```

```
class Properties extends Hashtable<Object,Object> {  
    public void setProperty(String key, String val) {  
        put(key, val);  
    }  
    public String getProperty(String key) {  
        return (String) get(key);  
    }  
}
```

```
Properties p = new Properties();  
Hashtable tbl = p;  
tbl.put("One", 1);  
p.getProperty("One"); // crash!
```

Violation of rep invariant

Properties class has a simple rep invariant:

- Keys and values are **Strings**

But client can treat **Properties** as a **Hashtable**

- Can put in arbitrary content, break rep invariant

From Javadoc:

*Because Properties inherits from Hashtable, the put and putAll methods can be applied to a Properties object. ... If the store or save method is called on a "compromised" Properties object that contains a non-String key or value, **the call will fail.***

Solution 1: Generics

Bad choice:

```
class Properties extends Hashtable<Object, Object> {  
    ...  
}
```

Better choice:

```
class Properties extends Hashtable<String, String> {  
    ...  
}
```

JDK designers deliberately didn't do this. Why?

- Backward-compatibility (Java didn't used to have generics)
- Postpone talking about generics: upcoming lecture
 - But only `Hashtable<Object, Object>` is compatible with all clients that might exist

Solution 2: Composition

```
class Properties {  
    private Hashtable<Object, Object> hashtable;  
  
    public void setProperty(String key, String value) {  
        hashtable.put(key, value);  
    }  
  
    public String getProperty(String key) {  
        return (String) hashtable.get(key);  
    }  
  
    ...  
}
```

Substitution principle for classes

If B is a **subtype** of A, a B can *always be substituted* for an A

Any property guaranteed by supertype A must be guaranteed by subtype B

- Anything provable about an A is provable about a B
- If an instance of subtype is treated purely as supertype (only supertype methods/fields used), then the result should be consistent with an object of the supertype being manipulated

Subtype B is *permitted to strengthen* properties and add properties

- An overriding method must have a stronger (or equal) spec
- Fine to add new methods (that preserve invariants)

Subtype B is *not permitted to weaken* the spec

- No method removal
- No overriding method with a weaker spec

Substitution principle for methods

Constraints on methods

- For each supertype method, subtype must have such a method
 - Could be inherited or overridden

Each overriding method must *strengthen* (or match) the spec:

- Ask nothing extra of client (“weaker precondition”)
 - *Requires* clause is at most as strict as in supertype’s method
- Guarantee at least as much (“stronger postcondition”)
 - *Effects* clause is at least as strict as in the supertype method
 - No new entries in *modifies* clause
 - Promise more (or the same) in *returns* clause
 - *Throws* clause must indicate fewer (or same) possible exception types, but nothing new


Spec strengthening: argument/result types

Method **inputs**:

- Argument types in A.foo may be replaced with supertypes in B.foo (“contravariance”)
- Places no extra demand on the clients
- But Java does not allow such overriding
 - (Why?)

Method **results**:

- Result type of A.foo may be replaced by a subtype in B.foo (“covariance”)
- No new exceptions (for values in the domain)
- Existing exceptions can be replaced with subtypes
(None of this violates what client can rely on)



Substitution exercise

Suppose we have a method which, when given one product, recommends another:

```
class Product {  
    Product recommend(Product ref);  
}
```

Which of these are possible forms of this method in **SaleProduct** (a true subtype of **Product**)?

```
Product recommend(SaleProduct ref); // bad
```

```
SaleProduct recommend(Product ref); // OK
```

```
Product recommend(Object ref); // OK, but is Java  
                                overloading
```

```
Product recommend(Product ref); // bad  
    throws NoSaleException;
```

Java subtyping

- Java types:
 - Defined by classes, interfaces, primitives
- Java subtyping stems from **B extends A** and **B implements A** declarations
- In a Java subtype, each corresponding method has:
 - Same argument types
 - If different, *overloading*: unrelated methods
 - Compatible (covariant) return types
 - Added to Java several years after initial release, not reflected in (e.g.) `clone`
 - No additional declared exceptions

Java subtyping guarantees

A variable's run-time type (i.e., the class of its run-time value) is a Java subtype of its declared type

```
Object o = new Date(); // OK
```

```
Date d = new Object(); // compile-time error
```

If a variable of *declared (compile-time)* type T1 holds a reference to an object of *actual (runtime)* type T2, then T2 must be a Java subtype of T1

(A type T is considered to be a subtype of itself to simplify things)

Corollaries:

- Objects always have implementations of the methods specified by their declared type
- *If* all subtypes are true subtypes, then all objects meet the specification of their declared type

This rules out a huge class of bugs

Clients can still infer implementation details

- Client use of `==` can reveal reuse of values
 - Return existing immutable value rather than creating a new copy
- Client use of iterator can reveal whether data is stored in any particular order (sorted or not, ...)
- Client use of subclassing can reveal self-calls in implementation (example below)
- Lesson: don't do this!
- Clients should not observe/depend on behavior not promised by the spec

Inheritance can break encapsulation

```
public class InstrumentedHashSet<E>
    extends HashSet<E> {
    private int addCount = 0; // count # insertions
    public InstrumentedHashSet(Collection<? extends E> c) {
        super(c);
    }
    public boolean add(E o) {
        addCount++;
        return super.add(o);
    }
    public boolean addAll(Collection<? extends E> c) {
        addCount += c.size();
        return super.addAll(c);
    }
    public int getAddCount() { return addCount; }
}
```

Dependence on implementation

What does this code print?

```
InstrumentedHashSet<String> s =  
    new InstrumentedHashSet<String> ();  
System.out.println(s.getAddCount());           // 0  
s.addAll(Arrays.asList("CSE", "331"));  
System.out.println(s.getAddCount());           // 4?!
```

- Answer *depends on implementation* of `addAll` in `HashSet`
 - Different implementations may behave differently!
 - If `HashSet`'s `addAll` calls `add`, then double-counting
- `AbstractCollection`'s `addAll` specification:
 - “Adds all of the elements in the specified collection to this collection.”
 - Does not specify whether it calls `add`
- Lessons:
 - Subclassing often requires [designing for extension](#)
 - Clients should not depend on unspecified implementation behavior

Solutions – how to count inserts

1. Change spec of **HashSet** (eliminate ambiguity)
 - Indicate all self-calls
 - Less flexibility for implementers of specification
 - Most clients don't care

2. Avoid spec ambiguity by avoiding self-calls
 - a) “Re-implement” methods such as **addAll**
 - Requires re-implementing methods
 - b) Use a wrapper
 - No longer a subtype (unless an interface is handy)
 - Bad for callbacks, equality tests, etc.
 - But avoids dependency on **HashSet** spec

Solution 2b: composition

Delegate

```
public class InstrumentedHashSet<E> {
    private final HashSet<E> s = new HashSet<E>();
    private int addCount = 0;
    public InstrumentedHashSet(Collection<? extends E> c) {
        this.addAll(c);
    }
    public boolean add(E o) {
        addCount++; return s.add(o);
    }
    public boolean addAll(Collection<? extends E> c) {
        addCount += c.size();
        return s.addAll(c);
    }
    public int getAddCount() { return addCount; }
    // ... and every other method specified by HashSet<E>
}
```

The implementation no longer matters

Composition (wrappers, delegation)

Implementation *reuse* without *inheritance*

- Example of a “wrapper” class
- Easy to reason about; self-calls are irrelevant
- Works around badly-designed / badly-specified classes
- Disadvantages (may be worthwhile price to pay):
 - Does not preserve subtyping
 - Tedious to write (your IDE should help you)
 - May be hard to apply to callbacks, equality tests

Composition does not preserve subtyping

- **InstrumentedHashSet** is not a **HashSet** anymore
 - So can't easily substitute it
- It may be a true subtype of **HashSet**
 - But Java doesn't know that!
 - Java requires declared relationships
 - Not enough just to meet specification
- Interfaces to the rescue
 - Can declare that we implement interface **Set**
 - If such an interface exists

Avoid encoding implementation details

Interfaces reintroduce Java source coupling

```
public class InstrumentedHashSet<E> implements Set<E> {
    private final Set<E> s = new HashSet<E>();
    private int addCount = 0;
    public InstrumentedHashSet(Collection<? extends E> c) {
        this.addAll(c);
    }
    public boolean add(E o) {
        addCount++;
        return s.add(o);
    }
    public boolean addAll(Collection<? extends E> c) {
        addCount += c.size();
        return s.addAll(c);
    }
    public int getAddCount() { return addCount; }
    // ... and every other method specified by Set<E>
}
```

What's bad about this constructor?

```
InstrumentedHashSet(Set<E> s) {
    this.s = s;
    addCount = s.size();
}
```

Interfaces and abstract classes

Provide *interfaces* for your functionality

- Clients code to interfaces rather than concrete classes
- Allows different implementations later
- Facilitates composition, wrapper classes
 - Basis of lots of useful, clever techniques
 - We'll see more of these later

Consider also providing helper/template *abstract classes*

- Can minimize number of methods that new implementation must provide by providing some implementations in abs. class
- Makes writing new implementations much easier
- Optional – not needed to use interfaces or to create different implementations of an interface

Java library interface/class example

```
// root interface of collection hierarchy
interface Collection<E>
// skeletal implementation of Collection<E>
abstract class AbstractCollection<E>
    implements Collection<E>
// type of all ordered collections
interface List<E> extends Collection<E>
// skeletal implementation of List<E>
abstract class AbstractList<E>
    extends AbstractCollection<E>
    implements List<E>
// an old friend...
class ArrayList<E> extends AbstractList<E>
```

Why interfaces instead of classes?

Java design decisions:

- A class has exactly one superclass
- A class may implement multiple interfaces
- An interface may extend multiple interfaces

Justification for Java decisions:

- Multiple superclasses are difficult to use and to implement
- Multiple interfaces + single superclass gets most of the benefit

Pluses and minuses of inheritance

- Inheritance is a powerful way to achieve code reuse
- Inheritance can break encapsulation
 - A subclass may wind up depending on unspecified details of the implementation of its superclass
 - example: pattern of self-calls
 - Subclass may need to evolve in tandem with superclass
 - Okay within a package where implementation of both is under control of same programmer
- Authors of superclass should design and document self-use, to simplify extension
 - Otherwise, avoid implementation inheritance and have clients use composition instead