

CSE 332: Data Structures and Parallelism

Section 2: Heaps and Asymptotics

0. Big-Oh Proofs

For each of the following, prove that $f \in \mathcal{O}(g)$.

(a)

$$f(n) = 7n$$

$$g(n) = \frac{n}{10}$$

(b)

$$f(n) = 1000$$

$$g(n) = 3n^3$$

(c)

$$f(n) = 7n^2 + 3n$$

$$g(n) = n^4$$

(d)

$$f(n) = n + 2n \lg n$$

$$g(n) = n \lg n$$

1. Is Your Program Running? Better Catch It!

For each of the following, determine the tight $\Theta(\cdot)$ bound for the worst-case runtime in terms of the free variables of the code snippets.

(a)

```
1 int x = 0
2 for (int i = n; i >= 0; i--) {
3     if ((i % 3) == 0) {
4         break
5     }
6     else {
7         x += n
8     }
9 }
```

(b)

```
1 int x = 0
2 for (int i = 0; i < n; i++) {
3     for (int j = 0; j < (n * n / 3); j++) {
4         x += j
5     }
6 }
```

(d)

(c)

```
1 int x = 0
2 for (int i = 0; i < n; i++) {
3     for (int j = 0; j < i; j++) {
4         x += j
5     }
6 }
```

```
1 int x = 0
2 for (int i = 0; i < n; i++) {
3     if (n < 100000) {
4         for (int j = 0; j < i * i * n; j++) {
5             x += 1
6         }
7     } else {
8         x += 1
9     }
10 }
```

(e)

```
1 int x = 0
2 for (int i = 0; i < n; i++) {
3     if (i % 5 == 0) {
4         for (int j = 0; j < n; j++) {
5             if (i == j) {
6                 for (int k = 0; k < n; k++) {
7                     x += i * j * k
8                 }
9             }
10        }
11    }
12 }
```

2. Asymptotics Analysis

Consider the following method which finds the number of unique Strings within a given array of length n .

```
1 int numUnique(String[] values) {  
2     boolean[] visited = new boolean[values.length]  
3     for (int i = 0; i < values.length; i++) {  
4         visited[i] = false  
5     }  
6     int out = 0  
7     for (int i = 0; i < values.length; i++) {  
8         if (!visited[i]) {  
9             out += 1  
10            for (int j = i; j < values.length; j++) {  
11                if (values[i].equals(values[j])) {  
12                    visited[j] = true  
13                }  
14            }  
15        }  
16    }  
17    return out;  
18 }
```

Determine the tight $\mathcal{O}(\cdot)$, $\Omega(\cdot)$, and $\Theta(\cdot)$ bounds of each function below. If there is no $\Theta(\cdot)$ bound, explain why. Start by (1) constructing an equation that models each function then (2) simplifying and finding a closed form.

(a) $f(n) =$ the worst-case runtime of `numUnique`

(b) $g(n) =$ the best-case runtime of `numUnique`

(c) $h(n) =$ the amount of memory used by `numUnique` (the space complexity)

3. *Oh Snap!*

For each question below, explain what's wrong with the provided answer. The problem might be the reasoning, the conclusion, or both!

- (a) Determine the tight $\Theta(\cdot)$ bound for the worst-case runtime of the following piece of code:

```
1 public static int waddup(int n) {  
2     if (n > 10000) {  
3         return n  
4     } else {  
5         for (int i = 0; i < n; i++) {  
6             System.out.println("It's dat boi!")  
7         }  
8         return 0  
9     }  
10 }
```

Bad answer: The runtime of this function is $\mathcal{O}(n)$, because when searching for an upper bound, we always analyze the code branch with the highest runtime. We see the first branch is $\mathcal{O}(1)$, but the second branch is $\mathcal{O}(n)$.

- (b) Determine the tight $\Theta(\cdot)$ worst-case runtime of the following piece of code:

```
1 public static void trick(int n) {  
2     for (int i = 1; i < Math.pow(2, n); i *= 2) {  
3         for (int j = 0; j < n; j++) {  
4             System.out.println("(" + i + "," + j + ")")  
5         }  
6     }  
7 }
```

Bad answer: The runtime of this function is $\mathcal{O}(n^2)$, because the outer loop is conditioned on an expression with n and so is the inner loop.

4. Look Before You Heap

(a) Insert 10, 7, 15, 17, 12, 20, 6, 32 into a *min heap*.

(b) Now, insert the same values into a *max heap*.

(c) Now, insert 10, 7, 15, 17, 12, 20, 6, 32 into a *min heap*, but use Floyd's buildHeap algorithm.

(d) Insert 1, 0, 1, 1, 0 into a *min heap*.

5. \mathcal{O} My God!

Recall the definition of $f \in \Omega(g)$ is as follows:

$$\exists(c, n_0 > 0). \forall(n \geq n_0). f(n) \geq cg(n)$$

Prove that $4n^2 + n^5 \in \Omega(n)$.