



pollev.com/cse333

About how long did Exercise 8 take you?

- A. [0, 2) hours
- B. [2, 4) hours
- C. [4, 6) hours
- D. [6, 8) hours
- E. 8+ Hours
- F. I didn't submit / I prefer not to say

C++ Inheritance II, Casts

CSE 333 Summer 2023

Instructor: Timmy Yang

Teaching Assistants:

Jennifer Xu

Leanna Nguyen

Pedro Amarante

Sara Deutscher

Tanmay Shah

Relevant Course Information (1/2)

- ❖ Homework 3 is due next Thursday (2/23)
 - Suggestion: write index files to `/tmp/`, which is a local scratch disk and is very fast, but please clean up when you're done
 - Start early!
 - Part A is difficult to debug, and some portions of Part B are challenging!
 - See HW3 demo last lecture

Relevant Course Information (2/2)

- ❖ Quiz 2 open today (7/24) @ 2:00pm
 - Will be administered on Gradescope, closes Wednesday (7/26) @ 11:59pm
 - Quiz should take ~45 min to complete (we tried to make it shorter).
 - Please keep **all** Quiz questions on Ed **private**
 - If anything is frequently asked, we'll make a separate announcement.
 - Questions about the Quiz in Office Hours can only be clarification questions.
 - TAs may ask you to post on the Ed board instead of answering directly.
 - Academic Conduct Policy applies to all Quizzes as well
 - Please don't copy other's work, do not use Chat-GPT
 - <https://courses.cs.washington.edu/courses/cse333/23su/quizzes/>

Lecture Outline

- ❖ **C++ Inheritance**
 - **Static Dispatch**
 - Constructors and Destructors
 - Assignment
- ❖ C++ Casting
- ❖ C++ Conversions

- ❖ Reference: *C++ Primer*, Chapter 15

Reminder: `virtual` is “sticky”

- ❖ If `X::F()` is declared `virtual`, then a vtable will be created for class `X` and for *all* of its subclasses
 - The vtables will include function pointers for (the correct) `F`
- ❖ `F()` will be called using dynamic dispatch even if overridden in a derived class without the `virtual` keyword
 - Good style to help the reader *and avoid bugs* by using `override`
 - Style guide controversy, if you use `override` should you use `virtual` in derived classes? Recent style guides say just use `override`, but you’ll sometimes see both, particularly in older code

What happens if we omit “virtual”?

- ❖ By default, without `virtual`, methods are dispatched *statically*
 - At compile time, the compiler writes in a `call` to the address of the class' method in the `.text` segment
 - Based on the compile-time visible type of the callee
 - This is *different* than Java

```
class Derived : public Base { ... };
```

```
int main(int argc, char** argv) {  
    Derived d;  
    Derived* dp = &d;  
    Base* bp = &d;  
    dp->Foo();  
    bp->Foo();  
    return EXIT_SUCCESS;  
}
```

Derived::Foo()
...

Base::Foo()
...

Static Dispatch Example

- ❖ Removed `virtual` on methods:

Stock.h

```
double Stock::GetMarketValue() const;
double Stock::GetProfit() const;
```

```
DividendStock dividend();
DividendStock* ds = &dividend;
Stock* s = &dividend;

// Invokes DividendStock::GetMarketValue()
ds->GetMarketValue();

// Invokes Stock::GetMarketValue()
s->GetMarketValue();

// invokes Stock::GetProfit().
// Stock::GetProfit() invokes Stock::GetMarketValue().
s->GetProfit();

// invokes Stock::GetProfit(), since that method is inherited.
// Stock::GetProfit() invokes Stock::GetMarketValue().
ds->GetProfit();
```



Why Not Always Use `virtual`?

- ❖ Two (fairly uncommon) reasons:
 - Efficiency:
 - Non-virtual function calls are a tiny bit faster (no indirect lookup)
 - A class with no virtual functions has objects without a `vptr` field
 - Control:
 - If `F()` calls `G()` in class `X` and `G` is not virtual, we're guaranteed to call `X::G()` and not `G()` in some subclass
 - Particularly useful for framework design
- ❖ In Java, all methods are virtual, except `static` class methods, which aren't associated with objects
- ❖ In C++ and C#, you can pick what you want
 - Omitting `virtual` can cause obscure bugs
 - (Most of the time, you want member function to be `virtual`)

Mixed Dispatch

- ❖ Which function is called is a mix of both compile time and runtime decisions as well as *how* you call the function
 - If called on an object (e.g. `obj.Fcn()`), usually optimized into a hard-coded function call at compile time
 - If called via a pointer or reference:

```
DeclaredT *ptr = new ActualT;  
ptr->Fcn(); // which version is called?
```



Mixed Dispatch Example

mixed.cc

```
class A {
public:
    // m1 will use static dispatch
    void M1() { cout << "a1, "; }
    // m2 will use dynamic dispatch
    virtual void M2() { cout << "a2"; }
};

class B : public A {
public:
    void M1() { cout << "b1, "; }
    // m2 is still virtual by default
    void M2() { cout << "b2"; }
};
```

```
void main(int argc,
           char** argv) {
    A a;
    B b;

    A* a_ptr_a = &a;
    A* a_ptr_b = &b;
    B* b_ptr_a = &a;
    B* b_ptr_b = &b;

    a_ptr_a->M1(); //
    a_ptr_a->M2(); //

    a_ptr_b->M1(); //
    a_ptr_b->M2(); //

    b_ptr_b->M1(); //
    b_ptr_b->M2(); //
}
```

Lecture Outline

❖ C++ Inheritance

- Static Dispatch
- **Constructors and Destructors**
- **Assignment**


❖ C++ Casting

❖ C++ Conversions

❖ Reference: *C++ Primer*, Chapter 15

Derived-Class Objects

- ❖ A derived object contains “subobjects” corresponding to the data members inherited from each base class
 - No guarantees about how these are laid out in memory (not even contiguousness between subobjects)
- ❖ Conceptual structure of `DividendStock` object:



Constructors and Inheritance

- ❖ A derived class **does not inherit** the base class' constructor
 - The derived class must have its own constructor
 - A synthesized default constructor for the derived class first invokes the default constructor of the base class and then initialize the derived class' member variables
 - Compiler error if the base class has no default constructor
 - The base class constructor is invoked *before* the constructor of the derived class
 - You can use the initialization list of the derived class to specify which base class constructor to use

Constructor Examples

badctor.cc

```
class Base { // no default ctor
public:
    Base(int yi) : y(yi) { }
    int y;
};

// Compiler error when you try to
// instantiate a Der1, as the
// synthesized default ctor needs
// to invoke Base's default ctor.
class Der1 : public Base {
public:
    int z;
};

class Der2 : public Base {
public:
    Der2(int yi, int zi)
        : Base(yi), z(zi) { }
    int z;
};
```

goodctor.cc

```
// has default ctor
class Base {
public:
    int y;
};

// works now
class Der1 : public Base {
public:
    int z;
};

// still works
class Der2 : public Base {
public:
    Der2(int zi) : z(zi) { }
    int z;
};
```

Destructors and Inheritance



baddtor.cc

- ❖ Destructor of a derived class:
 - *First* runs body of the dtor
 - *Then* invokes of the dtor of the base class
- ❖ Static dispatch of destructors is almost always a mistake!
 - Good habit to always define a dtor as virtual
 - Empty body if there's no work to do

```
class Base {
public:
    Base() { x = new int; }
    ~Base() { delete x; }
    int* x;
};

class Der1 : public Base {
public:
    Der1() { y = new int; }
    ~Der1() { delete y; }
    int* y;
};

void Foo() {
    Base* b0ptr = new Base;
    Base* b1ptr = new Der1;

    delete b0ptr; //
    delete b1ptr; //
}
```


Assignment and Inheritance

- ❖ C++ allows you to assign the value of a derived class to an instance of a base class
 - Known as **object slicing**
 - It's legal since `b = d` passes type checking rules
 - But `b` doesn't have space for any extra fields in `d`

[slicing.cc](#)

```
class Base {
public:
    Base(int xi) : x(xi) { }
    int x;
};

class Der1 : public Base {
public:
    Der1(int yi) : Base(16), y(yi) { }
    int y;
};

void Foo() {
    Base b(1);
    Der1 d(2);

    d = b;    //
    b = d;    //
}
```

STL and Inheritance

- ❖ Recall: STL containers store **copies of values**
 - What happens when we want to store mixes of object types in a single container? (*e.g.*, `Stock` and `DividendStock`)
 - You get sliced 😞

```
#include <list>
#include "Stock.h"
#include "DividendStock.h"

int main(int argc, char** argv) {
    Stock s;
    DividendStock ds;
    list<Stock> li;

    li.push_back(s);    // OK
    li.push_back(ds);  // OUCH!

    return EXIT_SUCCESS;
}
```

STL and Inheritance

- ❖ Instead, store **pointers to heap-allocated objects** in STL containers
 - No slicing! 😊
 - `sort()` does the wrong thing 😞
 - You have to remember to `delete` your objects before destroying the container 😞
 - Unless you use smart pointers!

Lecture Outline

- ❖ C++ Inheritance
 - Static Dispatch
 - Constructors and Destructors
 - Assignment
- ❖ **C++ Casting**
- ❖ C++ Conversions

- ❖ Reference: *C++ Primer* §4.11.3, 19.2.1

Explicit Casting in C

- ❖ Simple syntax: `lhs = (new_type) rhs;`
- ❖ Used to:
 - Convert between pointers of arbitrary type
 - Doesn't change the data, but treats it differently
 - Forcibly convert a primitive type to another
 - Actually changes the representation
- ❖ You *can* still use C-style casting in C++, but sometimes the intent is not clear
 - You *should not* use C-style casting in C++.



Casting in C++

- ❖ C++ provides an alternative casting style that is more informative:
 - `static_cast<to_type>(expression)`
 - `dynamic_cast<to_type>(expression)`
 - `const_cast<to_type>(expression)`
 - `reinterpret_cast<to_type>(expression)`
- ❖ Always use these in C++ code
 - Intent is clearer
 - Easier to find in code via searching

staticcast.cc

static_cast

- ❖ `static_cast` can convert:
 - Pointers to classes **of related type**
 - Compiler error if classes are not related
 - Dangerous to cast *down* a class hierarchy
 - Casting between `void*` and `T*`
 - Non-pointer conversion
 - e.g., `float` to `int`
- ❖ `static_cast` is checked at compile time

```
class A {
public:
    int x;
};

class B {
public:
    float x;
};

class C : public B {
public:
    char x;
};
```

```
void Foo() {
    B b; C c;

    // compiler error
    A* aptr = static_cast<A*>(&b);
    // OK
    B* bptr = static_cast<B*>(&c);
    // compiles, but dangerous
    C* cptr = static_cast<C*>(&b);
}
```

dynamic_cast

- ❖ `dynamic_cast` can convert:
 - Pointers to classes **of related type**
 - References to classes **of related type**
- ❖ `dynamic_cast` is checked at both compile time and run time

- Casts between unrelated classes fail at compile time
- Casts from base to derived fail at run time if the pointed-to object is not the derived type

```
class Base {
public:
    virtual void Foo() { }
    float x;
};

class Der1 : public Base {
public:
    char x;
};
```

```
void Bar() {
    Base b; Der1 d;

    // OK (run-time check passes)
    Base* bptr = dynamic_cast<Base*>(&d);
    assert(bptr != nullptr);

    // OK (run-time check passes)
    Der1* dptr = dynamic_cast<Der1*>(bptr);
    assert(dptr != nullptr);

    // Run-time check fails, returns nullptr
    bptr = &b;
    dptr = dynamic_cast<Der1*>(bptr);
    assert(dptr != nullptr);
}
```


const_cast

- ❖ `const_cast` adds or strips const-ness
 - Dangerous (!)

```
void Foo(int* x) {
    *x++;
}

void Bar(const int* x) {
    Foo(x); // compiler error
    Foo(const_cast<int*>(x)); // succeeds
}

int main(int argc, char** argv) {
    int x = 7;
    Bar(&x);
    return EXIT_SUCCESS;
}
```

reinterpret_cast

- ❖ `reinterpret_cast` casts between *incompatible* types
 - Low-level reinterpretation of the bit pattern
 - *e.g.*, storing a pointer in an `int`, or vice-versa
 - Works as long as the integral type is “wide” enough
 - Converting between incompatible pointers
 - Dangerous (!)
 - This is used (carefully) in hw3
 - Use any other C++ cast if you can!



Casting Style Considerations

- ❖ From the “Casting” and “Run-Time Type Information (RTTI)” sections of the Google C++ Style Guide:
 - When the logic of a program guarantees that a given instance of a base class is, in fact, an instance of a particular derived class, then a `dynamic_cast` may be used freely on the object.
 - Usually one can use a `static_cast` as an alternative in such situations
 - Only use `reinterpret_cast` if you know what you are doing and you understand the aliasing issues
 - For *unsafe conversions* of pointer types to and from integer and other pointer types, including `void*`

Lecture Outline

- ❖ C++ Inheritance
 - Static Dispatch
 - Constructors and Destructors
 - Assignment
- ❖ C++ Casting
- ❖ **C++ Conversions**

- ❖ Reference: *C++ Primer* §4.11.3, 19.2.1

Implicit Conversion

- ❖ The compiler tries to infer some kinds of conversions
 - When types are not equal and you don't specify an explicit cast, the compiler looks for an acceptable implicit conversion

```
void Bar(std::string x);

void Foo() {
    int x = 5.7;    // conversion, float -> int
    char c = x;    // conversion, int -> char
    Bar("hi");    // conversion, (const char*) -> string
}
```

Sneaky Implicit Conversions

- ❖ (`const char*`) to `string` conversion?
 - If a class has a constructor with a single parameter, the compiler will exploit it to perform implicit conversions
 - At most, one user-defined implicit conversion will happen
 - Can do `int` → `Foo`, but not `int` → `Foo` → `Baz`

```
class Foo {
public:
    Foo(int xi) : x(xi) { }
    int x;
};

int Bar(Foo f) {
    return f.x;
}

int main(int argc, char** argv) {
    return Bar(5); // equivalent to return Bar(Foo(5));
}
```



Avoiding Sneaky Implicit

- ❖ Declare one-argument constructors as `explicit` if you want to disable them from being used as an implicit conversion path
 - Usually a good idea

```
class Foo {
public:
    explicit Foo(int xi) : x(xi) { }
    int x;
};

int Bar(Foo f) {
    return f.x;
}

int main(int argc, char** argv) {
    return Bar(5); // compiler error
}
```

Extra Exercise #1

- ❖ Design a class hierarchy to represent shapes
 - *e.g.*, Circle, Triangle, Square
- ❖ Implement methods that:
 - Construct shapes
 - Move a shape (*i.e.*, add (x,y) to the shape position)
 - Returns the centroid of the shape
 - Returns the area of the shape
 - **Print** (), which prints out the details of a shape

Extra Exercise #2

- ❖ Implement a program that uses Extra Exercise #1 (shapes class hierarchy):
 - Constructs a vector of shapes
 - Sorts the vector according to the area of the shape
 - Prints out each member of the vector
- ❖ Notes:
 - Avoid slicing!
 - Make sure the sorting works properly!