

C++ Class Details, Heap

CSE 333

Instructor: Alex Sanchez-Stern

Teaching Assistants:

Justin Tysdal

Sayuj Shahi

Nicholas Batchelder

Leanna Mi Nguyen

Administrivia

- ❖ Homework 2 due Thursday night
 - **Check your work!!** Allocate time to clone the repo when you're done, do `git checkout hw2-final; cd hw1` and `copy/build libhw1.a; cd hw2; make`; then test everything looks good
 - Reminder: **do not modify header files**
 - Reminder: commit/push your work regularly, not all at once at the end

Administrivia

- ❖ Exercise 9 due this morning, Exercise 10 due on Wednesday
- ❖ Unfortunately, Exercise 11 needs to be due before the midterm...

Administrivia

- ❖ Midterm exam in a week:

Monday 7/22, 1:10 - 2:10 in SMI 211

- Topic list and old exams on website now (see exams link on resources page)
- Closed book, slides, etc., but you may have one 5x8 notecard with whatever handwritten notes you want on both sides

Administrivia

- ❖ Extra midterm points for coming to office hours this week
 - +5 points on the midterm (out of 100), but can't go above 100 total
 - Must go to an existing, in-person office hours and bring a problem set to work on; either from the extra-problems in the slides, or an old midterm question
 - Make sure the TA writes down your name

Administrivia

- ❖ Midterm review in section this week

Lecture Outline

- ❖ Class Details
 - **Rule of Three / Making Copies**
 - Access Controls and Friends
 - Namespaces
- ❖ Using the Heap
 - `new / delete / delete []`
 - `String` Class walkthrough

Rule of Three

- ❖ If you define any of:
 - 1) Destructor
 - 2) Copy Constructor
 - 3) Assignment (`operator=`)
- ❖ Then you should normally define all three
 - Can explicitly ask for default synthesized versions (C++11 & later):

```
class Point {  
public:  
    Point() = default;           // the default ctor  
    ~Point() = default;         // the default dtor  
    Point(const Point& copyme) = default; // the default cctor  
    Point& operator=(const Point& rhs) = default; // the default "="  
    ...  
};
```


Dealing with the insanity

❖ C++ style guide tip:

- If possible, **disable** the copy constructor and assignment operator if not needed – avoids implicit invocation and excessive copying. C++11 and later have direct syntax to indicate this: [Point_2011.h](#)

```
class Point {
public:
    Point(const int x, const int y) : x_(x), y_(y) { } // ctor
    ...
    Point(const Point& copyme) = delete; // declare ctor and "=" to
    Point& operator=(const Point& rhs) = delete; // be deleted (C++11)
private:
    ...
}; // class Point

Point w; // compiler error (no default constructor)
Point x(1, 2); // OK!
Point y = w; // compiler error (no copy constructor)
y = x; // compiler error (no assignment operator)
```

If you're dealing with old code ...

- ❖ In pre-C++11 code the copy constructor and assignment were often disabled by making them private and not implementing them (you may see this)...

Point.h

```
class Point {
public:
    Point(const int x, const int y) : x_(x), y_(y) { } // ctor
    ...
private:
    Point(const Point& copyme);           // disable cctor (no def.)
    Point& operator=(const Point& rhs);   // disable "=" (no def.)
    ...
}; // class Point

Point w;           // compiler error (no default constructor)
Point x(1, 2);    // OK!
Point y = w;      // compiler error (no copy constructor)
y = x;           // compiler error (no assignment operator)
```

Lecture Outline

- ❖ Class Details
 - Rule of Three / Making Copies
 - **Access Controls and Friends**
 - Namespaces
- ❖ Using the Heap
 - `new / delete / delete []`
 - `String` Class walkthrough

Access Control

- ❖ **Access modifiers** for members:
 - `public`: accessible to *all* parts of the program
 - `private`: accessible to the member functions of the class
 - Private to *class*, not object instances
 - `protected`: accessible to member functions of the class and any *derived* classes (subclasses – more to come, later)

- ❖ **Reminders:**
 - Access modifiers apply to *all* members that follow until another access modifier is reached

struct vs. class

- ❖ In C, a `struct` can only contain data fields
 - Has no methods and all fields are always accessible
 - In `struct foo`, the `foo` is a “struct tag”, not an ordinary data type
- ❖ In C++, `struct` and `class` are (nearly) the same!
 - Both define a new type (the `struct` or `class` name)
 - Both can have methods and member visibility (public/private/protected)
 - Only real (minor) difference: members are default *public* in a `struct` and default *private* in a `class`

struct vs. class

- ❖ Common style/usage convention:
 - Use `struct` for simple bundles of data
 - Convenience constructors can make sense though
 - Use `class` for abstractions with data + functions

Nonmember Functions

- ❖ “Nonmember functions” are just normal functions that happen to use some class
 - Called like a regular function instead of as a member of a class object instance
 - These do *not* have access to the class’ private members
- ❖ Useful nonmember functions often included as part of the interface to a class
 - Declaration goes in header file, but *outside* of class definition
 - But *inside* the same namespace as the class, if it has one

Nonmember Functions

- ❖ “Nonmember functions” are just normal functions that happen to use some class
 - Called like a regular function instead of as a member of a class object instance
 - These do *not* have access to the class’ private members
 - Often included as part of the interface to a class

```
class Complex { ... };
```

```
void ReadFromStream(std::istream& in, Complex& a);
```

```
void ReadFromStream(std::istream& in, Complex& a) {  
    double r;  
    in >> r  
    a.set_real(r);  
    // ... etc ...  
}
```


Nonmember Operators

- ❖ Operators can be member methods or non-member functions
 - Eg, overloaded operators (`operator+`, etc.), stream I/O (`operator<<`), etc. ...

Review: Operator Overloading

- ❖ Can overload operators using **member functions**
 - Restriction: left-hand side argument must be a class you are implementing

```
Complex& Complex::operator+=(const Complex &a) { ... }
```

- ❖ Can overload operators using **nonmember functions**
 - No restriction on arguments (can specify any two)
 - **Our only option** when the left-hand side is a class you do not have control over, like `ostream` or `istream`.
 - But no access to private data members

```
Complex operator+(const Complex &a, const Complex &b) { ... }
```

friend Nonmember Functions

- ❖ A class can give a nonmember function (or class) access to its `nonpublic` members by declaring it as a `friend` within its definition
 - `friend` function is not a class member, but has access privileges as if it were
 - `friend` functions are usually unnecessary if your class includes appropriate “getter” public functions

Complex.h

```
class Complex {  
    ...  
    friend std::istream& operator>>(std::istream& in, Complex& a);  
    ...  
}; // class Complex
```

```
std::istream& operator>>(std::istream& in, Complex& a) {  
    ...  
}
```

Complex.cc 19

When to use Nonmember and `friend`

- ❖ Member functions:
 - Operators that modify the object being called on
 - Assignment operator (`operator=`)
 - “Core” non-operator functionality that is part of the class interface
- ❖ Nonmember functions:
 - Used for commutative operators
 - *e.g.*, so `v1 + v2` is invoked as `operator+(v1, v2)` instead of `v1.operator+(v2)`
 - If operating on two types and the class is on the right-hand side
 - *e.g.*, `cin >> complex;`
 - Returning a “new” object, not modifying an existing one
 - Only grant `friend` permission if you NEED to

Lecture Outline

- ❖ Class Details
 - Rule of Three / Making Copies
 - Access Controls and Friends
 - **Namespaces**
- ❖ Using the Heap
 - `new / delete / delete []`
 - `String` Class walkthrough

Namespaces

- ❖ Each namespace is a separate scope
 - Useful for avoiding symbol collisions

- ❖ Namespace definition:

- ```
namespace name {
 // declarations go here
}
```

- Creates a new namespace name if it did not exist, otherwise *adds to the existing namespace (!)*
  - This means that components (classes, functions, etc.) of a namespace can be defined in multiple source files
    - All of the standard library is in namespace `std` but it has many source files

# Classes vs. Namespaces

- ❖ They seems somewhat similar, but classes are *not* namespaces:
  - There are no instances/objects of a namespace; a namespace is just a group of logically-related things (classes, functions, etc.)
  - To access a member of a namespace, you must use the fully qualified name (*i.e.* `nsp_name::member`)
    - Unless you are `using` that namespace or individual member item
    - You only used the fully qualified name of a class member when you are defining it outside of the scope of the class definition

# Lecture Outline

- ❖ Class Details
  - Rule of Three / Making Copies
  - Access Controls and Friends
  - Namespaces
- ❖ **Using the Heap**
  - `new / delete / delete []`
  - `String` Class walkthrough



# C++11 `nullptr`

- ❖ C and C++ have long used `NULL` as a pointer value that references nothing
- ❖ C++11 introduced a new literal for this: `nullptr`
  - New reserved word
  - Interchangeable with `NULL` for all practical purposes, but it has type  $T^*$  for any/every  $T$ , and is not an integer value
    - Avoids funny edge cases, especially with function overloading (`f(int)` vs `f(T*)`); see C++ references for details)
    - Still can convert to/from integer `0` for tests, assignment, etc.
  - Advice: prefer `nullptr` in C++11 code
    - Though `NULL` will also be around for a long, long time

# new/delete

- ❖ To allocate on the heap using C++, you use the `new` keyword instead of `malloc()` from `stdlib.h`
  - You can use `new` to allocate an object (*e.g.* `new Point`)
    - Will execute appropriate constructor as part of object allocate/create
  - You can use `new` to allocate a primitive type (*e.g.* `new int`)
- ❖ To deallocate a heap-allocated object or primitive, use the `delete` keyword instead of `free()` from `stdlib.h`
  - Don't mix and match!
    - Never `free()` something allocated with `new`
    - Never `delete` something allocated with `malloc()`
    - Careful if you're using a legacy C code library or module in C++

# new/delete Example

```
int* AllocateInt(int x) {
 int* heapy_int = new int;
 *heapy_int = x;
 return heapy_int;
}
```

```
Point* AllocatePoint(int x, int y) {
 Point* heapy_pt = new Point(x, y);
 return heapy_pt;
}
```

heappoint.cc

```
#include "Point.h"
using namespace std;

... // definitions of AllocateInt() and AllocatePoint()

int main() {
 Point* x = AllocatePoint(1, 2);
 int* y = AllocateInt(3);

 cout << "x's x_coord: " << x->get_x() << endl;
 cout << "y: " << y << ", *y: " << *y << endl;

 delete x;
 delete y;
 return 0;
}
```

# new/delete Example

```
g++ -Wall -g -std=c++17 -o heappoint \
 heappoint.cc Point.cc
valgrind ./heappoint
```

```
==3167334== Memcheck, a memory error detector
==3167334== Copyright (C) 2002-2022, and GNU GPL'd, by Julian Seward et al.
==3167334== Using Valgrind-3.22.0 and LibVEX; rerun with -h for copyright info
==3167334== Command: ./heappoint
==3167334==
Calling Point constructor
x's x_ coordinate: 1
distance between x and self: 0
y: 0x4daa110, *y: 3
==3167334==
==3167334== HEAP SUMMARY:
==3167334== in use at exit: 0 bytes in 0 blocks
==3167334== total heap usage: 4 allocs, 4 frees, 73,740 bytes allocated
==3167334==
==3167334== All heap blocks were freed -- no leaks are possible
==3167334==
==3167334== For lists of detected and suppressed errors, rerun with: -s
==3167334== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

# new/delete Behavior

## ❖ new behavior:

- When allocating you can specify a constructor or initial value
  - e.g., `new Point(1, 2)`, `new int(333)`
- If no initialization specified, it will use default constructor for objects and uninitialized (“mystery”) data for primitives
- You don’t need to check that `new` returns `nullptr`
  - When an error is encountered, an exception is thrown (that we won’t worry about)

## ❖ delete behavior:

- If you `delete` already `deleted` memory, then you will get undefined behavior (same as when you double `free` in C)

# Dynamically Allocated Arrays

## ❖ To dynamically allocate an array:

- Default initialize: `type* name = new type[size];`

## ❖ To dynamically deallocate an array:

- Use `delete [] name;`
- It is an *incorrect* to use “`delete name;`” on an array
  - The compiler probably won't catch this, though (!) because it can't always tell if `name*` was allocated with `new type[size];` or `new type;`
    - Especially inside a function where a pointer parameter could point to a single item or an array and there's no way to tell which!
  - Result of wrong `delete` is undefined behavior

# Arrays Example (primitive)

arrays.cc

```
#include "Point.h"
using namespace std;

int main() {
 int stack_int;
 int* heap_int = new int;
 int* heap_init_int = new int(12);

 int stack_arr[10];
 int* heap_arr = new int[10];

 int* heap_init_arr = new int[10](); // uncommon usage
 int* heap_init_error = new int[10](12); // bad syntax
 int* heap_init_error = new int[10]{12}; // C++11 allows
 ... // (uncommon)

 delete heap_int; // ok
 delete heap_init_int; // ok
 delete heap_arr; // error - must be delete[]
 delete[] heap_init_arr; // ok

 return 0;
}
```

# Arrays Example (class objects)

arrays.cc

```
#include "Point.h"
using namespace std;

int main() {
 ...

 Point stack_point(1, 2);
 Point* heap_point = new Point(1, 2);

 Point* err_pt_arr = new Point[10]; // bug-no Point() ctr

 Point* err2_pt_arr = new Point[10](1,2); // bad syntax
 Point* err2_pt_arr = new Point[10]{1,2}; // C++11 allows
 ... // (uncommon)

 delete heap_point;

 ...

 return 0;
}
```



# malloc vs. new

|                          | <code>malloc()</code>                           | <code>new</code>                                         |
|--------------------------|-------------------------------------------------|----------------------------------------------------------|
| What is it?              | a function                                      | an operator or keyword                                   |
| How often used (in C)?   | often                                           | never                                                    |
| How often used (in C++)? | rarely                                          | often                                                    |
| Typed                    | No                                              | Yes                                                      |
| Returns                  | a <code>void*</code><br><i>(should be cast)</i> | appropriate pointer type<br><i>(doesn't need a cast)</i> |
| When out of memory       | returns <code>NULL</code>                       | throws an exception                                      |
| Deallocating             | <code>free()</code>                             | <code>delete</code> or <code>delete []</code>            |

# Heap Member Example

- ❖ Let's build a class to simulate some of the functionality of the C++ string
  - Internal representation: c-string to hold characters
- ❖ What might we want to implement in the class?

# Lecture Outline

- ❖ Class Details
  - Rule of Three / Making Copies
  - Access Controls and Friends
  - Namespaces
- ❖ Using the Heap
  - `new / delete / delete []`
  - **String Class walkthrough**

# Str Example Walkthrough

See:

`Str.h`

`Str.cc`

`strtest.cc`

- ❖ Look carefully at assignment `operator=`
  - self-assignment test is especially important here

# Extra Exercise #1

- ❖ Write a C++ function that:
  - Uses `new` to dynamically allocate an array of strings and uses `delete []` to free it
  - Uses `new` to dynamically allocate an array of pointers to strings
    - Assign each entry of the array to a string allocated using `new`
  - Cleans up before exiting
    - Use `delete` to delete each allocated string
    - Uses `delete []` to delete the string pointer array
    - (whew!)