

[pollev.com/cse333](https://pollev.com/cse333)

## About how long did Exercises 5 and 6 take you? (2 polls)

- A. [0, 2) hours
- B. [2, 4) hours
- C. [4, 6) hours
- D. [6, 8) hours
- E. 8+ Hours
- F. I didn't submit / I prefer not to say

# Systems Programming

## C++ Templates

**Instructor:** Justin Hsia

**Teaching Assistants:**

Aadi Adgaonkar

Advaith Vijayakumar

Alice Fu

Andrew Vlahovich

Aviel Wood

Camden Harris

Esha Gore

Hannah Hempstead

Helena Wang

Laura Wang

Megan Frisella

Nina Tharamal

Shrihun Sankepally

Shriya Sateesh

Yusong Yan

# Relevant Course Information

- ❖ Exercise 7 not due until next Wed (11/4); focus on HW2 and Midterm
- ❖ Homework 2 due tomorrow (10/29)
  - Don't forget to clone your repo to double-check compilation!
  - Feel free to use late days if you can't finish & polish your submission – they exist for a reason
  - Don't modify header files, we will test with the original .h files
- ❖ Midterm: Monday, November 2 (see [Ed post #300](#))
  - [GUG 220](#) or [ARC 147](#), depending on your *registered* quiz section
  - [Reference sheet](#) and two-sided *handwritten* cheat sheet!
  - Midterm review session on Friday (2/6) from 4:30–6:20 PM (See [Ed post #304](#))
  - Practice midterms and solutions on the course website


# Lecture Outline

## ❖ Templates

# Suppose that...

- ❖ You want to write a function to compare two `ints`
- ❖ You want to write a function to compare two `strings`
  - Function overloading!

```
// returns 0 if equal, 1 if value1 is bigger, -1 otherwise
int compare(const int& value1, const int& value2) {
    if (value1 < value2) return -1;
    if (value2 < value1) return 1;
    return 0;
}
```



does something different in each case

```
// returns 0 if equal, 1 if value1 is bigger, -1 otherwise
int compare(const string& value1, const string& value2) {
    if (value1 < value2) return -1;
    if (value2 < value1) return 1;
    return 0;
}
```



# Hm...

- ❖ The two implementations of **compare** are nearly identical!
  - What if we wanted a version of **compare** for *every* comparable type?
  - We could write (many) more functions, but that's obviously wasteful and redundant *too much repeated code!*
- ❖ What we'd prefer to do is write “*generic code*”
  - Code that is **type-independent** (*i.e.*, **polymorphic** across types)

# C++ Parametric Polymorphism

❖ C++ has the notion of **templates**

- A function or class that accepts a **type** as a parameter
  - You define the function or class once in a type-agnostic way
  - When you invoke the function or instantiate the class, you specify (one or more) types or values as arguments to it
  - This is in addition to the normal function parameters

★ At **compile-time**, the compiler will generate the “specialized” code from your template using the types you provided

- Your template definition is NOT runnable code
- Code is *only* generated if you use your template

# Function Templates

❖ Template to **compare** two “things”:

```
#include <iostream>
#include <string>

// returns 0 if equal, 1 if value1 is bigger, -1 otherwise
template <typename T> // <...> can also be written <class T>
int compare(const T& value1, const T& value2) {
    if (value1 < value2) return -1;
    if (value2 < value1) return 1;
    return 0;
}

int main(int argc, char* argv[]) {
    std::string h("hello"), w("world");
    std::cout << compare<int>(10, 20) << std::endl; // -1
    std::cout << compare<std::string>(h, w) << std::endl; // -1
    std::cout << compare<double>(50.5, 50.6) << std::endl; // -1
    return EXIT_SUCCESS;
}
```

template parameter list (also written as: <class T>)

template function definition

T only needs to implement < to work with compare()

explicit template arguments  
(3 different instances of compare)

functiontemplate.cc

# Compiler Inference

❖ Same thing, but letting the compiler infer the types:

```
#include <iostream>
#include <string>

// returns 0 if equal, 1 if value1 is bigger, -1 otherwise
template <typename T>
int compare(const T& value1, const T& value2) {
    if (value1 < value2) return -1;
    if (value2 < value1) return 1;
    return 0;
}

int main(int argc, char* argv[]) {
    std::string h("hello"), w("world");
    std::cout << compare(10, 20) << std::endl; // ok infer int, -1
    std::cout << compare(h, w) << std::endl;    // ok infer std::string, -1
    std::cout << compare("Hello", "World") << std::endl; // hm... infer char*, could be ±1
    return EXIT_SUCCESS;
}
```

no explicit template argument

functiontemplate\_infer.cc

infer char\*, could be  $\pm 1$   
(based on addresses)

# Template Non-types

❖ You can use non-types (constant values) in a template:

```
#include <iostream>
#include <string>

// return pointer to new N-element heap array filled with val
// (not entirely realistic, but shows what's possible)
template <typename T, int N>
T* valarray(const T& val) {
    T* a = new T[N];
    for (int i = 0; i < N; ++i)
        a[i] = val;
    return a;
}

int main(int argc, char* argv[]) {
    int* ip = valarray<int, 10>(17);
    string* sp = valarray<string, 17>("hello");
    ...
}
```

↑ separate template arguments with commas like normal

valtemplate.cc

# What's Going On?

- ❖ The compiler doesn't generate any code when it sees the template function definition
  - It doesn't know what code to generate yet, since it doesn't know what types are involved – **different behavior for different types!**
- Only* ❖ When the compiler sees the function being used, then it understands what types are involved
  - It generates the ***instantiation*** of the template and compiles it (kind of like macro expansion)
    - The compiler generates template instantiations for *each* type used as a template parameter

# The Great Tragedy of C++ Templates

```
#ifndef COMPARE_H_
#define COMPARE_H_

template <typename T>
int comp(const T& a, const T& b);

#endif // COMPARE_H_
```

compare.h

*g++ -c compare.cc → empty compare.o!*

*#include "compare.h" (no usage of comp<>)*

```
template <typename T>
int comp(const T& a, const T& b) {
    if (a < b) return -1;
    if (b < a) return 1;
    return 0;
}
```

compare.cc

```
#include <cstdlib>
#include <iostream>

#include "compare.h"

using std::cout;
using std::endl;

int main(int argc, char* argv[]) {
    cout << comp<int>(10, 20);
    cout << endl;
    return EXIT_SUCCESS;
}
```

*g++ -c main.cc → main.o*  
*without*  
*definition of*  
*comp<int>*

main.cc

*g++ main.o compare.o → linker error*  
*(no comp<int>)*



# Solution #1 (Google Style Guide prefers)

```
#ifndef COMPARE_H_
#define COMPARE_H_

template <typename T>
int comp(const T& a, const T& b) {
    if (a < b) return -1;
    if (b < a) return 1;
    return 0;
}

#endif // COMPARE_H_
```

compare.h

```
#include <cstdlib>
#include <iostream>

#include "compare.h"

using std::cout;
using std::endl;

int main(int argc, char* argv[]) {
    cout << comp<int>(10, 20);
    cout << endl;
    return EXIT_SUCCESS;
}
```

main.cc

less implementation hiding!

## Solution #2 (you'll see this sometimes)

```
#ifndef COMPARE_H_
#define COMPARE_H_

template <typename T>
int comp(const T& a, const T& b);

#include "compare.cc"

#endif // COMPARE_H_
```

compare.h

```
template <typename T>
int comp(const T& a, const T& b) {
    if (a < b) return -1;
    if (b < a) return 1;
    return 0;
}
```

compare.cc

```
#include <cstdlib>
#include <iostream>

#include "compare.h"

using std::cout;
using std::endl;

int main(int argc, char* argv[]) {
    cout << comp<int>(10, 20);
    cout << endl;
    return EXIT_SUCCESS;
}
```

main.cc



# Poll Everywhere

pollev.com/cse333



## Which is the *simplest* way to compile our program (a.out)?

- Assume we are using Solution #2 (.h includes .cc)

A. `g++ main.cc`

B. `g++ main.cc compare.cc`

C. `g++ main.cc compare.h`

D. `g++ -c main.cc`

~~`g++ -c compare.cc`~~ → empty compare.o

`g++ main.o compare.o`

E. We're lost...

template definition added to main.cc  
via #include by preprocessor  
(main.cc → compare.h → compare.cc)

all of these command sets will work,  
but crossed out parts are  
unnecessary.

Make file

a.out: main.cc compare.h compare.cc  
g++ main.cc

# Class Templates

- ❖ Templates are useful for classes as well
  - (In fact, that was one of the main motivations for templates!)
- ❖ Imagine we want a class that holds a <sup>Pair</sup>pair of things. Users of the class can:
  - Set the value of the first thing
  - Set the value of the second thing
  - Get the value of the first thing
  - Get the value of the second thing
  - Swap the values of the things
  - Print the pair of things

# Pair Class Definition

Pair.h

```
#ifndef PAIR_H_
#define PAIR_H_

template <typename Thing>
class Pair {
public:    // default constructor
    Pair() { };

    Thing get_first() const { return first_; }
    Thing get_second() const { return second_; }
    void set_first(const Thing& copyme);
    void set_second(const Thing& copyme);
    void Swap();

private:
    Thing first_, second_;
};

#include "Pair.cc"

#endif // PAIR_H_
```

template class definition

inline definitions

declarations

could be primitive or another class

← following Solution #2 (for ease of slide separation)

# Pair Function Definitions

```
template <typename Thing>
void Pair<Thing>::set_first(const Thing& copyme) {
    first_ = copyme;
}

template <typename Thing>
void Pair<Thing>::set_second(const Thing& copyme) {
    second_ = copyme;
}

template <typename Thing>
void Pair<Thing>::Swap() {
    Thing tmp = first_;
    first_ = second_;
    second_ = tmp;
}

// nonmember template function to print out Pair values
template <typename T>
std::ostream& operator<<(std::ostream& out, const Pair<T>& p) {
    return out << "Pair(" << p.get_first() << ", "
               << p.get_second() << ")";
}
```

template function  
for template class  
member function

Pair.cc

member of template class instantiation with Thing

# Using Pair

```
#include <iostream>
#include <string>

#include "Pair.h"

int main(int argc, char* argv[]) {
    Pair<std::string> ps; // invokes default constructor
    std::string x("foo"), y("bar");

    ps.set_first(x); // ("foo", "")
    ps.set_second(y); // ("foo", "bar")
    ps.Swap(); // ("bar", "foo")
    std::cout << ps << std::endl; // invoke nonmember operator<< function

    return EXIT_SUCCESS;
}
```

usepair.cc

# Class Template Notes (look in *Primer* for more)

- ❖ **Thing** is replaced with template argument when class is instantiated
- ❖ Class template parameters are in scope everywhere within the class's curly braces `{ }`
  - Inline methods in the class's `{ }`s don't need a template<> line above them.
  - Method definitions outside of the `{ }`s must have a template<> line above them, with the same parameters
    - The names *should* match, but don't need to
- ❖ Only template methods that actually get called in your program are instantiated (but this is an implementation detail)

# Review Questions (Classes and Templates)

- ❖ Why are only **get\_first()** and **get\_second()** const?  
the accessors don't modify the class instance — the mutators and swap do  
— operator << is a non-member function
- ❖ Why do the accessor methods return **Thing** and not references?  
returning a reference to a private member violates the 'private' modifier,  
so we instead return a copy of Thing
- ❖ Why is **operator<<** not a **friend** function?  
it doesn't need access to private data members because it uses the  
accessors instead
- ❖ What happens in the default constructor when **Thing** is a class?  
data members still get initialized — in this case, invoke the default constructor  
of Thing for first\_ and second\_
- ❖ In the execution of **Swap()**, how many times are each of the following invoked (assuming **Thing** is a class)?

ctor 0

cctor 1  
tmp

op= 2  
first\_, second\_

dtor 1  
tmp