

pollev.com/cse333

Which of the following things have you done in preparation for the Midterm?

- A. Found a study group
- B. Created a cheat sheet
- C. Looked over past lectures
- D. Looked over past sections
- E. Looked over past assignments (exercise + homework)
- F. Looked over past midterms
- G. Prefer not to say

Systems Programming

C++ Standard Template Library

Instructor: Justin Hsia

Teaching Assistants:

Aadi Adgaonkar

Advaith Vijayakumar

Alice Fu

Andrew Vlahovich

Aviel Wood

Camden Harris

Esha Gore

Hannah Hempstead

Helena Wang

Laura Wang

Megan Frisella

Nina Tharamal

Shrihun Sankepally

Shriya Sateesh

Yusong Yan

Relevant Course Information

- ❖ Exercise 7 due **Wednesday** (after Midterm)
- ❖ Homework 2 was due last night
 - Don't forget to double-check your `hw2-submit` tag!
 - Use late days if you need to; they exist for a reason!
- ❖ Homework 3 will be released on Monday, due in **3 weeks**
 - Now in C++, but interfacing with the HW1 & HW2 C code!
- ❖ Midterm Review tonight @ 4:30 PM (CSE2 G01, Zoom)
- ❖ Midterm: November 2 from 5:30 – 6:40 PM
 - Info: [website](#), [Ed post #300](#)
 - No lecture on Monday

Lecture Outline

❖ C++ Standard Template Library (STL)

C++'s Standard Library

- ❖ C++'s Standard Library consists of four major pieces:
 - 1) The entire C standard library
 - 2) C++'s input/output stream library
 - `std::cin`, `std::cout`, `stringstreams`, `fstreams`, etc.
 - 3) C++'s standard template library (**STL**) 
 - Containers, iterators, algorithms (sort, find, etc.), numerics
 - 4) C++'s miscellaneous library
 - Strings, exceptions, memory allocation, localization

STL Containers 😄

- ❖ A **container** is an object that stores (in memory) a collection of other objects (elements)
 - Implemented as class templates, so hugely flexible
 - More info in *C++ Primer* §9.2, 11.2
- ❖ Several different classes of container
 - Sequence containers (vector, deque, list, array, ...)
 - Associative containers (set, map, multiset, multimap, bitset, ...)
 - Differ in algorithmic cost and supported operations

STL Containers 🙄

- ❖ STL containers store by *value*, not by *reference*
 - When you insert an object, the container makes a *copy*
 - If the container needs to rearrange objects, it makes copies
 - *e.g.*, if you sort a `vector`, it will make many, many copies
 - *e.g.*, if you insert into a `map`, that may trigger several copies
 - What if you don't want this (disabled copy constructor or copying is expensive)?
 - You can insert a wrapper object with a pointer to the object
 - We'll learn about these “smart pointers” soon

Our Tracer Class

- ❖ Wrapper class for an `unsigned int` `value_`
 - Also holds unique `unsigned int` `id_` (increasing from 0)
 - Default ctor, cctor, dtor, `op=`, `op<` defined
 - `friend` function `operator<<` defined
 - Private helper method `PrintID()` to return `"(id_, value_)"` as a string
 - Class and member definitions can be found in `Tracer.h` and `Tracer.cc`
- ❖ Useful for tracing behaviors of containers
 - All methods print identifying messages
 - Unique `id_` allows you to follow individual instances

STL **vector**

- ❖ A generic, dynamically resizable array
 - <https://cplusplus.com/reference/vector/vector/>
 - Elements are store in *contiguous* memory locations
 - Elements can be accessed using pointer arithmetic if you'd like
 - Random access is $O(1)$ time
 - Adding/removing from the end is cheap (amortized constant time)
 - Inserting/deleting from the middle or start is expensive (linear time)

vector/Tracer Example

```
#include <iostream>
#include <vector>
#include "Tracer.h"

using std::...;

int main(int argc, char* argv[]) {
    Tracer a, b, c;
    vector<Tracer> vec;

    cout << "vec.push_back " << a << endl;
    vec.push_back(a);
    cout << "vec.push_back " << b << endl;
    vec.push_back(b);
    cout << "vec.push_back " << c << endl;
    vec.push_back(c);

    cout << "vec[0]" << endl << vec[0] << endl;
    cout << "vec[2]" << endl << vec[2] << endl;

    return EXIT_SUCCESS;
}
```

vectorfun.cc

Why All the Copying?

STL iterator

- ❖ Each container class has an associated `iterator` class (e.g., `vector<int>::iterator`) used to iterate through elements of the container
 - <https://cplusplus.com/reference/iterator/iterator/>
 - `Iterator range` is from `begin` up to `end`, i.e., `[begin, end)`
 - `end` is one past the last container element!
 - Some container iterators support more operations than others
 - All can be incremented (`++`), copied, copy-constructed
 - Some can be dereferenced on RHS (e.g., `x = *it;`)
 - Some can be dereferenced on LHS (e.g., `*it = x;`)
 - Some can be decremented (`--`)
 - Some support random access (`[]`, `+`, `-`, `+=`, `-=`, `<`, `>` operators)

iterator Example

```
#include <vector>

#include "Tracer.h"

using std::...;

int main(int argc, char* argv[]) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(a);
    vec.push_back(b);
    vec.push_back(c);

    cout << "Iterating:" << endl;
    vector<Tracer>::iterator it;
    for (it = vec.begin(); it < vec.end(); ++it) {
        cout << *it << endl;
    }
    cout << "Done iterating!" << endl;
    return EXIT_SUCCESS;
}
```

vectoriterator.cc

Type Inference (C++11)

- ❖ The **auto** keyword can be used to infer types
 - Simplifies your life if, for example, functions return complicated types
 - The expression using **auto** must contain explicit initialization for it to work

```
// Calculate and return a vector  
// containing all factors of n  
std::vector<int> Factors(int n);  
  
void foo(void) {  
    // Manually identified type  
    std::vector<int> facts1 =  
        Factors(324234);  
  
    // Inferred type  
    auto facts2 = Factors(12321);  
  
    // Compiler error here  
    auto facts3;  
}
```

auto and Iterators

❖ Life becomes much simpler!

```
for (vector<Tracer>::iterator it = vec.begin(); it < vec.end(); ++it) {  
    cout << *it << endl;  
}
```



```
for (auto it = vec.begin(); it < vec.end(); ++it) {  
    cout << *it << endl;  
}
```

Range for Statement (C++11)

- ❖ Syntactic sugar similar to Java's foreach:

```
for ( declaration : expression ) {  
    statements  
}
```

- *declaration* defines loop variable
- *expression* is an object representing a sequence
 - Strings, initializer lists, arrays with an explicit length defined, STL containers that support iterators

```
// Prints out a string, one character per line  
std::string str("hello");  
  
for ( auto c : str ) {  
    std::cout << c << std::endl;  
}
```

Updated iterator Example

```
#include <vector>

#include "Tracer.h"

using std::...;

int main(int argc, char* argv[]) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(a);
    vec.push_back(b);
    vec.push_back(c);

    cout << "Iterating:" << endl;
    // "auto" is a C++11 feature not available on older compilers
    for (auto& p : vec) {
        cout << p << endl;
    }
    cout << "Done iterating!" << endl;
    return EXIT_SUCCESS;
}
```

vectoriterator_2011.cc

STL Algorithms

- ❖ A set of functions to be used on ranges of elements
 - **Range**: any sequence that can be accessed through *iterators* or *pointers*, like arrays or some of the containers
 - General form: `algorithm(begin, end, ...)`;
- ❖ Algorithms operate directly on range *elements* rather than the containers they live in
 - Make use of elements' copy ctor, =, ==, !=, <
 - Some do not modify elements
 - e.g., **find**, **count**, **for_each**, **min_element**, **binary_search**
 - Some do modify elements
 - e.g., **sort**, **transform**, **copy**, **swap**

Algorithms Example

```
#include <vector>
#include <algorithm>
#include "Tracer.h"
using std::...;

void PrintOut(const Tracer& p) {
    cout << " printout: " << p << endl;
}

int main(int argc, char* argv[]) {
    Tracer a, b, c;
    vector<Tracer> vec;

    vec.push_back(c);
    vec.push_back(a);
    vec.push_back(b);
    cout << "sort:" << endl;
    sort(vec.begin(), vec.end());
    cout << "done sort!" << endl;
    for_each(vec.begin(), vec.end(), &PrintOut);
    return EXIT_SUCCESS;
}
```

vectoralgorithms.cc

Copying For sort

Iterator Question

- ❖ Write a function **OrderNext()** that takes a `vector<Tracer>` iterator and then does the compare-and-possibly-swap operation we saw in **sort()** on that element and the one *after* it
 - Hint: Iterators behave similarly to pointers!
 - Example: **OrderNext**(`vec.begin()`) should order the first 2 elements of `vec`

Extra Exercise #1

- ❖ Using the `Tracer.h/.cc` files from lecture:
 - Construct a vector of lists of Tracers
 - *i.e.*, a `vector` container with each element being a `list` of `Tracers`
 - Observe how many copies happen 😊
 - Use the sort algorithm to sort the vector
 - Use the `list.sort()` function to sort each list