
Example 2

```
val x = 1
fun f y = let val x = 2 in fn z => x + y + z end
val x = 3
val g = f 4
val y = 5
g 6
```

CSE 341: Programming Languages

Spring 2005

Lecture 9 — More First Class Functions

CSE 341 Spring 2005, Lecture 9

1

CSE 341 Spring 2005, Lecture 9

2

Example 3

```
fun f g = let val x = 3 in g 2 end
val x = 4
fun h y = x + y
f h
```

CSE 341 Spring 2005, Lecture 9

3

Scope

A key language concept: how are user-defined things *resolved*?

We have seen that ML has *lexically scoped* variables

Another (more-antiquated-for-variables, sometimes-useful) approach is *dynamic scope*

Example of dynamic scope: Exception handlers (where does `raise` transfer control?)

Another example of dynamic scope: shell commands and shell scripts (environment variables)

The more restrictive “no free variables” makes important idioms impossible.

CSE 341 Spring 2005, Lecture 9

4

Why lexical scope?

1. Functions can be reasoned about (defined, type-checked, etc.) where defined
2. Function meaning not related to choice of variable names
3. "Closing over" local variables creates private data; function definer *knows* function users do not depend on it

Example:

```
fun add_2x x = fn z => z + x + x
```

```
fun add_2x x = let val y = x + x in fn z => z + y end
```

CSE 341 Spring 2005, Lecture 9

5

CSE 341 Spring 2005, Lecture 9

6

Key idioms with closures

- Create similar functions
- Pass functions with private data to iterators (map, fold, ...)
- Combine functions
- Provide an ADT
- As a *callback* without the "wrong side" specifying the environment.
- Partially apply functions ("currying")

Create similar functions

```
val addn = fn n => fn m => n+m
val increment = addn 1
val add_two = addn 2
fun f n =
  if n=0
  then []
  else (addn n)::(f (n-1))
```

CSE 341 Spring 2005, Lecture 9

7

CSE 341 Spring 2005, Lecture 9

8

Private data, for map/fold

Previously we saw map, this fold function is even more useful:

```
fun fold (f,acc,l) =
```

```
  case l of
```

```
    [] => acc
```

```
  | hd::tl => fold (f, f(acc,hd), tl)
```

Example uses (without using private data):

```
fun f1 l = fold ((fn (x,y) => x+y), 0, l)
```

```
fun f2 l = fold ((fn (x,y) => x andalso y >= 0), true, l)
```

Example use (with private data):

```
fun f3 (l,lo,hi) =
```

```
  fold ((fn (x,y) =>
```

```
    if y >= lo andalso y <= hi then x+1 else x),
    0, l)
```

CSE 341 Spring 2005, Lecture 9

7

CSE 341 Spring 2005, Lecture 9

8

More on fold and private data

Another more general example:

```
fun f4 (l,g) = fold ((fn (l2,y) => (g y)::l2), [], l)
```

A fold function over a data structure is much like a *visitor pattern* in OOP.

We define fold once and do not restrict the type of the function passed to fold or the environment in which it is defined.

In general, libraries should not unnecessarily restrict clients.

Combine functions

```
fun f1 (g,h) = fn x => g (h x)
```

```
fun f2 (g,h) = fn x =>
  case g x of NONE => h x | SOME y => y
```