

CSE 344: Section 3

Azure, Grouping and Nesting

October 12th, 2017

Administrivia

WQ2 due **TOMORROW!!!** (Friday, Oct 13th at 11:59 PM)

HW3 due **Friday, Oct 20th** at 11:00 PM

Set up Azure ASAP

Last day to turn in HW2 (with late days)

Azure Setup

- Set up early to avoid any problems!
 - Instructions in hw3 spec
- You should have received an email with an invitation from Microsoft to create an Azure account/database
 - If you haven't received an invitation email or are having problems setting up your database, please post on Piazza or contact course staff at cse344-staff@cs.washington.edu

How to Run HW3 Queries

- Azure portal
 - Still in preview mode; limited features
- SQL Server Management Studio (SSMS)
 - Fully-featured
 - Enables viewing of query execution plans
 - Windows only (lab computers)
- DataGrip
 - <https://www.jetbrains.com/student/>
 - Setup instructions posted on Piazza

Azure Set-up: Demo

Group By

- Powerful tool to handle “categories”
 - Treat rows with a same attribute as a category
- Careful when selecting
 - Only select attributes appeared in **GROUP BY** or **aggregates**
 - SQLite will guess (arbitrarily pick a value) `^(ツ)^/`
 - SQL Server will throw an error `∩`_´∩`

Group By - Examples

Do these queries work?

Enrolled(stu_id, course_num)

johndoe	311
johndoe	344
maryjane	311
maryjane	351
maryjane	369

```
SELECT stu_id, course_num
FROM Enrolled
GROUP BY stu_id
```


```
SELECT stu_id, count(course_num)
FROM Enrolled
GROUP BY stu_id
```

Group By - Examples

Do these queries work?

Enrolled(stu_id, course_num)

johndoe	?
maryjane	?



```
SELECT stu_id, course_num
FROM Enrolled
GROUP BY stu_id
```

```
SELECT stu_id, count(course_num)
FROM Enrolled
GROUP BY stu_id
```


Group By - Examples

Do these queries work?

Enrolled(stu_id, course_num)

johndoe	2
maryjane	3

```
SELECT stu_id, course_num
FROM Enrolled
GROUP BY stu_id
```

```
SELECT stu_id, count(course_num)
FROM Enrolled
GROUP BY stu_id
```

Group By - Examples

What happens when we try to do:

```
SELECT attr_1, attr_2, ..., attr_n  
FROM ...  
GROUP BY attr_1, attr_2, ..., attr_n;
```

Group By - Examples

What happens when we try to do:

```
SELECT attr_1, attr_2, ..., attr_n  
FROM ...  
GROUP BY attr_1, attr_2, ..., attr_n;
```

This is like `SELECT DISTINCT...`

Witnessing (i.e. argmax)

Find the student who is taking the most classes.

```
Student(stu_id, id_num)
Enrolled(id_num, class)
```

johndoe	973	973	CSE 311
maryjane	712	973	CSE 344
alsmith	899	712	CSE 311
		899	CSE 351

```
SELECT S.stu_id
       FROM Student S, Enrolled E
      WHERE S.id_num = E.id_num
      GROUP BY S.stu_id
     HAVING COUNT(E.class) >= ALL(
           SELECT COUNT(E1.class)
              FROM Enrolled E1
             GROUP BY E1.id_num);
```

Nested Queries

- Avoid when possible
- Danger of making simple queries slow and complicated
- Just because you can do it, doesn't mean you should



Subquery in SELECT

```
SELECT DISTINCT C.cname, (SELECT count(*)  
                           FROM Product P  
                           WHERE P.cid=C.cid)  
FROM Company C
```

Subquery in SELECT

Unnest using JOIN and GROUP BY

```
SELECT C.cname, COUNT(P.cid)
FROM Company C
LEFT OUTER JOIN Product ON C.cid = P.cid
GROUP BY C.cname;
```

Subquery in FROM

```
SELECT X.pname
   FROM (SELECT *
          FROM Product
          WHERE price > 20) AS X
 WHERE X.price < 500
```

More readable: WITH <name> AS <subquery>

Subquery in FROM

Unnest using WHERE

```
SELECT X.pname  
       FROM Product AS X  
       WHERE X.price < 500 AND X.price > 20;
```

Subquery in WHERE

```
SELECT DISTINCT C.cname
  FROM Company C
 WHERE EXISTS (SELECT *
                FROM Product P
                WHERE C.cid = P.cid AND P.price < 200)
```

Subquery in WHERE

```
SELECT DISTINCT C.cname  
  FROM Company C, Product P  
 WHERE C.cid = P.cid AND P.price < 200
```

Subquery in WHERE Syntax

- `SELECT WHERE EXISTS (sub);`
- `SELECT WHERE NOT EXISTS (sub);`
- `SELECT WHERE attribute IN (sub);`
- `SELECT WHERE attribute NOT IN (sub);`
- `SELECT WHERE attribute > ANY (sub);`
- `SELECT WHERE attribute > ALL (sub);`

(Non-)monotonic Queries

- “Can we take back outputs by looking at more data?”
- Is this a monotonic query?

```
SELECT count (*)  
  FROM T1  
 GROUP BY T1.attr
```

(Non-)monotonic Queries

- “Can we take back outputs by looking at more data?”
- Is this a monotonic query?

```
SELECT count (*)  
  FROM T1  
 GROUP BY T1.attr
```

No! This query does not satisfy **set containment**.

Ex:

Current output: $\{(6), (23), (10)\}$

After more data: $\{(6), (23), (11)\}$

$\{(6), (23), (10)\} \not\subseteq \{(6), (23), (11)\}$

To Nest or Not to Nest

- Not an exact science
- Figuring out what is actually wanted will help you find simpler solutions (best way is to practice)
- Trigger words to use sub-querying
 - Every, All (universal quantifiers)
 - No, None, Never (negation)
 - Only