

Processes II, Virtual Memory I

CSE 351 Spring 2020

Instructor:

Ruth Anderson

Teaching Assistants:

Alex Olshanskyy

Rehaan Bhimani

Callum Walker

Chin Yeoh

Diya Joy

Eric Fan

Edan Sneh

Jonathan Chen

Jeffery Tian

Millicent Li

Melissa Birchfield



Porter Jones

Joseph Schafer

Connie Wang

Eddy (Tianyi) Zhou

<http://rebrn.com/re/bad-chrome-1162082/>



Administrivia

- ❖ Lab 4 – Due Friday 5/22
 - Cache parameter puzzles and code optimizations

- ❖ **You must log on with your @uw google account to access!!**
 - **Google doc** for 11:30 Lecture: <https://tinyurl.com/351-05-15A>
 - **Google doc** for 2:30 Lecture: <https://tinyurl.com/351-05-15B>

Fork Example

```
void fork1() {
    int x = 1;
    pid_t fork_ret = fork();
    if (fork_ret == 0)
        printf("Child has x = %d\n", ++x);
    else
        printf("Parent has x = %d\n", --x);
    printf("Bye from process %d with x = %d\n", getpid(), x);
}
```


- ❖ Both processes continue/start execution after `fork`
 - Child starts at instruction after the call to `fork` (storing into `pid`)
- ❖ Can't predict execution order of parent and child
- ❖ Both processes start with `x = 1`
 - Subsequent changes to `x` are independent
- ❖ Shared open files: `stdout` is the same in both parent and child

Modeling fork with Process Graphs

- ❖ A *process graph* is a useful tool for capturing the partial ordering of statements in a concurrent program
 - Each vertex is the execution of a statement
 - $a \rightarrow b$ means a happens before b
 - Edges can be labeled with current value of variables
 - `printf` vertices can be labeled with output
 - Each graph begins with a vertex with no inedges
- ❖ Any *topological sort* of the graph corresponds to a feasible total ordering
 - Total ordering of vertices where all edges point from left to right

Fork Example: Possible Output

```
void fork1() {  
    int x = 1;  
    pid_t fork_ret = fork();  
    if (fork_ret == 0)  
        printf("Child has x = %d\n", ++x);  
    else  
        printf("Parent has x = %d\n", --x);  
    printf("Bye from process %d with x = %d\n", getpid(), x);  
}
```



Polling Question [Proc II]

❖ Are the following sequences of outputs possible?

■ Vote at <http://pollev.com/rea>

```
void nestedfork() {
    printf("L0\n");
    if (fork() == 0) {
        printf("L1\n");
        if (fork() == 0) {
            printf("L2\n");
        }
    }
    printf("Bye\n");
}
```

Seq 1: Seq 2:

L0	L0
L1	Bye
Bye	L1
Bye	L2
Bye	Bye
L2	Bye

- A. **No** **No**
- B. **No** **Yes**
- C. **Yes** **No**
- D. **Yes** **Yes**
- E. **We're lost...**

Fork-Exec


Note: the return values of `fork` and `exec*` should be checked for errors

❖ fork-exec model:

- `fork()` creates a copy of the current process
- `exec*` () replaces the current process' code and address space with the code for a different program
 - Whole family of `exec` calls – see **`exec(3)`** and **`execve(2)`**

```
// Example arguments: path="/usr/bin/ls",
//      argv[0]="/usr/bin/ls", argv[1]="-ahl", argv[2]=NULL
void fork_exec(char *path, char *argv[]) {
    pid_t fork_ret = fork();
    if (fork_ret != 0) {
        printf("Parent: created a child %d\n", fork_ret);
    } else {
        printf("Child: about to exec a new program\n");
        execv(path, argv);
    }
    printf("This line printed by parent only!\n");
}
```


Exec-ing a new program



execve Example

This is extra
(non-testable)
material


Execute `"/usr/bin/ls -l lab4"` in child process using current environment:



```
if ((pid = fork()) == 0) { /* Child runs program */
    if (execve(myargv[0], myargv, environ) < 0) {
        printf("%s: Command not found.\n", myargv[0]);
        exit(1);
    }
}
```

Run the `printenv` command in a Linux shell to see your own environment variables

Stack Structure on a New Program Start



exit: Ending a process

- ❖ **void** `exit(int status)`
 - Explicitly exits a process
 - Status code: 0 is used for a normal exit, nonzero for abnormal exit
- ❖ The `return` statement from `main()` also ends a process in C
 - The return value is the status code

Processes

- ❖ Processes and context switching
- ❖ Creating new processes
 - `fork()`, `exec*()`, and `wait()`
- ❖ **Zombies**

Zombies

- ❖ A terminated process still consumes system resources
 - Various tables maintained by OS
 - Called a “**zombie**” (a living corpse, half alive and half dead)
- ❖ *Reaping* is performed by parent on terminated child
 - Parent is given exit status information and kernel then deletes zombie child process
- ❖ What if parent doesn't reap?
 - If any parent terminates without reaping a child, then the orphaned child will be reaped by `init` process (pid of 1)
 - **Note:** on recent Linux systems, `init` has been renamed `systemd`
 - In long-running processes (*e.g.* shells, servers) we need *explicit* reaping

wait: Synchronizing with Children

- ❖ `int wait(int *child_status)`
 - Suspends current process (*i.e.* the parent) until one of its children terminates
 - Return value is the PID of the child process that terminated
 - *On successful return, the child process is reaped*
 - If `child_status != NULL`, then the `*child_status` value indicates why the child process terminated
 - Special macros for interpreting this status – see `man wait(2)`
- ❖ **Note:** If parent process has multiple children, `wait` will return when *any* of the children terminates
 - `waitpid` can be used to wait on a specific child process

wait: Synchronizing with Children


```

void fork_wait() {
    int child_status;

    if (fork() == 0) {
        printf("HC: hello from child\n");
        exit(0);
    } else {
        printf("HP: hello from parent\n");
        wait(&child_status);
        printf("CT: child has terminated\n");
    }
    printf("Bye\n");
}

```

forks.c



Feasible output:

HC
HP
CT
Bye

Infeasible output:

HP
CT
Bye
HC

Example: Zombie

```
void fork7() {
    if (fork() == 0) {
        /* Child */
        printf("Terminating Child, PID = %d\n",
            getpid());
        exit(0);
    } else {
        printf("Running Parent, PID = %d\n",
            getpid());
        while (1); /* Infinite loop */
    }
}
```

forks.c

```
linux> ./forks 7 &
[1] 6639
Running Parent, PID = 6639
Terminating Child, PID = 6640
linux> ps
  PID TTY          TIME CMD
 6585 ttyp9        00:00:00 tcsh
 6639 ttyp9        00:00:03 forks
 6640 ttyp9        00:00:00 forks <defunct>
 6641 ttyp9        00:00:00 ps
linux> kill 6639
[1] Terminated
linux> ps
  PID TTY          TIME CMD
 6585 ttyp9        00:00:00 tcsh
 6642 ttyp9        00:00:00 ps
```

❖ ps shows child process as "defunct"

❖ Killing parent allows child to be reaped by init

Example: Non-terminating Child

```
void fork8() {  
    if (fork() == 0) {  
        /* Child */  
        printf("Running Child, PID = %d\n",  
              getpid());  
        while (1); /* Infinite loop */  
    } else {  
        printf("Terminating Parent, PID = %d\n",  
              getpid());  
        exit(0);  
    }  
}
```

forks.c

```
linux> ./forks 8  
Terminating Parent, PID = 6675  
Running Child, PID = 6676  
linux> ps  
  PID TTY          TIME CMD  
 6585 tty9          00:00:00 tcsh  
 6676 tty9          00:00:06 forks  
 6677 tty9          00:00:00 ps  
linux> kill 6676  
linux> ps  
  PID TTY          TIME CMD  
 6585 tty9          00:00:00 tcsh  
 6678 tty9          00:00:00 ps
```

- ❖ Child process still active even though parent has terminated
- ❖ Must kill explicitly, or else will keep running indefinitely

Process Management Summary

- ❖ `fork` makes two copies of the same process (parent & child)
 - Returns different values to the two processes
- ❖ `exec*` replaces current process from file (new program)
 - Two-process program:
 - First `fork()`
 - `if (pid == 0) { /* child code */ } else { /* parent code */ }`
 - Two different programs:
 - First `fork()`
 - `if (pid == 0) { execv(...) } else { /* parent code */ }`
- ❖ `wait` or `waitpid` used to synchronize parent/child execution and to reap child process

Roadmap

C:

```
car *c = malloc(sizeof(car));
c->miles = 100;
c->gals = 17;
float mpg = get_mpg(c);
free(c);
```

Java:

```
Car c = new Car();
c.setMiles(100);
c.setGals(17);
float mpg =
    c.getMPG();
```

- Memory & data
- Integers & floats
- x86 assembly
- Procedures & stacks
- Executables
- Arrays & structs
- Memory & caches
- Processes
- Virtual memory**
- Memory allocation
- Java vs. C


Assembly language:

```
get_mpg:
    pushq    %rbp
    movq    %rsp, %rbp
    ...
    popq    %rbp
    ret
```

Machine code:

```
0111010000011000
100011010000010000000010
1000100111000010
110000011111101000011111
```

Computer system:



Virtual Memory (VM*)


- ❖ Overview and motivation
- ❖ VM as a tool for caching
- ❖ Address translation
- ❖ VM as a tool for memory management
- ❖ VM as a tool for memory protection

Warning: Virtual memory is pretty complex, but crucial for understanding how processes work and for debugging performance

**Not to be confused with “Virtual Machine” which is a whole other thing.*

Memory as we know it so far... is *virtual*!



- ❖ Programs refer to virtual memory addresses
 - `movq (%rdi), %rax`
 - Conceptually memory is just a very large array of bytes
 - System provides private address space to each process
- ❖ Allocation: Compiler and run-time system
 - Where different program objects should be stored
 - All allocation within single virtual address space
- ❖ But...
 - We *probably* don't have 2^w bytes of physical memory
 - We *certainly* don't have 2^w bytes of physical memory *for every process*
 - Processes should not interfere with one another
 - Except in certain cases where they want to share code or data



Problem 1: How Does Everything Fit?

64-bit virtual addresses can address
several exabytes
(18,446,744,073,709,551,616 bytes)

Physical main memory offers
a few gigabytes
(e.g. 8,589,934,592 bytes)



(Not to scale; physical memory would be smaller than the period at the end of this sentence compared to the virtual address space.)

1 virtual address space per process,
with many processes...

Problem 2: Memory Management

We have multiple processes:

Process 1
Process 2
Process 3
...
Process n


X

Each process has...


stack
heap
.text
.data
...

*What goes
where?*


Physical main memory



Problem 3: How To Protect




Problem 4: How To Share?




How can we solve these problems?

- ❖ “Any problem in computer science can be solved by adding another level of **indirection**.” – *David Wheeler, inventor of the subroutine*

- ❖ Without Indirection



- ❖ With Indirection




What if I want to move Thing?

Indirection

- ❖ *Indirection*: The ability to reference something using a name, reference, or container instead of the value itself. A flexible mapping between a name and a thing allows changing the thing without notifying holders of the name.
 - Adds some work (now have to look up 2 things instead of 1)
 - But don't have to track all uses of name/address (single source!)
- ❖ Examples:
 - **Phone system**: cell phone number portability
 - **Domain Name Service (DNS)**: translation from name to IP address
 - **Call centers**: route calls to available operators, etc.
 - **Dynamic Host Configuration Protocol (DHCP)**: local network address assignment

Indirection in Virtual Memory



- ❖ Each process gets its own private virtual address space
- ❖ Solves the previous problems!


Address Spaces

- ❖ **Virtual address space:** Set of $N = 2^n$ virtual addr
 - $\{0, 1, 2, 3, \dots, N-1\}$
- ❖ **Physical address space:** Set of $M = 2^m$ physical addr
 - $\{0, 1, 2, 3, \dots, M-1\}$

- ❖ Every byte in main memory has:
 - one physical address (PA)
 - zero, one, *or more* virtual addresses (VAs)

Mapping

- ❖ A virtual address (VA) can be mapped to either **physical memory** or **disk**
 - Unused VAs may not have a mapping
 - VAs from *different* processes may map to same location in memory/disk



Summary

- ❖ Virtual memory provides:
 - Ability to use limited memory (RAM) across multiple processes
 - Illusion of contiguous virtual address space for each process
 - Protection and sharing amongst processes


BONUS SLIDES

Detailed examples:

- ❖ Consecutive forks
- ❖ `wait()` example
- ❖ `waitpid()` example

Example: Two consecutive forks

```
void fork2() {
    printf("L0\n");
    fork();
    printf("L1\n");
    fork();
    printf("Bye\n");
}
```



Feasible output:

L0
L1
Bye
Bye
L1
Bye
Bye


Infeasible output:

L0
Bye
L1
Bye
L1
Bye
Bye

Example: Three consecutive forks

- ❖ Both parent and child can continue forking

```
void fork3() {  
    printf("L0\n");  
    fork();  
    printf("L1\n");  
    fork();  
    printf("L2\n");  
    fork();  
    printf("Bye\n");  
}
```



wait () Example

- ❖ If multiple children completed, will take in arbitrary order
- ❖ Can use macros WIFEXITED and WEXITSTATUS to get information about exit status

```
void fork10() {
    pid_t pid[N];
    int i;
    int child_status;
    for (i = 0; i < N; i++)
        if ((pid[i] = fork()) == 0)
            exit(100+i); /* Child */
    for (i = 0; i < N; i++) {
        pid_t wpid = wait(&child_status);
        if (WIFEXITED(child_status))
            printf("Child %d terminated with exit status %d\n",
                wpid, WEXITSTATUS(child_status));
        else
            printf("Child %d terminated abnormally\n", wpid);
    }
}
```

waitpid(): Waiting for a Specific Process

```
pid_t waitpid(pid_t pid, int &status, int options)
```

- suspends current process until specific process terminates
- various options (that we won't talk about)

```
void fork11() {
    pid_t pid[N];
    int i;
    int child_status;
    for (i = 0; i < N; i++)
        if ((pid[i] = fork()) == 0)
            exit(100+i); /* Child */
    for (i = 0; i < N; i++) {
        pid_t wpid = waitpid(pid[i], &child_status, 0);
        if (WIFEXITED(child_status))
            printf("Child %d terminated with exit status %d\n",
                wpid, WEXITSTATUS(child_status));
        else
            printf("Child %d terminated abnormally\n", wpid);
    }
}
```