

CSE 373: Selection & Simple Sorting

Selection: bits of Chapters 1, 4, 6, 7

Simple Sorting: Chapter 7



The Selection Problem

Goal: Given a list of n numbers, find the k^{th} smallest

Special Cases:

$k = 1$: `findMin()`

$k = n$: `findMax()`

$k = n/2$: the *median* of the list

Any ideas?

Selection Brainstorming

Which of the data structures that we've studied would be appropriate for selection?

- List
- Stack
- Queue
- Tree
- BST
- Hash Table
- Heap

– must be able to store data

– must maintain some sort of ordering information

List-Based Selection

Naive algorithm:

– Insert each element into a second list using `insertSorted()`

– Return the element in the *k*th position

– Running time?

Slightly improved algorithm:

– Store only the *k* smallest elements seen so far

– Running time?

Tree-Based Selection

Naive Algorithm:

- `insert()` all elements into a BST
- Traverse the tree using an in-order traversal
- Count off until we reach the k^{th} element
- Running time?

Improved Algorithm?

Heap-Based Selection

Naive Algorithm:

- `buildHeap()` all elements into a min-heap
- Perform `deleteMin()` k -1 times
- The next `deleteMin()` returns the target value
- Running time?

Improved Algorithm?

Relating Selection and Sorting



If we were to do selections for $k = 1, 2, \ldots, n$, we would end up with a sorted list

- Running time?

Alternatively, if we were to sort our input list, we could do any selection in O(1) time

- Running time?

Motivation for Sorting

- Sorted arrays allow us to do binary searches
- They also allow us to do fast selection
- The mode could be computed trivially in O(n) time if the input was sorted

(but perhaps most importantly…)

- Humans tend to like things in sorted order

How could we use our data structures to sort?

Which would be appropriate? Efficient?

Introduction to Sorting

Sorting: One of the most fundamental algorithms

Input: An array A[] of values and its size, n.

Output: The array stored in sorted order:
if $i < j$ then $A[i] \leq A[j]$, $\forall i,j \leq n$

Goals: sort as quickly as possible
ideally, use O(1) memory (other than A[])
handle pre-sorted lists quickly

Insertion Sort

Insertion Sort: One of the simplest sorting algorithms, based on List ADT `insert()`.

- n-1 passes
- after pass i, elements 0..i will be in sorted order
- in pass i, we ripple the i^{th} element down the array until it's sorted (with respect to elements 0..i-1)

Insertion Sort Example



position:	*0*	*1*	*2*	*3*	*4*	*5*
input:	**7**	**4**	**9**	**5**	**8**	**2**
pass 1:						
pass 2:						
pass 3:						
pass 4:						
pass 5:						

Insertion Sort Analysis

- Why ripple down rather than up?
- Best case input? Running time?
- Worst case input? Running time?

Adjacent Swap Algorithms

A class of algorithms that sort simply by comparing and swapping adjacent elements

- Insertion Sort
- Bubble Sort
- Selection Sort

Inversions

- Given A[], an *inversion* is a pair (*i*,*j*) such that *i* < *j*, but A[*i*] > A[*j*].
  - How many inversions in our example?

7 4 9 5 8 2

- The number of inversions in A[] equals the number of adjacent swaps required to sort it
  - Why?

Average Case Analysis

Q: What is the average number of inversions in a random input array?

A: Consider an arbitrary list L with n unique values
Consider the reversal of the list L_R
Every pair (i,j) represents an inversion in L or in L_R
The total number of distinct (i,j) pairs is $n(n\text{-}1)/2$
On average, half of these will be in L, half will be in L_R
Thus, the average array has $n(n\text{-}1)/4$ inversions
So, adjacent swap algorithms run in $\Theta(n^2)$ on average