Syntax Analysis/Parsing

Purpose:

- determine if tokens have the right form for the language (right syntactic structure)
- stream of tokens ⇒ abstract syntax tree (AST)

AST:

- captures hierarchical structure of input program
- a primary representation of program

Context-free grammars (CFG's)

Syntax specified using **CFG**'s

- capture important structural characteristics

Notation for CFG's: Backus Normal (Naur) Form (**BNF**)

- set of **terminal symbols** (tokens from lexical analysis)
- set of **nonterminals** (sequences of terminals &/or nonterminals):
  - impose the hierarchical structure
- set of **productions** combine terminals & nonterminals
  - nonterminal ::= nonterminals &/or terminals
- **start symbol**: nonterminal that denotes the language

CFG: set of productions that define a language

BNF description of PL/0 syntax

```
Program     ::=  module Id ; Block Id .
Block       ::=  DeclList begin StmtList end
DeclList    ::=  { Decl ; }
Decl        ::=  ConstDecl | ProcDecl | VarDecl
ConstDecl   ::=  const ConstDeclItem { , ConstDeclItem }
ConstDeclItem ::=Id : Type = ConstExpr
ConstExpr   ::=  Id | Integer
VarDecl     ::=  var VarDeclItem { , VarDeclItem }
VarDeclItem ::= Id : Type
ProcDecl    ::=  procedure Id ( [ FormalDecl {, FormalDecl }
                 ] ) ; Block Id
FormalDecl  ::=  Id : Type
Type        ::=  int
StmtList    ::=  { Stmt ; }
Stmt        ::=  CallStmt | AssignStmt | OutStmt | IfStmt |
                 WhileStmt
CallStmt    ::=  Id ( [ Exprs ] )
AssignStmt  ::=  LValue := Expr
LValue      ::=  Id
OutStmt     ::=  output := Expr
IfStmt      ::=  if Test then StmtList end
WhileStmt   ::=  while Test do StmtList end
Test        ::=  odd Sum | Sum Relop Sum
Relop       ::=  <= | <> | < | >= | > | =
Exprs       ::=  Expr { , Expr }
Expr        ::=  Sum
Sum         ::=  Term { (+ | -) Term }
Term        ::=  Factor { (* | /) Factor }
Factor      ::=  - Factor | LValue | Integer | input | ( Expr )
```


Context-free grammars vs. Regular Expressions

CFG can check everything a RE can but:

- not need CFG power for lexical analysis
- REs are a more concise notation for tokens
- lexical analyzers constructed automatically are more efficient
- more modular front end

RE's not powerful enough for parsing

- nested constructs
- recursion

Derivations & Parse Trees

Derivation:

- define the language specified by the grammar
- sequence of expansion steps, beginning with start symbol, leading to a string of terminals
- production seen as rewriting rule: nonterminal replaced by the rhs

Parsing: inverse of derivation

- given target string of terminals (tokens), want to recover nonterminals representing structure

Can represent derivation as a:

- **parse tree** (concrete syntax tree)
  - graphical representation for a derivation
  - keeps the grammar symbols
  - don't record the expansion order
- **abstract syntax tree** (AST)
  - simpler representation
  - precedence implied by the hierarchy

Example grammar

```
E  ::= E Op E | - E | ( E ) | id
Op ::= + | - | * | /
```

```
(a + b * -c) * d
```

```
E ->     E op E ->
         E op id ->
         E * id ->
         (E) * id ->
         (E op E) * id ->
         (E op -E) * id ->
         (E op -id) * id ->
         (E * -id) * id ->
         (E op E * -id) * id ->
         (E op id * -id) * id ->
         (E + id * -id) * id ->
         (id + id * -id) * id
```

AST's

Abstract syntax trees represent only important aspects of concrete syntax trees

- no need for "sign posts" like `( ), ;, do, end`
- rest of compiler only cares about abstract structure
- can regenerate concrete syntax tree from AST when needed

AST representations in project

AST extensions in project

Expressions:

- **true** and **false** constants
- array index expression
- function call expression
- **and**, **or** operators
- tests are expressions
- constant expressions

Statements:

- **for** statement
- **return** stmt
- **if** stmt with **else**
- array assignment stmt (similar to array index expression)

Declarations:

- procedures with result type
- **var** parameters (passed by reference)

Types:

- boolean type
- array type

Parsing algorithms

Given grammar, want to see if an input program can be generated by it

- check legality
- produce AST representing structure
- be efficient

Kinds of parsing algorithms:

- **top-down** ⇒ **LL(k)** grammar
- **bottom-up** ⇒ **LR(k)** grammar

  Left to right scan on input

  Leftmost/**R**ightmost derivation

  can see **k** tokens at once

Top-down parsing

Build parse tree for input program from the top (start symbol) down to leaves (terminals)

- find **leftmost derivation** for an input string (replace the leftmost nonterminal at each step)
- create parse tree nodes in preorder

Basic issue:

- when replacing a nonterminal with some rhs, how to pick which rhs?

E.g.

```
Stmt    ::= Call | Assign | If | While
Call    ::= Id
Assign  ::= Id := Expr
If      ::= if Test then Stmts end |
            if Test then Stmts else Stmts end
While   ::= while Test do Stmts end
```

Solution: look at input tokens to help decide

Predictive parsing

Predictive parser:
top-down parser that can select correct rhs looking at at most *k* input tokens (the **look-ahead**)

Efficient:

- no backtracking needed
- linear time to parse

Implementation of predictive parsers:

- **table-driven parser**
  - like table-driven FSA
  - plus stack to hold productions, recursively
- **recursive descent parser**
  - each nonterminal parsed by a procedure
  - call other procedures to parse sub-nonterminals, recursively

LL(*k*) grammars

Can construct predictive parser automatically/easily if grammar is **LL(*k*)**

- **L**eft-to-right scan of input, **L**eftmost derivation
- ***k*** tokens of look-ahead needed ($k \geq 1$) to make parsing decisions

Some restrictions:

- **no ambiguity**

  >1 parse tree (derivation) for a sentence in the language
- **no common prefixes of length ≥ *k***

```
S ::= if Test then Ss end |
      if Test then Ss else Ss end | ...
```

- **no left recursion**

```
E ::= E Op E | ...
```

- a few others

Restrictions guarantee that, given *k* input tokens, can always select correct rhs to expand nonterminal

Ambiguity

Some grammars are **ambiguous**:

- multiple parse trees with same final string
- produces more than one leftmost or rightmost derivation

Structure of parse tree captures much of meaning of program; ambiguity ⇒ multiple possible meanings for same program

Solutions:

1) add meta-rules
2) change the grammar
3) change the language

Famous ambiguities: "dangling else"

```
Stmt ::= ... |
         if Expr then Stmt |
         if Expr then Stmt else Stmt
```

"**if** e_1 **then if** e_2 **then** s_1 **else** s_2"

Resolving the ambiguity

Option 1: add a **meta-rule**

e.g. "`else` associates with closest previous `then`"

+ works
+ keeps original grammar intact
- ad hoc and informal

Resolving the ambiguity

Option 2: **rewrite the grammar** to resolve ambiguity explicitly

```
Stmt          ::= MatchedStmt | UnmatchedStmt
MatchedStmt   ::= ... |
                  if Expr then MatchedStmt
                          else MatchedStmt
UnmatchedStmt ::= if Expr then Stmt |
                  if Expr then MatchedStmt
                          else UnmatchedStmt
```

+ formal, no additional rules beyond syntax
- sometimes obscures original grammar

Resolving the ambiguity

Option 3: **redesign the language** to remove the ambiguity

```
Stmt ::= ... |
         if Expr then Stmt end |
         if Expr then Stmt else Stmt end
```

- extra **end** required for every `if`

+ formal, clear, elegant
- changing the language

Another famous ambiguity: expressions

```
E  ::= E Op E | - E | ( E ) | id
Op ::= + | - | * | /
```

"a + b * c"

Resolving the ambiguity

Option 1: add some **meta-rules**,
e.g. precedence and associativity rules

Example:

```
E  ::= E Op E | - E | ( E ) | id
Op ::= + | - | * | / | = | < | and | or
```

operator	precedence	associativity
prefix -	highest	right
*, /		left
+, -		left
=, <		none
and		left
or	lowest	left

Resolving the ambiguity

Option 2: **modify the grammar** to explicitly resolve the ambiguity

Strategy:

- create a nonterminal for each precedence level
- expr is lowest precedence nonterminal
  - each nonterminal can be rewritten with a higher precedence operator
  - highest precedence operator includes terminals
- at each precedence level, use:
  - left recursion for left-associative operators
  - right recursion for right-associative operators
  - no recursion for non-associative operators

Example

Expr ::= Expr0
Expr0 ::= Expr0 **or** Expr1 | Expr1
Expr1 ::= Expr1 **and** Expr2 | Expr2
Expr2 ::= Expr3 (**=**|**<**) Expr3| Expr3
Expr3 ::= Expr3 (**+**|**-**) Expr4 | Expr4
Expr4 ::= Expr4 (*|/) Expr5 | Expr5
Expr5 ::= **-**Expr5 | Expr6
Expr6 ::= **id** | **int** | ... | **(**Expr0**)**

Eliminating common prefixes

Can **left factor** common prefixes to eliminate them

- create new nonterminal for common prefix and/or different suffixes

Before:

```
If      ::= if Test then Stmts end |
            if Test then Stmts else Stmts end
```

After:

```
If      ::= if Test then Stmts IfCont
IfCont  ::= end | else Stmts end
```

Grammar a bit uglier

Easy to do by hand in recursive-descent parser

Eliminating left recursion

Can **rewrite grammar** to eliminate left recursion

Before:

```
E ::= E + T | T
T ::= T * F | F
F ::= id | ...
```

After:

```
E ::= T ECont
ECont ::= + T ECont | ε
T ::= F TCont
TCont ::= * F TCont | ε
F ::= id | ...
```

right-recursive productions

Transition Diagrams

"Railroad diagrams"

- another more graphical notation for CFGs
- diagram per nonterminal
- look like FSAs, where arcs can be labelled with nonterminals as well as terminals
  - if **terminal**: follow the arc
    parser gets a new token & compares it with the terminal on the arc
  - if **nonterminal**: go to new diagram
    parser calls the procedure for the nonterminal
    (recursive descent parser)

Table-driven predictive parser

Can automatically convert grammar into parsing table

PREDICT(*nonterminal*, *input-sym*) ⇒ *production*

- selects the right production to take given a nonterminal to expand and the next token of the input

Example:

```
stmt  ::= if expr then stmt else stmt |
          while expr do stmt |
          begin stmts end
stmts ::= stmt ; stmts |
          ε
expr  ::= id
```

Parsing table

	if	then	else	while	do	begin	end	id	;
stmt	1			2		3			
stmts	1			1		1	2		
expr								1	

Table-driven predictive parser

Stack implementation

- depends on **top of stack** & current **input token**
- initial stack configuration: Start $

- **top of stack** = **input token**
  - pop terminal, advance to next token
- **top of stack** = nonterminal
  - pop nonterminal
  - *pick production from parsing table*
  - push production
- **top of stack** = **input token** = $
  - halt

Errors:

- input token not match terminal on top of stack
- table entry empty

FOLLOW

Definition: For all nonterminals B in N, FOLLOW(B) is the set of terminals (or $) that can follow B in a derivation. I.e.,
FOLLOW(B) = { a in (T u {$}) | S$ ==>* α B a β for some
α, β in (N u T u {$})*}

Computing FOLLOW

+ Add $ to FOLLOW(S)
+ Repeat until no change:
  For all rules A -> α B β
  (i) add (FIRST(β)-{ε}) to FOLLOW(B)
  (ii) if ε in FIRST(β) [e.g. if β = ε]
  add FOLLOW(A) to FOLLOW(B)

Constructing PREDICT table

	FIRST	FOLLOW
S ::= **if** E **then** S **else** S		
| **while** E **do** S		
| **begin** Ss **end**		
Ss ::= S ; Ss		
| ε		
E ::= **id**		

	if	then	else	while	do	begin	end	id	;
stmt	1			2		3			
stmts	1			1		1	2		
expr								1	

Constructing PREDICT table

```
Start ::= S $
S     ::= id | If
If    ::= if E then S IfCont
IfCont ::= else S | ε
```

	FIRST	FOLLOW
Start ::= S $		
S ::= **id**		
::= If		
If ::= **if** E **then** S IfCont		
IfCont ::= **else** S		
::= ε		

	id	if	then	else	$
Start					
S					
If					
IfCont					

Another example

```
S  ::= E $
E  ::= T E'
E' ::= (+|-) T E' | ε
T  ::= F T'
T' ::= (*|/) F T' | ε
F  ::= - F | id | ( E )
```

	FIRST (RHS)	FOLLOW (X)
S ::= E $		
E ::= T E'		
E' ::= (+|-) T E'		
| ε		
T ::= F T'		
T' ::= (*|/) F T'		
| ε		
F ::= - F		
| id		
| (E)		

PREDICT and LL(1)

If PREDICT table has at most one entry in each cell, then grammar is LL(1)

- always exactly one right choice
  ⇒ fast to parse and easy to implement
- LL(1) ⇒ each column labelled by 1 token

Can have multiple entries in each cell

- common prefixes
- left recursion
- ambiguity

Recursive descent parsers

Write subroutine for each non-terminal

- each subroutine first selects correct r.h.s. by peeking at input tokens
- then consume r.h.s.
  - if terminal symbol, verify that it's next & then advance
  - if nonterminal, call corresponding subroutine
- construct & return AST representing r.h.s.

PL/0 parser is recursive descent

PL/0 scanner routines:

- `Token* Get();`
- `Token* Peek();`
- `Token* Read(SYMBOL expected_kind);`
- `bool CondRead(SYMBOL expected_kind);`

Example

ParseExpr => ParseSum => ParseTerm => ParseFactor

```
Sum      ::= Term { (+ | -) Term }
Term     ::= Factor { (* | /) Factor }
```

```
Expr* Parser::ParseSum() {
   Expr* expr = ParseTerm();
   for (;;) {
    Token* t = scanner->Peek();
    if (t->kind() == PLUS || t->kind() == MINUS)
      {scanner->Get(); ...}
    else { break; }
   }
}
Expr* Parser::ParseTerm() {
  Expr* expr = ParseFactor();
  for (;;) {
    Token* t = scanner->Peek();
    if (t->kind() == MUL || t->kind() == DIVIDE)
      {scanner->Get(); ...}
    else { break; }
   }
}
```


Example

```
If ::=  if Expr then Stmt [else Stmt] end ;
```

```
IfStmt* Parser::ParseIfStmt() {
   scanner->Read(IF);
   Expr* test = ParseExpr();
   scanner->Read(THEN);
   Stmt* then_stmt = ParseStmt();
   Stmt* else_stmt;
   if (scanner->CondRead(ELSE)) {
      else_stmt = ParseStmt();
   } else {
      else_stmt = NULL;
   }
   scanner->Read(SEMICOLON);
   return new IfStmt(test, then_stmt, else_stmt);
}
```


Example

```
Stmt         ::= IdStmt ;
IdStmt       ::= CallStmt | AssignStmt;
CallStmt     ::= IDENT "(" Expr ")"
AssignStmt   ::= IDENT := Expr
```

```
Stmt* Parser::ParseIdentStmt() {
   Token* t = scanner->Read(IDENT);
   ...
   if (scanner->CondRead(LPAREN)) {
   // call stmt: parse argument list
       ...
       args = ParseExprs();
       scanner->Read(RPAREN);
       ...
   } else {
   // assign stmt: parse the rest
   ...
   scanner->Read(GETS);
   Expr* expr = ParseExpr();
   ...
   }
}
```

Yacc

yacc: "**y**et **a**nother **c**ompiler-**c**ompiler"

Input:

- grammar
- possibly augmented with action code

Output:

- C functions to parse grammar and perform actions

LALR parser generator

- practical bottom-up parser
- more powerful than LL(1)
- used for parser generators

yacc++, bison, byacc are modern updates of yacc

Yacc input grammar

Example **declaration**:

```
%{
#include <stdio.h>
%}
%token INTEGER
```

Example **grammar** productions:

```
%%
assignstmt: IDENT GETS expr
          ;
ifstmt: IF test THEN stmts END
      | IF test THEN stmts ELSE stmts END
      ;

expr: term
    | expr '+' term
    | expr '-' term
    ;

factor: '-' factor
      | IDENT
      | INTEGER
      | INPUT
      | '(' expr ')'
      ;
%%
```


Yacc with semantic actions

Example **grammar** productions:

```
assignstmt: IDENT GETS expr
            { $$ = new AssignStmt($1, $3); }
          ;
ifstmt: IF test THEN stmtlist END
            { $$ = new IfStmt($2, $4); }
      | IF test THEN stmts ELSE stmts END
            { $$ = new IfElseStmt($2, $4, $6); }
      ;

expr: term { $$ = $1; }
    | expr '+' term
            { $$ = new BinOp(PLUS, $1, $3); }
    | expr '-' term
            { $$ = new BinOp(MINUS, $1, $3); }
    ;

factor: '-' factor { $$ = new UnOp(MINUS, $2); }
      | IDENT { $$ = new VarRef($1); }
      | INTEGER { $$ = new IntLiteral($1); }
      | INPUT { $$ = new InputExpr; }
      | '(' expr ')' { $$ = $2; }
      ;
```


Error handling

How to handle syntax error: **error recovery**

Option 1: **quit compilation** ⇒ PL/0

+ easy
- inconvenient for programmer

Option 2: **do more before quit**

+ try to catch as many errors as possible on one compile
- avoid streams of spurious errors

Option 3: **error correction**

+ fix syntax errors as part of compilation
- hard!