
CSE 413

Programming Languages & Implementation

Hal Perkins

Autumn 2012

Introduction to Ruby

(adapted from CSE 341, Dan Grossman)

The Plan

- Why Ruby?
- Some basics of Ruby programs
 - Syntax
 - Classes, methods
 - Fields, variables, scope
 - Dynamic typing
- We won't cover all (or most) of the details in class
- Focus on OO, dynamic typing, blocks, mixins
- References: online library docs +
 - Thomas *Programming Ruby* (1st ed online, ch 1-8, 2nd ed, v1.8, chs. 1-9, 3rd ed, v1.9, chs. 1-10)
 - Electronic copies available from publisher's site

Logistics

- We'll use Ruby 1.8.7
 - Ruby 1.9 has some differences we'll mention, but core ideas are the same
- REPL (irb) + full Ruby
- Installation instructions, etc. on course web
 - Windows: use “one click installer”
 - OS X: part of developer tools if you don't have it
 - Linux: use your favorite package manager

Why?

- Because:
 - Pure object-oriented language
 - Interesting, not entirely obvious implications
 - Interesting design decisions
 - Type system, mixins, syntax (“friendly”), etc.
- Also interesting, but we’re skipping: RAILS web framework
 - Major reason for industry interest in Ruby, but no time to cover (would take a month)
 - But you should be able to pick it up after 413

Where Ruby fits

- Design choices for O-O and functional languages

	dynamically typed	statically typed
functional	Scheme/Racket	Haskell, ML (not in 413)
object-oriented	Ruby	Java

- Dynamic typed OO helps isolate OO's essence without details of type system
- Historical note: Smalltalk
 - Classic dynamically typed, class-based, pure OO
 - Ruby takes much from this tradition

Ruby key ideas (1)

- *Everything* is an object (with constructor, fields, methods), even numbers, even classes(!)
 - Contrast w/Java primitive vs reference types
- Class based: every object has a class, which determines how it responds to messages
 - Like Java, not like Javascript
- Dynamic typing
 - vs static typing in Java
- Convenient reflection (runtime inspection of objects)
- Dynamic dispatch (like Java)
- Sends to *self* (same as *this* in Java)

Ruby Key Ideas (2)

- Everything is “dynamic”
 - Evaluation can add/remove classes, add/remove methods, add/remove fields, etc.
- Blocks and libraries encourage use of closure idioms
- Blocks are almost first-class anonymous function closures
 - Can convert to/from real lambdas
- mixins: neat, advanced modularity feature
- Syntax and scoping rules of a “scripting language”
 - Often many ways to say something – “why not” attitude
 - Variables “spring to life” on first use
 - Some interesting (odd?) scoping rules
- And a few C/Java-like features (loops, return, etc.)

Defining a class

(see web for full example)

```
class Rat =  
  # no instance variable (field) declarations  
  # just assign to @foo to create field foo  
  def initialize (num, den=1)  
    ...  
    @num = num  
    @den = den  
  end  
  
  def print ... end  
  def add r ... end  
end
```


Using a class (1)

- `ClassName.new(args)` creates a new instance of `ClassName` and calls its `initialize` method with `args`
- Every variable references an object (possibly the `nil` object)
 - Local variables (in a method) `f00`
 - Instance variables (fields) `@f00`
 - Class variables (static fields) `@@f00`
 - Global variables and constants `$f00` `$MAX`

Using a class (2)

- You use an object with a method call
 - Also known as message send
 - Object's class determines its behavior
- Examples: `x.m 4 x.m1.m2 (y.m3) -42.abs`
 - `m` and `m (...)` are syntactic sugar for `self.m` and `self.m (...)`
 - `e1+e2` is sugar for `e1.+ (e2)` (yup, really!!!)

No Variable Declarations

- If you assign to a variable, it's mutation
- If the variable is not in scope, it is created(!) (Do not mispeal things!!)
 - Scope of new variable is the method you are in
- Same with fields: if you assign to a field, that object has that field
 - So different objects of the same class can have different fields(!)
- Fewer keystrokes in programs, “cuts down on typing”, but compiler catches fewer bugs
 - A hallmark of “scripting languages”

Protection?

- Fields are inaccessible outside (individual) instances
 - All instance variables are private
 - Define getter/setter methods as needed
- Methods are public, protected, private
 - public is the default
 - protected: only callable from class or subclass object
 - private: only callable from self
 - Protected & private differ from Java (how?)

Getters and setters

- If you want outside access, must define methods

```
def foo          def foo= x
  @foo           @foo = x
end             end
```

- The foo= convention allows sugar via extra spaces

```
x.foo           x.foo = 42
```

- Shorter syntax for defining getters/setters

```
attr_reader :foo attr_writer :foo
```

- Overall, requiring getters/setters is more uniform, OO
 - Can change methods later without changing clients

Class definitions are dynamic

- All definitions in Ruby are dynamic
- Example: Any code can add or remove methods on existing classes
 - Very occasionally useful (or cute) to add your own method to an existing class that is then visible to all instances of that class
- Changing a class affects all instances – even if already created
 - Disastrous example: changing **Fixnum**'s + method
- Overall: a simple language where everything can be changed and method lookup uses instance's classes

Unusual syntax

(add to this list as you discover things)

- Newlines often matter – example: don't need semi-colon if a statement ends a line
- Message sends (function calls) with 0 or 1 arguments often don't need parentheses
- Infix operations like + are just message sends
- Can define operators including = []
- Conditional expressions `e1 if e2` and similar things (as well is `if e1 then e2`)

Unusual syntax

(add to this list as you discover things)

- Classes don't need to be defined in one place (similar to C#, not Java, C++)
- Class names must be capitalized
- `self` is Java's "this"
- Loops, conditionals, classes, methods are self-bracketing (end with `end`)
 - Actually not unusual except for programmers with too much exposure to C/Java/C#/C++ and other languages of the curly brace persuasion

A bit about Expressions

- Everything is an expression and produces a value
- `nil` means “nothing”, but it is an object (an instance of class `NilClass`)
- `nil` and `false` are false in a boolean context; everything else is true (including 0)
- ‘strings’ are taken literally (almost)
- “strings” allow more substitutions
 - including `{expressions}`
 - (Elaborate regular expression package. Won’t cover in class but learn/use if you wish.)

Top-level

- Expressions at top-level are evaluated in the context of an implicit “main” object with class **Object**
 - That is how a standalone program can “get started” rather than requiring creating an object and calling a method from within irb
- Top-level methods are added to **Object**, which makes them available everywhere
- irb: Ruby REPL/interpreter
 - Use load “*filename.rb*” to read code from file