

Lecture04

CSE 417 Algorithms

Richard Anderson




Autumn 2024

Lecture 4


1

Announcements


- Reading
 - Chapter 2.1, 2.2
 - Chapter 3 (Mostly review)
 - Start on Chapter 4
- Homework Guidelines
 - Submit homework with Gradescope
 - **Describing an algorithm**
 - Clarity is most important
 - Pseudocode generally preferable to just English
 - But sometimes both methods combined work best
 - **Prove that your algorithm works**
 - A proof is a "convincing argument"
 - **Give the run time for your algorithm**
 - Justify that the algorithm satisfies the runtime bound
 - **You may lose points for style**
 - **Homework assignments will (probably) be worth the same amount**



Five Problems



Scheduling
 Weighted Scheduling
 Bipartite Matching
 Maximum Independent Set
 Competitive Facility Location



Summary – Five Problems

- Scheduling
- Weighted Scheduling
- Combinatorial Optimization
- Maximum Independent Set
- Competitive Scheduling

What does it mean for an algorithm to be efficient?

Appropriate use of resources

Fast in practice

Faster than brute force.

Definitions of efficiency

- Fast in practice
- Qualitatively better worst case performance than a brute force algorithm

Polynomial time efficiency

- An algorithm is efficient if it has a polynomial run time
- Run time as a function of problem size
 - Run time: count number of instructions executed on an underlying model of computation
 - $T(n)$: maximum run time for all problems of size at most n

Polynomial Time

- Algorithms with polynomial run time have the property that increasing the problem size by a constant factor increases the run time by at most a constant factor (depending on the algorithm)

$$T(n) = n^k$$

$$T(n) = n^8$$

Why Polynomial Time?

- Generally, polynomial time seems to capture the algorithms which are efficient in practice



- The class of polynomial time algorithms has many good, mathematical properties

Polynomial vs. Exponential Complexity

- Suppose you have an algorithm which takes $n!$ steps on a problem of size n
- If the algorithm takes one second for a problem of size 10, estimate the run time for the following problems sizes:

12	14	16	18	20
2 min	6 hrs	2 mo	50 yr	20K yrs

Ignoring constant factors

- Express run time as $O(f(n))$
- Emphasize algorithms with slower growth rates
- Fundamental idea in the study of algorithms
- Basis of Tarjan/Hopcroft Turing Award

Why ignore constant factors?

- **Constant factors are arbitrary**
 - Depend on the implementation
 - Depend on the details of the model
- **Determining the constant factors is tedious and provides little insight**

Why emphasize growth rates?

- The algorithm with the lower growth rate will be faster for all but a finite number of cases
- Performance is most important for larger problem size
- As memory prices continue to fall, bigger problem sizes become feasible
- Improving growth rate often requires new techniques

Formalizing growth rates

- $T(n)$ is $O(f(n))$ $[T : \mathbb{Z}^+ \rightarrow \mathbb{R}^+]$
 - If n is sufficiently large, $T(n)$ is bounded by a constant multiple of $f(n)$
 - Exist c, n_0 , such that for $n > n_0$, $T(n) < c f(n)$

- $T(n)$ is $O(f(n))$ will be written as:

$$T(n) = O(f(n))$$

- Be careful with this notation

$$T(n) \in O(f(n))$$

Prove $3n^2 + 5n + 20$ is $O(n^2)$

Let $c = 6$

Let $n_0 = 5$

$$3n^2 + 5n + 20 \leq 3n^2 + n^2 + n^2 \\ = 5n^2$$

$T(n)$ is $O(f(n))$ if there exist c, n_0 , such that for $n > n_0$,
 $T(n) < c f(n)$

Order the following functions in increasing order by their growth rate

a) $n \log^4 n$

b) $2n^2 + 10n$

c) $2^{n/100}$

d) $1000n + \log^8 n$

e) n^{100}

f) 3^n

g) $1000 \log^{10} n$

h) $n^{1/2}$



Lower bounds

$2n^2$ is $O(n^3)$

- $T(n)$ is $\Omega(f(n))$
 - $T(n)$ is at least a constant multiple of $f(n)$
 - There exists an n_0 , and $\varepsilon > 0$ such that $T(n) > \varepsilon f(n)$ for all $n > n_0$

- Warning: definitions of Ω vary

$2n^2$ is $\Theta(n^2)$

- $T(n)$ is $\Theta(f(n))$ if $T(n)$ is $O(f(n))$ and $T(n)$ is $\Omega(f(n))$

Useful Theorems

$$f(n) = 3n^2 + 2$$
$$g(n) = n^2$$

- If $\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = c$ for $c > 0$ then $f(n) = \Theta(g(n))$
- If $f(n)$ is $O(g(n))$ and $g(n)$ is $O(h(n))$ then $f(n)$ is $O(h(n))$
- If $f(n)$ is $O(h(n))$ and $g(n)$ is $O(h(n))$ then $f(n) + g(n)$ is $O(h(n))$

Ordering growth rates

- For $b > 1$ and $x > 0$
 - $\log^b n$ is $O(n^x)$
- For $r > 1$ and $d > 0$
 - n^d is $O(r^n)$