

CSE 421 Section 8

Linear Programming Practice

+ What Tool?

How to Determine Which Algo Paradigm to Try

Administrivia



Announcements & Reminders

- Midterm Exam
- HW6
 - Due yesterday Nov 15.
- HW7
 - Due on Nov 29 but no other section before then.

Linear Programming



Review of Key Concepts

Linear programming is the following problem:

$$\begin{aligned} & \mathbf{max} \ c^T x \\ & \mathbf{subject\ to} \ Ax \leq b \end{aligned}$$

In other words,

$$\begin{aligned} & \mathbf{max} \ c_1 x_1 + c_2 x_2 + \cdots + c_n x_n \\ & \mathbf{subject\ to} \ a_{11} x_1 + a_{12} x_2 + \cdots + a_{1n} x_n \leq b_1 \\ & \qquad \qquad \qquad a_{21} x_1 + a_{22} x_2 + \cdots + a_{2n} x_n \leq b_2 \\ & \qquad \qquad \qquad \dots \\ & \qquad \qquad \qquad a_{m1} x_1 + a_{m2} x_2 + \cdots + a_{mn} x_n \leq b_m \\ & \qquad \qquad \qquad x \geq 0 \end{aligned}$$

Review of Key Concepts

Linear programming is the following problem:

$$\begin{aligned} & \max c^T x \\ & \text{subject to } Ax \leq b \end{aligned}$$

Standard form is maximization with less than or equal to constraints

In other words,

$$\begin{aligned} & \max c_1x_1 + c_2x_2 + \dots + c_nx_n \\ & \text{subject to } a_{11}x_1 + a_{12}x_2 + \dots + a_{1n}x_n \leq b_1 \\ & \quad a_{21}x_1 + a_{22}x_2 + \dots + a_{2n}x_n \leq b_2 \\ & \quad \dots \\ & \quad a_{m1}x_1 + a_{m2}x_2 + \dots + a_{mn}x_n \leq b_m \\ & \quad x \geq 0 \end{aligned}$$

Non-negativity constraint

The Strategy

1. Read and understand the problem
2. Identify the constraints and the objective function
3. Transform the constraints to standard form
4. Correctness (and running time)

Problem 1 – Happy Eating

You are given a list of foods indexed $1, \dots, n$, as well as the calories c_i , sugars (g) s_i , and vitamin D (mcg) d_i in each food. You're trying to maintain a healthy diet by eating exactly 2000 calories per day. You also heard that the American Heart Association recommends at most 30 grams of sugar per day. And because you just moved to Seattle from LA this year, it's your first winter and you need to eat at least 15 mcg of vitamin D to avoid SAD.

Along with the nutrition information, you also know that eating each food will give you happiness h_i . Find a way to compute a healthy diet that makes you happiest.

Problem 1.1 – Read the problem

Answer the usual quick-check questions:

- Are there any technical terms in the problem you don't know? Are there any words that look like normal words, but are actually technical terms?
- What is the input type?
- What is the output type?

Work through this problem with the people around you, and then we'll go over it together!

Problem 1.1 – Read the problem

Answer the usual quick-check questions:

- Are there any technical terms in the problem you don't know? Are there any words that look like normal words, but are actually technical terms?

Happiest: the sum of happiness values for the foods we choose is as high as possible

- What is the input type?

- What is the output type?

Problem 1.1 – Read the problem

Answer the usual quick-check questions:

- Are there any technical terms in the problem you don't know? Are there any words that look like normal words, but are actually technical terms?

Happiest: the sum of happiness values for the foods we choose is as high as possible

- What is the input type?

Four arrays of numbers c, s, d, h each indexed $1, \dots, n$

- What is the output type?

Problem 1.1 – Read the problem

Answer the usual quick-check questions:

- Are there any technical terms in the problem you don't know? Are there any words that look like normal words, but are actually technical terms?

Happiest: the sum of happiness values for the foods we choose is as high as possible

- What is the input type?

Four arrays of numbers c, s, d, h each indexed $1, \dots, n$

- What is the output type?

A quantity of food x_i for each food $1, \dots, n$

Problem 1.2 – Identify constraints and objective

This sounds like a linear programming problem. From what you know so far, what would the constraints be? What is the objective function? What parts are not yet in standard form?

Work through this problem with the people around you, and then we'll go over it together!

Problem 1.2 – Identify constraints and objective

This sounds like a linear programming problem. From what you know so far, what would the constraints be? What is the objective function? What parts are not yet in standard form?

$$\begin{aligned} & \mathbf{max} \quad h_1x_1 + \cdots + h_nx_n \\ & \mathbf{subject\ to} \quad c_1x_1 + \cdots + c_nx_n = 2000 \\ & \quad \quad \quad s_1x_1 + \cdots + s_nx_n \leq 30 \\ & \quad \quad \quad d_1x_1 + \cdots + d_nx_n \geq 15 \\ & \quad \quad \quad x \geq 0 \end{aligned}$$

The inequalities are not yet in standard form.

Problem 1.3 – Transform to standard form

How can you transform the equations from the previous part to be into standard form?

Work through this problem with the people around you, and then we'll go over it together!

Problem 1.3 – Transform to standard form

How can you transform the equations from the previous part to be into standard form?

$$\begin{aligned} & \mathbf{max} \quad h_1x_1 + \cdots + h_nx_n \\ & \mathbf{subject\ to} \\ & \quad c_1x_1 + \cdots + c_nx_n \leq 2000 \\ & \quad -c_1x_1 - \cdots - c_nx_n \leq -2000 \\ & \quad s_1x_1 + \cdots + s_nx_n \leq 30 \\ & \quad -d_1x_1 - \cdots - d_nx_n \leq -15 \\ & \quad x \geq 0 \end{aligned}$$

Convert equalities into two inequalities and multiply \geq inequalities by -1.

Problem 1.4 – Correctness and runtime

Explain why your algorithm is correct. For LP problems, the proof is usually just explaining how you've represented each part of the problem and relying on the correctness of the LP algorithm. (Runtime hasn't been covered in class yet, so don't worry about it for today.)

Work through this problem with the people around you, and then we'll go over it together!

Problem 1.4 – Correctness and runtime

Explain why your algorithm is correct. For LP problems, the proof is usually just explaining how you've represented each part of the problem and relying on the correctness of the LP algorithm. (Runtime hasn't been covered in class yet, so don't worry about it for today.)

If we pick x_i units of food i , then the total happiness we get is $h_i x_i$, so our goal is to maximize $h_1 x_1 + \dots + h_n x_n$. Similarly, we are given per-unit values for the amount of calories, sugar, and vitamin D, so our constraints are $c_1 x_1 + \dots + c_n x_n = 2000$, $s_1 x_1 + \dots + s_n x_n \leq 30$, and $d_1 x_1 + \dots + d_n x_n \geq 15$. We transformed them to standard form using basic algebra. Relying on an LP algorithm, we output the best x_1, \dots, x_n as desired.

What Tool?



In the real world...

When you come across a problem you'd like to solve (perhaps on an interview or on the final exam), you generally won't be told what kind of algorithm to write. You **COULD** just randomly start trying stuff, but that's going to be pretty inefficient, and you may waste a lot of time pursuing algorithmic paradigms that just won't work for the given problem.

Ideally, you want to be able to figure out what kind of algorithm to write in only a few tries. So how do you figure out what technique to use?

The Strategy

1. Read the Problem Carefully
2. Generate Example Inputs/Outputs
3. Ask Some Questions
4. Still Stuck?

Step 1: Read the Problem Carefully

- Are there any technical terms in the problem? Any words that look like normal words but really are technical terms?
- What is the input type?
- What is the output type?

If these questions look familiar, they should!

If you can't answer these, there's no way to figure out what technique to use—you don't even know what problem you're solving!

Step 2: Generate Example Inputs/Outputs

Spend a few minutes producing some examples. This will help make sure that you have a clear understanding of the problem. Like usual, it's helpful to think about a few different "typical" cases here, don't worry too much about edge cases yet.

Plus, you might stumble upon which technique to use here; for example, if you try to visualize an example input, and you start drawing a graph.

Step 3: Ask Some Questions

At this point, you should ask “is this really a graph modeling problem?” Some signs to look for:

- The problem mentions a graph or something graph-sounding (like “routes” or “maps”).
- There are “direct connections” between elements that could be edges.
- When you try to visualize an input example you end up drawing a graph.

Step 3: Ask Some Questions

If it doesn't feel like graph modeling, the next step to ask is probably "could I solve this problem recursively?" Try asking all of these:

- Is there a natural way to split things "in half" (or thirds, or...)?
- Could I make the problem a little bit smaller?
- What's "one step" toward the solution?

These might start leading you to either a divide and conquer (with the first bullet) or dynamic programming solution. In all cases, be sure you can see "how the recursion is helping".

Step 3: Ask Some Questions

Finally:

- Did an idea immediately jump to mind?
- Did you start a sentence with something like “Well, couldn’t I just...”?

Then maybe it’s time for a greedy algorithm. But really, it’s time for you to generate like 3 more examples and try them against your proposed algorithm. It’s not fun to write a bunch of code only to realize it doesn’t work! And greedy algorithms very often fail. Do some more checks before you jump into code writing.

Step 4: Still Stuck?

So, none of the earlier steps worked...

Take a deep breath, it's going to be ok.

Step 4.1: Get a Baseline Algorithm

Figure out what “brute force” or any other baseline would be, and jot it down quickly on paper. And when you’re scared, look to your baseline like that hang-in-there-cat motivational poster. Worst-case, you’re going to use that one. And if you figured out that one, you could probably find another one.

Hang in there.

Step 4.2: Write a Few More Examples

And solve them. How are you, as a person, solving them? You're doing **some** process. See if you can reflect on it and realize what it looks like. That might inspire you toward an algorithm.

Step 4.3: Ask Yourself Some More Questions

- Does this remind you of any of the problems you've seen before? If so, a similar approach might work.
- Can you solve a simpler version of the problem? If there are two variables, make one of them a constant (a small constant, like 1) and ask "now what would I do?" Maybe you can generalize from there.
- Can you sort the input? Assume a graph is connected or topologically sorted? What if it's a tree? What if the array contains only positive elements? Any of these might give you inspiration for the general case.

2. Try it Yourself



Problem 2 – Try it Yourself!

For each of these problems, get far enough through these steps that you're able to guess what technique you might want to use. Then write down a sentence or two about what in the problem lead you toward that technique.

Work through the parts of this problem with the people around you,
and then we'll go over it together!

Problem 2 – Try it Yourself!

- a) There are a total of n courses you have to take, labeled from 1 to n . You are given a list prerequisites where $\text{prerequisites}[i] = (a_i, b_i)$ indicates that you must take course b_i first if you want to take a_i . Return true if you can finish all courses. Otherwise return false.

Problem 2 – Try it Yourself!

- a) There are a total of n courses you have to take, labeled from 1 to n . You are given a list prerequisites where $\text{prerequisites}[i] = (a_i, b_i)$ indicates that you must take course b_i first if you want to take a_i . Return true if you can finish all courses. Otherwise return false.

Graph. The list prerequisites contains pairs of courses that can be represented as edges and the course numbers can represent vertices in a graph.

Problem 2 – Try it Yourself!

- b) You are given a list of integers `coins` representing coins of different denominations and an integer `amount` representing a total amount of money. Return the fewest number of coins you need to make up that amount. If that amount of money cannot be made up by any combination of coins, return -1.

Problem 2 – Try it Yourself!

- b) You are given a list of integers `coins` representing coins of different denominations and an integer `amount` representing a total amount of money. Return the fewest number of coins you need to make up that amount. If that amount of money cannot be made up by any combination of coins, return -1.

Dynamic Programming. Different combination of coins must be tested to find the minimum number to use. By using a coin, the total amount of money is reduced which becomes the next sub-problem.

Problem 2 – Try it Yourself!

- c) You are given an integer array `prices` where `prices[i]` is the price of a given stock on the i^{th} day. On each day, you may decide to buy and/or sell the stock. You can hold at most one share of the stock at any time. However, you can buy it and then immediately sell it on the same day. Find and return the maximum profit you can achieve.

Problem 2 – Try it Yourself!

- c) You are given an integer array `prices` where `prices[i]` is the price of a given stock on the i^{th} day. On each day, you may decide to buy and/or sell the stock. You can hold at most one share of the stock at any time. However, you can buy it and then immediately sell it on the same day. Find and return the maximum profit you can achieve.

Greedy/Dynamic Programming. The goal is to maximize the output, so dynamic programming can be used to memoize the smaller sub-problems for buying/selling on certain days. An indicator to try a greedy algorithm is that you can only hold one share at any time, so there might be a way to decide which share to hold and when to sell it

Problem 2 – Try it Yourself!

- d) You are given an array of k linked-lists, where each linked-list is sorted in ascending order. Merge all the linked-lists into one sorted linked-list and return it.

Problem 2 – Try it Yourself!

- d) You are given an array of k linked-lists, where each linked-list is sorted in ascending order. Merge all the linked-lists into one sorted linked-list and return it.

Divide and Conquer. We can split this into smaller sub-problems and we know that each linked list is sorted which is an indicator for divide and conquer algorithms.

Problem 2 – Try it Yourself!

- e) Given an array of distinct integers `nums` and a target integer `target`, return the number of possible combinations that add up to `target`.

Problem 2 – Try it Yourself!

- e) Given an array of distinct integers `nums` and a target integer `target`, return the number of possible combinations that add up to `target`.

Dynamic Programming. One key phrase is "number of possible combinations", so there must be a way to find the number of combinations for a sub-problem (a smaller target integer) which can be memoized using dynamic programming.

Problem 2 – Try it Yourself!

- f) There are n cities. Some of them are connected, while some are not. If city a is connected directly with city b and city b is connected directly with city c , then city a is connected indirectly with city c . A province is a group of directly or indirectly connected cities and no other cities outside of the group. You are given an $n \times n$ matrix `isConnected` where `isConnected[i][j] = 1` if the i th city and the j th city are directly connected, and `isConnected[i][j] = 0` otherwise. Return the total number of provinces.

Problem 2 – Try it Yourself!

- f) There are n cities. Some of them are connected, while some are not. If city a is connected directly with city b and city b is connected directly with city c , then city a is connected indirectly with city c . A province is a group of directly or indirectly connected cities and no other cities outside of the group. You are given an $n \times n$ matrix `isConnected` where `isConnected[i][j] = 1` if the i th city and the j th city are directly connected, and `isConnected[i][j] = 0` otherwise. Return the total number of provinces.

Graph. Some key words here are “ n cities” and “connected directly/indirectly” which represents a graph where cities are the vertices and whether they are connected or not as the edges.

Problem 2 – Try it Yourself!

- g) You are given an integer array `nums`. You are initially positioned at the array's first index, and each element in the array represents your maximum jump length at that position. Return `true` if you can reach the last index or `false` otherwise.

Problem 2 – Try it Yourself!

- g) You are given an integer array `nums`. You are initially positioned at the array's first index, and each element in the array represents your maximum jump length at that position. Return `true` if you can reach the last index or `false` otherwise.

Greedy/Dynamic Programming. A greedy algorithm can be used to always keep track of the furthest location you can jump to given which locations you've already been and similarly, with dynamic programming, it can be done by memoizing the furthest location for each location.

Problem 2 – Try it Yourself!

- h) Write an efficient algorithm that searches for a value target in an $m \times n$ integer matrix. This matrix has the following properties:
- i. Integers in each row are sorted in ascending order from left to right.
 - ii. Integers in each column are sorted in ascending order from top to bottom.

Problem 2 – Try it Yourself!

- h) Write an efficient algorithm that searches for a value target in an $m \times n$ integer matrix. This matrix has the following properties:
- i. Integers in each row are sorted in ascending order from left to right.
 - ii. Integers in each column are sorted in ascending order from top to bottom.

Divide and Conquer. Some keywords here are “search” and “ascending order”, so we know each column and row are sorted which can be split into smaller matrices that are sorted as well to find a value.

Problem 2 – Try it Yourself!

- i) You are given an integer array `height` of length n . There are n vertical lines drawn such that the two endpoints of the i th line are $(i, 0)$ and $(i, \text{height}[i])$. Find two lines that together with the x -axis form a container, such that the container contains the most water. Return the maximum amount of water a container can store.

Problem 2 – Try it Yourself!

- i) You are given an integer array `height` of length n . There are n vertical lines drawn such that the two endpoints of the i th line are $(i, 0)$ and $(i, \text{height}[i])$. Find two lines that together with the x -axis form a container, such that the container contains the most water. Return the maximum amount of water a container can store.

Greedy. The goal is to maximize the height and width, so walls that are further away and taller should be prioritized.

Problem 2 – Try it Yourself!

- j) There is a group of n people labeled from 0 to $n - 1$ where each person has a different amount of money and a different level of quietness. You are given an array `richer` where `richer[i] = [ai, bi]` indicates that a_i has more money than b_i and an integer array `quiet` where `quiet[i]` is the quietness of the i th person. All the given data in `richer` are logically correct (i.e., the data will not lead you to a situation where x is richer than y and y is richer than x at the same time). Return an integer array `answer` where `answer[x] = y` if y is the least quiet person (that is, the person y with the smallest value of `quiet[y]`) among all people who definitely have equal to or more money than the person x .

Problem 2 – Try it Yourself!

- j) There is a group of n people labeled from 0 to $n - 1$ where each person has a different amount of money and a different level of quietness. You are given an array `richer` where `richer[i] = [ai, bi]` indicates that a_i has more money than b_i and an integer array `quiet` where `quiet[i]` is the quietness of the i th person. All the given data in `richer` are logically correct (i.e., the data will not lead you to a situation where x is richer than y and y is richer than x at the same time). Return an integer array `answer` where `answer[x] = y` if y is the least quiet person (that is, the person y with the smallest value of `quiet[y]`) among all people who definitely have equal to or more money than the person x .

Graph. There is a relationship that is described here that shows a dependency such as showing that person a is richer than person b , so a graph would be used to map out the correct dependencies.

Problem 2 – Try it Yourself!

- k) Given an integer array `nums`, return an integer array `counts` where `counts[i]` is the number of smaller elements to the right of `nums[i]`.

Problem 2 – Try it Yourself!

- k) Given an integer array `nums`, return an integer array `counts` where `counts[i]` is the number of smaller elements to the right of `nums[i]`.

Divide and Conquer. Since we want to find the number of smaller elements to the right of an element in an unsorted array, there must be some sorting that occurs, so a modified divide and conquer sorting algorithm can be used.

Problem 2 – Try it Yourself!

- l) You are given several boxes with different colors represented by different positive numbers. You may experience several rounds to remove boxes until there is no box left. Each time you can choose some continuous boxes with the same color (i.e., composed of k boxes, $k \geq 1$), remove them and get $k * k$ points. Return the maximum points you can get.

Problem 2 – Try it Yourself!

- l) You are given several boxes with different colors represented by different positive numbers. You may experience several rounds to remove boxes until there is no box left. Each time you can choose some continuous boxes with the same color (i.e., composed of k boxes, $k \geq 1$), remove them and get $k * k$ points. Return the maximum points you can get.

Dynamic Programming. The indicator here is that we want to try out different permutations of removing boxes to maximize the output. After removing boxes, the problem becomes smaller, so dynamic programming should be used to memoize the solutions to smaller sub-problems.

Problem 2 – Try it Yourself!

- m) There are n rooms labeled from 0 to $n - 1$ and all the rooms are locked except for room 0. Your goal is to visit all the rooms. However, you cannot enter a locked room without having its key. When you visit a room, you may find a set of distinct keys in it. Each key has a number on it, denoting which room it unlocks, and you can take all of them with you to unlock the other rooms. Given an array `rooms` where `rooms[i]` is the set of keys that you can obtain if you visit room i , return `true` if you can visit all the rooms, or `false` otherwise.

Problem 2 – Try it Yourself!

- m) There are n rooms labeled from 0 to $n - 1$ and all the rooms are locked except for room 0. Your goal is to visit all the rooms. However, you cannot enter a locked room without having its key. When you visit a room, you may find a set of distinct keys in it. Each key has a number on it, denoting which room it unlocks, and you can take all of them with you to unlock the other rooms. Given an array `rooms` where `rooms[i]` is the set of keys that you can obtain if you visit room i , return `true` if you can visit all the rooms, or `false` otherwise.

Graph. There is a dependency on being able to visit a room since you must have found a key in the previous room to unlock it and the goal is to visit all rooms. Because of this, the problem can be represented as a graph with the goal as traversing through all nodes of the graph.

Problem 2 – Try it Yourself!

- n) Given an integer n , return the least number of perfect square numbers that sum to n . A perfect square is an integer that is the square of an integer, in other words, it is the product of some integer with itself. For example, 1, 4, and 9 are perfect squares while 3 and 11 are not.

Problem 2 – Try it Yourself!

- n) Given an integer n , return the least number of perfect square numbers that sum to n . A perfect square is an integer that is the square of an integer, in other words, it is the product of some integer with itself. For example, 1, 4, and 9 are perfect squares while 3 and 11 are not.

Dynamic programming. If a perfect square s is chosen to be part of the solution, then finding the least number of perfect square numbers that create $n - s$ is another sub-problem that should be memoized.

Problem 2 – Try it Yourself!

- o) You are given a network of n locations labeled from 1 to n . You are also given `times`, a list of travel times such that `times[i] = (ui, vi, wi)`, where u_i is the source, v_i is the destination and w_i is the time it takes for a signal to travel from the source to the destination. We will send a signal from a given location k . Return the minimum time it takes for all n locations to receive the signal. If it is impossible for all n locations to receive the signal, return -1 .

Problem 2 – Try it Yourself!

- o) You are given a network of n locations labeled from 1 to n . You are also given times, a list of travel times such that $\text{times}[i] = (u_i, v_i, w_i)$, where u_i is the source, v_i is the destination and w_i is the time it takes for a signal to travel from the source to the destination. We will send a signal from a given location k . Return the minimum time it takes for all n locations to receive the signal. If it is impossible for all n locations to receive the signal, return -1 .

Graph. The key takeaway here is that the list times is a list of weighted edges since for every element, it provides the source, destination and the weight. Another element in this question is that it wants to find the minimum time it takes for all n locations to receive a signal which alludes to some sort of graph traversal.

Problem 2 – Try it Yourself!

- p) You are given two integers n and k and two integer arrays `speed` and `efficiency` both of length n . There are n engineers numbered from 1 to n . `speed[i]` and `efficiency[i]` represent the speed and efficiency of the i th engineer respectively. Choose at most k different engineers out of the n engineers to form a team with the maximum performance. The performance of a team is the sum of their engineers' speeds multiplied by the minimum efficiency among their engineers. Return the maximum performance of this team.

Problem 2 – Try it Yourself!

- p) You are given two integers n and k and two integer arrays `speed` and `efficiency` both of length n . There are n engineers numbered from 1 to n . `speed[i]` and `efficiency[i]` represent the speed and efficiency of the i th engineer respectively. Choose at most k different engineers out of the n engineers to form a team with the maximum performance. The performance of a team is the sum of their engineers' speeds multiplied by the minimum efficiency among their engineers. Return the maximum performance of this team.

Greedy: Less trivial greedy idea: for each candidate, we treat him/her as the one who has the minimum efficiency in a team. Then, we select the rest of the team members based on this condition.

Problem 2 – Try it Yourself!

- q) There are n piles of stones arranged in a row. The i th pile has $\text{stones}[i]$ stones. A move consists of merging exactly k consecutive piles into one pile, and the cost of this move is equal to the total number of stones in these k piles. Return the minimum cost to merge all piles of stones into one pile.

Problem 2 – Try it Yourself!

- q) There are n piles of stones arranged in a row. The i th pile has $\text{stones}[i]$ stones. A move consists of merging exactly k consecutive piles into one pile, and the cost of this move is equal to the total number of stones in these k piles. Return the minimum cost to merge all piles of stones into one pile.

Dynamic programming. Since different merging orders could lead to the same subproblem, using a memo structure could reduce the amount of calculation needed.

Problem 2 – Try it Yourself!

- r) A series of highways connect n cities numbered from 0 to $n - 1$. You are given a 2D integer array `highways` where `highways[i] = [city1i, city2i, tolli]` indicates that there is a highway that connects `city1i` and `city2i`, allowing a car to go from `city1i` to `city2i` and vice versa for a cost of `tolli`. You are also given an integer `discounts` which represents the number of discounts you have. You can use a discount to travel across the i th highway for a cost of `tolli / 2` (integer division). Each discount may only be used once, and you can only use at most one discount per highway. Return the minimum total cost to go from city 0 to city $n - 1$, or -1 if it is not possible to go from city 0 to city $n - 1$.

Problem 2 – Try it Yourself!

- r) A series of highways connect n cities numbered from 0 to $n - 1$. You are given a 2D integer array `highways` where `highways[i] = [city1i, city2i, tolli]` indicates that there is a highway that connects `city1i` and `city2i`, allowing a car to go from `city1i` to `city2i` and vice versa for a cost of `tolli`. You are also given an integer `discounts` which represents the number of discounts you have. You can use a discount to travel across the i th highway for a cost of `tolli / 2` (integer division). Each discount may only be used once, and you can only use at most one discount per highway. Return the minimum total cost to go from city 0 to city $n - 1$, or -1 if it is not possible to go from city 0 to city $n - 1$.

Graph: Cities are the nodes and highways are undirected edges.

Problem 2 – Try it Yourself!

- s) A subsequence of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not). Given two strings source and target, return the minimum number of subsequences of source such that their concatenation equals target. If the task is impossible, return -1.

Problem 2 – Try it Yourself!

- s) A subsequence of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not). Given two strings source and target, return the minimum number of subsequences of source such that their concatenation equals target. If the task is impossible, return -1.

Greedy: we greedily concatenate source and check if we have target as a subsequence of the concatenated string or not.

That's All, Folks!

**Thanks for coming to section this week!
Any questions?**