


Neural Networks

UNIVERSITY *of* WASHINGTON

W

Single Node

“bias unit”




$$\mathbf{x} = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad \boldsymbol{\theta} = \begin{bmatrix} \theta_0 \\ \theta_1 \\ \theta_2 \\ \theta_3 \end{bmatrix}$$


$$h_{\boldsymbol{\theta}}(\mathbf{x}) = g(\boldsymbol{\theta}^T \mathbf{x}) \\ = \frac{1}{1 + e^{-\boldsymbol{\theta}^T \mathbf{x}}}$$

Binary
Logistic
Regression

Sigmoid (logistic) activation function: $g(z) = \frac{1}{1 + e^{-z}}$

Neural Network





$a_i^{(j)}$ = “activation” of unit i in layer j
 $\Theta^{(j)}$ = weight matrix stores parameters
from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)}x_0 + \Theta_{11}^{(1)}x_1 + \Theta_{12}^{(1)}x_2 + \Theta_{13}^{(1)}x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)}x_0 + \Theta_{21}^{(1)}x_1 + \Theta_{22}^{(1)}x_2 + \Theta_{23}^{(1)}x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)}x_0 + \Theta_{31}^{(1)}x_1 + \Theta_{32}^{(1)}x_2 + \Theta_{33}^{(1)}x_3)$$

$$h_\Theta(x) = a_1^{(3)} = g(\Theta_{10}^{(2)}a_0^{(2)} + \Theta_{11}^{(2)}a_1^{(2)} + \Theta_{12}^{(2)}a_2^{(2)} + \Theta_{13}^{(2)}a_3^{(2)})$$

If network has s_j units in layer j and s_{j+1} units in layer $j+1$,
then $\Theta^{(j)}$ has dimension $s_{j+1} \times (s_j + 1)$.

$$\Theta^{(1)} \in \mathbb{R}^{3 \times 4} \quad \Theta^{(2)} \in \mathbb{R}^{1 \times 4}$$

Multi-layer Neural Network - Binary Classification

$$a^{(1)} = x$$


$$a^{(2)} = g(\Theta^{(1)} a^{(1)})$$

:

$$a^{(l+1)} = g(\Theta^{(l)} a^{(l)})$$

:

$$\hat{y} = g(\Theta^{(L)} a^{(L)})$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Binary
Logistic
Regression

Multi-layer Neural Network - Binary Classification

$$a^{(1)} = x$$


$$a^{(2)} = \sigma(\Theta^{(1)} a^{(1)})$$

⋮

$$a^{(l+1)} = \sigma(\Theta^{(l)} a^{(l)})$$

⋮

$$\hat{y} = g(\Theta^{(L)} a^{(L)})$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$\sigma(z) = \max\{0, z\}$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Binary
Logistic
Regression

Multiple Output Units: One-vs-Rest



Pedestrian




Car



Motorcycle



Truck



$$h_{\Theta}(\mathbf{x}) \in \mathbb{R}^K$$

Multi-class
Logistic
Regression

We want:

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

when pedestrian

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$$

when car

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$

when motorcycle

$$h_{\Theta}(\mathbf{x}) \approx \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$$

when truck

Multi-layer Neural Network - Regression

$$a^{(1)} = x$$


$$a^{(2)} = \sigma(\Theta^{(1)} a^{(1)})$$

⋮

$$a^{(l+1)} = \sigma(\Theta^{(l)} a^{(l)})$$

⋮

$$\hat{y} = \Theta^{(L)} a^{(L)}$$



$$L(y, \hat{y}) = (y - \hat{y})^2$$

$$\sigma(z) = \max\{0, z\}$$

Regression

Neural Networks are arbitrary function approximators

Theorem 10 (Two-Layer Networks are Universal Function Approximators). *Let F be a continuous function on a bounded subset of D -dimensional space. Then there exists a two-layer neural network \hat{F} with a finite number of hidden units that approximate F arbitrarily well. Namely, for all x in the domain of F , $|F(x) - \hat{F}(x)| < \epsilon$.*

Cybenko, Hornik (theorem reproduced from CML, Ch. 10)

Training Neural Networks

UNIVERSITY *of* WASHINGTON

W

$$a^{(1)} = x$$

$$\underline{z^{(2)} = \Theta^{(1)} a^{(1)}}$$

$$a^{(2)} = g(z^{(2)})$$


⋮

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\widehat{y} = g(\Theta^{(L)} a^{(L)})$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Gradient Descent: $\Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$

Gradient Descent: $\Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$

Seems simple enough, why are packages like PyTorch, Tensorflow, Theano, Cafe, MxNet synonymous with deep learning?

1. Automatic differentiation

Gradient Descent: $\Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$

Seems simple enough, why are packages like PyTorch, Tensorflow, Theano, Cafe, MxNet synonymous with deep learning?

1. Automatic differentiation

2. Convenient libraries

Gradient Descent:

Seems simple enough
Tensorflow, Theano,
learning?

1. Automatic differentiation

2. Convenient library

```
class Net(nn.Module):

    def __init__(self):
        super(Net, self).__init__()
        # 1 input image channel, 6 output channels, 3x3 square convolution
        # kernel
        self.conv1 = nn.Conv2d(1, 6, 3)
        self.conv2 = nn.Conv2d(6, 16, 3)
        # an affine operation: y = Wx + b
        self.fc1 = nn.Linear(16 * 6 * 6, 120)  # 6*6 from image dimension
        self.fc2 = nn.Linear(120, 84)
        self.fc3 = nn.Linear(84, 10)

    def forward(self, x):
        # Max pooling over a (2, 2) window
        x = F.max_pool2d(F.relu(self.conv1(x)), (2, 2))
        # If the size is a square you can only specify a single number
        x = F.max_pool2d(F.relu(self.conv2(x)), 2)
        x = x.view(-1, self.num_flat_features(x))
        x = F.relu(self.fc1(x))
        x = F.relu(self.fc2(x))
        x = self.fc3(x)
        return x
```

```
# create your optimizer
optimizer = optim.SGD(net.parameters(), lr=0.01)

# in your training loop:
optimizer.zero_grad()    # zero the gradient buffers
output = net(input)
loss = criterion(output, target)
loss.backward()
optimizer.step()         # Does the update
```

Gradient Descent: $\Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$

Seems simple enough, why are packages like PyTorch, Tensorflow, Theano, Cafe, MxNet synonymous with deep learning?

1. Automatic differentiation

2. Convenient libraries

3. GPU support

Common training issues

Neural networks are **non-convex**

- For large networks, **gradients** can **blow up** or **go to zero**. This can be helped by **batchnorm** or ResNet architecture
- **Stepsize**, **batchsize**, **momentum** all have large impact on optimizing the training error *and* generalization performance
- Fancier alternatives to SGD (Adagrad, Adam, LAMB, etc.) can significantly improve training
- Overfitting is common and not undesirable: typical to achieve 100% training accuracy even if test accuracy is just 80%
- Making the network *bigger* may make training *faster!*

Common training issues

Training is too slow:

- Use larger step sizes, develop step size reduction schedule
- Use GPU resources
- Change batch size
- Use momentum and more exotic optimizers (e.g., Adam)
- Apply batch normalization
- Make network larger or smaller (# layers, # filters per layer, etc.)

Test accuracy is low

- Try modifying all of the above, plus changing other hyperparameters

Common training issues

<https://playground.tensorflow.org/>

Backprop

UNIVERSITY *of* WASHINGTON

W

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮


$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

Train by Stochastic Gradient Descent:

$$\Theta_{i,j}^{(l)} \leftarrow \Theta_{i,j}^{(l)} - \eta \frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

Train by Stochastic Gradient Descent:

$$\Theta_{i,j}^{(l)} \leftarrow \Theta_{i,j}^{(l)} - \eta \frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l)}} = \sum_k \frac{\partial L(y, \hat{y})}{\partial z_k^{(l+1)}} \cdot \frac{\partial z_k^{(l+1)}}{\partial z_i^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\begin{aligned} \delta_i^{(l)} &= \frac{\partial L(y, \hat{y})}{\partial z_i^{(l)}} = \sum_k \frac{\partial L(y, \hat{y})}{\partial z_k^{(l+1)}} \cdot \frac{\partial z_k^{(l+1)}}{\partial z_i^{(l)}} \\ &= \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)} g'(z_i^{(l)}) \\ &= a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)} \end{aligned}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$\begin{aligned} \delta_i^{(L+1)} &= \frac{\partial L(y, \hat{y})}{\partial z_i^{(L+1)}} = \frac{\partial}{\partial z_i^{(L+1)}} [y \log(g(z^{(L+1)})) + (1 - y) \log(1 - g(z^{(L+1)}))] \\ &= \frac{y}{g(z^{(L+1)})} g'(z^{(L+1)}) - \frac{1 - y}{1 - g(z^{(L+1)})} g'(z^{(L+1)}) \\ &= y - g(z^{(L+1)}) = y - a^{(L+1)} \end{aligned}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

:

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

:

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$\delta^{(L+1)} = y - a^{(L+1)}$$

Recursive Algorithm!

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backpropagation

Set $\Delta_{ij}^{(l)} = 0 \quad \forall l, i, j$

(Used to accumulate gradient)

For each training instance (\mathbf{x}_i, y_i) :

Set $\mathbf{a}^{(1)} = \mathbf{x}_i$

Compute $\{\mathbf{a}^{(2)}, \dots, \mathbf{a}^{(L)}\}$ via forward propagation

Compute $\boldsymbol{\delta}^{(L)} = \mathbf{a}^{(L)} - y_i$

Compute errors $\{\boldsymbol{\delta}^{(L-1)}, \dots, \boldsymbol{\delta}^{(2)}\}$


Compute gradients $\Delta_{ij}^{(l)} = \Delta_{ij}^{(l)} + a_j^{(l)} \delta_i^{(l+1)}$

Compute avg regularized gradient $D_{ij}^{(l)} = \begin{cases} \frac{1}{n} \Delta_{ij}^{(l)} + \lambda \Theta_{ij}^{(l)} & \text{if } j \neq 0 \\ \frac{1}{n} \Delta_{ij}^{(l)} & \text{otherwise} \end{cases}$

$D^{(l)}$ is the matrix of partial derivatives of $J(\Theta)$

Autodiff

Backprop for this simple network architecture is a special case of reverse-mode auto-differentiation:



This is the special sauce in Tensorflow, PyTorch, Theano, ...