

Training Neural Networks



$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$


$$\vdots$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

$$\vdots$$

$$\hat{y} = g(\Theta^{(L)} a^{(L)})$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

$$\text{Gradient Descent: } \Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$$

Gradient Descent: $\Theta^{(l)} \leftarrow \Theta^{(l)} - \eta \nabla_{\Theta^{(l)}} L(y, \hat{y}) \quad \forall l$

Seems simple enough, why are packages like PyTorch, Tensorflow, Theano, Cafe, MxNet synonymous with deep learning?

1. Automatic differentiation

2. Convenient libraries

3. GPU support

Gradient Descent:

Seems simple enough,
Theano, Cafe, MxNet s

1. Automatic differ

2. Convenient libra

```
class Net(nn.Module):
```

```
    def __init__(self):
        super(Net, self).__init__()
        # 1 input image channel, 6 output channels, 3x3 square convolution
        # kernel
        self.conv1 = nn.Conv2d(1, 6, 3)
        self.conv2 = nn.Conv2d(6, 16, 3)
        # an affine operation: y = Wx + b
        self.fc1 = nn.Linear(16 * 6 * 6, 120) # 6*6 from image dimension
        self.fc2 = nn.Linear(120, 84)
        self.fc3 = nn.Linear(84, 10)

    def forward(self, x):
        # Max pooling over a (2, 2) window
        x = F.max_pool2d(F.relu(self.conv1(x)), (2, 2))
        # If the size is a square you can only specify a single number
        x = F.max_pool2d(F.relu(self.conv2(x)), 2)
        x = x.view(-1, self.num_flat_features(x))
        x = F.relu(self.fc1(x))
        x = F.relu(self.fc2(x))
        x = self.fc3(x)
        return x
```

```
# create your optimizer
optimizer = optim.SGD(net.parameters(), lr=0.01)

# in your training loop:
optimizer.zero_grad() # zero the gradient buffers
output = net(input)
loss = criterion(output, target)
loss.backward()
optimizer.step() # Does the update
```

Common training issues

Neural networks are **non-convex**

- For large networks, **gradients** can **blow up** or **go to zero**. This can be helped by **batchnorm** or ResNet architecture
- **Stepsize**, **batchsize**, **momentum** all have large impact on optimizing the training error *and* generalization performance
- Fancier alternatives to SGD (Adagrad, Adam, LAMB, etc.) can significantly improve training
- Overfitting is common and not undesirable: typical to achieve 100% training accuracy even if test accuracy is just 80%
- Making the network *bigger* may make training *faster!*

Common training issues

Training is too slow:

- Use larger step sizes, develop step size reduction schedule
- Use GPU resources
- Change batch size
- Use momentum and more exotic optimizers (e.g., Adam)
- Apply batch normalization
- Make network larger or smaller (# layers, # filters per layer, etc.)

Test accuracy is low

- Try modifying all of the above, plus changing other hyperparameters

Intuition

<https://playground.tensorflow.org/>

Back Propagation

W

Forward Propagation

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮


$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$



$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

$$\vdots$$

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

$$\vdots$$

$$\hat{y} = a^{(L+1)}$$

Train by Stochastic Gradient Descent:

$$\Theta_{i,j}^{(l)} \leftarrow \Theta_{i,j}^{(l)} - \eta \frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

$$\vdots$$
$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

$$\vdots$$
$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

Train by Stochastic Gradient Descent:

$$\Theta_{i,j}^{(l)} \leftarrow \Theta_{i,j}^{(l)} - \eta \frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l)}} = \sum_k \frac{\partial L(y, \hat{y})}{\partial z_k^{(l+1)}} \cdot \frac{\partial z_k^{(l+1)}}{\partial z_i^{(l)}}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\begin{aligned} \delta_i^{(l)} &= \frac{\partial L(y, \hat{y})}{\partial z_i^{(l)}} = \sum_k \frac{\partial L(y, \hat{y})}{\partial z_k^{(l+1)}} \cdot \frac{\partial z_k^{(l+1)}}{\partial z_i^{(l)}} \\ &= \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)} g'(z_i^{(l)}) \\ &= a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)} \end{aligned}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

$$\vdots$$
$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

$$\vdots$$
$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$\begin{aligned} \delta_i^{(L+1)} &= \frac{\partial L(y, \hat{y})}{\partial z_i^{(L+1)}} = \frac{\partial}{\partial z_i^{(L+1)}} [y \log(g(z^{(L+1)})) + (1 - y) \log(1 - g(z^{(L+1)}))] \\ &= \frac{y}{g(z^{(L+1)})} g'(z^{(L+1)}) - \frac{1 - y}{1 - g(z^{(L+1)})} g'(z^{(L+1)}) \\ &= y - g(z^{(L+1)}) = y - a^{(L+1)} \end{aligned}$$

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backprop

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$

$$a^{(2)} = g(z^{(2)})$$

⋮

$$a^{(l)} = g(z^{(l)})$$

$$z^{(l+1)} = \Theta^{(l)} a^{(l)}$$

$$a^{(l+1)} = g(z^{(l+1)})$$

⋮

$$\hat{y} = a^{(L+1)}$$

$$\frac{\partial L(y, \hat{y})}{\partial \Theta_{i,j}^{(l)}} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}} \cdot \frac{\partial z_i^{(l+1)}}{\partial \Theta_{i,j}^{(l)}} =: \delta_i^{(l+1)} \cdot a_j^{(l)}$$

$$\delta_i^{(l)} = a_i^{(l)}(1 - a_i^{(l)}) \sum_k \delta_k^{(l+1)} \cdot \Theta_{k,i}^{(l)}$$

$$\delta^{(L+1)} = y - a^{(L+1)}$$

Recursive Algorithm!

$$L(y, \hat{y}) = y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})$$

$$g(z) = \frac{1}{1 + e^{-z}} \quad \delta_i^{(l+1)} = \frac{\partial L(y, \hat{y})}{\partial z_i^{(l+1)}}$$

Backpropagation

Set $\Delta_{ij}^{(l)} = 0 \quad \forall l, i, j$ (Used to accumulate gradient)

For each training instance (\mathbf{x}_i, y_i) :

Set $\mathbf{a}^{(1)} = \mathbf{x}_i$

Compute $\{\mathbf{a}^{(2)}, \dots, \mathbf{a}^{(L)}\}$ via forward propagation

Compute $\delta^{(L)} = \mathbf{a}^{(L)} - y_i$


Compute errors $\{\delta^{(L-1)}, \dots, \delta^{(2)}\}$

Compute gradients $\Delta_{ij}^{(l)} = \Delta_{ij}^{(l)} + a_j^{(l)} \delta_i^{(l+1)}$

Compute avg regularized gradient $D_{ij}^{(l)} = \begin{cases} \frac{1}{n} \Delta_{ij}^{(l)} + \lambda \Theta_{ij}^{(l)} & \text{if } j \neq 0 \\ \frac{1}{n} \Delta_{ij}^{(l)} & \text{otherwise} \end{cases}$

Autodiff

Backprop for this simple network architecture is a special case of *reverse-mode auto-differentiation*:



$$y = f(x_1, x_2) = \ln(x_1) + x_1 x_2 - \sin(x_2)$$

Forward Primal Trace		
$v_{-1} = x_1$	$=$	2
$v_0 = x_2$	$=$	5
<hr/>		
$v_1 = \ln v_{-1}$	$=$	$\ln 2$
$v_2 = v_{-1} \times v_0$	$=$	2×5
<hr/>		
$v_3 = \sin v_0$	$=$	$\sin 5$
$v_4 = v_1 + v_2$	$=$	$0.693 + 10$
<hr/>		
$v_5 = v_4 - v_3$	$=$	$10.693 + 0.959$
<hr/>		
$y = v_5$	$=$	11.652

Reverse Adjoint (Derivative) Trace		
$\bar{x}_1 = \bar{v}_{-1}$	$=$	5.5
$\bar{x}_2 = \bar{v}_0$	$=$	1.716
<hr/>		
$\bar{v}_{-1} = \bar{v}_{-1} + \bar{v}_1 \frac{\partial v_1}{\partial v_{-1}}$	$=$	$\bar{v}_{-1} + \bar{v}_1 / v_{-1} = 5.5$
$\bar{v}_0 = \bar{v}_0 + \bar{v}_2 \frac{\partial v_2}{\partial v_0}$	$=$	$\bar{v}_0 + \bar{v}_2 \times v_{-1} = 1.716$
$\bar{v}_{-1} = \bar{v}_2 \frac{\partial v_2}{\partial v_{-1}}$	$=$	$\bar{v}_2 \times v_0 = 5$
$\bar{v}_0 = \bar{v}_3 \frac{\partial v_3}{\partial v_0}$	$=$	$\bar{v}_3 \times \cos v_0 = -0.284$
$\bar{v}_2 = \bar{v}_4 \frac{\partial v_4}{\partial v_2}$	$=$	$\bar{v}_4 \times 1 = 1$
$\bar{v}_1 = \bar{v}_4 \frac{\partial v_4}{\partial v_1}$	$=$	$\bar{v}_4 \times 1 = 1$
$\bar{v}_3 = \bar{v}_5 \frac{\partial v_5}{\partial v_3}$	$=$	$\bar{v}_5 \times (-1) = -1$
$\bar{v}_4 = \bar{v}_5 \frac{\partial v_5}{\partial v_4}$	$=$	$\bar{v}_5 \times 1 = 1$
<hr/>		
$\bar{v}_5 = \bar{y}$	$=$	1

This is the special sauce in Tensorflow, PyTorch, Theano, ...