Butterfly Animation Tutorials

@davehunt, October 16, 2018 Unity 2018.3



Download the Butterfly example content here

Tutorials:

- 1 Playing an animation with the Animator state machine
- 2 Setting up random animation variants
- 3 Making a new animation clip in Animation Window
- 4 Setting up animation layers

1 - Playing an animation with the Animator state machine

1. Drag and drop the Butterfly.fbx model into your scene hierarchy Note that it already has an Animator component, but the Controller field is blank



- Create a new AnimatorController and assign it to the Butterfly Right-click in the Project window and Create > AnimatorController (name ButterflyIdle) Drag and drop it into the Controller field in the Butterfly's Animator component
- 3. Open the AnimatorController in the **Animator** state machine window Double-click the AnimatorController in the Project view to open the Animator window



4. Drag and drop the idle animation clip onto the Entry layer

<u> -</u> =	🛼 Animator				
4 % *	Layers Parameters	9	Base Layer		
Assets ► TestNinja ► Content ► Ch		+ ,			
ight_lower_wing_mesh_i	List is Empty				
ight_upper_wing_mesh					
ight_upper_wing_meeh_			Any State		
o idle				Clips	End
idle_var1			\sim	idle	60.0
o idle_var2				idle_var1	164.0
 idle_var3 				idle_var2	
			idle	idle_var3	400.0
o idle_var4			Entry	idle_var4	650.0
👙 ButterflyAvatar					+ -

Note that the clips have already been defined in the FBX import settings Animation tab

5. Press Play

in the Unity editor to see the idle animation play

The orange node identifies the default animation state, which will automatically play when gameplay starts



(End of Tutorial 1)

Note: there is a shortcut to do all of these steps at once:

Drag and drop a clip onto Butterfly (The object with Animator, but no Controller) This automatically creates AnimatorController and connect the clip as the default state



2 - Setting up random animation variants

1. In the Animator window, create a new Sub-State Machine

Right-click the background and Create New Sub-State Machine (name IdleVariants)



 Add a Transition from idle to the new IdleVariants sub-state machine Right-click on the orange idle state and Make Transition... Next, click on the IdleVariants node to connect the Transition



3. Double-click on the IdleVariants node to open it



4. Drag and drop the four idle variant clips onto the canvas

Note that the first clip automatically makes a transition from the Entry node. The arrow is orange, indicating that it is the default state

ion 📲 Timeline 🔒 🚛	👔 Animator			
4 % *	Layers Parameters 🔊	Base Layer 🔷 IdleVa		
Assets 🕨 TestNinja 🕨 Co	Q-Name +			
right_upper_v	List is Em pty	Any State	idle_var1	(Up) Base Layer
• idle_var1 • idle_var2			idie_var2	
• idle_var3 • idle_var4				Exit
ButterflyAvat ButterflyIdle ButterflyRandon				
• test_1				

5. Add Transitions from the Entry node to each of the animation clips Right-click the Entry node and **Make Transition**, then click on the clip

Base Layer IdleVariar	nts
Any State	idle_var1
Entry	idle_var2
	idle_var3
	idle_var4

- 6. Add Transitions from each of the animation clips to the Exit node
 - Right-click the animation clip and Make Transition, then click the Exit node



7. Press Play and it will start with idle, then transition to idle_var1 and repeat. There is currently nothing in the Transitions telling it which idle variant to choose so it automatically picks the default state, which is marked with the orange arrow. Add a new integer **Parameter** called IdleVariants to the sub-state machine Click the + in the Parameters tab and choose Int Name it IdleVariant and press enter



- 9. Add a new State Machine Behaviour to the IdleVariants sub-state machine
 - a. Navigate up to the Base Layer by clicking this link at the top
 - b. Select the IdleVariants sub-state machine. In the Inspector click Add Behaviour
 - c. Name the behaviour RandomIdleVariant. Press enter and then click Create and Add

Base Layer

9 I	nspector <u></u> 도ighting IdleVariants	5	<u>े</u> •≡ इ. ० ,
÷,			-1. *1
			Mute
	st is Empty		
	Add Behaviour		
	Q RandomIdleVariant		8
	Search		
	New Script		×

State Machine Behaviours docs

(Note that automatically saves the script to the Assets root folder. You may want to move it into a Scripts folder with your asset in order to keep your project organized)

- 10. Open the RandomIdleVariant.cs in **Visual Studio** by double-clicking it in Project view Note that it contains comments describing each of the callbacks that are available
- 11. Uncomment the **OnStateMachineEnter** function and add the following line of code

animator.SetInteger("IdleVariant", Random.Range(0, 4));



12. Set up Conditions in the transitions to idle variant clips

- a. Go back into the IdleVariants sub-state machine by double-clicking on the node
- b. Select the Transition arrow from Entry to idle_var2



c. In the Inspector in the Conditions tab, press the + to add a new one



- d. Set it to: IdleVariant Equals 1
- 13. Set up similar conditions for the rest of the transitions from Entry to the clip, incrementing the number by 1 each time. (idle_var3 = 2, idle_var4 = 3)
- 14. Create one more transition from Entry to idle_var1 Note that the orange arrow turns into a triple arrow



Select the triple arrow and in Inspector, narrow the selection to Animator Transition



Set the condition to IdleVariant Equals 0

15. Press Play the idle animation will play followed by a random variant, repeating



3 - Making a new animation clip in Animation Window

This section describes how to make a new animation clip with a single pose that can be used in the next tutorial for blending as an animation layer.

1. Select the Butterfly in the scene hierarchy and open **Animation Window** On the main menu choose **Window > Animation > Animation**

It will start on the first animation: idle. Switch between clips with the menu here:

🖮 Project 🕓 Animation					-=
Preview 🛑 া 🖬 🕨 🖬					
idle (Read-Only)					
0					
▶ 人abdomen : Position		•			
▶ 人abdomen : Rotation		•		•	•
▶ 人abdomen : Scale		•			
▶ 人left_antenna : Position		•			•
Left antenna · Rotation	-	•		•	

2. Create a new animation clip

Click the menu for selecting the active clip and choose **Create New Clip...** Name the new clip wings_closed_pose



3. Press the Record button in Animation Window



4. Select the Butterfly's left_wing and right_wing bones and rotate them upward to set keyframes



Note that keyframes are automatically set on properties that move when recording



5. You can also add more properties to the clip in the following ways:

Click the Add Property button

Blend shape properties can be found in the model's SkinnedMeshRenderer section



Click the + on the right to add the property

After the pose has been defined, you now have a new AnimationClip

(End of Tutorial 3)

4 - Setting up animation layers

This will be used to make a modified copy of the Butterfly AnimatorController so it can have a different animation style. It will be set up to play more subtle motion on a more closed wings pose using the same animations modified by an animation layer.

1. Duplicate the Butterfly in the scene Hierarchy

Select the Butterfly and press ctrl-d (name it Buttefly2)



- 2. Duplicate the AnimatorController and assign it to Butterfly2
 - a. Select the ButterflyIdle AnimatorController and press ctrl-d (name it ButterflyIdleClosed)



b. Drag and drop it into the Controller field in Butterfly2's Animator component

🔻 🔁 🔽 Animator		\$,
Controller	ButterflyIdleClosed	0
Avatar	불 ButterflyAvatar	\odot
Apply Root Motion		
Update Mode	Normal	\$
Culling Mode	Cull Update Transforms	\$

3. Open the ButterflyIdleClosed AnimatorController in the **Animator** state machine window This should look the same as the result of Tutorial 2

(If the new wings_closed_pose clip from Tutorial 3 is there, delete it from Base Layer)



4. Add a new Animation Layer

Switch to the Layers tab

Click the + to add a new layer (name it WingsClosed)

📲 Animator		
Layers Parameters	۲	WingsClosed
	Ð	
= Base Layer	₩	Any State
= WingsClosed	¥	
		Entry

5. Drag and drop the wings_closed_pose clip into the new layer

Note that since it is the first clip in this layer it automatically gets connected to Entry as the default animation state



6. Set the WingsClosed layer weight to 0.75

Click the settings icon on the WingsClosed layer Set the **Weight** value to 0.75 (Blending mode should stay at the default setting: Override)



7. Press Play

to see the animation playing back

Since the WingsClosed layer is set to Override, it will have the effect of making the idle animations look more subtle. It will play the same animations at a lower intensity blended with the wings closed pose.



(End of Tutorial 4)