

Lecture 3:

Loss Functions

Administrative: Assignment 0

- Due **tonight** by 11:59pm
- Easy assignment
- Hardest part is learning how to use colab and how to submit on gradescope
- Worth 0% of your grade
- Used to evaluate how prepared you are to take this course

Administrative: Assignment 1

Due 4/16 11:59pm

- K-Nearest Neighbor
- Linear classifiers: SVM, Softmax

Administrative: EdStem

Please make sure to check and read all pinned EdStem posts.

Administrative: Fridays

This Friday 9:30-10:30am and again 12:30-1:30pm

Project Design & Backprop

Administrative: Course Project

Project proposal due 4/29 11:59pm

“Is X a valid project for 493G1?”

- Anything related to deep learning or computer vision
- Maximum of 3 students per team
- Make a EdStem private post or come to TA Office Hours

More info on the website

Last time: Image Classification: A core task in Computer Vision



This image by [Nikita](#) is
licensed under [CC-BY 2.0](#)


(assume given a set of labels)
{dog, cat, truck, plane, ...}



cat
dog
bird
deer
truck

Recall from last time: Challenges of recognition

Viewpoint



Illumination



[This image](#) is [CC0 1.0](#) public domain

Deformation



[This image](#) by [Umberto Salvagnin](#) is licensed under [CC-BY 2.0](#)

Occlusion



[This image](#) by [jonsson](#) is licensed under [CC-BY 2.0](#)

Clutter



[This image](#) is [CC0 1.0](#) public domain


Intraclass Variation




[This image](#) is [CC0 1.0](#) public domain

Recall from last time: data-driven approach, kNN



airplane
automobile
bird
cat
deer
dog
frog
horse
ship
truck




1-NN classifier



5-NN classifier




Recall from last time: Linear Classifier



$$f(x, W) = Wx + b$$

Algebraic Viewpoint

$$f(x, W) = Wx$$




Visual Viewpoint

One template per class




Geometric Viewpoint

Hyperplanes cutting up space




Class 1:
 $1 \leq L2 \text{ norm} \leq 2$

Class 2:
Everything else





Class 1:
Three modes

Class 2:
Everything else




Interpreting a Linear Classifier: Visual Viewpoint




Example with an image with 4 pixels, and 3 classes (cat/dog/ship)

Algebraic Viewpoint


$$f(x,W) = Wx$$



Visual Viewpoint



Interpreting a Linear Classifier: Geometric Viewpoint



$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers
(3072 numbers total)

Plot created using [Wolfram Cloud](#)

[Cat image](#) by [Nikita](#) is licensed under [CC-BY 2.0](#)


Linear Classifier

Parametric Approach

Image



Array of **32x32x3** numbers
(3072 numbers total)



W

parameters
or weights

10 numbers giving
class scores

Parametric Approach: Linear Classifier

Image



Array of **32x32x3** numbers
(3072 numbers total)

$$f(x, W) = Wx$$


$f(\mathbf{x}, \mathbf{W})$

\mathbf{W}


parameters
or weights

10 numbers giving
class scores

Parametric Approach: Linear Classifier



Parametric Approach: Linear Classifier




Neural Network

Linear
classifiers




[This image](#) is [CC0 1.0](#) public domain



[Krizhevsky et al. 2012]


Linear layers



[He et al. 2015]

Recall CIFAR10

airplane



automobile



bird



cat



deer



dog



frog




horse



ship



truck



50,000 training images
each image is **32x32x3**

10,000 test images.


Algebraic viewpoint: Example with an image with 4 pixels, and 3 classes (cat/dog/ship)

Flatten tensors into a vector




Algebraic viewpoint: Example with an image with 4 pixels, and 3 classes (cat/dog/ship)

Flatten tensors into a vector




Algebraic viewpoint: Example with an image with 4 pixels, and 3 classes (cat/dog/ship)


Flatten tensors into a vector




Algebraic viewpoint: Example with an image with 4 pixels, and 3 classes (cat/dog/ship)



Algebraic viewpoint: Example with an image with 4 pixels, and 3 classes (cat/dog/ship)





Algebraic viewpoint: Bias trick to simplify computation





Visual Viewpoint: learning templates



Algebraic viewpoint:





Visual Viewpoint: learning templates






Visual Viewpoint: learning templates




Visual Viewpoint: learning templates



Visual Viewpoint: learning templates



Geometric Viewpoint: linear decision boundaries




$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers
(3072 numbers total)

Geometric Viewpoint: linear decision boundaries




$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers
(3072 numbers total)

Geometric Viewpoint: linear decision boundaries



$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers
(3072 numbers total)

Plot created using [Wolfram Cloud](#)

[Cat image](#) by [Nikita](#) is licensed under [CC-BY 2.0](#)


Hard cases for a linear classifier

Class 1:

First and third quadrants

Class 2:

Second and fourth quadrants




Class 1:

$1 \leq \text{L2 norm} \leq 2$

Class 2:

Everything else




Class 1:

Three modes

Class 2:



Everything else



Recall the Minsky report 1969 from last lecture

Unable to learn the XNOR function


X	Y	$F(x,y)$
0	0	0
0	1	1
1	0	1
1	1	0



Three viewpoints for interpreting linear classifiers

Algebraic Viewpoint

$$f(x, W) = Wx$$




Visual Viewpoint

One template
per class



Geometric Viewpoint

Hyperplanes
cutting up space



Next: How to train the weights in a Linear Classifier

TODO:

1. Define a **loss function** that quantifies our unhappiness with the scores across the training data.
2. Come up with a way of efficiently finding the parameters that minimize the loss function. (**optimization**)

Example output for CIFAR-10:




airplane	-3.45	-0.51	3.42
automobile	-8.87	6.04	4.64
bird	0.09	5.31	2.65
cat	2.9	-4.22	5.1
deer	4.48	-4.19	2.64
dog	8.02	3.58	5.55
frog	3.78	4.49	-4.34
horse	1.06	-4.37	-1.5
ship	-0.36	-2.09	-4.79
truck	-0.72	-2.93	6.14

- A random W produces the following 10 scores for the 3 images to the left.
- 10 scores because there are 10 classes.
- **First column bad** because dog is highest.
- **Second column good.**
- **Third column bad** because frog is highest


[Cat image](#) by [Nikita](#) is licensed under [CC-BY 2.0](#); [Car image](#) is [CC0 1.0](#) public domain; [Frog image](#) is in the public domain

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1


Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

A **loss function** tells how good
our current classifier is

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1


A **loss function** tells how good our current classifier is

Given a dataset of examples

$$\{(x_i, y_i)\}_{i=1}^N$$

Where x_i is image and
 y_i is (integer) label

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

A **loss function** tells how good our current classifier is

Given a dataset of examples


$$\{(x_i, y_i)\}_{i=1}^N$$

Where x_i is image and
 y_i is (integer) label

Loss over the dataset is a
average of loss over examples:

$$L = \frac{1}{N} \sum_i L_i(f(x_i, W), y_i)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:


Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases} \\
 &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$

$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,


and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$

$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:


Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:


$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$
$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1


Interpreting Multiclass SVM loss:



$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$


$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1


Interpreting Multiclass SVM loss:



$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$


$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1


Interpreting Multiclass SVM loss:



$$L_i = \sum_{j \neq y_i} \begin{cases} 0 & \text{if } s_{y_i} \geq s_j + 1 \\ s_j - s_{y_i} + 1 & \text{otherwise} \end{cases}$$

$$= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Multiclass SVM loss:


Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Losses: **2.9**

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,


and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$= \max(0, 5.1 - 3.2 + 1) + \max(0, -1.7 - 3.2 + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Losses: **2.9**

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$


the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$= \max(0, 5.1 - 3.2 + 1)$$

$$+ \max(0, -1.7 - 3.2 + 1)$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1

Losses: **2.9**

Multiclass SVM loss:


Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\
 &= \max(0, 5.1 - 3.2 + 1) \\
 &\quad + \max(0, -1.7 - 3.2 + 1) \\
 &= \max(0, 2.9) + \max(0, -3.9)
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9		

Multiclass SVM loss:

Given an example (x_i, y_i)
where x_i is the image and
where y_i is the (integer) label,

and using the shorthand for the
scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned} L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\ &= \max(0, 5.1 - 3.2 + 1) \\ &\quad + \max(0, -1.7 - 3.2 + 1) \\ &= \max(0, 2.9) + \max(0, -3.9) \\ &= 2.9 + 0 \\ &= 2.9 \end{aligned}$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	

Multiclass SVM loss:


Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\
 &= \max(0, 1.3 - 4.9 + 1) \\
 &\quad + \max(0, 2.0 - 4.9 + 1) \\
 &= \max(0, -2.6) + \max(0, -1.9) \\
 &= 0 + 0 \\
 &= 0
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:


Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$\begin{aligned}
 L_i &= \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \\
 &= \max(0, 2.2 - (-3.1) + 1) \\
 &\quad + \max(0, 2.5 - (-3.1) + 1) \\
 &= \max(0, 6.3) + \max(0, 6.6) \\
 &= 6.3 + 6.6 \\
 &= 12.9
 \end{aligned}$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Loss over full dataset is average:


$$L = \frac{1}{N} \sum_{i=1}^N L_i$$

$$L = (2.9 + 0 + 12.9)/3 \\ = 5.27$$

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:

Multiclass SVM loss:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$



Q1: What happens to loss if car scores decrease by 0.5 for this training example?

cat 1.3

car 4.9


frog 2.0

Losses: 0

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:

Multiclass SVM loss:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$



cat 1.3

car 4.9

frog 2.0

Losses: 0


Q1: What happens to loss if car scores decrease by 0.5 for this training example?

Q2: what is the min/max possible SVM loss L_i ?

Suppose: 3 training examples, 3 classes.
With some W the scores $f(x, W) = Wx$ are:

Multiclass SVM loss:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$



cat 1.3

car 4.9

frog 2.0


Losses: 0

Q1: What happens to loss if car scores decrease by 0.5 for this training example?

Q2: what is the min/max possible SVM loss L_i ?

Q3: At initialization W is small so all $s \approx 0$. What is the loss L_i , assuming N examples and C classes?

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q4: What if the sum
 was over all classes?
 (including $j = y_i$)

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,


and using the shorthand for the
 scores vector: $s = f(x_i, W)$

the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q5: What if we used
 mean instead of
 sum?

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:

Given an example (x_i, y_i)
 where x_i is the image and
 where y_i is the (integer) label,

and using the shorthand for the
 scores vector: $s = f(x_i, W)$


the SVM loss has the form:

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Q6: What if we used


$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)^2$$

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	12.9

Multiclass SVM loss:



Q6: What if we used

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)^2$$

Multiclass SVM Loss: Example code

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

```
def L_i_vectorized(x, y, W):  
    scores = W.dot(x)  
    margins = np.maximum(0, scores - scores[y] + 1)  
    margins[y] = 0  
    loss_i = np.sum(margins)  
    return loss_i
```

First calculate scores
Then calculate the margins $s_j - s_{y_i} + 1$
only sum j is not y_i , so when $j = y_i$, set to zero.
sum across all j

$$f(x, W) = Wx$$

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

Q7. Suppose that we found a W such that $L = 0$.
Is this W unique?


$$f(x, W) = Wx$$

$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

E.g. Suppose that we found a W such that $L = 0$.
Is this W unique?

No! $2W$ is also has $L = 0$!

Suppose: 3 training examples, 3 classes.
 With some W the scores $f(x, W) = Wx$ are:



cat	3.2	1.3	2.2
car	5.1	4.9	2.5
frog	-1.7	2.0	-3.1
Losses:	2.9	0	

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Before:

$$\begin{aligned}
 &= \max(0, 1.3 - 4.9 + 1) \\
 &\quad + \max(0, 2.0 - 4.9 + 1) \\
 &= \max(0, -2.6) + \max(0, -1.9) \\
 &= 0 + 0 \\
 &= 0
 \end{aligned}$$

With W twice as large:

$$\begin{aligned}
 &= \max(0, 2.6 - 9.8 + 1) \\
 &\quad + \max(0, 4.0 - 9.8 + 1) \\
 &= \max(0, -6.2) + \max(0, -4.8) \\
 &= 0 + 0 \\
 &= 0
 \end{aligned}$$

$$f(x, W) = Wx$$


$$L = \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, f(x_i; W)_j - f(x_i; W)_{y_i} + 1)$$

E.g. Suppose that we found a W such that $L = 0$.
Is this W unique?

No! $2W$ is also has $L = 0$!

How do we choose between W and $2W$?

Regularization

$$L(W) = \frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)$$


Data loss: Model predictions
should match training data


Regularization

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$


Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data


Regularization intuition: toy example training data



Regularization intuition: Prefer Simpler Models



Regularization: Prefer Simpler Models



Regularization pushes against fitting the data
too well so we don't fit noise in the data

Regularization

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss: Model predictions should match training data}} + \underbrace{\lambda R(W)}_{\text{Regularization: Prevent the model from doing too well on training data}}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Occam's Razor: Among multiple competing hypotheses, the simplest is the best, William of Ockham 1285-1347

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Simple examples

L2 regularization: $R(W) = \sum_k \sum_l W_{k,l}^2$

L1 regularization: $R(W) = \sum_k \sum_l |W_{k,l}|$

Elastic net (L1 + L2): $R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Simple examples

L2 regularization: $R(W) = \sum_k \sum_l W_{k,l}^2$

L1 regularization: $R(W) = \sum_k \sum_l |W_{k,l}|$

Elastic net (L1 + L2): $R(W) = \sum_k \sum_l \beta W_{k,l}^2 + |W_{k,l}|$

More complex:

Dropout

Batch normalization, layer norm

Stochastic depth, fractional pooling, etc

Regularization

λ = regularization strength
(hyperparameter)

$$L(W) = \underbrace{\frac{1}{N} \sum_{i=1}^N L_i(f(x_i, W), y_i)}_{\text{Data loss}} + \underbrace{\lambda R(W)}_{\text{Regularization}}$$

Data loss: Model predictions should match training data

Regularization: Prevent the model from doing *too* well on training data

Why regularize?

- Express preferences over weights
- Make the model *simple* so it works on test data
- Improve optimization by adding curvature

Regularization: Expressing Preferences

L2 Regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2$$

Which of w_1 or w_2 will
the L2 regularizer prefer?

$$x = [1, 1, 1, 1]$$

$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$

$$w_1^T x = w_2^T x = 1$$

Regularization: Expressing Preferences

$$x = [1, 1, 1, 1]$$

$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$

$$w_1^T x = w_2^T x = 1$$

L2 Regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2$$

Which of w_1 or w_2 will
the L2 regularizer prefer?

L2 regularization likes to
“spread out” the weights

Regularization: Expressing Preferences

$$x = [1, 1, 1, 1]$$

$$w_1 = [1, 0, 0, 0]$$

$$w_2 = [0.25, 0.25, 0.25, 0.25]$$

$$w_1^T x = w_2^T x = 1$$

L2 Regularization

$$R(W) = \sum_k \sum_l W_{k,l}^2$$

Which of w_1 or w_2 will the L2 regularizer prefer?

L2 regularization likes to “spread out” the weights

Which one would L1 regularization prefer?

Softmax classifier

Softmax Classifier (Multinomial Logistic Regression)

Want to interpret raw classifier scores as **probabilities**



cat	3.2
car	5.1
frog	-1.7

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

cat	3.2
car	5.1
frog	-1.7

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

cat	3.2	exp →	24.5
car	5.1		164.0
frog	-1.7		0.18

unnormalized
probabilities

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

cat	3.2
car	5.1
frog	-1.7

exp

24.5
164.0
0.18

normalize

0.13
0.87
0.00

unnormalized
probabilities

probabilities

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

$$\rightarrow L_i = -\log(0.13) = 2.04$$

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

$$\rightarrow L_i = -\log(0.13) = 2.04$$

Maximum Likelihood Estimation
Choose weights to maximize the
likelihood of the observed data

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

Kullback–Leibler
divergence

$$D_{KL}(P||Q) =$$

$$\sum_y P(y) \log \frac{P(y)}{Q(y)}$$

1.00
0.00
0.00

Correct
probs

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}}$$

Softmax
Function

Probabilities
must be ≥ 0

Probabilities
must sum to 1

$$L_i = -\log P(Y = y_i|X = x_i)$$

cat
car
frog

3.2
5.1
-1.7

Unnormalized
log-probabilities / logits

exp

24.5
164.0
0.18

unnormalized
probabilities

normalize

0.13
0.87
0.00

probabilities

compare

1.00
0.00
0.00

Correct
probs

Cross Entropy

$$H(P, Q) = H(p) + D_{KL}(P||Q)$$

Softmax Classifier (Multinomial Logistic Regression)



Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}} \quad \text{Softmax Function}$$

Maximize probability of correct class

$$L_i = -\log P(Y = y_i | X = x_i)$$

Putting it all together:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

cat	3.2
car	5.1
frog	-1.7

Softmax Classifier (Multinomial Logistic Regression)



cat	3.2
car	5.1
frog	-1.7

Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}} \quad \text{Softmax Function}$$

Maximize probability of correct class

$$L_i = -\log P(Y = y_i|X = x_i)$$

Putting it all together:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

Q1: What is the min/max possible softmax loss L_i ?

Softmax Classifier (Multinomial Logistic Regression)



cat	3.2
car	5.1
frog	-1.7

Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}} \quad \text{Softmax Function}$$

Maximize probability of correct class

$$L_i = -\log P(Y = y_i|X = x_i)$$

Putting it all together:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

Q1: What is the min/max possible softmax loss L_i ?

Q2: At initialization all s_j will be approximately equal; what is the softmax loss L_i , assuming C classes?

Softmax Classifier (Multinomial Logistic Regression)



cat	3.2
car	5.1
frog	-1.7

Want to interpret raw classifier scores as **probabilities**

$$s = f(x_i; W)$$

$$P(Y = k|X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}} \quad \text{Softmax Function}$$

Maximize probability of correct class

$$L_i = -\log P(Y = y_i|X = x_i)$$


Putting it all together:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

Q2: At initialization all s will be approximately equal; what is the loss?
A: $-\log(1/C) = \log(C)$,
If $C = 10$, then $L_i = \log(10) \approx 2.3$

Softmax vs. SVM


matrix multiply + bias offset



hinge loss (SVM)

$$\begin{aligned} &\max(0, -2.85 - 0.28 + 1) + \\ &\max(0, 0.86 - 0.28 + 1) \\ &= \\ &\mathbf{1.58} \end{aligned}$$

cross-entropy loss (Softmax)



Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

assume scores:

[10, -2, 3]

[10, 9, 9]

[10, -100, -100]

and $y_i = 0$

Q: What is the **SVM loss**?

Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

assume scores:

[10, -2, 3]

[10, 9, 9]

[10, -100, -100]

and $y_i = 0$

Q: What is the **SVM loss**?

Q: Is the **Softmax** loss zero for any of them?

Softmax vs. SVM

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

assume scores:

[20, -2, 3]

[20, 9, 9]

[20, -100, -100]

and $y_i = 0$

Q: What is the **SVM loss**?

Q: Is the **Softmax** loss zero for any of them?

I doubled the correct class score from 10 -> 20?


Recap

- We have some dataset of (x,y)
- We have a **score function**: $s = f(x; W) \stackrel{\text{e.g.}}{=} Wx$
- We have a **loss function**:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right) \quad \text{Softmax}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + R(W) \quad \text{Full loss}$$



Recap


How do we find the best W ?

- We have some dataset of (x, y)
- We have a **score function**: $s = f(x; W) \stackrel{\text{e.g.}}{=} Wx$
- We have a **loss function**:

$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right) \quad \text{Softmax}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + R(W) \quad \text{Full loss}$$



Next time:
Optimization & backpropagation