## CSE 517 Natural Language Processing Winter 2019

Frame Semantics Yejin Choi

Some slides adapted from Martha Palmer, Chris Manning, Ray Mooney, Lluis Marquez ...

## Frames

#### Theory:

Frame Semantics (Fillmore 1968)

#### Resources:

- VerbNet(Kipper et al., 2000)
- FrameNet (Fillmore et al., 2004)
- PropBank (Palmer et al., 2005)
- NomBank
- Statistical Models:
  - Task: Semantic Role Labeling (SRL)



"Case for Case"

# **reddit** AMA (ask me anything): Michael Jordan

(Sep 2014)

- [–]CyberByte
- If you got a billion dollars to spend on a huge research project that you get to lead, what would you like to do?



- [–]michaelijordan
- I'd use the billion dollars to build a NASA-size program focusing on natural language processing (NLP), in all of its glory (semantics, pragmatics, etc).
- Intellectually I think that NLP is fascinating, allowing us to focus on highlystructured inference problems, on issues that go to the core of "what is thought" but remain eminently practical, and on a technology that surely would make the world a better place.

# **reddit** AMA (ask me anything): Michael Jordan

#### (Sep 2014)



- Although current deep learning research tends to claim to encompass NLP, I'm (1) much less convinced about the strength of the results, compared to the results in, say, vision; (2) much less convinced in the case of NLP than, say, vision, the way to go is to couple huge amounts of data with black-box learning architectures.
- I'd invest in some of the human-intensive labeling processes that one sees in projects like FrameNet and (gasp) projects like Cyc. I'd do so in the context of a full merger of "data" and "knowledge", where the representations used by the humans can be connected to data and the representations used by the learning systems are directly tied to linguistic structure. I'd do so in the context of clear concern with the usage of language (e.g., causal reasoning).

## Frames

#### Theory:

Frame Semantics (Fillmore 1968)

#### Resources:

- VerbNet(Kipper et al., 2000)
- FrameNet (Fillmore et al., 2004)
- PropBank (Palmer et al., 2005)
- NomBank
- Statistical Models:
  - Task: Semantic Role Labeling (SRL)



"Case for Case"

## Frame Semantics

- Frame: Semantic frames are schematic representations of situations involving various participants, propositions, and other conceptual roles.
- Frame Elements (FEs) include events, states, relations and entities.
- ✓ Frame: "The case for case" (Fillmore 1968)
  - 8k citations in Google Scholar.
- ✓ Script: knowledge about situations like eating in a restaurant.
  - "Scripts, Plans, Goals and Understanding: an Inquiry into Human Knowledge Structures" (Schank & Abelson 1977)
- ✓ Political Framings: George Lakoff's recent writings on the framing of political discourse.

### C4C: Capturing Generalizations over Related Predicates & Arguments

verb	BUYER	GOODS	SELLER	MONEY	PLACE
Buy	subject	object	from	for	at
Sell	to	object	subject	for	at
Cost	ndirect object	subject		object	at
Spend	subject	on		object	at

### Case Grammar -> Frames

- Valency: Predicates have arguments (optional & required)
  - Example: "give" requires 3 arguments:
    - Agent (A), Object (O), and Beneficiary (B)
    - Jones (A) gave money (O) to the school (B)
- Frames:
  - commercial transaction frame: Buy/Sell/Pay/Spend
  - Save <good thing> from <bad situation>
  - Risk <valued object> for <situation>|<purpose>|<beneficiary>|<motivation>
- Collocations & Typical predicate argument relations
  - Save whales from extinction (not vice versa)
  - Ready to risk everything for what he believes
- Representation Challenges: What matters for practical NLP?

## Thematic (Semantic) Roles

- AGENT the volitional causer of an event
  - The waiter spilled the soup
- EXPERIENCER the experiencer of an event
  - John has a headache
- FORCE the non-volitional causer of an event
  - The wind blows debris from the mall into our yards.
- THEME the participant most directly affected by an event
  - Only after Benjamin Franklin broke the ice ...
- RESULT the end product of an event
  - The French government has built a regulation-size baseball diamond ...

## Thematic (Semantic) Roles

- INSTRUMENT an instrument used in an event
  - He turned to poaching catfish, stunning them with a shocking device ...
- BENEFICIARY the beneficiary of an event
  - Whenever Ann makes hotel reservations for her boss ...
- SOURCE the origin of the object of a transfer event
  - I flew in from Boston
- GOAL the destination of an object of a transfer event
  - I drove to Portland
- Can we read semantic roles off from PCFG or dependency parse trees?

## Semantic roles **#**Grammatical roles

- Agent the volitional causer of an event
  - usually "subject", sometimes "prepositional argument", ...
- Theme the participant directly affected by an event
  - usually "object", sometimes "subject", ...
- Instrument an instrument (method) used in an event
  - usually prepositional phrase, but can also be a "subject"
- John broke the window.
- John broke the window with a rock.
- The rock broke the window.
- The window broke.
- The window was broken by John.

## **Ergative Verbs**

- Ergative verbs
  - subject when intransitive = direct object when transitive.
  - "it broke the window" (transitive)
  - "the window broke" (intransitive).
- Most verbs in English are not ergative (the subject role does not change whether transitive or not)
  - "He ate the soup" (transitive)
  - "He ate" (intransitive)
- Ergative verbs generally describe some sort of "changes" of states:
  - Verbs suggesting a change of state break, burst, form, heal, melt, tear, transform
  - Verbs of cooking bake, boil, cook, fry
  - Verbs of movement move, shake, sweep, turn, walk
  - Verbs involving vehicles *drive, fly, reverse, run, sail*

## FrameNet

## Frames

#### Theory:

Frame Semantics (Fillmore 1968)

#### Resources:

- VerbNet(Kipper et al., 2000)
- FrameNet (Fillmore et al., 2004)
- PropBank (Palmer et al., 2005)
- NomBank
- Statistical Models:
  - Task: Semantic Role Labeling (SRL)



"Case for Case"

#### Words in "change\_position\_on \_a\_scale" frame:

<b>VERBS:</b>	dwindle	move	soar	escalation	shift
advance	edge	mushroom	swell	explosion	tumble
climb	explode	plummet	swing	fall	
decline	fall	reach	triple	fluctuation	<b>ADVERBS:</b>
decrease	fluctuate	rise	tumble	gain	increasingly
diminish	gain	rocket		growth	
dip	grow	shift	NOUNS:	hike	
double	increase	skyrocket	decline	increase	
drop	jump	slide	decrease	rise	

- Frame := the set of words sharing a similar predicateargument relations
- Predicate can be a verb, noun, adjective, adverb
- The same word with multiple senses can belong to multiple frames

#### Roles in "change\_position\_on \_a\_scale" frame

Core Roles			
ATTRIBUTE	The ATTRIBUTE is a scalar property that the ITEM possesses.		
DIFFERENCE	The distance by which an ITEM changes its position on the		
	scale.		
FINAL_STATE	A description that presents the ITEM's state after the change in		
	the ATTRIBUTE's value as an independent predication.		
FINAL_VALUE	The position on the scale where the ITEM ends up.		
INITIAL_STATE	A description that presents the ITEM's state before the change		
	in the ATTRIBUTE's value as an independent predication.		
$INITIAL\_VALUE$	The initial position on the scale from which the ITEM moves		
	away.		
ITEM	The entity that has a position on the scale.		
VALUE_RANGE	A portion of the scale, typically identified by its end points,		
	along which the values of the ATTRIBUTE fluctuate.		
Some Non-Core Roles			
DURATION	The length of time over which the change takes place.		
SPEED	The rate of change of the VALUE.		
GROUP	The GROUP in which an ITEM changes the value of an		
	ATTRIBUTE in a specified way.		

# Example

		<ul> <li>[Oil] rose [in price] [by 2%].</li> </ul>
	ATTRIBUTE	
	DIFFERENCE	
	EINAL CTATE	<ul> <li>[It] has increased [to having them 1 day a month].</li> </ul>
	FINAL_STATE	
	FINAL_VALUE	<ul> <li>[Microsoft shares] fell [to 7 5/8].</li> </ul>
	INITIAL_STATE	
		[concertingidence] fell [by 50%] [emong men]
	INITIAL_VALUE	<ul> <li>[cancer incidence] fell [by 50%] [among men].</li> </ul>
	ITEM	a steady increase [from 9.5] [to 14.3] [in dividends].
	VALUE_RANGE	
		E [50/] [dividend] increase
-	DUDATION	a [5%] [dividend] increase
	DURATION	
	SPEED GROUP	
	GROUP	

## Find "Item" roles?

ATTRIBUTE	<ul> <li>[Oil] rose [in price] [by 2%].</li> </ul>
DIFFERENCE FINAL_STATE	<ul> <li>[It] has increased [to having them] [1 day a month].</li> </ul>
FINAL_VALUE INITIAL_STATE	<ul> <li>[Microsoft shares] fell [to 7 5/8].</li> </ul>
INITIAL_VALUE	<ul> <li>[cancer incidence] fell [by 50%] [among men].</li> </ul>
ITEM VALUE_RANGE	<ul> <li>a steady increase [from 9.5] [to 14.3] [in dividends].</li> </ul>
DURATION SPEED GROUP	<ul> <li>a [5%] [dividend] increase</li> </ul>

### Find "Difference" & "Final\_Value" roles?

	<ul> <li>[Oil] rose [in price] [by 2%].</li> </ul>
ATTRIBUTE	
DIFFERENCE	[It] has increased [to having them] [1 day a month].
FINAL_STATE	- [It] has increased [to having them] [1 day a month].
FINAL_VALUE	<ul> <li>[Microsoft shares] fell [to 7 5/8].</li> </ul>
INITIAL_STATE	
INITIAL_VALUE	[cancer incidence] fell [by 50%] [among men].
INTIAL_VALUE	
ITEM	a steady increase [from 9.5] [to 14.3] [in dividends].
VALUE_RANGE	
	a [5%] [dividend] increase
DURATION	
SPEED	
GROUP	

## FrameNet (2004)

- Project at UC Berkeley led by Chuck Fillmore for developing a database of frames, general semantic concepts with an associated set of roles.
- Roles are specific to frames, which are "invoked" by the predicate, which can be a verb, noun, adjective, adverb
  - JUDGEMENT frame
    - Invoked by: V: blame, praise, admire; N: fault, admiration
    - Roles: JUDGE, EVALUEE, and REASON
- Specific frames chosen, and then sentences that employed these frames selected from the British National Corpus and annotated by linguists for semantic roles.
- Initial version: 67 frames, 49,013 sentences, 99,232 role fillers

## PropBank (proposition bank)

### PropBank := proposition bank (2005)

- Project at Colorado led by Martha Palmer to add semantic roles to the Penn treebank.
- Proposition := verb + a set of roles
- Annotated over 1M words of Wall Street Journal text with existing gold-standard parse trees.
- Statistics:
  - 43,594 sentences
    99,265 propositions
  - 3,324 unique verbs 262,281 role assignments

## PropBank argument numbering

- Numbered roles, rather than named roles.
  - Arg0, Arg1, Arg2, Arg3, …
- Different numbering scheme for each verb sense.
- The general pattern of numbering is as follows.
- Arg0 = "Proto-Agent" (agent)
- Arg1 = "Proto-Patient" (direct object / theme / patient)
- Arg2 = indirect object (benefactive / instrument / attribute / end state)
- Arg3 = start point (benefactive / instrument / attribute)
- Arg4 = end point

### Different "frameset" for each verb sense

- Mary left the room.
- Mary left her daughter-in-law her pearls in her will.

Frameset **leave.01** "move away from": Arg0: entity leaving Arg1: place left

Frameset **leave.02** "give": Arg0: giver Arg1: thing given Arg2: beneficiary

## Semantic Role Labeling

## Semantic Role Labeling (Task)

- Shallow meaning representation beyond syntactic parse trees
- Question Answering
  - "Who" questions usually use Agents
  - "What" question usually use Patients
  - "How" and "with what" questions usually use Instruments
  - "Where" questions frequently use Sources and Destinations.
  - "For whom" questions usually use Beneficiaries
  - "To whom" questions usually use Destinations
- Machine Translation Generation
  - Semantic roles are usually expressed using particular, distinct syntactic constructions in different languages.
- Summarization, Information Extraction

SRL  $\stackrel{def}{=}$  detecting basic event structures such as *who* did *what* to *whom*, *when* and *where* [IE point of view]



Example from Lluis Marquez

SRL <sup>def</sup> = identify the arguments of a given verb and assign them semantic labels describing the *roles* they play in the predicate (i.e., identify predicate argument structures) [CL point of view]



Example from Lluis Marquez

#### Linguistic nature of the problem

Argument identification is strongly related to syntax



Role labeling is a semantic task

e.g., selectional preferences should play an important role

Example from Lluis Marquez

## SRL as Parse Node Classification

- Assume that a syntactic parse is available
- Treat problem as classifying parse-tree nodes.
- Can use any machine-learning classification method.
- Critical issue is engineering the right set of features for the classifier to use.

Color Code: not-a-role agent patient source destination instrument beneficiary

