

Computer Vision

CSE/ECE 576

Motion and Optical Flow

Linda Shapiro

Professor of Computer Science & Engineering
Professor of Electrical & Computer Engineering


We live in a moving world

- Perceiving, understanding and predicting motion is an important part of our daily lives



Motion and perceptual organization


- Even “impoverished” motion data can evoke a strong percept



G. Johansson, “Visual Perception of Biological Motion and a Model For Its Analysis”, *Perception and Psychophysics* 14, 201-211, 1973.


Motion and perceptual organization

- Even “impoverished” motion data can evoke a strong percept







G. Johansson, “Visual Perception of Biological Motion and a Model For Its Analysis”, *Perception and Psychophysics* 14, 201-211, 1973.

Seeing motion from a static picture?




More examples



How is this possible?

- The true mechanism is yet to be revealed
- FMRI data suggest that illusion is related to some component of eye movements
- We don't expect computer vision to "see" motion from these stimuli, yet



The cause of motion

- Three factors in imaging process
 - Light
 - Object
 - Camera
- Varying either of them causes motion
 - Static camera, moving objects (surveillance)
 - Moving camera, static scene (3D capture)
 - Moving camera, moving scene (sports, movie)
 - Static camera, moving objects, moving light (time lapse)



Motion scenarios (priors)



Static camera, moving scene



Moving camera, static scene



Moving camera, moving scene



Static camera, moving scene, moving light

We still don't touch these areas



How can we recover motion?

Recovering motion

- Feature-tracking
 - Extract visual features (corners, textured areas) and “track” them over multiple frames
- Optical flow
 - Recover image motion at each pixel from spatio-temporal image brightness variations (optical flow)

Two problems, one registration method

B. Lucas and T. Kanade. [An iterative image registration technique with an application to stereo vision](#). In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 674–679, 1981.

Feature tracking

- Challenges
 - Figure out which features can be tracked
 - Efficiently track across frames
 - Some points may change appearance over time (e.g., due to rotation, moving into shadows, etc.)
 - Drift: small errors can accumulate as appearance model is updated
 - Points may appear or disappear: need to be able to add/delete tracked points


What is Optical Flow?

What is Optical Flow?

Movement



What is Optical Flow?

Movement





What is Optical Flow?

Movement



What is Optical Flow?


Movement



What is Optical Flow?

Movement



Object



What is Optical Flow?

Movement



Pan



What is Optical Flow?

Movement

Forward



What is Optical Flow?


Movement



Why do we want Optical Flow?


Why do we want Optical Flow?

Motion Estimation



Why do we want Optical Flow?

Motion Estimation




Object Tracking



Why do we want Optical Flow?


Motion Estimation



Object Tracking



Visual Odometry



Estimating the position of a robot.

How do we find the
flow in an image?

Feature Matching

Previously: Features!

- Highly descriptive local regions
- Ways to describe those regions
- Useful for:
 - Matching
 - Recognition
 - Detection










Image gradients




Keypoint descriptor




Feature Matching



Feature Matching



Feature Matching



Feature Matching

Disadvantages:

Feature Matching

Disadvantages:

- Sparse!



Feature Matching

Disadvantages:

- Sparse!

- Feature alignment not exact

Feature Matching



Feature Matching

Disadvantages:

- Sparse!
- Feature alignment not exact
- Low accuracy

Feature Matching

Disadvantages:

- Sparse!
- Feature alignment not exact
- Low accuracy

Advantages:

Feature Matching

Disadvantages:

- Sparse!
- Feature alignment not exact
- Low accuracy

Advantages:

- Scale/rotation invariant
- *kinda* lighting invariant
- Can handle large movements

Feature Matching

Disadvantages:

- Sparse!
- Feature alignment not exact
- Low accuracy


Advantages:

- Scale/rotation invariant
- *kinda** lighting invariant
- Large movements


**Overall: Doesn't work
very well for Optical Flow**

What do we do
instead?

Feature tracking




$I(x,y,t)$



$I(x,y,t+1)$

- Given two subsequent frames, estimate the point translation
- Key assumptions of Lucas-Kanade Tracker
 - **Brightness constancy:** projection of the same point looks the same in every frame
 - **Small motion:** points do not move very far
 - **Spatial coherence:** points move like their neighbors

The brightness constancy constraint



- Brightness Constancy Equation:

$$I(x, y, t) = I(x + u, y + v, t + 1)$$

Take Taylor expansion of $I(x+u, y+v, t+1)$ at (x, y, t) to linearize the right side:

$$I(x + u, y + v, t + 1) \approx I(x, y, t) + \overset{\text{Image derivative along x}}{I_x} \cdot u + I_y \cdot v + \overset{\text{Difference over frames}}{I_t}$$

$$I_t(x, y) = I(x, y, t + 1) - I(x, y, t)$$

- Difference in intensity at the same pixel between one image and the previous one.

The brightness constancy constraint

$$I(x+u, y+v, t+1) \approx I(x, y, t) + I_x \cdot u + I_y \cdot v + I_t$$

$$I(x+u, y+v, t+1) - I(x, y, t) = +I_x \cdot u + I_y \cdot v + I_t$$

So: $I_x \cdot u + I_y \cdot v + I_t \approx 0$

$$\rightarrow \nabla I \cdot [u \ v]^T + I_t = 0$$

The brightness constancy constraint

Can we use this equation to recover image motion (u,v) at each pixel?

$$\nabla I \cdot [u \ v]^T + I_t = 0$$

- How many equations and unknowns per pixel?
 - One equation (this is a scalar equation!), two unknowns (u,v)

The component of the motion perpendicular to the gradient (i.e., **parallel to the edge**) cannot be measured

Solving the ambiguity...

B. Lucas and T. Kanade. An iterative image registration technique with an application to stereo vision. In *Proceedings of the International Joint Conference on Artificial Intelligence*, pp. 674–679, 1981.

- How to get more equations for a pixel?
- **Spatial coherence constraint**
- Assume the pixel's neighbors have the same (u,v)
 - If we use a 5x5 window, that gives us 25 equations per pixel

$$0 = I_t(\mathbf{p}_i) + \nabla I(\mathbf{p}_i) \cdot [u \ v]$$

$$\begin{bmatrix} I_x(\mathbf{p}_1) & I_y(\mathbf{p}_1) \\ I_x(\mathbf{p}_2) & I_y(\mathbf{p}_2) \\ \vdots & \vdots \\ I_x(\mathbf{p}_{25}) & I_y(\mathbf{p}_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(\mathbf{p}_1) \\ I_t(\mathbf{p}_2) \\ \vdots \\ I_t(\mathbf{p}_{25}) \end{bmatrix}$$

Solving the ambiguity...

- Least squares problem:

$$\begin{bmatrix} I_x(p_1) & I_y(p_1) \\ I_x(p_2) & I_y(p_2) \\ \vdots & \vdots \\ I_x(p_{25}) & I_y(p_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(p_1) \\ I_t(p_2) \\ \vdots \\ I_t(p_{25}) \end{bmatrix} \quad \begin{matrix} A & d = b \\ 25 \times 2 & 2 \times 1 & 25 \times 1 \end{matrix}$$

Matching patches across images

- Overconstrained linear system

$$\begin{bmatrix} I_x(p_1) & I_y(p_1) \\ I_x(p_2) & I_y(p_2) \\ \vdots & \vdots \\ I_x(p_{25}) & I_y(p_{25}) \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} I_t(p_1) \\ I_t(p_2) \\ \vdots \\ I_t(p_{25}) \end{bmatrix} \quad \begin{matrix} A & d = b \\ 25 \times 2 & 2 \times 1 & 25 \times 1 \end{matrix}$$

Least squares solution for d given by $(A^T A) d = A^T b$

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

$A^T A$ $A^T b$

The summations are over all pixels in the $K \times K$ window

$$d = (A^T A)^{-1} A^T b$$

Conditions for solvability

Optimal (u, v) satisfies Lucas-Kanade equation

$$\begin{bmatrix} \sum I_x I_x & \sum I_x I_y \\ \sum I_x I_y & \sum I_y I_y \end{bmatrix} \begin{bmatrix} u \\ v \end{bmatrix} = - \begin{bmatrix} \sum I_x I_t \\ \sum I_y I_t \end{bmatrix}$$

$A^T A$ $A^T b$


When is this solvable? I.e., what are good points to track?

- $A^T A$ should be invertible
- $A^T A$ should not be too small due to noise
 - eigenvalues λ_1 and λ_2 of $A^T A$ should not be too small
- $A^T A$ should be well-conditioned
 - λ_1 / λ_2 should not be too large (λ_1 = larger eigenvalue)

Does this remind you of anything?

Criteria for Harris corner detector

Aperture problem





Corners

Lines

Flat regions




Edge



$$\sum \nabla I (\nabla I)^T$$

- large gradients, all the same
- large λ_1 , small λ_2



Low Texture Region



$$\sum \nabla I (\nabla I)^T$$

- gradients have small magnitude
- small λ_1 , small λ_2

High Texture Region



$$\sum \nabla I (\nabla I)^T$$

- gradients are different, large magnitudes
- large λ_1 , large λ_2

Errors in Lukas-Kanade

- What are the potential causes of errors in this procedure?
 - Suppose $A^T A$ is easily invertible
 - Suppose there is not much noise in the image

When our assumptions are violated




- Brightness constancy is **not** satisfied
- The motion is **not** small
- A point does **not** move like its neighbors
 - window size is too large
 - what is the ideal window size?

Revisiting the small motion assumption




- Is this motion small enough?
 - Probably not—it's much larger than one pixel (2^{nd} order terms dominate)
 - How might we solve this problem?

Reduce the resolution!



Coarse-to-fine optical flow estimation



A Few Details

- Top Level


- Apply L-K to get a flow field representing the flow from the first frame to the second frame.
- Apply this flow field to warp the first frame toward the second frame.
- Rerun L-K on the new warped image to get a flow field from it to the second frame.
- Repeat till convergence.

- Next Level

- Upsample the flow field to the next level as the first guess of the flow at that level.
- Apply this flow field to warp the first frame toward the second frame.
- Rerun L-K and warping till convergence as above.

- Etc.

Coarse-to-fine optical flow estimation




$u=1.25$ pixels

$u=2.5$ pixels



$u=5$ pixels

$u=10$ pixels



The Flower Garden Video


What should the
optical flow be?




Optical Flow Results

Lucas-Kanade
without pyramids


Fails in areas of large
motion



Optical Flow Results



Lucas-Kanade with Pyramids



Flow quality evaluation




Flow quality evaluation




Flow quality evaluation

- Middlebury flow page
 - <http://vision.middlebury.edu/flow/>




Ground Truth




Flow quality evaluation


- Middlebury flow page
 - <http://vision.middlebury.edu/flow/>



Lucas-Kanade flow



Ground Truth




Flow quality evaluation


- Middlebury flow page
 - <http://vision.middlebury.edu/flow/>



Best-in-class alg



Ground Truth




Video stabilization



Video denoising

Original



Denoised



Video super resolution

Low-Res



Robust Visual Motion Analysis: Piecewise-Smooth Optical Flow

Ming Ye

Electrical Engineering
University of Washington

Estimating Piecewise-Smooth Optical Flow with Global Matching and Graduated Optimization

Problem Statement:

*Assuming only **brightness conservation** and **piecewise-smooth motion**, find the optical flow to best describe the intensity change in three frames.*

Approach: Matching-Based Global Optimization

- Step 1. Robust local gradient-based method for high-quality initial flow estimate.

Uses least median of squares instead of regular least squares.

- Step 2. Global gradient-based method to improve the flow-field coherence.

Minimizes a global energy function $E = \sum (E_B(V_i) + E_S(V_i))$ where E_B is the brightness difference and E_S is the smoothness at flow vector V_i

- Step 3. Global matching that minimizes energy by a greedy approach.


Visits each pixel and updates it to be consistent with neighbors, iteratively.

TT: Translating Tree



150x150 (Barron 94)

	$e_{\angle} (^{\circ})$	$e_{ \bullet } (\text{pix})$	$\bar{e} (\text{pix})$
BA	2.60	0.128	0.0724
S3	0.248	0.0167	0.00984




e: error in pixels, cdf: cumulative distribution function for all pixels

DT: Diverging Tree




150x150 (Barron 94)

	$e_{\angle}(^{\circ})$	$e_{ \bullet }(\text{pix})$	$\bar{e}(\text{pix})$
BA	6.36	0.182	0.114
S3	2.60	0.0813	0.0507




YOS: Yosemite Fly-Through



316x252 (Barron, cloud excluded)

	$e_{\angle} (^{\circ})$	$e_{ \bullet } (\text{pix})$	$\bar{e} (\text{pix})$
BA	2.71	0.185	0.118
S3	1.92	0.120	0.0776



TAXI: Hamburg Taxi




256x190, (Barron 94)
max speed 3.0 pix/frame




LMS



BA



Ours



Error map




Smoothness error


Traffic



512x512
(Nagel)
max speed:
6.0 pix/frame




BA



Ours



Error map



Smoothness error

FG: Flower Garden



360x240 (Black)

Max speed: 7pix/frame




BA




LMS



Ours



Error map



Smoothness error

Representing Moving Images with Layers





J. Y. Wang and E. H. Adelson

MIT Media Lab

Goal

- Represent moving images with sets of overlapping layers
- Layers are ordered in depth and occlude each other
- Velocity maps indicate how the layers are to be warped over time


Simple Domain: Gesture Recognition




More Complex: What are the layers?




Motion Analysis Example




(a) velocity estimates



(b) velocity smoothing



(c) regularization



(d) robust estimation

2 separate layers
shown as 2 affine
models (lines);

The gaps show
the occlusion.

Motion Estimation Steps

1. Conventional optical flow algorithm and representation (uses multi-scale, coarse-to-fine Lucas-Kanade approach).
2. From the optical flow representation, determine a set of affine motions. Segment into regions with an affine motion within each region.

Results




Figure 11: (a) The optic flow from multi-scale gradient method. (b) Segmentation obtained by clustering optic flow into affine motion regions. (c) Segmentation from consistency checking by image warping. Representing moving images with layers.




Figure 12: The layers corresponding to the tree, the flower bed, and the house shown in figures (a-c), respectively. The affine flow field for each layer is superimposed.

Results



(a)



(b)



(c)

Figure 13: Frames 0, 15, and 30 as reconstructed from the layered representation shown in figures (a-c), respectively.



(a)



(b)



(c)

Figure 14: The sequence reconstructed without the tree layer shown in figures (a-c), respectively.

Results




Figure 15: Frames 0, 15 and 30, of MPEG Calendar sequence shown in figures (a-c), respectively.




Figure 16: The layers corresponding to the ball, the train, and the background shown in figures (a-c), respectively.

Summary

- Major contributions from Lucas, Tomasi, Kanade
 - Tracking feature points
 - Optical flow
 - Stereo
 - Structure from motion
- Key ideas
 - By assuming brightness constancy, truncated Taylor expansion leads to simple and fast patch matching across frames
 - Coarse-to-fine registration
 - Global approach by former EE student Ming Ye
 - Motion layers methodology by Wang and Adelson

Homework 6

Optical Flow

WILL NOT BE ASSIGNED

Motion

