



US007193440B1

(12) **United States Patent**
Schmit et al.

(10) **Patent No.:** **US 7,193,440 B1**
(45) **Date of Patent:** **Mar. 20, 2007**

(54) **CONFIGURABLE CIRCUITS, IC'S, AND SYSTEMS**

(76) Inventors: **Herman Schmit**, 2919 Simkins Ct., Palo Alto, CA (US) 94303; **Michael Butts**, 2734 NE. 49th Ave., Portland, OR (US) 97213; **Brad L. Hutchings**, 44825 Lynx Dr., Fremont, CA (US) 94539; **Steven Teig**, 935 College Ave., Menlo Park, CA (US) 94025

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/882,946**

(22) Filed: **Jun. 30, 2004**

Related U.S. Application Data

(60) Provisional application No. 60/560,747, filed on Feb. 14, 2004.

(51) **Int. Cl.**

H01L 29/10 (2006.01)

H01L 29/40 (2006.01)

H01L 29/06 (2006.01)

H01L 29/08 (2006.01)

H01L 51/00 (2006.01)

(52) **U.S. Cl.** **326/47**; 326/37; 326/38; 326/39; 326/40; 326/41; 716/16

(58) **Field of Classification Search** 326/37-41, 326/47; 716/16

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,873,459 A 10/1989 El Gamal et al.
5,349,250 A 9/1994 New
5,357,153 A 10/1994 Chiang et al.

5,365,125 A 11/1994 Goetting et al.
5,521,835 A 5/1996 Trimberger
5,552,721 A 9/1996 Gould
5,610,829 A 3/1997 Trimberger
5,631,578 A 5/1997 Clinton et al.
5,646,544 A 7/1997 Iadanza
5,659,484 A 8/1997 Bennett et al.
5,692,147 A 11/1997 Larsen et al.
5,694,057 A 12/1997 Gould
5,719,889 A 2/1998 Iadanza
5,732,246 A 3/1998 Gould et al.
5,737,235 A 4/1998 Kean et al.

(Continued)

OTHER PUBLICATIONS

"§3 Programmable Logic Devices," *Digital System Design*, 2001, pp. 3.1-3.28.

(Continued)

Primary Examiner—Rexford Barnie


Assistant Examiner—Dylan White

(74) *Attorney, Agent, or Firm*—Stattler Johansen & Adeli LLP

(57) **ABSTRACT**

Some embodiments of the invention provide a configurable integrated circuit (IC). The configurable IC includes first and second interconnect circuits. The first interconnect circuit has a set of input terminals, a set of output terminals, and several connection schemes for communicatively coupling the input terminal set to the output terminal set. During the operation of the IC, the second connection circuit supplies sets of configuration data to the first interconnect circuit at a particular rate for at least a particular time period. At least two supplied configuration data sets are different and configure the first interconnect circuit to use two different connection schemes that differently couple the input and output terminal sets.

23 Claims, 21 Drawing Sheets



U.S. PATENT DOCUMENTS

- 5,745,422 A 4/1998 Iadanza
 5,745,734 A 4/1998 Craft et al.
 5,764,954 A 6/1998 Fuller et al.
 5,777,360 A 7/1998 Rostoker et al.
 5,802,003 A 9/1998 Iadanza et al.
 5,815,726 A * 9/1998 Cliff 712/1
 5,889,411 A 3/1999 Chaudhary
 5,914,616 A 6/1999 Young et al.
 5,914,906 A 6/1999 Iadanza et al.
 5,982,655 A * 11/1999 Doyle 365/63
 6,002,991 A 12/1999 Conn, Jr.
 6,023,421 A 2/2000 Clinton et al.
 6,038,192 A 3/2000 Clinton et al.
 6,044,031 A 3/2000 Iadanza et al.
 6,054,873 A 4/2000 Laramie
 6,069,490 A 5/2000 Ochotta et al.
 6,075,745 A 6/2000 Gould et al.
 6,086,631 A 7/2000 Chaudhary et al.
 6,091,263 A 7/2000 New et al.
 6,091,645 A 7/2000 Iadanza
 6,107,821 A 8/2000 Kelem et al.
 6,110,223 A 8/2000 Southgate et al.
 6,118,707 A 9/2000 Gould et al.
 6,130,854 A 10/2000 Gould et al.
 6,140,839 A 10/2000 Kaviani et al.
 6,150,838 A 11/2000 Wittig et al.
 6,175,247 B1 1/2001 Scalera et al.
 6,184,707 B1 * 2/2001 Norman et al. 326/39
 6,233,191 B1 5/2001 Gould et al.
 6,292,019 B1 * 9/2001 New et al. 326/41
 6,381,732 B1 4/2002 Burnham et al.
 6,487,709 B1 11/2002 Keller et al.
 6,490,707 B1 12/2002 Baxter
 6,515,505 B1 * 2/2003 Rees 326/38
 6,515,509 B1 2/2003 Baxter
 6,526,559 B2 2/2003 Schiefele et al.
 6,529,040 B1 * 3/2003 Carberry et al. 326/40
 6,545,501 B1 4/2003 Bailis et al.
 6,593,771 B2 7/2003 Bailis et al.
 6,601,227 B1 7/2003 Trimberger
 6,603,330 B1 8/2003 Snyder
 6,629,308 B1 9/2003 Baxter
 6,636,070 B1 10/2003 Altaf
 6,642,744 B2 11/2003 Or-Bach et al.
 6,667,635 B1 12/2003 Pi et al.
 6,668,361 B2 12/2003 Bailis et al.
 6,675,309 B1 1/2004 Baxter
 6,714,041 B1 3/2004 Darling et al.
 6,806,730 B2 10/2004 Bailis et al.
 6,831,479 B2 12/2004 Lo
 6,838,902 B1 1/2005 Elftmann et al.
 6,956,399 B1 * 10/2005 Bauer 326/41
 6,992,505 B1 1/2006 Zhou
 6,998,872 B1 * 2/2006 Chirania et al. 326/40
 2002/0008541 A1 1/2002 Young et al.
 2002/0125914 A1 9/2002 Kim
 2002/0163357 A1 11/2002 Ting
 2003/0042931 A1 3/2003 Ting
 2003/0080777 A1 5/2003 Baxter
 2003/0110430 A1 6/2003 Bailis et al.
 2004/0196066 A1 10/2004 Ting
 2006/0158217 A1 * 7/2006 Madurawe 326/39

OTHER PUBLICATIONS

- IBM, "Cell Broadband Engine Architecture, Version 1.0," Aug. 8, 2005, pp. 1-319, USA.
 U.S. Appl. No. 10/882,583, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,276, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,486, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/882,839, filed Jun. 30, 2004, Schmit.

- U.S. Appl. No. 10/882,579, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,213, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,051, filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/882,583 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,276 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,486 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/882,839 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/882,579 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,213 (office action), filed Jun. 30, 2004, Schmit.
 U.S. Appl. No. 10/883,051 (office action), filed Jun. 30, 2004, Schmit.
 "§3 Programmable Logic Devices," *Digital System Design*, 2001, pp. 3.1-3.28, month n/a.
 "Design for Low Power in Actel Antifuse FPGAs", Actel Application Note, 2000 Actel Corporation, Sep. 2000, pp. 1-8.
 "The Xilinx Virtex Series FPGA," Jan. 22, 2001, slides 1-22.
 "Unifying Sequential and Spatial Computing with a Single Instruction Set Architecture," *ISCA '04*, 2004, ACM, Munchen, Oberbayem, Germany, month n/a.
 Agrawal, O., et al., "An Innovative, Segmented High Performance FPGA Family with Variable-Grain-Architecture and Wide-gating Functions," *FPGA 99*, 1999, pp. 17-26, ACM, Monterey, CA, USA, month n/a.
 Ahmed, E., et al., "The Effect of LUT and Cluster Size on Deep-Submicron FPGA Performance and Density," *FPGA 2000*, 2000, ACM, Monterey, CA, USA, month n/a.
 Alpert, C.J., et al., "Quadratic Placement Revisited," *Design Automation Conference*, '97, Jun. 1997, ACM.
 Altera Corp., "6. DSP Blocks in Stratix II Devices," *SII52006-1.0*, Feb. 2004, pp. 1-32.
 Altera, "Stratix II DSP Performance," *White Paper*, Feb. 2004, pp. 1-9, ver. 1.0, Altera Corporation, San Jose, CA.
 Andraka Consulting Group, Inc., "Multiplication in FGAs," <http://www.andraka.com/multipli.htm>, Jan. 25, 2006, pp. 1-7.
 Backus, J., "Can Programming be Liberated from the Von Neumann Style? A Functional Style and its Algebra of Programs," *Communications of the ACM*, Aug. 1978, pp. 613-641, vol. 21, No. 8, ACM.
 Barker, R., "QuickSilver ACM SilverStream Design Methodology with the Inspire SDK Tool Set," *A Technology Application Whitepaper*, 2004, pp. 1-8, QuickSilver Technology, Inc., San Jose, California, month n/a.
 Brand, D., et al., "Minimization of AND-EXOR Expressions Using Rewrite Rules," *IEEE Transactions on Computers*, May 1993, pp. 568-576, IEEE.
 Butts, M., "Future Directions of Dynamically Reprogrammable Systems," *IEEE 1995 Custom Integrated Circuits Conference*, 1995, pp. 487-494, IEEE, month n/a.
 Camposano, R., "The Growing Semiconductor Zoo: ASICs, CSSP, ASSP, ASIP, Structured Arrays, FPGAs, Processor Arrays, Platforms . . . and Other Animalia," 2003, pp. 1-62, Synopsys, Inc, month n/a.
 Caspi, E., et al., "A Streaming Multi-Threaded Model," *MSP-3*, Dec. 2, 2001, pp. 1-23.
 Caspi, E., et al., "Stream Computations Organized for Reconfigurable Execution (SCORE): Introduction and Tutorial," Aug. 25, 2000, pp. 1-31, Version 1.0.
 Chiricescu, S., et al., "Morphable Multipliers," *FPL 2002, LNCS 2438*, 2002, pp. 647-656, Springer-Verlag Berlin Heidelberg, month n/a.
 Ciemat, J.V., et al., "Annealing Placement by Thermodynamic Combinatorial Optimization," *ACM Transactions on Design Automation of Electronic Systems*, Jul. 2004, pp. 310-332, vol. 9, No. 3, ACM, New York, NY.
 Compton, K., et al., "Reconfigurable Computing: A Survey of Systems and Software," *ACM Computing Surveys*, Jun. 2002, pp. 171-210, vol. 34, No. 2, ACM, New York, NY.

- Cong, J., et al., "Combinational Logic Synthesis for LUT Based Field Programmable Gate Arrays," *ACM Transactions on Design Automation of Electronic Systems*, Apr. 1996, pp. 145-204, vol. 1, No. 2, ACM, Inc.
- Cong, J., et al., "Large-Scale Circuit Placement," *ACM Transactions on Design Automation of Electronic Systems*, Apr. 2005, pp. 389-430, vol. 10, No. 2, ACM Inc., Broadway, New York, NY.
- Davare, A., et al., "The Best of Both Worlds: The Efficient Asynchronous Implementation of Synchronous Specifications," *DAC '04*, Jun. 7-11, 2004, ACM, San Diego, California, USA.
- Dehon, A., "Balancing Interconnect and Computation in a Reconfigurable Computing Array (or, why don't you really want 100% LUT utilization)," *Proceedings of the International Symposium on Field Programmable Gate Arrays*, Feb. 1999, pp. 125-134.
- Dehon, A., "DPGA Utilization and Application," Feb. 11-13, 2006.
- Dehon, A., "Dynamically Programmable Gate Arrays: A Step Toward Increased Computational Density," *Proceedings of the Fourth Canadian Workshop on Field-Programmable Devices*, May 1996, pp. 47-54.
- Dehon, A., "Reconfigurable Architectures for General-Purpose Computing," *A.I. Technical Report No. 1586*, Oct. 1996, pp. i-353.
- Dehon, A., "The Density Advantage of Configurable Computing," Apr. 2000, pp. 41-49, IEEE.
- Dehon, A., "Transit Note #121: Notes on Programmable Interconnect," *M.I.T. Transit Project*, Feb. 1995, pp. 1-13.
- Dehon, A., et al., "Design Patterns for Reconfigurable Computing," *Proceedings of the IEEE Symposium on Field-Programmable Custom Computing Machines*, Apr. 2004.
- Dehon, A., et al., "DPGA-Coupled Microprocessors: Commodity ICs for the Early 21st Century," *FCCM '94-IEEE Workshop on FPGAs for Custom Computing Machines*, Apr. 10-13, year n/a.
- Dehon, A., et al., "Reconfigurable Computing: What, Why, and Implications for Design Automation," *DAC 99*, New Orleans, Louisiana, 1999, ACM, month n/a.
- Gayasen, A., et al., "Reducing Leakage Energy in FPGAs Using Region-Constrained Placement," *FPGA '04*, Feb. 22-24, 2004, pp. 51-58, ACM, Monterey, California, USA.
- George, V., "Low Energy Field-Programmable Gate Array," *A Dissertation Submitted in Partial Satisfaction of the Requirements for the Degree of Doctor of Philosophy in Engineering-Electrical Engineering and Computer Sciences in the Graduate Division of the University of California, Berkeley*, Fall 2000, pp. 1-190, month n/a.
- Goldstein, S.C., et al., "PipeRench: A Reconfigurable Architecture and Compiler," 2000, pp. 70-77, IEEE, Apr.
- Heidari, G., et al., "Introducing a Paradigm Shift in the Design and Implementation of Wireless Devices," *A Wireless Devices Whitepaper*, Apr. 28, 2004 but © 2003, pp. 1-10, QuickSilver Technology, Inc., San Jose, California.
- Hofstee, H.P., "Cell Broadband Engine Architecture from 20,000 Feet," Aug. 24, 2005, pp. 1-5.
- Huang, A.S., "Tao: An Architecturally Balanced Reconfigurable Hardware Processor," *Submitted to the Dept. of Electrical Engineering and Computer Science in Partial Fulfillment of the Requirements for the Degrees of Bachelor of Science in Electrical Science and Engineering and Master of Engineering in Electrical Engineering and Computer Science at the Massachusetts Institute of Technology*, May 23, 1997, pp. 1-109.
- IBM, "Cell Broadband Engine Architecture, Version 1.0," Aug. 8, 2005, pp. 1-319, USA.
- IBM, "SPU Application Binary Interface Specification, Version 1.3," *CBEA JSRE Series*, Aug. 1, 2005, pp. iv-26, USA.
- IBM, "SPU Assembly Language Specification, Version 1.2," *CBEA JSRE Series*, Aug. 1, 2005, pp. iii-22, USA.
- IBM, "SPU C/C++ Language Extensions, Version 2.0" *CBEA JSRE Series*, Aug. 1, 2005, pp. iv-84, USA.
- IBM, "Synergistic Processor Unit Instruction Set Architecture, Version 1.0," Aug. 1, 2005, pp. 1-257, USA.
- Kocan, F., et al., "Logic Modules with Shared SRAM Tables for Field-Programmable Gate Arrays," *FPL 2004*, 2004, pp. 289-300, Springer-Verlag, Berlin Heidelberg, month n/a.
- Lemieux, G., et al., "Generating Highly-Routable Sparse Crossbars for PLDs," *FPGA 2000*, 2000, ACM, Monterey, California, USA, month n/a.
- Lemieux, G., et al., "Using Sparse Crossbars within LUT Clusters," *FPGA 2001*, Feb. 11-13, 2001, ACM, Monterey, CA.
- Lin, J.Y., et al., "Placement-Driven Technology Mapping for LUT-Based FPGAs," *FPGA '03*, Feb. 23-25, 2003, pp. 121-126, ACM, Monterey, California, USA.
- Ling, A., "The Search for the Optimal FPGA Logic Block," 2001, ACM, month n/a.
- M2000, "FlexEOS Embedded FPGA Cores," 2003, M2000, month n/a.
- Markovskiy, Y., et al., "Analysis of Quasi-Static Scheduling Techniques in a Virtualized Reconfigurable Machine," *FPGA '02*, Feb. 24-26, 2002, ACM, Monterey, California, USA.
- Master, P., "The Next Big Leap in Reconfigurable Systems," *A Technology Vision Whitepaper*, Apr. 28, 2004 but © 2003, pp. 1-8, QuickSilver Technology, Inc., San Jose, California.
- Mathstar, Inc., "MathStar FPOA Architecture: A New Approach to High Throughput, Scalable, and Reprogrammable Design," *Technology Overview*, 2003, MathStar, Inc., month n/a.
- Mirsky, E., et al., "MATRIX: A Reconfigurable Computing Architecture with Configurable Instruction Distribution and Deployable Resources," *Proceedings of the IEEE Workshop on FPGAs for Custom Computing Machines*, Apr. 1996.
- Mirsky, E., et al., "MATRIX: A Reconfigurable Computing Device with Configurable Instruction Distribution and Deployable Resources," *Hot Chips Symposium 1997*, 1997, month n/a.
- Mishchenko, A., et al., "A New Enhanced Constructive Decomposition and Mapping Algorithm," *DAC 2003*, Jun. 2-6, 2003, pp. 143-148, ACM, Anaheim, California, USA.
- Morris, K., "Lattice Launches XP: Non-Volatility at the Forefront of FPGA," *FPGA and Programmable Logic Journal*, 2005, pp. 1-5, Techfocus Media, Inc., Mar.
- Morris, K., "Rationalizing Reconfigurability: The Importance of Being Programmable," *FPGA and Structured ASIC Journal*, Sep. 27, 2005.
- Nelson, B.E., "Reconfigurable Computing: An Introduction and Overview," Sep. 23, 1998, pp. 1-43.
- Ochotta, E.S., et al., "A Novel Predictable Segmented FPGA Routing Architecture," *FPGA 98*, 1998, pp. 3-11, ACM, Monterey, CA, USA, month n/a.
- Ohkura, J., et al., "Dataflow in the Adaptive Computing Machine (ACM)," *A Technology Application Whitepaper*, Apr. 28, 2004 but © 2003, pp. 1-9, QuickSilver Technology, Inc., San Jose, California.
- Parhami, B., "Part IV: Low-Diameter Architectures," *ECE 254B: Advanced Computer Architecture: Parallel Processing*, UCSB, Spring 2005, slides 1-93, Behrooz Parhami, Santa Barbara, CA., month N/A.
- Perissakis, S., et al., "Embedded DRAM for a Reconfigurable Array," *Proceedings of the 1999 Symposium on VLSI Circuits*, Jun. 1999.
- Plunkett, B., "In Search of the SDR Holy Grail," *A Technology Application Whitepaper*, Apr. 28, 2004 but © 2003, pp. 1-7, QuickSilver Technology, Inc., San Jose, California.
- Plunkett, B., et al., "Adapt2400 ACM Architecture Overview," *A Technology Whitepaper*, 2004, pp. 1-9, QuickSilver Technology, Inc., month n/a.
- QuickSilver Technology, Inc., "Adapt2000 ACM System Platform," Apr. 2004, pp. 1-39, QuickSilver Technology, Inc., San Jose, California.
- QuickSilver Technology, Inc., "InSpire SDK Tool Set," *Product Brief*, 2004, QuickSilver Technology, Inc., San Jose, California, month n/a.
- QuickSilver Technology, Inc., "QS2412 Adaptive Computing Machine," *Product Brief*, 2004, QuickSilver Technology, Inc., San Jose, California, month n/a.
- Rahman, A., et al., "Wiring Requirement and Three-Dimensional Integration Technology for Field Programmable Gate Arrays," *IEEE Transactions on Very Large Scale Integration (VLSI) Systems*, Feb. 2003, pp. 44-54, vol. 11, No. 1, IEEE.
- Ronsse, M., et al., "Record/Replay for Nondeterministic Program Executions," *Communications of the ACM*, Sep. 2003, pp. 62-67, vol. 46, No. 9.

- Sambhwani, S., et al., "Implementing W-CDMA Transceiver Structure on an Adaptive Computing Platform," *A Technology Application Whitepaper*, Apr. 28, 2004 but © 2003, pp. 1-12, QuickSilver Technology, Inc., San Jose, California.
- Schmit, H., "Extra-Dimensional Island-Style FPGAs," 2003, month n/a.
- Schmit, H., et al., "FPGA Switch Block Layout and Evaluation," *FPGA '02*, Feb. 24-26, 2002, ACM, Monterey, California, USA.
- Scholl, C., "Mutli-output Functional Decomposition with Exploitation of Don't Cares," May 19-21, 1997??.
- Singh, A., et al., "Interconnect Pipelining in a Throughput-Intensive FPGA Architecture," *FPGA 2001*, Feb. 11-13, 2001, pp. 153-160, ACM, Monterey, CA, USA.
- Singh, A., et al., "PITIA: An FPGA for Throughput-Intensive Applications," *IEEE Transactions on Very Large Scale Integration (VLSI) Systems*, Jun. 2003, pp. 354-363, vol. 11, No. 3, IEEE.
- Snider, G., "Performance-Constrained Pipelining of Software Loops onto Reconfigurable Hardware," *FPGA '02*, Feb. 24-26, 2002, pp. 177-186, ACM, Monterey, California, USA.
- Tau, E., et al., "A First Generation DPGA Implementation," *Proceedings of the Third Canadian Workshop on Field-Programmable Devices*, May 1995, pp. 138-143.
- Tau, E., et al., "Transit Note #114: A First Generation DPGA Implementation," *M.I.T. Transit Project*, Jan. 1995, pp. 1-8.
- Teifel, J., et al., "Highly Pipelined Asynchronous FPGAs" *FPGA '04*, ACM, Monterey, California, USA, 2004 month n/a.
- Tom, M., et al., "Logic Block Clustering of Large Designs for Channel-Width Constrained FPGAs," *DAC 2005*, Jun. 13-17, 2005, pp. 726-731, ACM, Anaheim, California, USA.
- Trimberger, S., "Effects of FPGA Architecture on FPGA Routing," *32nd ACM/IEEE Design Automation Conference*, 1995, ACM, month n/a.
- Tsu, W., et al., "HSRA: High-Speed, Hierarchical Synchronous Reconfigurable Array," *Proceedings of the International Symposium on Field Programmable Gate Arrays*, Feb. 1999, pp. 69-78.
- Wawrzynek, J., "EECS150-Digital Design: Lecture 5—Field Programmable Gate Arrays (FPGAs)," Feb. 4, 2002, pp. 1-20.
- Weaver, N., et al., "The SFRA: A Corner-Turn FPGA Architecture," *FPGA '04*, Feb. 22-24, 2004, ACM, Monterey, California, USA.
- Wegener, I., "The Complexity of Boolean Functions," *Wiley-Teubner Series in Computer Science*, 1987, John Wiley & Sons Ltd. and B.G. Teubner, Stuttgart, New York, month n/a.
- Wilton, S.J.E., "Memory-to-Memory Connection Structures in FPGAs with Embedded Memory Arrays," *FPGA 97*, 1997, pp. 10-16, ACM, Monterey, California, USA, month n/a.
- Xilinx, Inc., "Virtex-4 Family Overview," *Advance Product Specification*, Sep. 10, 2004, pp. 21-30, v1.1, Xilinx, Inc.
- Xing, S., et al., "FPGA Adders: Performance Evaluation and Optimal Design," *IEEE Design & Test of Computers*, Jan.-Mar. 1998, pp. 24-29, IEEE.
- Zhang, M., et al., "Design of Soft Error Tolerant Logic Circuits," Ming Zhang, *University of Illinois at Urbana-Champaign*, 2005, 2005, pp. 1-23, month n/a.
- Zuchowski, P.S., "A Hybrid ASIC and FPGA Architecture," 2002, IEEE, month N/A.

* cited by examiner




Figure 1
Prior Art




Figure 2
Prior Art




Figure 3
Prior Art




Figure 4
Prior Art






Figure 7

*Figure 5**Figure 6*




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19






Figure 20







Figure 23

*Figure 24*




Figure 25




Figure 26




Figure 27







Figure 28

*Figure 29*

*Figure 30**Figure 32*




Figure 31




Figure 33

1

CONFIGURABLE CIRCUITS, IC'S, AND SYSTEMS

CLAIM OF BENEFIT TO PRIOR APPLICATION

This patent application claims benefit of an earlier-filed U.S. Provisional Patent Application entitled "Configurable Integrated Circuits with Programmable Vias," filed on Feb. 14, 2004, and having Ser. No. 60/560,747.

CROSS REFERENCE TO RELATED APPLICATIONS

This Application is related to the following applications: U.S. patent application Ser. No. 10/882,583 filed on Jun. 30, 2004; U.S. patent application Ser. No. 10/883,276 filed on Jun. 30, 2004; U.S. patent application Ser. No. 10/883,486 filed on Jun. 30, 2004; U.S. patent application Ser. No. 10/882,839 filed on Jun. 30, 2004; U.S. patent application Ser. No. 10/882,579 filed on Jun. 30, 2004; U.S. patent application Ser. No. 10/883,213 filed on Jun. 30, 2004; and U.S. patent application Ser. No. 10/883,051 filed on Jun. 30, 2004.

FIELD OF THE INVENTION

The present invention is directed towards configurable circuits, IC's, and systems.

BACKGROUND OF THE INVENTION

The use of configurable integrated circuits ("IC's") has dramatically increased in recent years. One example of a configurable IC is a field programmable gate array ("FPGA"). An FPGA is a field programmable IC that has an internal array of logic circuits (also called logic blocks) that are connected together through numerous interconnect circuits (also called interconnects) and that are surrounded by input/output blocks. Like some other configurable IC's, the logic circuits and interconnect circuits of an FPGA are configurable.

FIG. 1 illustrates an example of a configurable logic circuit 100. This logic circuit can be configured to perform a number of different functions. As shown in FIG. 1, the logic circuit 100 receives a set of input data 105 and a set of configuration data 110. The configuration data set is stored in a set of SRAM cells 115. From the set of functions that the logic circuit 100 can perform, the configuration data set specifies a particular function that this circuit has to perform on the input data set. Once the logic circuit performs its function on the input data set, it provides the output of this function on a set of output lines 120. The logic circuit 100 is said to be configurable, as the configuration data set "configures" the logic circuit to perform a particular function, and this configuration data set can be modified by writing new data in the SRAM cells.

FIG. 2 illustrates an example of a configurable interconnect circuit 200. This interconnect circuit 200 connects a set of input data 205 to a set of output data 210. This circuit receives configuration data bits 215 that are stored in a set of SRAM cells 220. The configuration bits specify how the interconnect circuit should connect the input data set to the output data set. The interconnect circuit 200 is said to be configurable, as the configuration data set "configures" the interconnect circuit to use a particular connection scheme that connects the input data set to the output data set in a

2

desired manner. Moreover, this configuration data set can be modified by writing new data in the SRAM cells.

FIG. 3 illustrates one example of the interconnect circuit 200. This example is a 4-to-1 multiplexer 300. Based on the configuration bits 215 that this multiplexer receives, the multiplexer 300 passes one of its four inputs 205 to its output 305. FIG. 4 illustrates a decoder 400, which is another example of the interconnect circuit 200. Based on the configuration bits 215 that this decoder receives, the decoder 400 passes its one input 405 to one or more of its outputs 210, while having the outputs that are not connected to the input at a constant value (e.g., ground or VDD) or at a high impedance state.

FPGA's have become popular as their configurable logic and interconnect circuits allow the FPGA's to be adaptively configured by system manufacturers for their particular applications. Also, in recent years, several configurable IC's have been suggested that are capable of reconfiguration at runtime. However, there has not been much innovation regarding IC's that can configure one or more times during one clock cycle. Consequently, most reconfigurable IC's take several cycles (e.g., tens, hundreds, or thousands of cycles) to reconfigure.

Recently, some have suggested a new type of configurable IC that is called a via programmable gate array ("VPGA"). U.S. Pat. No. 6,633,182 ("the '182 patent") discloses such configurable circuits. This patent defines a VPGA as a configurable IC similar to an FPGA except that in a VPGA the programmability is provided by modifying the placement of vias rather than modifying data bits stored in a memory. As further stated in this patent, in the interconnect structure of a VPGA, the programmable interconnect point is a single via, which replaces several transistors in an FPGA.

There is a need in the art for configurable IC's that use novel VPGA structures. There is also a need in the art for configurable IC's that can configure at least once during each clock cycle. Ideally, the configurable IC can configure multiple times within one clock cycle. Such configurability would have many advantages, such as enabling an IC to perform numerous functions within any given clock cycle.

SUMMARY OF THE INVENTION

Some embodiments of the invention provide a configurable integrated circuit (IC). The configurable IC includes first and second interconnect circuits. The first interconnect circuit has a set of input terminals, a set of output terminals, and several connection schemes for communicatively coupling the input terminal set to the output terminal set. During the operation of the IC, the second connection circuit supplies sets of configuration data to the first interconnect circuit at a particular rate for at least a particular time period. At least two supplied configuration data sets are different and configure the first interconnect circuit to use two different connection schemes that differently couple the input and output terminal sets.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth in the appended claims. However, for purpose of explanation, several embodiments of the invention are set forth in the following figures.

FIG. 1 illustrates an example of a configurable logic circuit.

FIGS. 2–4 illustrate several example of configurable interconnect circuits.

FIG. 3 illustrates one example of the interconnect circuit.

FIGS. 5 and 6 present two examples of interface circuits of IC's.

FIG. 7 illustrates an example of a sub-cycle signal generator.

FIGS. 8–10 present an example that illustrates how a larger, slower IC design can be implemented by a smaller, faster IC design.

FIG. 11 illustrates a sub-cycle configurable logic circuit of some embodiments of the invention.

FIG. 12 illustrates a complex logic circuit that is formed by four LUT's and an interconnect circuit.

FIGS. 13–15 illustrate three logic circuits that are three examples of the logic circuit of FIG. 11.

FIG. 16 illustrates a logic circuit of another embodiment of the invention.

FIG. 17 illustrates a sub-cycle configurable interconnect circuit of some embodiments of the invention.

FIGS. 18 and 19 illustrate two examples of the interconnect circuit of FIG. 17.

FIG. 20 illustrates the interconnect circuit of some embodiments of the invention.

FIG. 21 illustrates a VPA interconnect circuit of some embodiments of the invention.

FIG. 22 presents an example that illustrates the setting of vias in a VPA structure of FIG. 21.

FIG. 23 illustrates another VPA interconnect circuit of some embodiments of the invention.

FIG. 24 conceptually illustrates a process that transforms a non-VPA configurable interconnect circuit into a VPA configurable interconnect circuit.

FIG. 25 illustrates an example of VPA configurable logic circuits.

FIG. 26 presents an example that illustrates the setting of vias in a VPA structure of a logic circuit.

FIG. 27 illustrates an example of the invention's VPA configurable logic circuit, which has phase bits as part of its VPA structure.

FIG. 28 illustrates an example of the setting of certain vias in the VPA of FIG. 27.

FIG. 29 illustrates a portion of a configurable IC that has an array of logic circuits and interconnect circuits.

FIG. 30 illustrates a traditional microprocessor design.

FIG. 31 illustrates a configuration data pool for the configurable IC.

FIG. 32 illustrates an IC that has an array of non-traditional processing units and configurable interconnects.

FIG. 33 conceptually illustrates a more detailed example of a computing system that includes an IC of the invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following description, numerous details are set forth for purpose of explanation. However, one of ordinary skill in the art will realize that the invention may be practiced without the use of these specific details. For instance, not all embodiments of the invention need to be practiced with the specific number of bits and/or specific devices (e.g., multiplexers) referred to below. In other instances, well-known structures and devices are shown in block diagram form in order not to obscure the description of the invention with unnecessary detail.

I. DEFINITIONS

Some embodiments of the invention are circuit elements that can be configured within "sub-cycles" of a "design cycle" or an "interface cycle" of an IC. An IC typically has numerous clocks that are used to synchronize its operations. A clock typically has a number of repetitive cycles. A clock also has a period and a frequency (also called a rate). A clock's period is the temporal duration of one of its repetitive cycles, while its frequency (or rate) is the inverse of its period. For example, a clock with a 10 ns period has a frequency of 100 MHz.

The design clock rate (or frequency) of an IC or a portion of an IC is the clock rate for which the design of the IC or the portion of the IC has been specified. In some cases, the design clock rate is defined as one over the duration of time between the fastest, stable (i.e., non-transient) change in a state of the design (e.g., the fastest change in an output of the design). When the design is a Register Transfer Level (RTL) design, the design clock rate can be the clock rate for which the user specifies his or her design in a hardware definition language (HDL), such as VHDL or Verilog.

An interface rate of an IC is the rate at which the IC communicates with other circuitry. For instance, in some cases, an IC's interface rate is the rate that an interface circuit of the IC passes signals to and/or receives signals from circuits outside of the IC. An IC can have one or more interface circuits, and these interface circuits can have the same or different interface rates. FIGS. 5 and 6 present two examples of interface circuits. FIG. 5 illustrates an IC 500 that has four one-directional interface circuits 505, 510, 515, and 520 that operate at three different interface rates. Specifically, the interface circuit 505 receives input at a first rate R1, the interface circuit 510 receives input at a second rate R2, the interface circuit 515 provides output at a third rate R3, and the interface circuit 520 provides output at a first rate R1. FIG. 6 illustrates an IC 600 that has two bi-directional interface circuits 605 and 610 that operate at the same interface rate of R5.

An alternative term for an IC's interface rate is an input/output rate of the IC. An interface cycle is one over the interface rate, while a design cycle is one over the design rate. A sub-cycle of a design or interface cycle is a portion of the design or interface cycle. In the discussion of sub-cycle configurable circuits below, the term "primary cycle" refers to either a design cycle or an interface cycle. Similarly, the term "primary clock" refers to either a design clock or an interface clock.

In some embodiments, a primary cycle's period is broken into several sub-cycles of equal duration. For instance, a 10 ns cycle can be broken into 10 sub-cycles of 1 ns each. Some embodiments use sub-cycle signal generators that generate sub-cycle clocks and/or signals that have some relation with the primary clock but have faster rates than the primary clock. For instance, in some embodiments, the sub-cycle clocks and/or signals are derived from the primary clock. In some embodiments, the sub-cycle clocks and/or signals have rates that share a least common multiple with the rate of the primary clock. Also, in some embodiments, the sub-cycle clocks and/or signals are aligned with the primary clock on at least some of their edge transitions. In some of these embodiments, each sub-cycle that falls within a particular cycle of the primary clock is referred to as a "phase."

FIG. 7 illustrates an example of a sub-cycle signal generator 700. This generator receives a primary clock 705 and generates a sub-cycle clock 710 that is four times faster than the received clock. Hence, as shown in FIG. 7, the sub-cycle

5

clock has four phases $\phi 0$, $\phi 1$, $\phi 2$, $\phi 3$, during each cycle of the received clock. The sub-cycle signal generator can provide configurable circuit elements with its sub-cycle clock. In conjunction with this clock, or instead of this clock, the generator can provide configurable circuit elements with a signal whose value can change in each sub-cycle period. For instance, in FIG. 7, the sub-cycle signal generator 700 generates a 2-bit phase signal, with four different values 00, 01, 10, and 11. These four values represent the four sub-cycles during each primary cycle. In this figure, these generated phase signals change in each sub-cycle and reset at the start of each period of the received clock.

Although FIG. 7 shows these phase signals as changing sequentially, these phase signals change in a non-sequential manner in some embodiments. Also, in some embodiments, the order of the phase signals in each period of the received clock can differ, e.g., in one clock period the phase bits might appear as 00, 10, 11, 01, and in the next clock period the phase bits might appear as 11, 10, 01, 00. In some embodiments, the sub-cycle signal generator can generate phase signals that have different ordering in different primary cycles by generating the phase bits based not only on the primary clock signal but also on programming signals that it receives. Such programming signals programmably direct the sub-cycle signal generator to generate different phase signals at different times.

Moreover, in some or all primary cycles, the sub-cycle signal generator can generate a phase signal that does not utilize all possible phase bit permutations or that utilizes one or more of the phase bit permutations more than once during a primary cycle. Furthermore, the sub-cycle signal generator might use different encoding schemes (e.g., a Gray code encoding scheme, a one-hot encoding scheme, etc.) to generate its phase signals. Also, a primary cycle might be divided into more or fewer than four sub-cycles.

Some embodiments of the invention are IC's with sub-cycle configurable logic and interconnect circuits. As further described below, a configurable logic circuit is a circuit that can be configured to perform a set of functions on a set of input data that it receives. The logic circuit receives a set of configuration data that cause the logic circuit to perform a particular function within its set of functions on the input data set. The logic circuit then outputs the result of this function as a set of output data. A logic circuit is sub-cycle configurable if the logic circuit can be configured one or more times within one primary cycle to perform more than one function. In other words, such a logic circuit can be reconfigured one or more times in a primary cycle. In some of the embodiments described below, the sub-cycle configurable logic circuits can be reconfigured to perform a new function within each sub-cycle of a primary cycle.

A configurable interconnect circuit is a circuit that can configurably connect an input set to an output set in a variety of manners. An interconnect circuit receives a configuration data set that causes the interconnect circuit to connect its input set to its output set in a particular manner. An interconnect circuit is sub-cycle configurable if it can be configured one or more times within one primary cycle to change the way it connects the input and output sets. In other words, a sub-cycle configurable interconnect circuit is a configurable interconnect circuit that can be reconfigured one or more times within a primary cycle. In some of the embodiments described below, a sub-cycle configurable interconnect circuit can be reconfigured within each sub-cycle of a primary cycle to change its connection scheme.

Examples of sub-cycle configurable logic and interconnect circuits will be provided below in Sections III–VI

6

below. However, before providing these examples, the benefit of sub-cycle reconfiguration will be first described in Section II.

II. Sub-Cycle Configuration

Sub-cycle configurability has many advantages. One advantage is that it allows a larger, slower IC design to be implemented by a smaller, faster IC design. FIGS. 8–10 present an example that illustrates this benefit. FIG. 8 illustrates a set of Boolean gates that compute two functions G3 and P3 based on a set of inputs A0, B0, A1, B1, A2, and B2. The set of Boolean gates has to compute these two functions based on the received input set in one design cycle. In this example, one design cycle lasts 10 ns, as the design clock's frequency is 100 MHz. However, in this example, the technology could easily operate at 400 MHz. Hence, each design cycle can be broken down into 4 sub-cycles of 2.5 ns duration.

FIG. 9 illustrates the design 800 of FIG. 8 after its gates have been placed into four groups. These gates have been placed into four groups in order to break down the design 800 into four separate groups of gates that can be configured and executed in four sub-cycles by a smaller group of gates. The groupings illustrated in FIG. 9 are designed to separate out the computation of different sets of gates while respecting the operational dependencies of other gates. For instance, gates 805, 810, and 815 are defined as a separate group from gates 820, 825, and 830, as these two sets of gates have no operational dependencies (i.e., the output of the gates in one set is not dependent on the output of the gates in the other set). As these two sets of gates have no operational dependencies, one set is selected for computation during the first sub-cycle (i.e., during phase 1), while the other set is selected for computation during the second sub-cycle (i.e., during phase 2). On the other hand, gates 835, 840, and 845 are dependent on the outputs of the first two sets of gates. Hence, they are designated for configuration and execution during the third sub-cycle (i.e., during phase 3). Finally, the gate 850 is dependent on the output of the first and third sets of gates, and thus it is designated for configuration and execution during the fourth sub-cycle (i.e., during phase 4).

FIG. 10 illustrates another representation of the design 800 of FIG. 8. Like FIG. 9, the schematic in FIG. 10 illustrates four phases of operation. However, now, each gate in the design 800 has been replaced by a sub-cycle configurable logic circuit 1005, 1010, or 1015. Also, only three logic circuits 1005, 1010, and 1015 are used in FIG. 10, as each of the gates in FIG. 8 can be implemented by one logic circuit, and the groupings illustrated in FIGS. 9 and 10 require at most 3 gates to be executing during any given phase. (In FIG. 10, each logic circuit's operation during a particular phase is identified by a superscript; so, for example, reference numbers 1005¹, 1005², and 1005³, respectively, identify the operation of the logic circuit 1005 during phases 1, 2, and 3.)

As shown in FIG. 10, the outputs of certain logic circuits in earlier phases need to be supplied to logic circuit operations in the later phases. One of ordinary skill will realize that such earlier outputs can be preserved for later computations by using state elements (such as registers) that are operated at the sub-cycle frequency. Such state elements (not shown) can be standalone circuit elements or can part of one or more sub-cycle configurable interconnect circuits (not shown) that are configured to connect the logic circuits in the desired manner.

Accordingly, FIGS. 8–10 illustrate that sub-cycle configurability allows a ten-gate design that operates at 100 MHz to be implemented by three sub-cycle configurable logic circuits and associated configurable interconnect circuits and state elements that operate at 400 MHz. It should be noted that even fewer than three logic circuits might be necessary if one logic gate can perform the operation of two or more gates that are executing during each phase illustrated in FIG. 9.

III. Sub-Cycle Configurable Logic Circuit

FIG. 11 illustrates a sub-cycle configurable logic circuit 1100 of some embodiments of the invention. This logic circuit includes a core logic circuit 1105 that can perform a variety of functions on a set of input data 1110 that it receives. The core logic circuit 1105 also receives a set of four configuration data bits 1115 through a switching circuit 1120. The switching circuit receives a larger set of sixteen configuration data bits 1125 that, in some embodiments, are stored in a set of memory cells 1130 (e.g., SRAM cells). This switching circuit is controlled by a phase ϕ , which is generated by the above-described sub-cycle signal generator 700.

As described above and illustrated in FIG. 7, the generator 700 in some embodiments generates a phase signal that is a 2-bit phase signal, which has a value that changes sequentially during each sub-cycle period and resets at the start of each primary cycle period. However, in other embodiments, the sub-cycle signal generator 700 generates a phase signal in other sequential or non-sequential manners with different ordering and/or encoding schemes.

During each phase (i.e., each sub-cycle), the switching circuit supplies four configuration data bits 1115 to the logic circuit 1105. In some embodiments, the switching circuit is a set of four multiplexers 1140. A multiplexer is any device that can select k-of-n signals, where k and n are any integer values. Multiplexers include pass transistors, sets of tri-stated buffers or transistors, or any device that can select k-of-n signals. During each sub-cycle, each multiplexer 1140 supplies one of four configuration bits that it receives to the logic circuit 1105. One of ordinary skill will realize that other switching circuits and sub-cycle generators can be used in other embodiments of the invention.

Based on the set of configuration data 1115, the logic circuit 1105 performs on the input data set 1110 a particular function from the set of functions that it can perform. As the switching circuit 1120 can supply different configuration data sets 1115 to the logic circuit 1105 during different sub-cycles, the logic circuit 1105 can be configured to perform different functions on the input data set 1110 during different sub-cycles.

The core logic circuit 1105 has a set of n output lines 1145, where n is an integer. This circuit provides the result of performing its configured function on the input data set 1110 along its output lines 1145. These output lines provide the output of the overall logic circuit 1100.

The core logic circuit 1105 is different in different embodiments of the invention. In some cases, a logic circuit 1105 is nothing more than a switching circuit that routes one or more of the input data bits to one or more of the output lines based on the value of the configuration data. However, in other cases, the logic circuit 1105 does not simply route a selection or a permutation of the input data set to the output data set but rather performs computations on the input data set to derive the output data set.

Any number of known logic circuits (also called logic blocks) can be used in conjunction with the invention.

Examples of such known logic circuits include look-up tables (LUT's), universal logic modules (ULM's), sub-ULM's, multiplexers, and PAL/PLA. Also, logic circuits can be complex logic circuit formed by multiple logic and interconnect circuits. For instance, FIG. 12 illustrates a complex logic circuit 1200 that is formed by four LUT's 1205 and an interconnect circuit 1210. One of ordinary skill will realize that the illustration of the logic circuit 1200 is a simplification that does not show several circuit elements (e.g., fast-carry logic, etc.) that are commonly in complex logic circuits. This illustration is provided only to convey the principle that more complex logic circuits are often formed by combining simpler logic circuits and interconnect circuits. Examples of simple and complex logic circuits can be found Architecture and CAD for Deep-Submicron FPGAs, Betz, et al., ISBN 0792384601, 1999.

FIGS. 13–15 illustrate three logic circuits 1300, 1400, and 1500, which are three examples of the logic circuit 1100. In these three examples, the core logic circuits 1305, 1405, and 1505 (which are one implementation of the core logic circuit 1105 of FIG. 11) are multiplexers. The logic circuits 1300, 1400, and 1500 are all commutative with respect to the ordering of the input data set 1110 and the sub-cycle signals 1150. Specifically, labeling the two input signals as I1 and I2 and the two sub-cycle signals as ϕ_i and ϕ_j , the logic circuits 1300, 1400, and 1500 all provides the same output for the same configuration data set 1125, even though the ordering of the sub-cycle signals and the input data sets is different in these three examples.

FIG. 16 illustrates another embodiment of the invention. This embodiment is a logic circuit 1600 that, like the logic circuit 1100 of FIG. 11, can be reconfigured in each sub-cycle. However, unlike the logic circuit 1100 that can be configured in a non-sequential manner when the sub-cycle signal generator 700 provides a non-sequential signal, the logic circuit 1600 is only configured in a sequential manner. Specifically, the logic circuit 1600 has a core logic circuit 1105 and a sequential circuit 1610. The sequential circuit 1610 provides the core logic circuit 1105 with a configuration data set in each sub-cycle. In this example, four shift registers 1615 form the sequential circuit 1610. Each shift register stores one configuration data set. At the start of each sub-cycle period, the shift registers pass their content (i.e., their configuration data bits) to each other in a counterclockwise manner as illustrated in FIG. 16 (i.e., 1615a passes its content to 1615b, 1615b passes its content to 1615c, 1615c passes its content to 1615d, and 1615d passes its content to 1615a). Also, at the start of each sub-cycle period, the configuration data set in the register 1615d is supplied to the logic circuit 1105.

Based on the set of configuration data that it receives, the logic circuit 1105 selects, from the set of functions that it can perform, a particular function to perform on its input data set 1110. As the sequential circuit 1610 can supply different configuration data sets to the logic circuit 1105 during different sub-cycles, the logic circuit 1105 can be configured to perform different functions on the input data set during different sub-cycles. The core logic circuit 1105 provides its output (i.e., provides the result of performing the configured function on the input data set 1110) along its set of n output lines 1145.

IV. Sub-Cycle Configurable Interconnect

FIG. 17 illustrates a sub-cycle configurable interconnect circuit 1700 of some embodiments of the invention. This circuit configurably connects a set of input data terminals 1710 to a set of output data terminals 1715 based on a set of

configuration data **1720**. This interconnect circuit includes a core interconnect circuit **1705** that receives an input data set along the input data terminals **1710** and provides an output data set along the output data terminals **1715**. The core interconnect circuit **1705** also receives the configuration data set **1720** through a switching circuit **1725**. The switching circuit receives a larger set of configuration data bits **1730** that, in some embodiments, are stored in a set of memory cells **1130** (e.g., SRAM cells). This switching circuit is controlled by a phase ϕ , which is generated by the sub-cycle signal generator **700**.

As described above and illustrated in FIG. 7, the generator **700** in some embodiments generates a phase signal that is a 2-bit phase signal, which has a value that changes sequentially during each sub-cycle period and resets at the start of each primary cycle period. However, in other embodiments, the sub-cycle signal generator **700** generates a phase signal in other sequential or non-sequential manners, with different ordering and/or encoding schemes.

During each phase (i.e., each sub-cycle), the switching circuit **1725** supplies two of the eight configuration data bits **1730** as the configuration data set **1720** to the interconnect circuit **1705**. In FIG. 17, two multiplexers **1740** form the switching circuit. During each sub-cycle, each multiplexer **1740** supplies one of four configuration bits that it receives to the interconnect circuit **1705**. In FIG. 17, a two-bit phase value is written next to each configuration bit that is received by each switching multiplexer **1740**. These two-bit values identify the configuration bit associated with each pair of phase bits. One of ordinary skill will realize that other switching circuits and/or sub-cycle signal generators can be used in other embodiments of the invention.

Based on the set of configuration data **1720** that it receives, the interconnect circuit **1705** connects the input terminal set **1710** to the output terminal set **1715**. As the switching circuit **1725** can supply different configuration data sets **1720** to the interconnect circuit **1705** during different sub-cycles, the interconnect circuit **1705** can differently connect the input terminal set **1710** to the output terminal set **1715** during different sub-cycles. The output terminal set **1715** provides the output of the overall interconnect circuit **1700** in some embodiments.

The core interconnect circuit is different in different embodiments of the invention. Any number of known interconnect circuits (also called interconnects or programmable interconnects) can be used in conjunction with the invention. Examples of such interconnect circuits include switch boxes, connection boxes, switching or routing matrices, full- or partial-cross bars, etc. Such interconnects can be implemented using a variety of known techniques and structures. Examples of interconnect circuits can be found Architecture and CAD for Deep-Submicron FPGAs, Betz, et al., ISBN 0792384601, 1999.

As shown in FIG. 17, the input terminal set **1710** is a first set of lines, while the output terminal set **1715** is a second set of lines. The second set of lines might be collinear with the first set of lines, or might be in a direction that is offset (e.g., is at 90°) from the first set of lines. Alternatively, some of the second set of output lines might be collinear with some of the first set of input lines, while other second-set lines might be at an angle with respect to some of the first-set lines.

In some embodiments, the interconnect circuit **1700** is bi-directional. Specifically, in these embodiments, the interconnect circuit can use some or all of the terminal set **1710** to receive input data signals during some sub-cycles, while using the same terminals to supply output data signals

during other sub-cycles. Similarly, in these embodiments, the interconnect circuit can use some or all of the terminal set **1715** to supply output data signals during some sub-cycles, while using the same terminals to receive input data signals during other sub-cycles.

Although the interconnect circuit **1700** is shown as a sub-cycle configurable interconnect circuit in FIG. 17, this circuit **1700** is not sub-cycle configurable in other embodiments of the invention. In these other embodiments, in place of the phase signal ϕ **1150**, this circuit receives a control signal whenever a new configuration data set needs to be supplied to the core interconnect circuit **1705**. In some embodiments, this control signal has a frequency that is as fast as or faster than the primary clock rate. In other embodiments, this control signal's rate is slower than the primary clock rate. Alternatively, the control signal might not have any predictable rate.

FIGS. 18 and 19 illustrate two examples **1800** and **1900** of interconnect circuit **1700**. In FIG. 18, the core interconnect circuit **1805** is a 4-to-1 multiplexer that connects during any given sub-cycle one of its four input lines **1710** to its one output line **1718**, based on the configuration data set **1720** that the multiplexer receives along its select lines. By having the ability to change the configuration data set **1720** during each sub-cycle, the multiplexer **1805** can be configured to connect a different input line to its output line during each sub-cycle.

In FIG. 19, the core interconnect circuit **1905** is a 1-to-4 decoder. Based on the configuration data set **1720** that it receives along its configuration lines, this decoder connects during any given sub-cycle its input line **1710** to one or more of its output lines **1715**, while having the outputs that are not connected to the input set at a constant value (e.g., ground or VDD) or to a high impedance state. By having the ability to change the configuration data set **1720** during each sub-cycle, the decoder **1905** can be configured to connect a different set of output lines to its input line during each sub-cycle.

FIG. 20 illustrates another embodiment of the invention. This embodiment is an interconnect circuit **2000** that, like the interconnect circuit **1700** of FIG. 17, can be reconfigured in each sub-cycle. However, unlike the interconnect circuit **1700** that can be configured in a non-sequential manner when the sub-cycle signal generator **700** provides a non-sequential signal, the interconnect circuit **2000** can only be configured in a sequential manner. Specifically, the interconnect circuit **2000** has a core interconnect circuit **1705** and a sequential circuit **1610**. In this example, the sequential circuit **1610** is identical to the sequential circuit **1610** of FIG. 16. In other words, it is formed by four-shift registers **1615**, where each shift register (1) stores one configuration data set during each sub-cycle and (2) passes its configuration data set to another shift register in a counterclockwise direction (that is shown in FIG. 20) at the start of each sub-cycle. Also, at the start of each sub-cycle period, the configuration data set in the register **1615d** is supplied to the interconnect circuit **1705** of the circuit **2000**.

The interconnect circuit **1705** then connects the input data set **1710** to the output data set **1715** based on the set of configuration data that this circuit receives. As the sequential circuit **1610** can supply different configuration data sets to the interconnect circuit **1705** during different sub-cycles, the interconnect circuit **1705** can be configured to connect the input and output data sets differently during different sub-cycles.

V. Configurable Interconnect Circuit with Via Programmable Structure

Sections V and VI describe several interconnect and logic circuits with via programmable structures. This description refers to vias, potential vias, via programmable arrays, and

VPGA'S. A via is connection between two wires (e.g., two conductive lines) on two different wiring layers. Vias can be defined in an IC in a variety of ways (e.g., by defining a cut between two layers, by defining two electrical structures or devices on two different layers that can establish an electrical connection at runtime, etc.) If the wires are on two layers that have one or more intervening wiring layers, the via might be formed as a set of stacked vias, where each via in the stack is between two adjacent layers.

A potential via is a site in an IC design for possibly defining a via. A via programmable array (VPA) is a set of vias or potential vias for a particular configurable interconnect or logic circuit. A configurable VPA interconnect or logic circuit is an interconnect or logic circuit that has an associated VPA. In some of the embodiments described below, configuration data for a configurable interconnect or logic circuit is provided to the circuit by defining certain vias in the circuit's associated VPA.

A. Structure

FIG. 21 illustrates an interconnect circuit 2100 of some embodiments of the invention. For a given phase signal 1150 and configuration data set 1730, the interconnect circuit 2100 can be used in place of the interconnect circuit 1700. The interconnect circuit 2100 includes a VPA 2105 and a core interconnect circuit 2110, which directly receives the phase signal 1150. The VPA structure 2105 is formed by two sets of lines that overlap. Typically, the two sets of lines appear on two different wiring layers of the IC, although these lines might appear on three or more layers in some embodiments. The first set is a set of input lines 2115, while the second set is a set of lines 2120 that are the inputs of the core logic circuit 2110. As shown in FIG. 21, each line in the first set overlaps each line in the second set at a 90° angle. In other embodiments, each line in the first set might not overlap every line in the second set, and/or each overlap might not be at a 90° angle.

As shown in FIG. 21, the VPA structure 2105 includes a potential via 2125 at each location where a line in the first set 2115 overlaps a line in the second set 2120. When the values of the phase signals 1150 and the configuration data set 1730 are known for the interconnect circuit 1700, certain vias in the array of potential vias can be set (i.e., defined) based on these values to complete the definition of the interconnect circuit 2100.

FIG. 22 presents an example that illustrates the setting of vias in a VPA structure 2204. Specifically, this example illustrates how a non-VPA interconnect circuit 2250 can be transformed into a sub-cycle configurable VPA interconnect circuit 2200. The non-VPA interconnect circuit 2250 is similar to the above described interconnect circuit 1805 of FIG. 18. Just like the interconnect circuit 1805, the interconnect circuit 2250 includes (1) a set of configuration storage elements 1130, (2) a switching circuit 1725 that is formed by two 4-to-1 multiplexers 1740, and (3) a core 4-to-1 multiplexer 1805.

The interconnect circuit 2200 includes a 4-to-1 multiplexer 2202 and a VPA 2204. The multiplexer 2202 and the VPA 2204 together subsume all the functionalities of the switching multiplexers 1740, configuration storage elements 1130, and 4-to-1 multiplexer 1805 of the interconnect circuit 2250, when the configuration data set 1730 has the values illustrated in FIG. 22 and the phase signal has values 00, 01,

10, and 11. In FIG. 22, a two-bit value is written next to each bit that is received by a 4-to-1 multiplexer 1740 to identify the bit associated with each received pair of bits. Similarly, a two-bit configuration value is written next to each input line that is received by the core multiplexer 1805 to identify the input line associated with each possible configuration data set.

At any given time, the 4-to-1 multiplexer 1805 connects one of its four input lines 1710 to its one output line 1715, based on the configuration data set 1720 that the multiplexer receives along its select lines. For the configuration data set 1730 illustrated in FIG. 22, the interconnect circuit 1805 receives 01, 00, 10, and 11 as the configuration data set 1720 as the phase signal ϕ cycles through the values 00, 01, 10, and 11. The phase signal ϕ does not need to proceed through the values 00, 01, 10, and 11 in any particular order or frequency. However, in some embodiments, this signal passes through these values in sequence and changes values in each sub-cycle.

Based on the configuration data set 1720 that it receives, the interconnect circuit 1805 connects one of its input lines to its output line 1715. Specifically, it connects its output line 1715 to (1) input I2 when the phase is 00 (as this circuit receives the configuration data 01 during this phase), (2) input I1 when the phase is 01 (as this circuit receives the configuration data 00 during this phase), (3) input I3 when the phase is 10 (as this circuit receives the configuration data 10 during this phase), and (4) input I4 when the phase is 11 (as this circuit receives the configuration data 11 during this phase).

In FIG. 22, the vias that are defined in the VPA structure 2204 are illustrated as black boxes. These defined vias allow the interconnect circuit 2200 to connect its input and output sets 2115 and 2225 in the same manner as the interconnect circuit 1805 in FIG. 22, for the phase signal values 00, 01, 10, and 11. Specifically, like the output line 1715 of the interconnect circuit 1805, the output line 2225 connects (1) to input line I2 through via 2205 during phase 00, (2) to input line I1 through via 2210 during phase 01, (3) to input line I3 through via 2215 during phase 10, and (4) to input line I4 through via 2220 during phase 11.

The migration from a non-VPA interconnect structure to a VPA interconnect structure not only eliminates the configuration bits and switching circuit, but it can also change the core interconnect circuit. FIG. 23 presents an example that more clearly illustrates this transformation. This figure illustrates a VPA interconnect circuit 2300 and a non-VPA interconnect circuit 2305 that are functionally equivalent for a given phase signal and configuration data set.

The non-VPA circuit 2305 is similar to the non-VPA interconnect circuit 2250 illustrated in FIG. 22, except that instead of the 4-to-1 multiplexer 1805 and two switching multiplexers 1740, it uses an 8-to-1 multiplexer 2310 and three switching multiplexers 1740. Each of the three switching multiplexers 1740 is controlled by the two-bit phase signal ϕ of the sub-cycle signal generator 700. As before, in some embodiments, this phase signal has the values 00, 01, 10, and 11, although it can have a different set of phases in other embodiments as described above. The three switching multiplexers act as a switching circuit 2380 that outputs four 3-bit configuration values during the four phases. (As before, the two-bit phase values are written next to each configuration bit that is received by each 4-to-1 multiplexer to show the configuration bit associated with each pair of phase bits.) The 8-to-1 multiplexer 2310 receives these 3-bit values 2325 on its select lines, and, based on each set of three values, connects one of its 8 inputs 2315 to its output

13

2320. (A three-bit configuration value is written next to each input line of the 8-to-1 multiplexer to show the input bit associated with possible configuration data set.)

For the configuration data set **2330** illustrated in FIG. **23**, the multiplexer **2310** receives **001**, **100**, **110**, and **011** as the configuration data set **2325**, while the phase signal ϕ cycles through the values **00**, **01**, **10**, and **11**. As before, the phase signal ϕ does not need to proceed through all the values or through the values **00**, **01**, **10**, and **11** in any particular order or frequency. However, in some embodiments, this signal passes through these values in sequence and changes values in each sub-cycle.

Based on the configuration data set **2325** that it receives, the interconnect circuit **2310** connects one of its input lines **2315** to its output line **2320**. Specifically, it connects its output line **2320** to (1) input **I2** when the phase is **00** (as this circuit receives the configuration data **001** during this phase), (2) input **I5** when the phase is **01** (as this circuit receives the configuration data **100** during this phase), (3) input **I7** when the phase is **10** (as this circuit receives the configuration data **110** during this phase), and (4) input **I4** when the phase is **11** (as this circuit receives the configuration data **011** during this phase).

As mentioned above, the VPA interconnect circuit **2300** illustrated in FIG. **23** is equivalent to the non-VPA interconnect circuit **2305** for the configuration data set and phase bits illustrated in this figure. The interconnect circuit **2300** includes a 4-to-1 multiplexer circuit **2350** and a VPA **2355**, which together subsume all the functionalities of the switching multiplexers **1740**, configuration storage elements **1130**, and 8-to-1 multiplexer **2310**.

The VPA structure **2355** is formed by two sets of lines that overlap. Typically, the two sets of lines appear on two different wiring layers of the IC, although these lines might appear on three or more layers in some embodiments. The first set of overlapping lines is a set of eight input lines **2315**, while the second set of overlapping lines is a set of four lines **2360** that are the inputs of the multiplexer **2350**. As shown in FIG. **23**, each line in the first set is at a 90° angle to each line in the second set. In other embodiments, each line in the first set might not overlap every line in the second set, and/or each overlap might not be a 90° angle.

As shown in FIG. **23**, the VPA structure **2355** includes a potential via **2365** at the overlap of each first-set line **2315** and each second-set line **2360**. FIG. **23** identifies as black boxes the vias that need to be defined in the VPA structure **2355**, so that the interconnect circuit **2300** can connect its input and output sets **2315** and **2370** in the same manner as the interconnect circuit **2305**. Specifically, with these defined vias, the output line **2370** of the VPA interconnect circuit **2300** connects to (1) input line **I2** through via **2372** during phase **00**, (2) input line **I5** through via **2374** during phase **01**, (3) input line **I7** through via **2376** during phase **10**, and (4) input line **I4** through via **2378** during phase **11**. This connection scheme is identical to the connection scheme of the interconnect circuit **2305** as described above.

VPA interconnect circuits (such as circuits **2100**, **2200**, and **2300**) have several advantages. For instance, they do not use costly SRAM cells to store configuration data. Instead, they encode such configuration data in their VPA's. VPA interconnects are also very efficient switching circuits, as they avoid much of the transistor switch logic of non-VPA interconnect circuit by using vias for their switching. In other words, non-VPA interconnect circuits supply configuration data through switching and storage circuits that have many transistors on the IC substrate. Such switching requires signals to traverse back and forth between the

14

higher wiring layers and the IC substrate. VPA interconnects avoid these space- and time-consuming switching and storage circuits by defining vias that act as switches between two wiring layers. Hence, IC's that use VPA interconnects can be smaller and faster than traditional configurable IC's (e.g., FPGA's) while having cheaper masks than traditional ASIC's.

B. Process for Transforming a Non-VPA Configurable Interconnect Circuit to a VPA Configurable Interconnect Circuit

FIG. **24** conceptually illustrates a process **2400** that transforms a non-VPA configurable interconnect circuit into a VPA configurable interconnect circuit. This process will be explained by reference to the above-described example that was illustrated in FIG. **23**. As shown in FIG. **24**, the process **2400** initially selects (**2405**) a sub-cycle configurable non-VPA interconnect circuit to transform to a VPA configurable interconnect circuit. For instance, at **2405**, the process selects non-VPA configurable interconnect circuit **2305** of FIG. **23**. The selected non-VPA interconnect circuit typically includes a core interconnect circuit (e.g., the interconnect circuit **2310** of FIG. **23**) and a switching circuit (e.g., the switching circuit **2380** of FIG. **23**) that supplies a configuration data set to the core interconnect circuit during each sub-cycle.

Next, at **2410**, the process specifies a VPA interconnect circuit, which includes a core interconnect circuit and a VPA structure. The core interconnect circuit and the VPA structure of the VPA circuit are specified based on the core interconnect circuit of the selected non-VPA circuit, the number of sub-cycles, and the number of inputs. In the example illustrated in FIG. **23**, there are only four sub-cycles. During each of these four cycles, the core interconnect circuit **2310** relays the signal from one of its input lines **2315** to its one output line **2320**. Accordingly, for this example, the process specifies (at **2410**) a core interconnect circuit that has at least one output line and at least four input lines. Also, given that the core interconnect circuit **2310** receives eight input lines, the VPA structure that is specified at **2410** needs to be eight lines wide in the input signal direction. Accordingly, these minimum requirements result in the specification (at **2410**) of the 4-to-1 multiplexer **2350** and VPA structure **2355** of FIG. **23**.

After specifying (at **2410**) the structure of the VPA interconnect circuit, the process **2400** (at **2415**) selects one of the sub-cycles and identifies the configuration data set that is received during this sub-cycle by the core interconnect circuit of the non-VPA circuit. For instance, in the example illustrated in FIG. **23**, the process could (at **2415**) select the sub-cycle **00** and thus identify **001** as the configuration data set **2325** during this sub-cycle.

Next, at **2420**, the process **2400** identifies the state of the core interconnect circuit during the selected sub-cycle for the identified configuration data set. For instance, in the example illustrated in FIG. **23**, the process determines (at **2420**) that the core interconnect circuit **2310** relays the signal from the input line **I2** to its output line **2320** when it receives the configuration data set **001** during the sub-cycle **00**.

Based on the state of the interconnect circuit that is identified at **2420**, the process **2400** then defines (at **2425**) one or more vias in the VPA structure that was specified at **2410**. In the example illustrated in FIG. **23**, the process defines (at **2425**) the via **2372** to allow the input **I2** to be communicatively coupled to the output line **2370** of the VPA circuit **2300** during the sub-cycle **00**.

15

After **2425**, the process determines (at **2430**) whether it has examined all of the sub-cycles. If not, the process (at **2415**) selects another sub-cycle and identifies the configuration data set that is received during this sub-cycle by the core interconnect circuit of the non-VPA circuit. The process then transitions back to **2420** to identify the state of the core interconnect circuit during the selected sub-cycle for the identified configuration data set and then to **2425** to define a via in the VPA structure to account for this state. In this manner, the process **2400** loops through **2415–2430** until it defines a via in the VPA structure to account for all the possible states of the non-VPA interconnect circuit. For example, after identifying via **2372** in the example illustrated in FIG. **23**, the process loops through **2415–2430** three more times to define vias **2374**, **2376**, and **2378** to account for the connection of inputs **15**, **17**, and **14** during sub-cycle phases **01**, **10**, and **11**. When the process **2400** determines (at **2430**) that it has examined the non-VPA circuit's operation during all potential sub-cycles, the process **2400** terminates.

VI. Configurable Logic Circuit with VPA Structure

Some embodiments of the invention are VPA configurable logic circuits. FIG. **25** illustrates an example of one such logic circuit **2500**. As shown in this figure, the VPA configurable logic circuit **2500** is functionally equivalent to the logic circuit **1100** of FIG. **11**. The only structural difference between the logic circuits **2500** and **1100** is that the memory cells **1130** of the logic circuit **1100** have been replaced by a VPA structure **2505** in logic circuit **2500**.

The VPA structure **2505** is formed by two sets of lines that overlap. Typically, the two sets of lines appear on two different wiring layers of the IC, although these lines might appear on three or more layers in some embodiments. The first set includes two lines **2510**, one of which carries the 0 value, while the other carries the 1 value. The second set of lines is a set of lines **2515** that are the inputs of the multiplexers **1140**. As shown in FIG. **25**, each line in the first set overlaps each line in the second set at a 90° angle. In other embodiments, each line in the first set might not overlap every line in the second set, and/or each overlap might not be at a 90° angle.

The VPA structure **2505** includes a potential via **2520** at each location where a line in the first set **2510** and a line in the second set **2515** overlap. When the values of the configuration data set stored in the memory cells **1130** are known for the logic circuit **1100**, certain vias in the array of potential vias can be set (i.e., defined) to complete the definition of the logic circuit **2500**.

FIG. **26** presents an example that illustrates the setting of vias in a VPA structure of a logic circuit. Specifically, this example illustrates a particular configuration data set **1125** for the logic circuit **1100**. For this set of configuration data, FIG. **26** then illustrates sixteen black boxes in the VPA structure **2505** that represent the vias that are defined in this structure **2505**. These defined vias allow the logic circuit **2500** in FIG. **26** to perform the same function as the logic circuit **1100** in FIG. **26**.

In some embodiments, the invention's VPA configurable logic circuits have phase bits as part of their VPA structure. FIG. **27** illustrates an example of one such embodiment. Specifically, this figure illustrates a VPA configurable logic circuit **2700** that is functionally equivalent to the VPA configurable logic circuit **2500** of FIG. **25** and, hence, functionally equivalent to the non-VPA configurable logic circuit **1100** for a known configuration data set and phase signal.

16

The structure of the logic circuit **2700**, however, has two differences from the logic circuit **2500**. First, the 4-to-1 switching multiplexers of logic circuit **2500** have been replaced by 2-to-1 switching multiplexers **2740** that are controlled by only the phase bit ϕ_j . Second, the other phase bits ϕ_i and its complement ϕ_i' are part of the VPA structure **2705** of the logic circuit **2700**. Specifically, the VPA structure **2705** is formed by two sets of overlapping lines **2710** and **2715**. The first set **2710** includes four lines, two of which carry the 0 and 1 values, while the other two carry the phase bit ϕ_i and its complement ϕ_i' . The second set of lines **2715** are inputs to the multiplexers **2740**. As shown in FIG. **27**, each line in the first set overlaps each line in the second set at a 90° angle. In other embodiments, each line in the first set might not overlap every line in the second set, and/or each overlap might not be at a 90° angle.

The VPA structure **2705** includes a potential via **2720** at the intersection of each first-set line **2710** and each second-set line **2715**. For a particular configuration data set that is stored in the memory cells **1130** of the logic circuit **1100** or that is embedded in the VPA structure **2505** of the logic circuit **2500**, certain vias in the VPA **2705** of the logic circuit **2700** can be set (i.e., defined) to complete the definition of the logic circuit **2700**.

FIG. **28** illustrates an example of the setting of certain vias in the VPA **2705**. In this example, the defined vias are shown as black boxes. In FIG. **28**, the vias are defined in the VPA **2705** to allow the logic circuit **2700** in this figure to function equivalently to the logic circuits **1100** and **2500** as configured in FIG. **26**. Like logic circuit **1300**, **1400**, and **1500**, the logic circuits **2500** and **2700** of FIGS. **25–28** are commutative with respect to the ordering of the input data set and the sub-cycle signals when the core logic circuits **1105** in these circuits is a multiplexer or some other logic circuit that is commutative. Hence, in some embodiments, the invention's VPA configurable logic circuits can have input bits as part of its VPA structure.

VII. Configurable IC and System

FIG. **29** illustrates a portion of a configurable IC **2900** that has an array of logic circuits **2905** and interconnect circuits **2910**. A logic circuit **2905** can be any of the configurable logic circuits illustrated in FIGS. **11–16** and **25–28**, or it can include several of the configurable logic circuits illustrated in FIGS. **11–16** and **25–28**. Similarly, an interconnect circuit **2910** can be any configurable interconnect circuit described above by reference to FIGS. **17–21**, or it can include several of the configurable interconnect circuits illustrated in these figures. Alternatively, in some embodiments, some or all of the logic or interconnect circuits illustrated in FIG. **29** might not be configurable.

As shown in FIG. **29**, the IC **2900** has two types of interconnect circuits **2910a** and **2910b**. Interconnect circuits **2910a** connect interconnect circuits **2910b** and logic circuits **2905** (i.e., connect logic circuits **2905** to other logic circuits **2905** and interconnect circuits **2910b**, and connect interconnect circuits **2910b** to other interconnect circuits **2910b** and logic circuits **2905**). Interconnect circuits **2910b**, on the other hand, connect interconnect circuits **2910a** to other interconnect circuits **2910a**.

As shown in FIG. **29**, the IC **2900** includes several signal generators **2902** that control the reconfiguration of the circuits **2905** and **2910**. In some embodiments, the signal generators are sub-cycle signal generators that generate signals that enable some or all of the logic circuits to be sub-cycle configurable, as described above. In some embodiments, the signal generators are not directly con-

nected to all logic and interconnect circuits that they control. For instance, in some of these embodiments, the signals from these generators are routed to the appropriate configurable circuits through the configurable interconnect circuits **2910**.

Although two signal generators are illustrated in FIG. **29**, other configurable IC's of the invention use more or fewer signal generators. For instance, the configurable IC's of some embodiments might only have one signal generator, or might not have a signal generator but instead might connect to a signal generator outside of the IC.

In some embodiments, the configurable IC **2900** has a large number of logic and interconnect circuits (e.g., hundreds, thousands, etc. of such circuits). The configurable IC's of some embodiments might employ different architectures for arranging their logic and interconnect circuits. For instance, some embodiments might use a LAB architecture (a logic-array-block architecture), other symmetrical or asymmetrical architectures. Some embodiments might also use some of the architectural arrangements disclosed in United States Patent Application entitled "Configurable Integrated Circuit Architecture," having Ser. No. 10/882, 713, filed concurrently with this application. This Application is incorporated in the present application by reference.

In some embodiments, all logic circuits or large sets (e.g., hundreds) of logic circuits of the configurable IC have the same circuit structure (e.g., the same circuit elements and wiring between the circuit elements). Similarly, in some embodiments, the configurable IC will have all of its interconnect circuits or large sets (e.g., hundreds) of its interconnect circuits have the same circuit structure. Re-using the same circuit structure for a large set of logic circuits or a large set of interconnect circuits simplifies the design and manufacturing of the configurable IC. Alternatively, some embodiments might use numerous different structures for their logic circuits and/or their interconnect circuits.

In some embodiments, the logic circuits of the configurable IC **2900** are not traditional processing units that use traditional microprocessor designs (such as the Von Neumann design). FIG. **30** illustrates a traditional microprocessor design. A typical microprocessor **3000** often operates by repetitively performing fetch, decode, and execute operations. Specifically, as shown in FIG. **30**, a microprocessor typically has an instruction processing pipeline that (1) fetches an encoded instruction from a program **3005** in memory **3010**, (2) decodes this instruction, (3) executes the decoded instruction, and (4) writes the result of the execution back to memory. The program is generated from a fixed set of encoded instructions upon which the design of the microprocessor is based. A microprocessor's instruction processing pipeline often includes an instruction fetch unit **3015** for fetching instructions, a decoder **3020** for decoding the instructions, and one or more processing units **3025** for executing the decoded instruction. A microprocessor might have several instruction processing pipelines in order to perform several fetch-decode-execute cycles in parallel. In such cases, the microprocessor often has a separate decoder for each pipeline. As shown in FIG. **30**, a traditional microprocessor uses separate address and data buses **3030** and **3035** to identify locations in memory to read and write.

As mentioned above, in some embodiments, the logic circuits **2905** of the configurable IC **2900** do not use traditional microprocessor designs. This is because these logic circuits do not employ a fetch-decode-execute operational cycle. Instead, these logic circuits (1) can directly receive configuration data sets that configure the logic circuits to

perform certain operations, and (2) can directly pass the results of their operations to other logic circuits.

FIG. **31** illustrates a more detailed example of this. Specifically, this figure illustrates a configuration data pool **3105** for the configurable IC **2900**. This pool includes N configuration data sets (CDS). This pool is stored in one or more memory/storage units, such as SRAMs, DRAMs, Flash, shift registers, disk, etc.

As shown in FIG. **31**, an input/output circuitry **3120** of the configurable IC **2900** routes different configuration data sets to different configurable logic and interconnect circuits of the IC **2900**. The I/O circuitry **3120** can directly route numerous configuration data sets to numerous configurable circuits without first passing the configuration data through one or more decoders. Also, a configuration data set (CDS) might be sent to numerous (e.g., 5) different configurable circuits (e.g., configurable logic circuits **3125**).

For instance, FIG. **31** illustrates configurable circuit **3145** receiving configuration data sets **1**, **3**, and **J** through the I/O circuitry, while configurable circuit **3150** receives configuration data sets **3**, **K**, and **N-1** through the I/O circuitry. In some embodiments, the configuration data sets are stored within each configurable circuit. Also, in some embodiments, a configurable circuit can store multiple configuration data sets so that it can reconfigure quickly by changing to another configuration data set. In some embodiments, some configurable circuits store only one configuration data set, while other configurable circuits store multiple such data sets.

In configurable IC **2900**, the logic circuits can receive as input data the outputs of other logic circuits (i.e., the logic circuits can pass the result of their operations to other logic circuits without first writing these results in memory and having other logic circuits retrieve these results from memory). For example, in FIG. **31**, the logic circuit **3150** might pass its output to the logic circuit **3160** through the interconnect circuit **3155** without first storing this output in a memory outside of the circuit array **3100** illustrated in this figure.

In some embodiments, some of the logic circuits **2905** of the configurable IC **2900** of FIG. **29** do not use traditional microprocessor designs, while other logic circuits **2905** use traditional microprocessor designs. For instance, in some embodiments, some logic circuits **2905** of the IC **2900** are Von Neumann processors that use the fetch-decode-execute operational cycle described above. In other embodiments, all the logic circuits **2905** of the IC **2900** are traditional, Von Neumann processors.

Yet in other embodiments, the configurable IC **2900** includes (1) an array of configurable logic circuits that do not use a traditional processor design, and (2) processor units outside of the array that use a traditional processor design. FIG. **32** illustrates one such example. Specifically, this figure illustrates the IC **2900** as having an array **3220** of non-traditional processing units **2905** and configurable interconnects **2910**. The processing units are logic circuits that are configured and operated according to the approach illustrated in FIG. **31**. FIG. **32** also shows the IC **2900** as having one on-chip processor **3205** that follows the traditional Von Neumann design that was described above in FIG. **30**. This on-chip processor **3205** can read and write instructions and/or data from an on-chip memory **3210** or an offchip memory **3215**. The processor **3205** can communicate with the configurable array **3220** through memory **3210** and/or **3215** through on-chip bus **3225** and/or off-chip bus **3230**. The buses **3225** and **3230** collectively represent all

19

conductive paths that communicatively connect the devices or components illustrated in FIG. 32.

FIG. 33 conceptually illustrates a more detailed example of a computing system 3300 that includes an IC 3305 of the invention. This system 3300 can be a stand-alone computing or communication device, or it can be part of another electronic device. As shown in FIG. 33, the system 3300 not only includes the IC 3305, but also includes a bus 3310, a system memory 3315, a read-only memory 3320, a storage device 3325, input devices 3330, output devices 3335, and communication interface 3340.

The bus 3310 collectively represents all system, peripheral, and chipset interconnects (including bus and non-bus interconnect structures) that communicatively connect the numerous internal devices of the system 3300. For instance, the bus 3310 communicatively connects the IC 3305 with the read-only memory 3320, the system memory 3315, and the permanent storage device 3325.

The configuration data pool is stored in one or more of these memory units in some embodiments of the invention. Also, from these various memory units, the IC 3305 receives data for processing and configuration data for configuring the IC's configurable logic and/or interconnect circuits. When the IC 3305 has a processor, the IC also retrieves from the various memory units instructions to execute. The read-only-memory (ROM) 3320 stores static data and/or instructions that are needed by the IC 3305 and other modules of the system 3300. The storage device 3325, on the other hand, is read-and-write memory device. This device is a non-volatile memory unit that stores instruction and/or data even when the system 3300 is off. Like the storage device 3325, the system memory 3315 is a read-and-write memory device. However, unlike storage device 3325, the system memory is a volatile read-and-write memory, such as a random access memory. The system memory stores some of the instructions and/or data that the IC needs at runtime.

The bus 3310 also connects to the input and output devices 3330 and 3335. The input devices enable the user to enter information into the system 3300. The input devices 3330 can include touch-sensitive screens, keys, buttons, keyboards, cursor-controllers, microphone, etc. The output devices 3335 display the output of the system 3300.

Finally, as shown in FIG. 33, bus 3310 also couples system 3300 to other devices through a communication interface 3340. Examples of the communication interface include network adapters that connect to a network of computers, or wired or wireless transceivers for communicating with other devices. One of ordinary skill in the art would appreciate that any other system configuration may also be used in conjunction with the invention, and these system configurations might have fewer or additional components.

One of ordinary skill will realize that the configurable circuits, IC's, and systems described above have numerous advantages. For instance, the logic and interconnect circuits can reconfigure and execute multiple times within one design or interface cycle, as they are sub-cycle configurable. By configuring and executing these circuits on a sub-cycle basis, a smaller, faster IC can be specified. Such a smaller, faster IC can be used to implement the design of a larger, slower IC, at a fraction of the cost for manufacturing the larger IC.

Also, several of the invention's logic and interconnect circuits can be reconfigured in a non-sequential manner. Rather, each of these circuits can be reconfigured to perform a number of operations in a number of arbitrary sequences. These circuits can be reconfigured in such a non-sequential

20

manner because the sub-cycle signal generator 700 can generate a sub-cycle signal that has no particular pattern, which, in turn, allows these circuits to supply any desirable, arbitrary sequence of configuration data sets to their core interconnect or logic circuits.

On the other hand, the signal generator in some embodiments generates a sub-cycle signal that has a pattern that may or may not sequentially increment or decrement through all possible values of the signal. Such flexibility in the signal generation and the architecture of the configurable circuits provides tremendous gains in speed and size of the configurable IC.

While the invention has been described with reference to numerous specific details, one of ordinary skill in the art will recognize that the invention can be embodied in other specific forms without departing from the spirit of the invention. For instance, although FIG. 29 illustrates an IC with homogenous architectures, the IC's of other embodiments might use heterogeneous architectures (e.g., SOC architectures) such as the one illustrated in FIG. 32.

Also, the VPA circuits of FIGS. 21-28 are sub-cycle reconfigurable VPA interconnect circuits as they receive a sub-cycle signal 1150. In other embodiments, however, these interconnect circuits might not be sub-cycle reconfigurable. For instance, they might receive a different set of signals than the phase signal 1150.

One of ordinary skill will also realize that there might be intervening devices between the logic and/or interconnect circuits described above. For instance, in the logic circuit 1100 of FIG. 11, buffers can be placed between the multiplexers 1140 and circuit 1105 and/or after the circuit 1105. Buffer circuits are not logic or interconnect circuits. Buffer circuits can be used to achieve one or more objectives (e.g., maintain the signal strength, reduce noise, delay signal, etc.) for connections between circuits. Inverting buffer circuits also allow an IC design to reconfigure logic circuits less frequently and/or use fewer types of logic circuits. In some embodiments, buffer circuits are formed by one or more inverters (e.g., two or more inverters that are connected in series).

Alternatively, the intermediate circuits between the logic and/or interconnect circuits can be viewed as a part of the devices illustrated in these figures. For instance, the inverters that can be placed after the devices 1105 and 1140 can be viewed as being part of these devices. Some embodiments use such inverters in order to allow an IC design to reconfigure logic circuits less frequently and/or use fewer types of logic circuits.

Also, although several of the above-described embodiments reconfigure both interconnect and logic circuits, one of ordinary skill will realize that some embodiments do not reconfigure both interconnect and logic circuits. For instance, some embodiments only reconfigure interconnect circuits on a sub-cycle basis. Some of these embodiments might never reconfigure the logic circuits, or might reconfigure these circuits at a slower rate than the sub-cycle rate.

In addition, although FIGS. 5 and 6 illustrate IC's with dedicated interface circuits, one of ordinary skill will realize that IC's of some embodiments do not have dedicated interface circuits. For instance, in some embodiments, the IC's have circuits that are reconfigured into interface circuits periodically to receive or output signals.

Although some of the timing diagrams show the sub-cycle phases as falling completely within a primary cycle, one of ordinary skill will understand that the sub-cycle phases might be offset by some amount from their associated primary cycles. Thus, one of ordinary skill in the art would

21

understand that the invention is not to be limited by the foregoing illustrative details, but rather is to be defined by the appended claims.

We claim:

1. An integrated circuit (IC) comprising:
 - 1) a set of configurable logic circuits, each configurable logic circuit for configurably performing a set of functions;
 - 2) a set of configurable interconnect circuits for configurably coupling the logic circuits;
 wherein each of a plurality of configurable interconnect circuits comprises:
 - a) a first interconnect circuit having a set of input terminals, a set of output terminals, a set of configuration data lines, and a plurality of connection schemes for communicatively coupling the input terminal set to the output terminal set; and
 - b) a second connection circuit for supplying sets of configuration data to said configuration data lines of the first interconnect circuit, wherein during an operation of the IC, the second connection circuit receives a control signal that directs the second connection circuit to supply configuration data sets to the first interconnect circuit at a particular rate for at least a particular time period, wherein the control signal has a rate that is at least equal to the particular rate, wherein at least two supplied configuration data sets are different and configure the first interconnect circuit to use two different connection schemes that differently couple the input and output terminal sets, wherein said supplied configuration data sets are simultaneously stored in the IC.
2. The IC of claim 1, wherein the set of configurable interconnect circuits includes at least one hundred configurable interconnect circuits.
3. The IC of claim 1, wherein the first interconnect circuit is a multiplexer.
4. An integrated circuit (IC) comprising:
 - 1) a set of configurable logic circuits, each configurable logic circuit for configurably performing a set of functions;
 - 2) a set of configurable interconnect circuits for configurably coupling the logic circuits;
 wherein each of a plurality of configurable interconnect circuits comprises:
 - a) a first interconnect circuit having a set of input terminals, a set of output terminals, a set of configuration data lines, and a plurality of connection schemes for communicatively coupling the input terminal set to the output terminal set, wherein the first interconnect circuit is a decoder; and
 - b) a second connection circuit for supplying sets of configuration data to said configuration data lines of the first interconnect circuit at a particular rate for at least a particular time period, wherein at least two supplied configuration data sets are different and configure the first interconnect circuit to use two different connection schemes that differently couple the input and output terminal sets, wherein said supplied configuration data sets are simultaneously stored in the IC.
5. The IC of claim 1 further comprising a storage for storing configuration data, wherein the second connection circuit communicatively couples to the first interconnect circuit and to the storage to supply sets of configuration data stored in the storage to the first interconnect circuit.

22

6. The IC of claim 5, wherein the storage comprises memory cells.

7. The IC of claim 6, wherein the memory cells are read-writeable memory cells.

8. The IC of claim 1, wherein the control signal is a clock signal.

9. The IC of claim 8, wherein the control signal has a value that changes at the rate of the control signal.

10. The IC of claim 1, wherein the second circuit includes a plurality of sub-circuits, wherein each sub-circuit stores configuration data, and configuration data from the sub-circuits is supplied to the first interconnect circuit at the particular rate.

11. A configurable interconnect circuit for an integrated circuit (IC), the configurable interconnect circuit comprising:

a) a first interconnect circuit having a set of input terminals, a set of output terminals, a set of configuration data lines, and a plurality of connection schemes for communicatively coupling the input terminal set to the output terminal set; and

b) a second connection circuit for supplying sets of configuration data to said set of configuration data lines of the interconnect circuit, wherein said sets of configuration data are simultaneously stored in the IC;

wherein the second connection circuit comprises at least a third interconnect circuit and a fourth interconnect circuit;

wherein each of said third and fourth interconnect circuits simultaneously provides data for at least one of said configuration data lines;

wherein at least two supplied configuration data sets are different and configure the configurable interconnect circuit to use two different connection schemes that differently couple the input and output terminal sets;

wherein during an operation of the IC, the second connection circuit supplies configuration data sets to the first interconnect circuit at a particular rate for at least a duration of time;

wherein during the operation of the IC, the second connection circuit receives a control signal that directs the second connection circuit to supply configuration data sets to the first interconnect circuit at the particular rate; wherein the control signal has a rate that is at least equal to the particular rate.

12. The configurable interconnect circuit of claim 11 further comprising a storage for storing configuration data, wherein the second connection circuit communicatively couples to the first interconnect circuit and to the storage to supply sets of configuration data stored in the storage to the first interconnect circuit.

13. The configurable interconnect circuit of claim 12, wherein the storage comprises memory cells.

14. The configurable interconnect circuit of claim 13, wherein the memory cells are read-writeable memory cells.

15. The configurable interconnect circuit of claim 11, wherein the control signal is a clock signal.

16. The configurable interconnect circuit of claim 15, wherein the control signal has a value that changes at the rate of the control signal.

17. The configurable interconnect circuit of claim 11, wherein the second circuit includes a plurality of sub-circuits, wherein each sub-circuit stores configuration data, and configuration data from the sub-circuits is supplied to the first interconnect circuit at the particular rate.

23

18. A system comprising

- a) a memory for storing data; and
 - b) configurable integrated circuit (IC) communicatively coupled to the memory to receive and process the data, the configurable IC comprising:
 - 1) a set of configurable logic circuits for configurably performing a set of functions;
 - 2) a set of configurable interconnect circuits for configurably coupling the logic circuits;
- wherein each of a plurality of configurable interconnect circuits comprises:
- i) a first interconnect circuit having a set of input terminals, a set of output terminals, a set of configuration data lines, and a plurality of connection schemes for communicatively coupling the input terminal set to the output terminal set; and
 - ii) a second connection circuit for supplying sets of the configuration data to said configuration data lines of the first interconnect circuit, wherein at least two different configuration data sets that configure the first interconnect circuit are different and configure the first interconnect circuit to use two different connection schemes, wherein said supplied configuration data sets are simultaneously stored in the IC;
- wherein during an operation of the IC, a particular second connection circuit of a particular configurable interconnect circuit of at least a sub-set of configurable interconnect circuits sup-

24

plies configuration data sets to the particular first interconnect circuit of the particular configurable interconnect circuit at a particular rate for at least a duration of time;

wherein during the operation of the IC, the particular second connection circuit receives a control signal that directs the second connection circuit to supply configuration data sets to the particular first interconnect circuit at the particular rate;

wherein the control signal has a rate that is at least equal to the particular rate.

19. The system of claim 18, wherein the set of configurable interconnect circuits includes at least one hundred configurable interconnect circuits.

20. The system of claim 18, wherein a plurality of the configurable interconnect circuits are multiplexers and a plurality of the configurable interconnect circuit are decoders.

21. The system of claim 18, wherein the control signal is a clock signal.

22. The system of claim 21, wherein the control signal has a value that changes at the rate of the control signal.

23. The system of claim 18, wherein the second circuit includes a plurality of sub-circuits, wherein each sub-circuit stores configuration data, and configuration data from the sub-circuits is supplied to the first interconnect circuit at the particular rate.

* * * * *