



# CSE P 501 – Compilers

---

Threads and Memory Models

Hal Perkins

Autumn 2011



# References

---

- *Memory Models: A Case for Rethinking Parallel Languages and Hardware*  
Adve and Boehm, CACM Aug. 2010
- *Foundations of the C++ Concurrency Memory Model*  
Boehm and Adve, PLDI 2008
- *The Java Memory Model*  
Manson, Pugh, and Adve, POPL 2005
- Slides by Vijay Menon, CSE 501, Sp09



# Threads and shared memory

---

- Multithreaded programs allow multiple threads to run concurrently
  - each thread has its own local variables (stack and registers), but...
  - all threads share a common view of memory (globals / statics)
- Pervasive with multiple cores



# Safety of optimization

---

- A standard constraint / definition:
  - *If, in their actual program context, the result of evaluating  $e'$  cannot be distinguished from the result of evaluating  $e$ , the compiler can substitute  $e'$  for  $e$*
- What does this mean in a multi-threaded setting?



# Register promotion

---

```
// x is global, initially 0
```

```
void foo(int* a, int n) {  
    for (int i = 0; i < n; ++i)  
        x += i;  
}
```

*or*



# Register promotion

---

```
// x is global, initially 0
```

```
void foo(int* a, int n) {  
    for (int i = 0; i < n; ++i)  
        x += i;  
}
```



```
// Optimized
```

```
void foo(int* a, int n) {  
    int reg = x;  
    for (int i = 0; i < n; ++i)  
        reg += i;  
    x = reg;  
}
```



# Before optimization

---

```
// x is global, initially 0
```

```
// Thread 1
```

```
void foo(int* a, int n) {  
    for (int i = 0; i < n; ++i)  
        x += i;  
}
```

```
// Thread 2
```

```
void bar() {  
    x = 10;  
    ...  
}
```

What happens when `n == 0`?



# After optimization

---

```
// x is global, initially 0
```

```
// Thread 1
```

```
void foo(int* a, int n) {  
    int reg = x;  
    for (int i = 0; i < n; ++i)  
        reg += i;  
    x = reg;  
}
```

```
// Thread 2
```

```
void bar() {  
    x = 10;  
    ...  
}
```

What happens when `n == 0`?





# What happened?

---

- In executions where  $n == 0$ , the compiler optimization creates a value out of thin air.
  - Original code:  $x == 10$  is guaranteed
  - Optimized code: new write of  $x = 0$  (inserted  $x = \text{reg}$ ) creates new result
- Safety is no longer maintained



# How did we get here?

---

- C & C++ originally defined as single-threaded languages
  - Compilers didn't consider threads
  - Threads were provided by externally libraries (e.g. pthreads) that defined their own semantics
- This is a broken model!
  - New specs explicitly deal with threads (Boehm, et al)



# Dekker's example

---

- Initially,  $x == y == 0$

Thread 1

$x = 1;$  (a)

$r1 = y;$  (b)

Thread 2

$y = 1;$  (c)

$r2 = x;$  (d)

- What are possible executions?



# Dekker's example

---

- Initially,  $x == y == 0$

Thread 1

$x = 1;$  (a)

$r1 = y;$  (b)

Thread 2

$y = 1;$  (c)

$r2 = x;$  (d)

- What are possible executions?
  - Consider interleavings of thread 1 & 2:
    - $abcd, acbd, acdb, cdab, cadb, cabd$



# Dekker's example

---

- Initially,  $x == y == 0$

Thread 1

$x = 1;$

$r1 = y;$

Thread 2

$y = 1;$

$r2 = x;$

- Can  $r1 == r2 == 0$ ?
  - No interleaving gives this results, but...
  - Most hardware will allow it (store buffers)
  - Many compilers will allow it (instruction scheduling)



# What is a correct execution?

---

- Simplest notion: *sequential consistency* (Lamport '79)  
*"... the result of any execution is the same as if the operations of all the processors were executed in some sequential order, and the operations of each individual processor appear in this sequence in the order specified by its program."*
- This is essentially the interleaving model
- Too expensive (?)
  - Nobody implements this in practice



# Refined notion

---

- Guarantee sequential consistency only for *correctly synchronized* programs (Adve)
  - Give the programmer rules to follow
  - Give simple semantics when rules are obeyed
- Correctly synchronized
  - Must be intuitive to programmer
  - Must not be restrictive for implementer



# Data races

---

- ! ■ Two operations *conflict* if they both access a memory location and one is a write
- A execution contains a *data race* if two adjacent operations from two different threads conflict
- ■  $x = 1; y = 1; r1 = y; r2 = x;$
- A program is *race free* if no sequentially consistent execution (i.e., interleaving) has a data race





# Correct synchronization

---

- We call a program *correctly synchronized* if it is data race free
- Basic contract:
  - If programmers write race free programs, implementers will provide sequentially consistent semantics
  - This is the fundamental underpinning for Java, C, and C++ memory models



# How do we avoid races?

---

- Mutual exclusion:
  - Thread acquires lock before accessing a shared variable:


```
Thread 1  
lock (mutex);  
[ tmp1 = x;  
  tmp2 = tmp1 + 1;  
  x = tmp2  
unlock (mutex);
```


```
Thread 2  
lock (mutex);  
[ tmp3 = x;  
  tmp4 = tmp3 + 1;  
  x = tmp4  
unlock (mutex);
```

- Locks disallow problematic interleavings

# How do we avoid races?

- Volatile variables (atomic in new C++):
  - Certain variables are declared with stronger ordering semantics (initially, `x` and `flag` are 0):

Thread 1  
 `x = 1;`  
`flag = 1;`

Thread 2  
 `if (flag == 1)`  
`t = x;`

- If `flag` is declared volatile, then write to `x` cannot be sunk in T1 and read from `x` cannot be hoisted in T2 by definition
  - Compiler must respect ordering



# What does this mean for compilers?

---

- In the absence of synchronization, compilers may *almost* operate as if programs were single-threaded
- Compilers must respect ordering due to synchronization (and generate necessary hardware instructions)
- Caveat: compiler must not introduce races into correctly synchronized code (e.g. register promotion)



# What happens on a race?

---

- In C++, undefined semantics

Thread 1	( $x == y == 0$ )	Thread 2	
$x = 1;$	(a)	$y = 1;$	(c)
$r1 = y;$	(b)	$r2 = x;$	(d)

- Valid results:



# What happens on a race?

---

- In C++, undefined semantics

Thread 1	( $x == y == 0$ )	Thread 2	
$x = 1;$	(a)	$y = 1;$	(c)
$r1 = y;$	(b)	$r2 = x;$	(d)

- Valid results:
  - $r1 = 0$  and  $r2 = 0$
  - $r1 = 0$  and  $r2 = 2$
  - "format c:\"
- No such thing as a benign race in C++!




# Hard to bound effects

---

```
unsigned x;
```

```
if (x < 3) {  
    // x modified by another  
    // thread  
    switch (x) {  
        case 0: ...  
        case 1: ...  
        case 2: ...  
    }  
}
```



- Compiler should be able to generate table
  - Assumes x in range after check
  - Async change to x causes arbitrary behavior



# Type-safety issues

---

- In Java, data races cannot violate type safety
  - Java promises a measure of security
  - Synchronization errors may be used on purposed by untrusted code to open / exploit holes
  - Java memory model must provide some guarantees in the presence of races





# Java ordering

---

- Java's memory model defines a partial order over all actions in a program
  - For each thread, actions must happen in program order
  - Globally, synchronization actions must be totally ordered
  - These two must be consistent