

Buffer Overflows

Part A Due (Sloits 1+2): Thursday, October, 10, 11:59pm

Part B Due (Sloits 3,5,6): Thursday, October, 24, 11:59pm

Extra Credit (Sloit 4,7,8): Thursday, October, 24, 11:59pm

Turn in: All parts on Gradescope, see Deliverables

Individual or group: Individual or partners

Points:

10 per sloit (Extra credit is worth 5)

5 per writeup (Individually done)

EC worth 2 per sloit, 1 per writeup.

Before you start:

- Make sure you can SSH into the CSE Linux servers: umnak.cs.washington.edu
 - This uses the same credentials as attu.cs.washington.edu

Overview

Goal:

- The goal of this assignment is to gain hands-on experience with the effects of buffer overflow bugs and similar problems. We strongly suggest doing all work on **umnak.cs.washington.edu**
- You are given the source code for seven exploitable programs ([targets/targetN](#))
- Your goal is to write seven exploit programs ([sploit1](#), ..., [sploit7](#)). Program [sploit\[i\]](#) will execute program `./targets/target[i]`, giving it an input you construct that results in shellcode running.
- Each exploit, when run including [checkcode.h](#) (instead of [shellcode.h](#)) should print a success message.
 - When run including [shellcode.h](#) it should start a new (nested) shell.
- Sloits 1,2,3,5,6 are required. Sloits 4,7,8 are extra credit.

Contents:

First, you will need to make a fork of the lab1 gitlab:

<https://gitlab.cs.washington.edu/dkohlbre/buffer-lab-24au>

- Please make this fork *private* so that other students don't find it!
- Share this fork with your partner if you have one.

- Then clone your fork to wherever you are working (probably `umnak`)

The Targets (`targets/`)

- Read the source files carefully, along with any header files they include.
 - Note that the extra bits included (`strcpy` and `tmalloc`) are standard implementations: they don't have bugs we care about, but you will want to read them and understand what they do.
- Make sure to build the targets.
- Do not modify the targets, even for debugging purposes.
- You should examine the target binaries, and will find value in using `objdump` to get the assembly of the targets.

The Exploits (`splloits/`)

The `splloits/` directory contains skeletons for each of the exploits you will write, a `Makefile` for building them, and two options for shellcode: `shellcode.h` and `checkcode.h`. `checkcode.h` will try to run the `check` script, rather than start a shell. Build them with `make`, do not build manually.

Printf exercises (`printf-exercises/`)

These are a few small exploitable programs that use `printf` in bad ways.

Toy1: Your goal is to give an input to the program that will cause it to print out the secret string.

Toy2: Your goal is to give an input to the program that will *change* the value of a variable such that the toy prints out a success message.

These are a great way to get some experience working with printf exploits before you try `splloit6`.

Extra Credit

Targets 4 and 7 are similar to earlier exploits, but with interesting wrinkles.

Target 8 requires a different exploit technique! For 8, you can see that the source code is exactly the same as `target0`, except this time, the stack is not executable. You might want to try a `return2libc` attack. Here's a good tutorial for it: [RET2LIBC](#) (starting from page 52).

Deliverables (See Gradescope)

Lab 1a:

- Your `splloit1.c` and `splloit2.c` files.

- An *individual* writeup explaining your exploit strategies for spoils 1+2

Lab 1b:

- Your `spl0it3.c`, `spl0it5.c`, and `spl0it6.c` files.
- An *individual* writeup explaining your exploit strategies for spoils 3, 5, and 6

Writeups

You should produce a brief writeup for each of the spoils you solved. Writeups are *individual*, each exploit writeup should be The goal here is that if teammate B discovered the key insight for exploit3, teammate A needs to really understand that insight to do the writeup. **Your writeups should be in your own words, and written solely by you. If your whole team submits copies of the same writeups, you won't get full credit for this.**

A writeup should explain what your exploit does, and what goals it accomplishes along the way. This writeup should be relative to the complexity of the exploit, and should be at most 2 paragraphs long for the most complex ones. **Maximum length of 500 words per-exploit.** If you aren't sure, consider what you'd tell a TA if they asked you "how did you exploit this?"

A spl0it 0 writeup is quite simple, and might say:

"Unfortunately, strcpy does not have a bounds check, so the copy is able to go past the end of the stack buffer in foo if our input is larger than the buffer. We use this to write arbitrary values to anything above the buffer on the stack. Specifically, we write over the return pointer on the stack for fo (e.g. the one that points back into main) with the address of the stack buffer buf. This buffer was first filled with our shellcode, so when foo returns it does not return to main, and instead executes our shellcode."

Important: For spl0it1, you should **not** simply copy/lightly reword the spl0it0 example above. That is one of many, many reasonable ways to explain spl0it0 or 1. Write a new one, in your own words, to demonstrate that you really understand what's going on! We do understand that you and your partner will have similar writeups for many exploits, but make sure you do them independently.

Miscellaneous

gdb

You will want to use `gdb`. We recommend using extensions to `gdb` if you are comfortable learning them:

- `gef` (<https://hugsy.github.io/gef/>) is an exploitation-focused set of `gdb` extensions. To use it, download the `gef.py` file to wherever you are using `gdb` and then add loading `gef.py`

to your `.gdbinit`. In `gef`, if you lost the original nice display, you can use `context` to tell it to reprint it. We highly recommend learning `gef`.

There's lots of online documentation for `gdb`. Here's one you might start with: [GDB Notes \(formerly hosted at CMU\)](#)

`gdb` is your best friend in this assignment, particularly to understand what's going on.

Specifically, note the `disassemble` and `stepi` commands.

- The `layout` command is helpful for seeing multiple things, e.g. `layout src` will show the source code of the target and the location of breakpoints.
- The `info register` command is helpful in printing out the contents of registers such as `ebp` and `esp`. The 'info frame' command also tells you useful information, such as where the return `eip` is saved.
- You may find the `x(eXamine)` command useful to examine memory (and the different ways you can print the contents such as `/a /i` after `x`).
- Since you are running `sploit` but want to debug `target` you will need to catch the switch from `sploit` to `target`. This can be done with `catch exec` which will break once `exec` is called. Now you can set your breakpoints for the `target`. Note that if you try to set breakpoints in `target` before you have hit `exec`, it won't work as expected.

Hints

- Remember 351's bomblab? This is similar, but there are many points of difference. Notably this is 32-bit, not 64-bit.
- Read Aleph One's "[Smashing the Stack for Fun and Profit](#)." Carefully! We also recommend reading Chien and Szor's "[Blended Attacks](#)" paper. These readings will help you have a good understanding of what happens to the stack, program counter, and relevant registers before and after a function call, but you may wish to experiment as well. It will be helpful to have a solid understanding of the basic buffer overflow exploits before reading the more advanced exploits.
- Read "once upon a free()" <http://phrack.org/issues/57/9.html>
- Read scut's "[format strings](#)" paper. You may also wish to read <http://seclists.org/bugtraq/2000/Sep/214>.
- `gdb`. Really. Before you ask a TA, try walking through before and after your exploit triggers any state corruption using `gdb`.
- `objdump` is a great tool as well, it will let you print out the assembly of a program for further reference.
- Make sure that your exploits work on the server if you did some work locally.
- **Start early!!!** Theoretical knowledge of exploits does not readily translate into the ability to write working exploits. Target1 is relatively simple and the other problems are quite a bit more complicated.
- Find more FAQs answered in the FAQ doc linked on the assignment page.

Warnings

Aleph One gives code that calculates addresses on the target's stack based on addresses on the exploit's stack. Addresses on the exploit's stack can change based on how the exploit is executed (working directory, arguments, environment, etc.); in our testing, we do not guarantee to execute your exploits as bash does. **You must therefore hard-code target stack locations in your exploits.** You should **not** use a function such as `get_sp()` in the exploits you hand in.

Credits

This project was originally designed for Dan Boneh and John Mitchell's CS155 course at Stanford, and was then also extended by Hovav Shacham at UCSD. Thanks Dan, John, and Hovav! Previous UW security instructors David Kohlbrenner and Yoshi Kohno also contributed significantly to the UW version of this lab.