



CSE341: Programming Languages

Lecture 23

Multiple Inheritance, Mixins, Interfaces, Abstract Methods

Dan Grossman
Winter 2013

What next?

Have used classes for OOP's essence: inheritance, overriding, dynamic dispatch

Now, what if we want to have more than *just 1 superclass*

- *Multiple inheritance*: allow > 1 superclasses
 - Useful but has some problems (see C++)
- Ruby-style *mixins*: 1 superclass; > 1 method providers
 - Often a fine substitute for multiple inheritance and has fewer problems (see also Scala *traits*)
- Java/C#-style *interfaces*: allow > 1 types
 - Mostly irrelevant in a dynamically typed language, but fewer problems

Winter 2013

CSE341: Programming Languages

2

Multiple Inheritance

- If inheritance and overriding are so useful, why limit ourselves to one superclass?
 - Because the semantics is often awkward (this topic)
 - Because it makes static type-checking harder (not discussed)
 - Because it makes efficient implementation harder (not discussed)
- Is it useful? Sure!
 - Example: Make a `ColorPt3D` by inheriting from `Pt3D` and `ColorPt` (or maybe just from `Color`)
 - Example: Make a `StudentAthlete` by inheriting from `Student` and `Athlete`
 - With single inheritance, end up copying code or using non-OOP-style helper methods

Winter 2013


CSE341: Programming Languages

3


Trees, dags, and diamonds

- Note: The phrases *subclass*, *superclass* can be ambiguous
 - There are *immediate* subclasses, superclasses
 - And there are *transitive* subclasses, superclasses

- Single inheritance: the *class hierarchy* is a tree
 - Nodes are classes
 - Parent is immediate superclass
 - Any number of children allowed



- Multiple inheritance: the class hierarchy no longer a tree
 - Cycles still disallowed (a directed-acyclic graph)
 - If multiple paths show that X is a (transitive) superclass of Y, then we have *diamonds*




Winter 2013

CSE341: Programming Languages

4

What could go wrong?



- If V and Z both define a method `m`, what does Y inherit? What does `super` mean?
 - *Directed resends* useful (e.g., `Z::super`)
- What if X defines a method `m` that Z but not V overrides?
 - Can handle like previous case, but sometimes undesirable (e.g., `ColorPt3D` wants `Pt3D`'s overrides to "win")
- If X defines fields, should Y have one copy of them (`f`) or two (`V::f` and `Z::f`)?
 - Turns out each behavior can be desirable (next slides)
 - So C++ has (at least) two forms of inheritance

Winter 2013

CSE341: Programming Languages

5

3DColorPoints

If Ruby had multiple inheritance, we would want `ColorPt3D` to inherit methods that share one `@x` and one `@y`

```

class Pt
  attr_accessor :x, :y
  ...
end
class ColorPt < Pt
  attr_accessor :color
  ...
end
class Pt3D < Pt
  attr_accessor :z
  ... # override some methods
end
class ColorPt3D < Pt3D, ColorPt # not Ruby!
end
  
```

Winter 2013

CSE341: Programming Languages

6

ArtistCowboys

This code has `Person` define a pocket for subclasses to use, but an `ArtistCowboy` wants *two* pockets, one for each `draw` method

```
class Person
  attr_accessor :pocket
  ...
end
class Artist < Person # pocket for brush objects
  def draw # access pocket
  ...
end
class Cowboy < Person # pocket for gun objects
  def draw # access pocket
  ...
end
class ArtistCowboy < Artist, Cowboy # not Ruby!
end
```

Winter 2013

CSE341: Programming Languages

7

Mixins

- A *mixin* is (just) a collection of methods
 - Less than a class: no instances of it
- Languages with mixins (e.g., Ruby modules) typically let a class have one superclass but *include* number of mixins
- Semantics: *Including a mixin makes its methods part of the class*
 - Extending or overriding in the order mixins are included in the class definition
 - More powerful than helper methods because mixin methods can access methods (and instance variables) on `self` not defined in the mixin

Winter 2013

CSE341: Programming Languages

8

Example

```
module Doubler
  def double
    self + self # assume included in classes w/ +
  end
end
class String
  include Doubler
end
class AnotherPt
  attr_accessor :x, :y
  include Doubler
  def + other
    ans = AnotherPt.new
    ans.x = self.x + other.x
    ans.y = self.y + other.y
    ans
  end
end
```

Winter 2013

CSE341: Programming Languages

9

Lookup rules

Mixins change our lookup rules slightly:

- When looking for receiver `obj`'s method `m`, look in `obj`'s class, then mixins that class includes (later includes shadow), then `obj`'s superclass, then the superclass' mixins, etc.
- As for instance variables, the mixin methods are included in the same object
 - So usually bad style for mixin methods to use instance variables since a name clash would be like our `CowboyArtist` pocket problem (but sometimes unavoidable?)

Winter 2013

CSE341: Programming Languages

10

The two big ones

The two most popular/useful mixins in Ruby:

- Comparable: Defines `<`, `>`, `==`, `!=`, `>=`, `<=` in terms of `<=>`
- Enumerable: Defines many iterators (e.g., `map`, `find`) in terms of `each`

Great examples of using mixins:

- Classes including them get a bunch of methods for just a little work
 - Classes do not “spend” their “one superclass” for this
 - Do not need the complexity of multiple inheritance
- See the code for some examples

Winter 2013

CSE341: Programming Languages

11

Replacement for multiple inheritance?

- A mixin works pretty well for `ColorPt3D`:
 - Color a reasonable mixin except for using an instance variable

```
module Color
  attr_accessor :color
end
```

- A mixin works awkwardly-at-best for `ArtistCowboy`:
 - Natural for `Artist` and `Cowboy` to be `Person` subclasses
 - Could move methods of one to a mixin, but it is odd style and still does not get you two pockets

```
module ArtistM ...
class Artist < Person
  include ArtistM
class ArtistCowboy < Cowboy
  include ArtistM
```

Winter 2013

CSE341: Programming Languages

12

Statically-Typed OOP

- Now contrast multiple inheritance and mixins with Java/C#-style [interfaces](#)
- Important distinction, but interfaces are about static typing, which Ruby does not have
- So will use Java code after quick introduction to static typing for class-based OOP...
 - Sound typing for OOP prevents “method missing” errors

Winter 2013

CSE341: Programming Languages

13

Classes as Types

- In Java/C#/etc. each class is also a type
 - Methods have types for arguments and result
- ```
class A {
 Object m1(Example e, String s) {...}
 Integer m2(A foo, Boolean b, Integer i) {...}
}
```
- If C is a (transitive) subclass of D, then C is a *subtype* of D
    - Type-checking allows subtype anywhere supertype allowed
    - So can pass instance of C to a method expecting instance of D

Winter 2013

CSE341: Programming Languages

14

## Interfaces are Types

```
interface Example {
 void m1(int x, int y);
 Object m2(Example e, String s);
}
```

- An interface is not a class; it is only a type
  - Does not contain method *definitions*, only their *signatures* (types)
    - Unlike mixins
  - Cannot use `new` on an interface
    - Like mixins

Winter 2013

CSE341: Programming Languages

15

## Implementing Interfaces

- A class can explicitly implement any number of interfaces
  - For class to type-check, it must implement every method in the interface with the right type
    - More on allowing subtypes later!
  - Multiple interfaces no problem; just implement everything
- If class type-checks, it is a subtype of the interface

```
class A implements Example {
 public void m1(int x, int y) {...}
 public Object m2(Example e, String s) {...}
}
class B implements Example {
 public void m1(int pizza, int beer) {...}
 public Object m2(Example e, String s) {...}
}
```

Winter 2013

CSE341: Programming Languages

16

## Multiple interfaces

- Interfaces provide no methods or fields
  - So no questions of method/field duplication when implementing multiple interfaces, unlike multiple inheritance
- What interfaces are for:
  - “Caller can give any instance of any class implementing **I**”
    - So callee can call methods in **I** regardless of class
  - So much more flexible type system
- Interfaces have little use in a dynamically typed language
  - Dynamic typing *already* much more flexible, with trade-offs we studied

Winter 2013

CSE341: Programming Languages

17

## Connections

Let's now answer these questions:

- What does a statically typed OOP language need to support “required overriding”?
- How is this similar to higher-order functions?
- Why does a language with multiple inheritance (e.g., C++) not need Java/C#-style interfaces?

[Explaining Java's [abstract methods](#) / C++'s [pure virtual methods](#)]

Winter 2013

CSE341: Programming Languages

18

## Required overriding

Often a class expects all subclasses to override some method(s)

- The purpose of the superclass is to abstract common functionality, but some non-common parts have no default

A Ruby approach:

- Do not define must-override methods in superclass
- Subclasses can add it
- Creating instance of superclass can cause method-missing errors

```
do not use A.new
all subclasses should define m2
class A
 def m1 v
 ... self.m2 e ...
 end
end
```

Winter 2013

CSE341: Programming Languages

19

## Static typing

- In Java/C#/C++, prior approach fails type-checking
  - No method `m2` defined in superclass
  - One solution: provide error-causing implementation

```
class A
 def m1 v
 ... self.m2 e ...
 end
 def m2 v
 raise "must be overridden"
 end
end
```

- Better: Use static checking to prevent this error...

Winter 2013

CSE341: Programming Languages

20

## Abstract methods

- Java/C#/C++ let superclass give signature (type) of method subclasses should provide
  - Called *abstract methods* or *pure virtual methods*
  - Cannot create instances of classes with such methods
    - Catches error at compile-time
    - Indicates intent to code-reader
    - Does *not* make language more powerful

```
abstract class A {
 T1 m1 (T2 x) { ... m2 (e); ... }
 abstract T3 m2 (T4 x);
}
class B extends A {
 T3 m2 (T4 x) { ... }
}
```

Winter 2013

CSE341: Programming Languages

21

## Passing code to other code

- Abstract methods and dynamic dispatch: An OOP way to have subclass “pass code” to other code in super class

```
abstract class A {
 T1 m1 (T2 x) { ... m2 (e); ... }
 abstract T3 m2 (T4 x);
}
class B extends A {
 T3 m2 (T4 x) { ... }
}
```

- Higher-order functions: An FP way to have caller “pass code” to callee

```
fun f (g, x) = ... g e ...
fun h x = ... f ((fn y => ...), ...)
```

Winter 2013

CSE341: Programming Languages

22

## No interfaces in C++

- If you have multiple inheritance and abstract methods, you do not also need interfaces
- Replace each interface with a class with all abstract methods
- Replace each “implements interface” with another superclass

So: Expect to see interfaces only in statically typed OOP without multiple inheritance

- Not Ruby
- Not C++

Winter 2013

CSE341: Programming Languages

23